

Regarding the release of Star Cool controller software RCCU 0240 rev. 1, there are some changes that will affect the user of the Star Cool unit.

In addition to the new Star Cool RCCU 0240 controller software, an updated **Operating and Service manual** Item. No. 810900B has been released.

RCCU 0240 rev. 1

- An error has been fixed to prevent Alarm 901 from appearing unintentionally.

RCCU 0240

- Set Point.

Change of the Set Point value has been moved from the main display to the Operation menu.

- Graphical view.

A graphical view of the Set, Sup, Ret and USDA1+2+3 temperature has been added to the Datalog view. The  on the keypad is a shortcut to the Graphical view.

- Trip start.

The manual trip start function has been removed.

- Program.

A program function has been added to the Operation menu. The program function consists of 2 separated programs:

Multiple Temperature Settings (MTS): A program which automatically changes the unit settings throughout the journey. The wanted settings (setpoint, humidity, duration and ramp up/down speed) are set prior to the program start.

Cold Treatment (CT): A program which monitor the 3 USDA temperature sensors throughout the cold treatment. The wanted settings (Treatment setpoint, treatment duration, maximum USDA temperature and final temperature) are set prior to the program start. During the cold treatment it is only possible to change the treatment temperature and final temperature.

- Defrost function.

The user controlled Defrost interval has been removed, an automatic Demand Defrost (DoD) has been integrated.

- Fresh air exchange.

The fresh air scale has been updated.

- Function test.

The user can start the individual steps in the function test.