A2 PROSOIL	BOREHOLE NO: 01	
	LOCATION : Baligaw (CH.26+081) Road (R-812).	
PROJECT : Baligaw Steel Bridge, Munshigonj.	DEPTH OF BORING : 51.0m	CHAINAGE : 26+081 m R. L. : 6.096m
CLIENT : Roads and Highway Department.	DATE OF BORING : 09-06-2016 to 10-06-2016	B. W. T : 3.6 m below from E. G. L.

RL/ THICKNESS	SOIL STRATA	BORELOG	SAMPLING FROM (m)	SAMPLING TO (m)	SPT-N Value Blow/300mm N1=150 (mm)	N2=300 (mm)	N3=450 (mm)	N=N2+N3	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	Max^{m} Penetration
4.5m	Brown 7.5YR (5/4), medium dense, silty Sand, SM.		1.5	1.95	4	7	8	15	D-1	15	
			3	3.45	3	4	5	9	D-2	9	
			4.5	4.95	2	2	3	5	D-3	5	
1.5m	Light Yellowish Brown 10YR (6/4), loose, silty Sand, SM.		6	6.45	1	1	1	2	D-4	2	
1.5m	Gray 7.5YR (5/1), very loose, silty Sand, SM.		7.5	7.95	3	5	7	12	D-5	12	
1.5m	Dark Gray 7.5YR (4/1), medium dense, silty Sand, SM.		9	9.45	4	6	8	14	D-6	14	
6.0m	Gray 7.5YR (5/1), loose to medium dense, silty Sand, SM.		10.5	10.95	2	3	4	7	D-7	7	
			12	12.45	1	2	2	4	D-8	4	
			13.5	13.95	1	2	3	5	D-9	5	
			15	15.45	5	6	7	13	D-10	13	
1.5m	Gray 7.5YR (6/1), medium dense, silty Sand, SM.		16.5	16.95	6	7	9	16	D-11	16	
6.0m	Gray 7.5YR (5/1), dense, silty Sand, SM.		18	18.45	7	7	9	16	D-12	16	
			19.5	19.95	5	7	12	19	D-13	19	
			21	21.45	5	13	15	28	D-14	28	
			22.5	22.95	7	11	13	24	D-15	24	
3.0m	Brown 7.5YR (5/3), dense, silty Sand, SM.		24	24.45	6	12	14	26	D-16	26	
			25.5	25.95	7	17	21	38	D-17	38	
10.5m	Brown 7.5YR (5/2), very dense, silty Sand, SM.		27	27.45	9	22	25	47	D-18	47	
			28.5	28.95	9	20	24	44	D-19	44	
			30	30.45	9	28	20	48	D-20	48	
			31.5	31.95	11	30	10	40	D-21	40	
			33	33.45	10	29	11	40	D-22	40	
			34.5	34.95	12	30	17	47	D-23	47	
			36	36.45	10	31	10	41	D-24	41	
6.0m	Brown 7.5YR (5/3), very dense, silty Sand, SM.		37.5	37.95	15	35	10	45	D-25	45	
			39	39.45	15	30	13	43	D-26	43	
			40.5	40.95	13	30	14	44	D-27	44	
			42	42.45	15	30	10	40	D-28	40	
9.45m	Brown 7.5YR (5/2), very dense, silty Sand, SM.		43.5	43.95	18	41	9	50	D-29	50/175	
			45	45.45	19	43	7	50	D-30	50/162.5	
			46.5	46.95	17	30	20	50	D-31	50/175	
			48	48.45	16	26	24	50	D-32	50/175	
			49.5	49.95	17	40	10	50	D-33	50/200	
			51	51.45	16	36	14	50	D-34	50/200	

RL WITH REPECT TO TOPOGRAPHY SURVEY.

LEGEND FOR BOREHOLE AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY | SILT | PEAT/HIGHLY ORGANIC SOIL | UNDISTURBED SAMPLE

MICACEOUS FINE SAND/SILT | SAND | SHALE | DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS. AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED