A2 PROSOIL	BOREHOLE NO: 01	
	LOCATION : (CH. 18+500) Sreenagar, Munshiganj.	
PROJECT : Alamin Bazar Bridge.	DEPTH OF BORING : 33.0m	**CHAINAGE : CH. 18+500 R. L. : 4.0m**
CLIENT : Roads and Highways Departmnt.	DATE OF BORING : 07-04-2016 to 08-04-2016	B. W. T : 7.0m below from E. G. L.

RL/ THICKNESS	SOIL STRATA	BORELOG	SAMPLING FROM (m)	SAMPLING TO (m)	SPT-N Value Blow/300mm N1=150 (mm)	N2=300 (mm)	N3=450 (mm)	N=N2 +N3	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	Max^{m} Penetration
4.5m	**RUBBISH.**		4.5	4.95	4	6	9	15	D-3	15	
			6	6.45	5	7	10	17	D-4	17	
6.0m	Brown 7.5YR (5/2), stiff to very stiff, Low Plasticity Clay with Sand, CL.		7.5	7.95	5	6	10	16	D-5	16	
			9	9.45	5	8	12	20	D-6	20	
			10.5	10.95	10	15	23	38	D-7	38	
			12	12.45	14	18	25	43	D-8	43	
			13.5	13.95	15	22	25	47	D-9	47	
			15	15.45	17	23	26	49	D-10	49	
			16.5	16.95	16	22	26	48	D-11	48	
			18	18.45	18	28	22	50	D-12	50/250	
			19.5	19.95	17	25	25	50	D-13	50/250	
22.95m	Brown 7.5YR (5/2), very dense, Silty Sand, SM.		21	21.45	20	30	20	50	D-14	50/225	
			22.5	22.95	18	29	21	50	D-15	50/250	
			24	24.45	19	33	17	50	D-16	50/175	
			25.5	25.95	19	32	18	50	D-17	50/200	
			27	27.45	20	35	15	50	D-18	50/200	
			28.5	28.95	20	33	17	50	D-19	50/225	
			30	30.45	22	37	13	50	D-20	50/175	
			31.5	31.95	22	40	10	50	D-21	50/175	
			33	33.45	25	42	8	50	D-22	50/163	

RL WITH REPECT TO TOPOGRAPHY SURVEY.

LEGEND FOR BOREHOLE AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY	SILT	PEAT/HIGHLY ORGANIC SOIL	UNDISTURBED SAMPLE
MICACEOUS FINE SAND/SILT	SAND	SHALE	DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS. AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED