A2 PROSOIL	BOREHOLE NO: BH-01	
	LOCATION : Munshiganj	
PROJECT : Jinjira-Keraniganj-Nawabganj-Dohar-Srinagar Highway Development (with Kadamtoli to Johnny Tower Link) (R-820)	DEPTH OF BORING : 30.0m	R. L. : 9.91m
CLIENT : ROADS & HIGHWAYS DEPARTMENT.	DATE OF BORING : 11-02-2021	B. W. T : 2.5m below from E. G. L.

RL/ THICKNESS	SOIL STRATA	BORELOG	SAMPLING FROM (m)	SAMPLING TO (m)	SPT-N Value Blow/300mm N1=150 (mm)	N2=300 (mm)	N3=450 (mm)	N=N2 +N3	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	Max^{m} Penetration
6.0m	Grayish Brown, loose, Silty Sand, SM.		1.5	1.95	2	2	4	6	D-1	6	
			3	3.45	2	2	2	4	D-2	4	
			4.5	4.95	2	3	5	8	D-3	8	
4.5m	Gray, medium stiff, Lean Clay, CL.		6	6.45	2	3	4	7	D-4	7	
			7.5	7.95	2	3	4	7	D-5	7	
			9	9.45	1	2	3	5	D-6	5	
1.5m	Gray, loose, Silty Sand, SM.		10.5	10.95	2	3	5	8	D-7	8	
3.0m	Gray, very loose to loose, Silt, ML.		12	12.45	2	2	3	5	D-8	5	
			13.5	13.95	1	1	2	3	D-9	3	
1.5m	Gray, medium stiff, Lean Clay, CL.		15	15.45	2	2	3	5	D-10	5	
4.5m	Gray, very loose to loose, Silt, ML.		16.5	16.95	2	2	3	5	D-11	5	
			18	18.45	1	1	2	3	D-12	3	
			19.5	19.95	1	2	2	4	D-13	4	
3.0m	Gray, soft to medium stiff, Lean Clay, CL.		21	21.45	1	2	3	5	D-14	5	
			22.5	22.95	1	2	2	4	D-15	4	
1.5m	Gray, medium dense, Silt, ML.		24	24.45	3	5	6	11	D-16	11	
4.95m	Gray, medium dense to very dense, Silty Sand, SM.		25.5	25.95	6	10	15	25	D-17	25	
			27	27.45	10	12	12	24	D-18	24	
			28.5	28.95	10	12	16	28	D-19	28	
			30	30.45	11	24	27	51	D-20	51	

RL WITH RESPECT TO TOPOGRAPHIC SURVEY.

LEGEND FOR BOREHOLE AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY	SILT	PEAT/HIGHLY ORGANIC SOIL	UNDISTURBED SAMPLE
MICACEOUS FINE SAND/SILT	SAND	SHALE	DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS. AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED