A2 PROSOIL	BOREHOLE NO: Pier-01	Easting: 772087	Northing: 2889165
	LOCATION : Sonahat Bridge Bhurungamari,Kurigram.		CHAINAGE: 4+900 km.
PROJECT : DESIGN OF 645.015M (4×36.58M+10×48.78M) LONG P.C GIRDER SONAHAT BRIDGE OVER DUDHKUMAR RIVER AT 6TH K.M.	DEPTH OF BORING : 51.0m		R. L. : 26.698m.
CLIENT : ROADS & HIGHWAYS DEPARTMENT.	DATE OF BORING : 01-09-2020 to 05-09-2020		B. W. T : 1.0m below from E. G. L.

RL/ THICKNESS	SOIL STRATA	BORELOG	SAMPLING FROM (m)	SAMPLING TO (m)	SPT-N Value Blow/300mm N1=150 (mm)	N2=300 (mm)	N3=450 (mm)	N=N2 +N3	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	Max^{m} Penetration
4.5m	Gray, very soft, Lean Clay, CL.		1.5	1.95	1		1	1	D-1	1	
			3	3.45	1		1	1	D-2	1	
3.0m	Gray, loose, Silt, ML.		4.5	4.95	1	2	3	5	D-3	5	
			6	6.45	1	2	2	4	D-4	4	
1.0m	Gray, soft, Lean Clay, CL.		7.5	7.95	1	1	1	2	D-5	2	
1.0m	Gray, loose, Silt, ML.		9	9.45	1	2	3	5	D-6	5	
			10.5	10.95	1	2	3	5	D-7	5	
			12	12.45	4	4	5	9	D-8	9	
			13.5	13.95	3	4	5	9	D-9	9	
			15	15.45	4	5	7	12	D-10	12	
			16.5	16.95	6	8	12	20	D-11	20	
			18	18.45	5	10	16	26	D-12	26	
			19.5	19.95	20	13	14	27	D-13	27	
			21	21.45	8	10	14	24	D-14	24	
			22.5	22.95	9	11	12	23	D-15	23	
40.95m	Gray to Brown, loose to very dense, Silty Sand, SM. (trace mica from 10.5m to 18.0m)		24	24.45	13	22	19	41	D-16	41	
			25.5	25.95	10	10	11	21	D-17	21	
			27	27.45	7	9	11	20	D-18	20	
			28.5	28.95	22	22	22	44	D-19	44	
			30	30.45	24	23	27	50	D-20	50/290	
			31.5	31.95	21	32	18	50	D-21	50/230	
			33	33.45	21	26	24	50	D-22	50/270	
			34.5	34.95	15	19	18	37	D-23	37	
			36	36.45	18	19	24	43	D-24	43	
			37.5	37.95	20	31	19	50	D-25	50/270	
			39	39.45	13	17	17	34	D-26	34	
			40.5	40.95	15	20	24	44	D-27	44	
			42	42.45	17	17	20	37	D-28	37	
			43.5	43.95	14	17	26	43	D-29	43	
			45	45.45	20	25	25	50	D-30	50/280	
			46.5	46.95	17	18	28	46	D-31	46	
			48	48.45	20	28	22	50	D-32	50/240	
			49.5	49.95	8	14	36	50	D-33	50/295	
			51	51.45	42	43	7	50	D-34	50/160	

RL WITH RESPECT TO TOPOGRAPHIC SURVEY.

LEGEND FOR BORELOG AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY | SILT | PEAT/HIGHLY ORGANIC SOIL | UNDISTURBED SAMPLE

MICACEOUS FINE SAND/SILT | SAND | SHALE | DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS. AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED