A2	PROSOIL	BH NO: 14	Longitude: E 89°14'11.98"	Latitude: N 23°32'31.15"
		Location: Mail Post Magura 21KM.		CHAINAGE: .
Name of Project:Geotechnical Investigation for Subregional Transport Project Preparatory Facility, Road Component: Package-2		Type of Drill Rig: Manual Rotary	Borehole Depth: 15.0m	RL: 2.31m above from Road Level
CLIENT : Hifab International.		Commencement Date: 03-04-2015	Completed Date: 03-04-2015	G. W. T : 5.48m below from E.G.L.

RL/ THICKNESS	SOIL STRATA	BORE LOG	SAMPLING From (m)	SAMPLING To (m)	SPT-N Value Blow/300mm N1=150 (mm)	N2=300 (mm)	N3=450 (mm)	N=N2+N3	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	% Sand	% Passing 200	% LL	% PI	SP Gravity	% W_n
1.5			1.5	1.95	3	4	5	9	D-1	9	20.9	79.1	55.8	53.6	2.66	24.88
0			3.0	3.45	3	5	5	10	D-2	10	20.9	75.7	55.5	55.8	2.66	23.93
-3			4.5	4.95	3	5	5	10	D-3	10	24.3	75.7	62.9	55.5	2.66	22.73
-6			6.0	6.45	3	5	7	12	D-4	12	20.9	75.7	60.5	62.9	2.66	22.36
			7.5	7.95	4	6	7	13	D-5	13	16	84	46.3	60.5	2.63	22.6
-7			9.0	9.45	5	7	8	15	D-6	15	20.9	75.7	53.5	46.3	2.66	20.01
-9			10.5	10.95	7	9	12	21	D-7	21	12.9	87.1	46.3	53.5	2.65	24.19
-12			12.0	12.45	12	20	25	45	D-8	45	20.9	75.7	53.5	41.9	2.66	24.88
			13.5	13.95	13	26	24	50	D-9	50	80.7	19.3	55.8	55.8	2.68	23.93
-13			15.0	15.45	14	25	25	50	D-10	50	80.6	19.3	55.5	55.5	2.66	22.73

RL WITH REPECT TO TOPOGRAPHY SURVEY.

7.5m — Light Gray 10YR (7/1), medium dense, fine Sand, SM.

3.0m — Gray 10YR (6/1), Micaceous, fine Sand, SM.

4.95m — Gray 10YR (6/1), dense to very dense, fine Sand, SM.

D

LEGEND FOR BORELOG AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY | SILT | PEAT/HIGHLY ORGANIC SOIL | UNDISTURBED SAMPLE

MICACEOUS FINE SAND/SILT | SAND | SHALE | DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS. AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED 50/X = BLOWS 50, "X" MM PENETRATION