A2	PROSOIL	BOREHOLE NO: BH-1	
		LOCATION: Salampur Bazar, Natore.	
PROJECT : Telecommunication Tower.		DEPTH OF BORING: 21.0m	R. L.: 0.91m below from Road Level.
CLIENT : AXIATA (Bangladesh) Ltd.		DATE OF BORING: 26-03-2010.	G. W. T : 3.04m below from E. G. L.

THICKNESS	SOIL STRATA	BORELOG	UNDISTURBED SAMPLE	DISTURBED SAMPLE	DEPTH (m) SPT VALUES (BLOWS / 300mm)	Grain Size Distribution, % Clay %, Silt %, Sand %	Max^{m} Penetration
5.0m	Brown 7.5YR (5/4), medium plasticity, very soft to medium stiff Clay, CL.		UD-1, UD-2, UD-3, UD-4	D-1, D-2, D-3, D-4, D-5	3, 3, 2, 1, 7		
4.0m	Very pale Brown 10YR (7/3), high plasticity, very soft to stiff Clay, CH.			D-6, D-7, D-8, D-9	9, 10, 11, 2		
3.0m	Brown 7.5YR (5/4), medium plasticity, very soft to very stiff, silty Clay, CL.			D-10, D-11	5, 26		
1.5m	Light bluish Gray Gley2 (7/1), dense to very loose, fine Sand, SW.			D-12	1		
1.5m	Brown 7.5YR (5/4), medium plasticity, very soft to stiff Clay, CL.			D-13	10		
4.5m	Very pale Brown 10YR (7/3), high plasticity, medium stiff to very stiff Clay, CH.			D-14, D-15, D-16	15, 16, 26		
1.95m	Red 2.5YR (5/6), dense to very dense, silty Sand, SM.			D-17	33		

LEGEND FOR BORELOG AND GRAIN SIZE DISTRIBUTION (BASED ON 'ASTM CLASSIFICATION D-2487')

PLASTIC CLAY | SAND | SILT | SHALE

PEAT/HIGHLY ORGANIC SOIL | MICACEOUS FINE SAND/SILT | UNDISTURBED SAMPLE | DISTURBED SAMPLE

N- BLOWS DELIVERED PER FOOT BY A 140 LB HAMMER FALLING 30 INCHES

MAX^{m} PENETRATION= 50 BLOWS

AFTER 50 BLOWS PENETRATION DEPTH WERE MEASURED