Holo-Projector Lite - User Manual

Official Technical Specification, Operating Instructions & Support Policy

Category:	Electronics	**Retail Price:**	$299.50
Model Number:	HPL-300-VOL	**Warranty Term:**	1 Month Limited

1. Product Overview & Technical Specifications

The Holo-Projector Lite is a portable spatial holographic projection terminal designed to render true volumetric 3D imagery directly into mid-air without requiring specialized eyewear or projection screens. Featuring a precision micro-laser diode array combined with a high-speed optical refraction prism, it outputs 4K equivalent spatial voxel resolution across a generous 180-degree hemispherical viewing angle. The hardware integrates dual spatial audio speakers (5W RMS each) that sync acoustic wavefronts directly with projected imagery. With comprehensive connectivity including Wi-Fi 6E, Bluetooth 5.3, HDMI 2.1, and 100W USB-C Power Delivery, the Holo-Projector Lite bridges the gap between creative multimedia production, interactive architectural modeling, rapid engineering design reviews, and immersive telepresence conferencing.

2. Setup & Operating Instructions

Operating the Holo-Projector Lite requires minimal setup. Place the projector on a stable, level surface in an indoor setting with moderate to low ambient lighting for optimal contrast. Connect the supplied 100W USB-C fast charger into the power port. Depress the power button for two seconds until the illuminated perimeter ring glows azure. Pair the device with your laptop, smartphone, or workstation using the HoloSync app or connect directly via the high-speed HDMI input. Use the tactile rotary dial on top of the projector to adjust spatial depth focus until the floating calibration cube aligns sharply in the air. To stream content, drag compatible OBJ, glTF, or spatial video formats into the streaming window, and manage viewing angles via touch gestures in the companion software or through the included infrared remote control.

3. Troubleshooting & Diagnostics Guide

If you encounter technical issues during projection, execute the following troubleshooting protocols. Issue 1: Projected hologram appears blurry, fragmented, or flickers intermittently. Resolution: Gently wipe the top optical refraction glass with the included anti-static microfiber cloth, verify there are no harsh direct spotlights striking the lens, and adjust the focal depth dial. Issue 2: Audio playback is unsynchronized with the 3D visual stream. Resolution: Re-pair the Bluetooth connection or switch from wireless casting to direct HDMI 2.1 cable mode to minimize latency. Issue 3: Projector suddenly powers down during rendering. Resolution: Check for ventilation blockages around the base cooling intake; if the overheat safety sensor tripped, allow the unit 15 minutes to cool before restarting at reduced ambient room temperature. Always ensure air filters are clean.

4. Warranty Terms & Customer Support Information

Warranty Summary: 1 Month (30 Days) Limited Manufacturer Protection

The Holo-Projector Lite includes a comprehensive 1-month (30-day) limited hardware warranty valid from the verified delivery date. The warranty protects against factory defects in laser projection assemblies, optical emitter failures, internal power board defects, and integrated wireless module malfunctions. Damage caused by drops, scratches on the prism glass, liquid immersion, or using uncertified power adapters is strictly excluded from warranty protection. For warranty claims or technical RMA processing within the 1-month period, email our customer service desk at support@agentichelpdesk.com. Please provide your transaction receipt, device serial number, and a brief video documenting the optical failure to initiate prompt return processing.