Hyper-Drive SSD 2TB - User Manual

Official Technical Specification, Operating Instructions & Support Policy

Category:	Electronics	**Retail Price:**	$199.99
Model Number:	HD-2TB-NVME	**Warranty Term:**	1 Month Limited

1. Product Overview & Technical Specifications

The Hyper-Drive SSD 2TB is a premier M.2 2280 NVMe solid-state drive built on PCIe 4.0 x4 architecture, designed for hardcore PC gamers, creative video editors, and machine learning practitioners who require blistering storage performance. Featuring cutting-edge 176-layer 3D TLC NAND flash coupled with a multi-core controller and 2GB of dedicated DDR4 DRAM cache, the drive achieves sequential read speeds up to 7,400 MB/s and sequential write speeds up to 6,800 MB/s. It comes equipped with an ultra-thin graphene thermal heat-spreader to mitigate thermal throttling under prolonged sustained workloads, and supports hardware-accelerated AES 256-bit encryption along with a formidable endurance rating of 1,200 Terabytes Written (TBW).

2. Setup & Operating Instructions

Follow standard precautions when installing the Hyper-Drive SSD 2TB into your motherboard. First, shut down your desktop PC, disconnect the main AC power cord, and touch an unpainted metal surface to discharge static electricity. Locate the primary M.2 slot connected directly to the CPU PCIe lanes for maximum throughput. Carefully insert the drive at a 30-degree angle into the M.2 keyed slot until fully seated, then gently press down and secure it with the provided M.2 mounting screw or motherboard retention latch. Reassemble your PC and boot into the operating system. In Windows, open Disk Management (or 'fdisk / parted' in Linux), initialize the newly detected disk as GPT, and create an NTFS or ext4 partition to begin lightning-fast file operations.

3. Troubleshooting & Diagnostics Guide

Consult the troubleshooting guide below to resolve storage detection or speed concerns. Issue 1: BIOS/UEFI or Windows does not recognize the SSD. Resolution: Ensure the drive is installed in an NVMe-capable slot rather than a legacy SATA-only M.2 slot, update your motherboard BIOS to the latest version, and verify storage controller settings are set to AHCI/NVMe rather than legacy IDE. Issue 2: Sequential transfer speeds test significantly below 7,000 MB/s. Resolution: Confirm the drive is running in PCIe 4.0 x4 mode rather than PCIe 3.0 x2 via CrystalDiskInfo or Hyper-Drive Utility. Issue 3: Drive reports high temperatures. Resolution: Ensure the motherboard M.2 thermal heatsink or included graphene pad makes complete contact with the controller chip.

4. Warranty Terms & Customer Support Information

Warranty Summary: 1 Month (30 Days) Limited Manufacturer Protection

The Hyper-Drive SSD 2TB includes a 1-month (30-day) limited hardware warranty valid from the confirmed delivery date. The warranty guarantees protection against NAND silicon failure, controller chip burnout, and firmware corruption under normal consumer workload patterns. The 1-month warranty is rendered void if the drive exceeds 100 TBW written within the initial 30 days (such as from continuous crypto-mining plots), or if the circuit board displays evidence of physical snapping, soldering modifications, or liquid contact. To initiate a warranty return within 1 month, contact support@agentichelpdesk.com with your invoice and a SMART diagnostic health screenshot for rapid RMA authorization.