

A Major-Project Report

on

Evaluating the Performance of LSTM, GRU, RNN in Traffic Flow Prediction at Different Time Scales

Submitted to the Dept. of Information Technology, SNIST
in the partial fulfillment of the academic requirements for the award of

B. Tech (Information Technology)

under JNTUH

by

Mohd Umair Ahmed (22311A12B2)


N.Naveen (22311A12B3)

P.Sushanth (22311A12C2)

under the guidance of

Mr. G. Nuthan Kumar

Assistant Professor



Department of Information Technology

School of Computer Science and Informatics

SreeNidhi Institute of Science and Technology (An Autonomous Institution)

Yamnampet, Ghatkesar Mandal, R. R. Dist., Hyderabad – 501301


affiliated to

Jawaharlal Nehru Technological University Hyderabad

Hyderabad – 500 085

2025–26

Department of Information Technology
School of Computer Science and Informatics
SreeNidhi Institute of Science and Technology



Certificate

This is to certify that the Group-Project report on “Evaluating the Performance of LSTM, GRU, RNN in Traffic Flow Prediction at Different Time Scales” is a Bonafide work carried out by Mohd Umair Ahmed (22311A12B2), N. Naveen (22311A12B3), P. Sushanth (22311A12C2) in the partial fulfillment for the award of B. Tech degree in Information Technology, SreeNidhi Institute of Science and Technology, Hyderabad, affiliated to Jawaharlal Nehru Technological University Hyderabad (JNTUH), Hyderabad under our guidance and supervision. The results embodied in the Group-Project work have not been submitted to any other University or Institute for the award of any degree or diploma.

Internal Guide	Project Coordinator1	Project Coordinator2	Head of the Department
Mr.G.Nuthan Kumar	Dr. K. Kranthi Kumar	Mr. P. Mahesh Kumar	Dr. Sunil Bhutada
Assistant Professor	Associate Professor	Assistant Professor	Professor & HOD IT
Dept. of IT	Dept. of IT	Dept. of IT	

External Examiner

Date:

DECLARATION

We, Mohd Umair Ahmed(22311A12B2), N. Naveen(22311A12B3) P. Sushanth(22311A12C2) students of **SreeNidhi Institute of Science and Technology, Yamnampet, Ghatkesar**, studying ivth year iind semester, **Information Technology** solemnly declare that the Group project work, titled “**Evaluating the Performance of LSTM, GRU, RNN in Traffic Flow Prediction at Different Time Scales**” is submitted to **SreeNidhi Institute of Science and Technology** for partial fulfillment for the award of degree of Bachelor of technology in **Information Technology**.

It is declared to the best of our knowledge that the work reported does not form part of any dissertation submitted to any other University or Institute for award of any degree.

Acknowledgements

We would like to express our immense gratitude and sincere thanks to **Mr. G. Nuthan Kumar, Assistant Professor** in Information Technology for his guidance, valuable suggestions and encouragement in completing the Group-Project work within the stipulated time.

We would like to express our sincere thanks to Dr. **P. Narasimha Reddy**, Executive Director, **Dr. T. Ch. Siva Reddy**, Principal, **Dr. Sunil Bhutada**, Professor & Head of the Department of Information Technology, **Dr. K. Kranthi Kumar**, Associate Professor & Group-Project Work Coordinator of the Department of Information Technology, SreeNidhi Institute of Science and Technology (An Autonomous Institution), Hyderabad for permitting us to do our Group-Project work.

Finally, we would also like to thank the people who have directly or indirectly helped us and parents and friends for their cooperation in completing the Group-Project work.

Mohd Umair Ahmed(22311A12B2)

N. Naveen(22311A12B3)

P. Sushanth(22311A12C2)

Abstract

Traffic congestion in smart and major cities has been one of the main problems in traffic management and system guidance. Due to the fast economic growth and the highly increasing number of vehicles, the first challenge is to successfully predict accurate traffic flow information to minimize traffic congestion and traffic accidents. Not long ago, many researchers started to focus more concentration on deep learning techniques, including Recurrent Neural Networks (RNN), especially due to their capacity to learn long term dependencies of sequence data and capture the nonlinearity nature of traffic flow. This paper has applied three different kinds of recurrent neural network architecture such as simple RNN, Long Short-Term Memory (LSTM) and Gated Recurrent Unit (GRU) by considering different time intervals. The dataset collected from the California department of transportation in the year 2018 and 2019 have been used; however, few missing values have been discovered due to incorrect measurement and equipment errors. In this study, to ensure the data quality to be trained in our models and increase the model performance, the mean method on the same hours has been used to calculate and substitute the missing values. LSTM model is proposed in this study on both short and long-time intervals. Two popular metrics, including Mean Absolute Percentage Errors (MAPE) and Root Mean Squared Error (RMSE), have been used to evaluate the prediction efficiency.

LIST OF FIGURES

S. No	Fig. No.	Title of Figure	Page No.
1	5.1.1	System Architecture of Traffic Flow Prediction	16
2	4.5.1	Use Case Diagram	19
3	4.5.2	Class Diagram	20
4	4.5.3	Sequence Diagram	21
5	4.5.4	Activity Diagram	24
6	6.7.1	Python DJANGO webserver startup	45
7	6.7.2	Homepage of the Web Application	45
8	6.7.3	Simple RNN traffic prediction	47
9	6.7.4	GRU Traffic Prediction	48
10	6.7.5	LSTM Traffic Prediction	48
11	6.7.6	Traffic prediction for a particular area	49
12	6.7.7	Traffic status in entered area 1	50
13	6.7.8	Traffic status in entered area 2	51

LIST OF ABBREVIATIONS

Abbreviations	Full Form
RNN	Recurrent Neural Network
LSTM	Long Short Term Memory
GRU	Gated Recurrent Unit
MSE	Mean Squared Error
RMSE	Root Mean Squared Error
MAPE	Mean Absolute Percentage Error
CSV	Comma Separated Values
AI	Artificial Intelligence
ML	Machine Learning
DL	Deep Learning
ANN	Artificial Neural Network
SVM	Support Vector Machine
KNN	K-Nearest Neighbors
ARIMA	Autoregressive Integrated Moving Average
API	Application Programming Interface

GUI	Graphical User Interface
HTTP	HyperText Transfer Protocol
GPU	Graphics Processing Unit
CPU	Central Processing Unit
HTML	HyperText Markup Language
CSS	Cascading Style Sheets
JSON	JavaScript ObjectNotation
IDE	Integrated Development Environment
HDF5	Hierarchical Data Format version 5
URL	Uniform Resource Locator

TABLE OF CONTENTS

Abstract	v
List of Figures	vi
List of Abbreviations	vii
1. INTRODUCTION	1-4
1.1 Overview of Traffic Flow Prediction	1
1.2 Real-World Impact of Traffic Congestion	2
1.3 Need for Intelligent Traffic Prediction Systems	2
1.4 Characteristics of Traffic Data	2
1.5 Significance of Deep Learning in Traffic Prediction	3
1.6 Traditional vs Deep Learning Approaches	3
1.7 Problem Statement	4
1.8 Scope and Contributions of the Project	4
1.9 Objectives of the Project	4
2. LITERATURE SURVEY	5-9
2.1 Introduction	5
2.2 Evolution of Traffic Flow Prediction Techniques	5
2.2.1 Statistical Models	6
2.2.2 Machine Learning Models	6
2.2.3 Deep Learning Models	6
2.3 Review of Existing Methods	7
2.3.1 Statistical Approaches	7
2.3.2 Machine Learning Approaches	7
2.3.3 Recurrent Neural Networks (RNN)	8
2.3.4 Long Short-Term Memory (LSTM) Models	8
2.3.5 Gated Recurrent Unit (GRU)	8
2.3.6 Hybrid and Ensemble Models	8
2.4 Comparative Analysis of Existing Techniques	9
2.5 Limitations of Existing Work	9
2.6 Research Gap	9

2.7 Conclusion	10
3. SYSTEM ANALYSIS	11-14
3.1 Introduction	11
3.2 Existing System	11
3.3 Limitations Of Existing Functions	12
3.4 Proposed Systems	12
3.5 Advantages of Proposed Systems	13
3.6 Functional Requirements	13
3.7 Non-Functional Requirements	13
3.8 Data Requirements	13
3.9 Feasibility Study	14
3.10 Summary	14
4. SYSTEM DESIGN	15-25
4.1 Introduction	15
4.2 Overall System Architecture	15
4.3 Modules of System Architecture	16
4.3.1 Collection Module	16
4.3.2 Data Preprocessing Module	16
4.3.3 Sequence Generation Module	16
4.3.4 Model Training Module	16
4.3.5 Evaluation Module	17
4.3.6 Prediction Module	17
4.3.7 Visualization Module	17
4.3.8 Web Interface Module	18
4.4 Data Flow Prediction	18
4.5 UML Diagrams Overview	18
4.5.1 Use Case Diagram	19
4.5.2 Class Diagram	20
4.5.3 Sequence Diagram	21

4.5.4 Activity Diagram	24
4.6 Design Consideration	24
4.7 Summary	25
5. IMPLEMENTATION	26-42
5.1 Implementation Overview	26
5.2 Data Preprocessing Implementation	27
5.2.1 Code Snippet	
5.2.2 Algorithm	
5.3 Sequence Generation	28
5.4 Model Implementation	29
5.4.1 Simple RNN Implementation and Code Snippet	
5.4.2 GRU Implementation and Code Snippet	
5.4.3 LSTM Implementation and Code Snippet	
5.5 Model Training	30
5.5.1 Code Snippet	
5.6 Prediction Process	31
5.6.1 Code Snippet	
5.6.2 Algorithm	
5.7 Performance Evaluation	31
5.8 Web Application Implementation	31
5.8.1 Code Snippet	
5.9 Django views implementation	32-40
5.10 System Workflow	41
5.11 Data Flow Explanation	42
5.12 Summary	42
6. RESULTS AND DISCUSSION	43-51
6.1 Introduction	43
6.2 RNN Model Results	43
6.3 GRU Model Results	44

6.4 LSTM Model Results	44
6.5 Comparative Analysis	44
6.6 Prediction Results	44
6.7 Discussion	45-51
7. TESTING AND VALIDATION	52-55
7.1 Introduction	52
7.2 Types of Testing	52
7.3 Test Cases	53
7.4 Validation of Results	53
7.5 Performance Testing	54
8. CONCLUSION AND FUTURE SCOPE	56-57
8.1 Conclusion	55
8.2 Future Scope	57
REFERENCES	58-59
APPENDIX	60-65
Plagiarism Report	67

CHAPTER – 1 INTRODUCTION

Traffic congestion has become a major issue in modern cities due to rapid urbanization and the increasing number of vehicles. It leads to longer travel times, fuel wastage, pollution, and increased accident risks. Accurate traffic flow prediction is therefore essential for efficient traffic management and development of smart transportation systems. Traditional methods such as statistical models and regression techniques have been used for traffic prediction, but they struggle to handle the complex and dynamic nature of traffic data. Traffic patterns are nonlinear and depend on past observations, making it difficult for these methods to provide reliable results. With advancements in deep learning, models like Recurrent Neural Networks (RNNs) have gained importance for time-series prediction. However, simple RNNs face limitations in capturing long-term dependencies. To overcome this, advanced models such as Long Short-Term Memory (LSTM) and Gated Recurrent Unit (GRU) are used, as they can retain important information over longer periods and improve prediction accuracy. This project focuses on evaluating and comparing the performance of Simple RNN, GRU, and LSTM models for traffic flow prediction at different time intervals. The study uses real-world traffic data and applies preprocessing techniques such as handling missing values and normalization to improve data quality. The models are trained and evaluated using metrics like Mean Squared Error (MSE) and Root Mean Squared Error (RMSE).

The results of this project help identify the most effective model for accurate traffic prediction and contribute to the development of efficient and intelligent traffic management systems.

1.1 Overview of Traffic Flow Prediction

Traffic flow prediction is mainly about estimating how traffic will behave in the future based on past data. It is an important part of modern transportation systems because it helps in managing congestion and improving road conditions. In cities, traffic patterns keep changing throughout the day depending on factors like working hours, signals, and road usage. Because of this, predicting traffic is not a simple task.

Earlier, traffic prediction was done using basic statistical methods, but those approaches were not very effective when the data became large and complex. Nowadays, with the increase in data availability and computing power, more advanced methods are being used. In this project, we focus on using deep learning techniques to understand traffic patterns and make better predictions. These methods are more suitable for handling time-based data and can give more accurate results compared to older approaches.

1.2 Real-World Impact of Traffic Congestion

Traffic congestion is not just an inconvenience—it affects daily life in many ways. People waste a lot of time stuck in traffic, which reduces productivity and increases stress. It also leads to higher fuel consumption and contributes to air pollution. In busy cities, traffic jams can even affect emergency services like ambulances and fire vehicles. Because of these reasons, solving traffic-related problems has become very important. A good prediction system can help reduce these issues by giving early insights into traffic conditions.

1.3 Need for Intelligent Traffic Prediction Systems

In recent years, traffic congestion has increased a lot, especially in urban areas. The number of vehicles is growing continuously, but road infrastructure is not expanding at the same rate. Because of this imbalance, traffic jams have become very common. Traditional traffic control systems are mostly fixed and cannot respond quickly to changing conditions.

This creates a need for intelligent traffic prediction systems that can analyse data and give useful insights. Such systems can help reduce waiting time, avoid unnecessary delays, and improve overall traffic flow. They can also be useful for drivers to choose better routes and for authorities to manage traffic more efficiently. So, developing a system that can predict traffic accurately is very important for improving daily transportation.

1.4 Characteristics of Traffic Data

Traffic data has some unique properties that make it difficult to handle. It is time-dependent, meaning current traffic depends on past values. It is also highly dynamic and can change quickly due to various reasons like accidents, weather, or peak hours.

Another issue is that traffic data often contains missing or incorrect values because of sensor errors. This makes preprocessing an important step before applying any model. Understanding these characteristics is important for building a good prediction system.

1.5 Significance of Deep Learning in Traffic Prediction

Deep learning is useful in traffic prediction because it can handle complex and large datasets. It can automatically learn patterns from data without requiring too much manual effort. Models like RNN, LSTM, and GRU are designed for sequential data. A simple RNN can capture short-term patterns, but it has some limitations. LSTM and GRU improve upon this by remembering important information for longer periods. Because of this, they provide better prediction accuracy and are widely used in time-series problems.

1.6 Traditional vs Deep Learning Approaches

Traditional methods such as ARIMA and regression models were used earlier for traffic prediction. These methods work well only for simple and linear data. However, traffic data is complex and nonlinear, so these methods are not very effective.

Deep learning approaches are more advanced and can handle such complexity. They can learn from past data and adapt to changing conditions. In this project, both traditional ideas (basic understanding) and deep learning models are considered, but the main focus is on comparing RNN, GRU, and LSTM models.

1.7 Problem Statement

Traffic congestion is a growing problem in urban areas due to the increase in vehicles and changing traffic patterns. Existing prediction methods are not accurate enough because they cannot handle the complexity of traffic data.

Also, real-world datasets contain missing and noisy values, which affect performance. There is a need to build a system that can handle these issues and provide better predictions. This project focuses on solving this problem using deep learning models and comparing their performance.

1.8 Scope and Contributions of the Project

The scope of this project is to develop a traffic prediction system using deep learning techniques. It includes preprocessing the dataset, handling missing values, and converting the data into sequences using a sliding window method.

Three models—Simple RNN, GRU, and LSTM—are implemented and compared. The performance of these models is evaluated using error metrics. The project also includes a Django-based web application where users can view predictions. The main contribution is identifying the best model for traffic prediction and demonstrating its practical use.

1.9 Objectives of the Project

- To study traffic data and understand its behaviour.
- To preprocess the dataset and handle missing values
- To implement RNN, GRU, and LSTM models
- To compare their performance using evaluation metrics.
- To select the best model for prediction.
- To develop a web-based system using Django.
- To provide accurate traffic predictions for better decision-making.

CHAPTER – 2: LITERATURE SURVEY

2.1 Introduction

Traffic congestion has become a major concern in modern cities due to rapid urbanization, population growth, and the increasing number of vehicles on roads. Efficient traffic management requires accurate prediction of traffic flow patterns so that appropriate decisions can be made in advance. Traffic flow prediction plays a critical role in intelligent transportation systems by enabling better route planning, reducing travel time, minimizing congestion, and improving road safety.

However, predicting traffic flow is a complex task because traffic patterns are highly dynamic and influenced by multiple factors such as time of day, weather conditions, road infrastructure, and unexpected events. Traditional statistical models often fail to capture these nonlinear and time-dependent relationships effectively. As a result, researchers have increasingly turned to machine learning and deep learning approaches for more accurate and reliable predictions.

Among these approaches, deep learning models, especially Long Short-Term Memory (LSTM) networks, have shown significant promise in handling time-series data. LSTM models are capable of learning long-term dependencies and capturing temporal variations in traffic data. Despite their advantages, challenges such as missing data, noise in datasets, and computational complexity still affect their performance. This chapter reviews various research works related to traffic flow prediction, focusing on traditional models, machine learning techniques, and deep learning approaches, particularly LSTM-based methods.

2.2 Evolution of Traffic Flow Prediction Techniques

Traffic flow prediction methods have evolved over time, moving from simple mathematical models to advanced artificial intelligence-based techniques. These methods can be broadly categorized into three main groups:

2.2.1 Statistical Models

Early research in traffic prediction relied heavily on statistical techniques such as Autoregressive Integrated Moving Average (ARIMA) and Kalman filtering. These models assume that traffic data follows a linear pattern and remains relatively stable over time. While they are simple to implement, they are not suitable for capturing sudden fluctuations and nonlinear patterns in traffic data.

2.2.2 Machine Learning Models

With the advancement of computational techniques, machine learning models such as Support Vector Machines (SVM), K-Nearest Neighbors (KNN), and Decision Trees were introduced. These models improved prediction accuracy by learning patterns from historical data. However, they still require manual feature selection and struggle with sequential dependencies in time-series data.

2.2.3 Deep Learning Models

Deep learning approaches, particularly Recurrent Neural Networks (RNN) and LSTM, have revolutionized traffic flow prediction. These models automatically learn features from data and are capable of modeling complex temporal relationships. LSTM, in particular, addresses the limitations of traditional RNNs by retaining long-term memory and avoiding the vanishing gradient problem.

2.3 Review of Existing Methods

2.3.1 Statistical Approaches

Statistical models were among the earliest methods used for traffic prediction. ARIMA is one of the most widely used techniques in this category. It models traffic data as a time series and predicts future values based on past observations.

Although ARIMA performs reasonably well for short-term predictions under stable conditions, it has several limitations. It assumes linear relationships in data and cannot effectively handle nonlinear variations or sudden changes in traffic patterns. Additionally, it requires the data to be stationary, which is not always the case in real-world scenarios.

Kalman filtering is another statistical method used for traffic prediction. It provides real-time predictions by continuously updating estimates based on new observations. However, its performance is highly dependent on predefined parameters and assumptions, making it less flexible for complex datasets.

2.3.2 Machine Learning Approaches

Machine learning techniques improved upon statistical models by allowing systems to learn patterns directly from data. Models such as Support Vector Regression (SVR), KNN, and Artificial Neural Networks (ANN) have been widely used for traffic prediction tasks. KNN is a simple algorithm that predicts traffic flow based on similar past patterns. While it is easy to implement, its performance decreases with large datasets due to high computational cost.

Support Vector Regression maps input data into a higher-dimensional space and performs regression analysis. It provides better accuracy than traditional models but requires careful parameter tuning. Artificial Neural Networks introduced the ability to model nonlinear relationships in traffic data. However, traditional ANN models lack memory, making them less suitable for time-series prediction where past data plays a crucial role.

2.3.3 Recurrent Neural Networks (RNN)

Recurrent Neural Networks were developed to address the limitations of traditional neural networks in handling sequential data. RNNs use feedback connections to retain information from previous time steps, making them suitable for time-series prediction tasks such as traffic forecasting. Despite their advantages, RNNs suffer from issues such as vanishing and exploding gradients, which make it difficult to learn long-term dependencies. This limitation reduces their effectiveness in capturing complex traffic patterns over extended periods.

2.3.4 Long Short-Term Memory (LSTM) Models

LSTM is an advanced form of RNN designed to overcome the limitations of traditional RNNs. It introduces memory cells and gating mechanisms that control the flow of information through the network.

The three main components of an LSTM cell are:

- Forget gate (decides what information to discard)
- Input gate (determines what new information to store)
- Output gate (controls the output of the cell)

These mechanisms allow LSTM models to retain important information over long periods and ignore irrelevant data. As a result, LSTM has become one of the most effective models for traffic flow prediction. Several studies have demonstrated that LSTM outperforms traditional models in terms of accuracy and reliability. It can capture both short-term and long-term patterns in traffic data, making it suitable for real-time and future predictions. However, LSTM models require large amounts of data and are sensitive to missing or noisy values. Data preprocessing techniques are often required to improve their performance.

2.3.5 Gated Recurrent Unit (GRU)

GRU is another variant of RNN that simplifies the LSTM architecture by combining the forget and input gates into a single update gate. It requires fewer parameters and is computationally more efficient than LSTM. While GRU performs similarly to LSTM in many cases, LSTM is generally preferred for complex datasets due to its ability to model long-term dependencies more effectively.

2.3.6 Hybrid and Ensemble Models

To improve prediction accuracy, researchers have proposed hybrid models that combine multiple techniques. For example, combining LSTM with statistical models or other neural networks can enhance performance. Ensemble learning methods, which combine the outputs of multiple models, have also been used to improve robustness and accuracy. However, these approaches increase computational complexity and may not be suitable for real-time applications.

2.4 Comparative Analysis of Existing Techniques

A comparison of different traffic prediction approaches reveals the following insights:

- Statistical models are simple but limited to linear patterns

- Machine learning models improve accuracy but lack temporal understanding
- RNN models handle sequential data but struggle with long-term dependencies
- LSTM models provide the best performance for time-series prediction
- Hybrid models offer improved accuracy but increase complexity

Overall, LSTM-based models provide a good balance between accuracy and efficiency, making them the most widely used approach in modern traffic prediction systems.

2.5 Limitations of Existing Work

Despite significant advancements, existing traffic flow prediction models face several challenges:

- Inability to handle missing or incomplete data effectively
- High computational requirements for deep learning models
- Sensitivity to noise and data inconsistencies
- Difficulty in capturing sudden changes in traffic conditions
- Limited generalization across different locations and scenarios
- Lack of real-time adaptability in some models

These limitations highlight the need for improved models that can handle real-world complexities more effectively.

2.6 Research Gap

From the analysis of existing methods, it is evident that while LSTM models provide high accuracy, they still face challenges related to data quality and computational efficiency. Most existing approaches focus on improving prediction accuracy but do not adequately address issues such as missing data and real-time adaptability.

There is a need for a more robust system that can handle incomplete datasets, reduce computational overhead, and maintain high prediction accuracy. Additionally, integrating efficient preprocessing techniques with advanced deep learning models can significantly improve performance.

2.7 Conclusion

This chapter reviewed various approaches used for traffic flow prediction, including statistical methods, machine learning techniques, and deep learning models. Among these, LSTM has emerged as the most effective model for handling time-series data due to its ability to capture long-term dependencies.

However, several challenges remain, particularly in handling missing data and improving real-time performance. Addressing these challenges is essential for developing more reliable and efficient traffic prediction systems. The proposed work aims to overcome these limitations by enhancing the performance of LSTM-based models through improved data preprocessing and model optimization techniques.

CHAPTER – 3: SYSTEM ANALYSIS

3.1 Introduction

System analysis is an important phase in any project as it helps in understanding how the system should work and what requirements are needed. In this project, the analysis mainly focuses on understanding traffic data, selecting suitable models, and identifying how different components interact with each other. It also helps in defining the system's functionality, performance expectations, and limitations.

3.2 Existing Systems

Existing systems for traffic prediction suffer from multiple limitations that reduce their effectiveness in real-world scenarios. Most traditional models assume that traffic patterns follow a linear trend, which is rarely true in practice due to the dynamic and unpredictable nature of road conditions. These systems also struggle to handle large and complex datasets efficiently, leading to slower processing and less reliable outputs. Another major drawback is their inability to capture long-term dependencies in time-series data, which is essential for understanding traffic flow over extended periods. Additionally, they are not capable of adapting quickly to sudden changes such as accidents, roadblocks, or peak-hour congestion. As a result of these shortcomings, the overall prediction accuracy remains relatively low. Therefore, there is a clear need for more advanced and intelligent approaches that can overcome these challenges and provide more accurate and reliable traffic predictions.

3.3 Limitations of Existing Functions

Existing systems for traffic prediction have several limitations that reduce their effectiveness in real-world scenarios. Most traditional approaches assume that traffic patterns are linear, which is rarely the case due to the dynamic and unpredictable nature of road conditions. They also struggle to handle large and complex datasets efficiently, resulting in slower processing and less reliable outcomes. Another major drawback is their inability to capture long-term dependencies in time-series data, which is important for understanding patterns over time. In addition, these systems cannot quickly adapt to sudden changes such as accidents or peak-hour congestion. Due to all these issues,

their prediction accuracy remains comparatively low. Therefore, there is a clear need for more advanced approaches that can overcome these challenges and provide more accurate and practical traffic predictions.

3.4 Proposed Systems

The proposed system makes use of deep learning techniques to improve the accuracy of traffic flow prediction by implementing three main models: Simple RNN, GRU, and LSTM. Initially, the dataset is preprocessed by handling missing values and applying normalization to ensure consistent input for the models. A sliding window technique is then used to convert the continuous data into sequential patterns, which helps the models learn temporal relationships effectively. These sequences are used to train all three models and evaluate their performance. Among them, LSTM is expected to give better results because of its strong ability to capture long-term dependencies in time-series data. Additionally, the system is integrated with a web application developed using Django, which allows users to easily interact with the system and view traffic predictions in a practical and user-friendly manner.

3.5 Advantages of Proposed Systems

The proposed system offers several advantages over traditional traffic prediction methods, making it more effective for real-world applications. By leveraging deep learning models, it achieves higher prediction accuracy and can handle nonlinear and complex traffic patterns more efficiently. It is capable of capturing both short-term and long-term dependencies in time-series data, which improves the overall understanding of traffic flow. The system also performs well with large datasets, ensuring better scalability and robustness. In addition, the integration of a user-friendly web interface allows users to easily interact with the system and view predictions. Overall, the proposed approach provides more reliable and practical results for real-world traffic management scenarios.

3.6 Functional Requirements

Functional requirements define what the system is expected to perform in terms of its core operations. The system should allow users to upload or load a traffic dataset and then preprocess the data by handling missing values and applying normalization techniques. It must convert the processed data into sequences using a sliding window approach to make it suitable for time-series modeling. The system should be capable of training multiple deep learning models such as RNN, GRU, and LSTM, and then evaluate their performance using appropriate error metrics. Based on the trained models, it should predict future traffic values with good accuracy. Additionally, the system must display the results in a clear graphical format for better understanding and analysis, and also classify the predicted traffic levels into categories such as Low, Mild, and High for easier interpretation.

3.7 Non-Functional Requirements

Non-functional requirements describe how well the system should perform while carrying out its tasks. The system is expected to provide accurate and reliable traffic predictions, ensuring meaningful results for users. It should respond quickly to user inputs, offering a smooth and efficient interaction experience. The system must be capable of handling moderate-sized datasets without performance issues, maintaining good processing speed and stability. It should be designed in a way that is easy to use and understand, even for users with basic technical knowledge. Additionally, the system needs to be reliable during execution, minimizing errors or crashes, and it should utilize system resources efficiently to ensure optimal performance without unnecessary overhead.

3.8 Data Requirements

The system requires traffic data that includes time-based attributes such as date, time, and vehicle count, as these factors are essential for analyzing traffic patterns over time. The dataset should be provided in a structured format like CSV to ensure easy processing and compatibility with the system. Before feeding the data into the models, proper preprocessing is necessary. This involves handling missing values to avoid inconsistencies, removing irrelevant or unnecessary fields, and normalizing the data to maintain uniformity across all inputs. Effective data preparation plays a crucial role in

improving the performance and accuracy of the models, as well-processed data helps in better learning and more reliable predictions.

3.9 Feasibility Study

A feasibility study is carried out to determine whether the project can be implemented successfully in practical conditions. From a technical perspective, the system is developed using Python along with widely used libraries such as TensorFlow, Keras, and Pandas, all of which are easily accessible and well-supported. The system can run on standard computers without the need for high-end hardware, making it technically feasible. In terms of economic feasibility, the project does not involve significant costs since most of the tools and technologies used are open-source, keeping expenses minimal. From an operational point of view, the system is designed to be user-friendly and can be operated by individuals with basic technical knowledge. The inclusion of a web-based interface further simplifies user interaction, ensuring smooth and efficient usage.

3.10 Summary

This chapter discussed the analysis of the system, including existing methods, their limitations, and the proposed solution. It also explained the requirements, feasibility, and constraints of the system. This analysis helps in designing and implementing the system effectively in the next stages.

CHAPTER – 4: SYSTEM DESIGN

4.1 Introduction

System design explains how the proposed system is structured and how different components work together. In this project, the design focuses on handling traffic data, training deep learning models, and generating predictions. The system is divided into multiple modules so that each part can perform a specific task efficiently. This modular approach makes the system easier to understand and implement.

4.2 Overall System Architecture

The overall system architecture of the Traffic Flow Prediction System is designed in a structured and modular manner, as shown in Fig. 4.1.1 It follows a step-by-step flow, starting from raw data input and ending with the final prediction output displayed to the user. The architecture is divided into multiple layers, each responsible for a specific task, ensuring smooth data processing and efficient model performance.

The first layer is the **Data Ingestion and Transformation Layer**, where the system takes raw input data from the traffic dataset (CSV file containing attributes like vehicle count, time, and ID). This data is initially unprocessed and may contain inconsistencies or missing values. Therefore, it is passed to the preprocessing stage, where data cleaning and normalization are performed. This step ensures that the data is consistent and suitable for model training. After preprocessing, the system applies a **sequence generation process using the sliding window technique**, which converts the data into sequential input-output pairs required for time-series prediction.

The next layer is the **Deep Learning Core (Training Layer)**. In this stage, the processed sequences are used to train multiple deep learning models, namely Simple RNN, GRU, and LSTM. These models are trained in parallel to compare their performance. During training, an optimizer such as Adam is used to adjust model weights through backpropagation, and a loss function like Mean Squared Error (MSE) is used to measure the difference between actual and predicted values. This layer is responsible for learning patterns and dependencies in traffic data.

After training, the system moves to the **Evaluation and Serialization Layer**. In this stage, the performance of each model is evaluated using metrics such as RMSE, MAE, or error rates. Based on these metrics, the best-performing model is selected. This

selected model is then saved (serialized) in a suitable format (such as .h5) so that it can be reused later without retraining. This improves system efficiency and reduces computation time.

The final layer is the **Django Application Layer**, which handles user interaction and system integration. The backend processes include loading the trained model, receiving user input, and performing inference. The frontend interface allows users to enter inputs such as junction ID or area name and view the predicted results. The output is displayed in the form of graphs and categorized traffic levels like Low, Medium, or High for better understanding.

System Architecture




Fig 4.1.1 shows the architecture of the LSTM model used in the system for traffic flow prediction.

4.3 Modules of System Architecture

The system is divided into different modules, each performing a specific function:

4.3.1 Collection Module

This module is responsible for loading the dataset. The dataset contains traffic-related information such as date, time, and vehicle count. It serves as the input for the entire system.

4.3.2 Data Preprocessing Module

In this module, the raw data is cleaned and prepared for model training. Missing values are handled using suitable methods, and normalization is applied to scale the data. This step is important to improve model performance.

4.3.3 Sequence Generation Module

The processed data is converted into sequences using a sliding window approach. In this method, a set of previous values is used as input to predict the next value, helping the model learn temporal patterns effectively.

4.3.4 Model Training Module

This module includes implementation of deep learning models such as Simple RNN, GRU, and LSTM. Each model is trained using the prepared dataset.

4.3.5 Evaluation Module

After training, the models are evaluated using metrics like Mean Squared Error (MSE) and Root Mean Squared Error (RMSE). This helps in comparing model performance.

4.3.6 Prediction Module

The best-performing model is used to predict future traffic values based on the given input data. It processes the input through the trained model and generates accurate traffic predictions for upcoming time intervals, which are then presented to the user in a clear and understandable format.

4.3.7 Visualization Module

This module generates graphs to compare actual and predicted traffic values. It helps in understanding how well the model is performing.

4.3.8 Web Interface Module

A Django-based web application is used to interact with the system. Users can train models and view predictions through this interface.

4.4 Data Flow Prediction

The flow of data in the system follows a structured and organized process from input to output. Initially, the dataset is loaded and sent to the preprocessing module, where data cleaning and normalization are performed to ensure consistency and quality. After preprocessing, the data is transformed into sequences using appropriate techniques, making it suitable for time-series modeling. These sequences are then used to train the deep learning models effectively. Once the training phase is completed, the system uses new input data to generate predictions. The predicted results are then evaluated using relevant metrics and displayed in a graphical format for better understanding. This systematic flow ensures that each stage is properly executed and contributes effectively to producing accurate and meaningful results.

4.5 UML Diagrams Overview

To better understand the system design, different UML diagrams are used. These diagrams visually represent the structure and behavior of the system.

4.5.1 Use Case Diagram

The use case diagram of the Traffic Flow Prediction System represents how different users interact with the system and what functionalities are provided. It mainly focuses on the external view of the system, showing the relationship between users and various operations. In this project, two main actors are identified: the **Admin** and the **User**.

The **Admin** plays a major role in managing the system. The admin is responsible for uploading the dataset that contains traffic-related information such as date, time, and vehicle count. After uploading the dataset, the admin initiates the preprocessing step where missing values are handled and the data is normalized. The admin also triggers the model training process, where different deep learning models like RNN, GRU, and LSTM are trained using the prepared dataset. This role ensures that the system is properly configured and ready for prediction.

The **User**, on the other hand, interacts with the system to obtain traffic predictions. The user does not need technical knowledge about the backend process. Through the web interface, the user can provide input details such as a specific time or area and request traffic prediction. The system processes this input using the trained model and displays the predicted traffic conditions. The output is usually shown in a simple and understandable format, sometimes along with graphical representation.

The main use cases involved in the system include dataset loading, data preprocessing, sequence generation, model training, prediction, and result visualization. These use cases are connected to the respective actors based on their responsibilities. The admin is associated with operations like data handling and model training, while the user is mainly associated with prediction and viewing results.




Fig 4.5.1: Use Case Diagram of Traffic Flow Prediction System

4.5.2 Class Diagram

The class diagram of the Traffic Flow Prediction System represents the internal structure of the system by showing different classes, their attributes, and their relationships. It explains how the system is organized and how data flows between components. The system is divided into classes such as Dataset, Preprocessing, Sequence Generator, Model, Evaluation, and Prediction.

The **Dataset class** handles input data by loading traffic data from a CSV file. The **Preprocessing class** cleans the data by handling missing values, normalization, and feature extraction. The **Sequence Generator class** converts processed data into sequences using a sliding window technique for time-series prediction.

The **Model class** is responsible for building and training models like RNN, GRU, and LSTM. The **Evaluation class** measures model performance using metrics

such as MSE and RMSE. The **Prediction class** uses the best model to generate future traffic values.

All these classes are interconnected, where the output of one becomes the input for another, ensuring smooth data flow and efficient system implementation.




Fig 4.5.2: Class Diagram of Traffic Flow Prediction System

4.5.3 Sequence Diagram

The sequence diagram of the Traffic Flow Prediction System shows how different components of the system interact with each other in a step-by-step manner to generate traffic predictions. It mainly focuses on the flow of messages between the user, web interface, and backend modules over time. This diagram helps in understanding how a request is processed from start to end.

The process begins when the **User** interacts with the web interface and requests a traffic prediction by providing input details such as time or location. This request is first received by the **Django web application**, which acts as the main controller of the

system . The web server processes the request and forwards it to the appropriate backend functions.

Initially, the system ensures that the required dataset and trained model are available. If needed, the request is passed to the **Preprocessing module**, where the input data is cleaned, normalized, and converted into a suitable format. After preprocessing, the data is sent to the **Sequence Generation module**, which transforms the input into sequences using the sliding window technique.

These sequences are then passed to the **Prediction module**, where the trained LSTM model is used to generate the predicted traffic values. The model processes the input sequence and produces an output that represents the expected traffic condition.

Once the prediction is generated, the result is sent back to the Django server. The server then prepares the output in a user-friendly format, which may include numerical values and graphical representation. Finally, the result is displayed to the user through the web interface.

In case of model training, a similar sequence is followed where the admin initiates training, and the request flows through preprocessing, sequence generation, model training, and evaluation modules before storing the trained model.




Fig 4.5.3: Sequence Diagram of Traffic Flow Prediction System

4.5.4 Activity Diagram

The activity diagram of the Traffic Flow Prediction System represents the overall workflow of the system from input to output. It shows how different activities are performed step-by-step and how data flows through various stages. This diagram helps in understanding the complete working process of the system in a simple and structured way.

The process starts with **loading the dataset**, which contains traffic-related information such as date, time, and vehicle count . Once the dataset is loaded, the next step is **data preprocessing**, where missing values are handled and normalization is applied. This step ensures that the data is clean and suitable for further processing.

After preprocessing, the system moves to the **sequence generation stage**, where the data is converted into sequences using the sliding window technique. This is an important step because traffic data is time-dependent, and the models need sequential input to learn patterns effectively.

The next activity is **model training**, where deep learning models such as RNN, GRU, and LSTM are trained using the prepared dataset. During this stage, the models learn patterns from historical traffic data. Once training is completed, the system performs **model evaluation** using metrics like Mean Squared Error (MSE) and Root Mean Squared Error (RMSE) to determine which model performs best.

Based on the evaluation results, the best-performing model (LSTM) is selected for the next stage, which is **prediction**. In this step, the model takes input data and generates future traffic predictions.

After prediction, the system performs **result visualization**, where the predicted values are displayed in graphical form along with actual values for comparison. This helps users easily understand the results.

Finally, the output is shown to the user through the **web interface**, where the user can view traffic conditions such as low, medium, or high traffic.

Overall, the activity diagram clearly explains the complete workflow of the system, starting from data input to final output. It helps in visualizing how each step is connected and how the system processes data to produce accurate traffic predictions.

The activity diagram of the Traffic Flow Prediction System represents the overall workflow of the system from input to output. It shows how different activities are performed step-by-step and how data flows through various stages. This diagram helps

in understanding the complete working process of the system in a simple and structured way.

The process starts with **loading the dataset**, which contains traffic-related information such as date, time, and vehicle count . Once the dataset is loaded, the next step is **data preprocessing**, where missing values are handled and normalization is applied. This step ensures that the data is clean and suitable for further processing.

After preprocessing, the system moves to the **sequence generation stage**, where the data is converted into sequences using the sliding window technique. This is an important step because traffic data is time-dependent, and the models need sequential input to learn patterns effectively.

The next activity is **model training**, where deep learning models such as RNN, GRU, and LSTM are trained using the prepared dataset. During this stage, the models learn patterns from historical traffic data. Once training is completed, the system performs **model evaluation** using metrics like Mean Squared Error (MSE) and Root Mean Squared Error (RMSE) to determine which model performs best.

Based on the evaluation results, the best-performing model (LSTM) is selected for the next stage, which is **prediction**. In this step, the model takes input data and generates future traffic predictions.

After prediction, the system performs **result visualization**, where the predicted values are displayed in graphical form along with actual values for comparison. This helps users easily understand the results.

Finally, the output is shown to the user through the **web interface**, where the user can view traffic conditions such as low, medium, or high traffic.

Overall, the activity diagram clearly explains the complete workflow of the system, starting from data input to final output. It helps in visualizing how each step is connected and how the system processes data to produce accurate traffic predictions.

Additionally, the workflow ensures that each stage is executed in a proper sequence, improving the overall efficiency of the system. It also helps in identifying the role of each module clearly, making the system easier to understand. The structured flow reduces errors and improves the reliability of the predictions. It also allows easy debugging and testing of individual stages. Moreover, the modular design makes it easier to update or enhance the system in the future. This organized approach ultimately contributes to better performance and scalability of the system.




Fig 4.5.4: Activity Diagram of Traffic Flow Prediction System

4.6 Design Considerations

The system is implemented using a combination of widely used tools and technologies that support efficient development and performance. Python is used as the primary programming language for overall development due to its simplicity and strong ecosystem. Libraries like Pandas and NumPy are utilized for data processing and handling large datasets effectively. For building and training deep learning models, frameworks such as TensorFlow and Keras are used, as they provide powerful tools for model development. Visualization of results is done using Matplotlib, which helps in presenting data in a clear graphical format. Additionally, a web application is developed

using Django to enable user interaction. These technologies are widely adopted and offer strong support for building reliable and scalable machine learning applications.

4.7 Summary

This chapter explained the design of the traffic prediction system, including its architecture, modules, and data flow. It also described different UML diagrams used to represent the system structure and behavior. The design ensures that the system is well-organized and capable of providing accurate predictions.

CHAPTER – 5: IMPLEMENTATION

5.1 Implementation Overview

The implementation of the proposed Traffic Prediction System is carried out using Python, the Django framework, and deep learning techniques such as RNN, GRU, and LSTM. The system is designed as a web-based application that enables users to train models and predict traffic conditions efficiently. The backend of the system is developed using Django, which manages HTTP requests, URL routing, and template rendering. The frontend is built using HTML and CSS to provide a simple and interactive interface where users can initiate model training and prediction processes. The dataset is loaded from a CSV file containing traffic-related attributes such as date Time and vehicle count. The date Time field is processed to extract relevant features such as year, month, date, and hour. These features are used as input variables for training the models. Data preprocessing is performed using Min-Max Scaler to normalize the dataset. A sliding window technique is applied to transform the dataset into sequences suitable for deep learning models, which helps in capturing temporal dependencies in traffic data.

Three deep learning models are implemented:

- Simple RNN for capturing short-term dependencies
- GRU for improved learning efficiency and faster training
- LSTM for capturing long-term dependencies and achieving higher accuracy

The models are trained using historical data and stored in JSON and H5 formats for future use. During prediction, the trained LSTM model is loaded and used to forecast traffic values for different time intervals. Matplotlib is used for visualizing the results by plotting actual and predicted traffic values. The system also computes performance metrics such as Mean Squared Error (MSE) to evaluate the accuracy of the models.

5.2 Data Preprocessing Implementation

Before applying any model, the dataset is cleaned and prepared to ensure better performance. The dataset contains time-based attributes such as date, time, and vehicle

count. Missing values present in the dataset are handled using the mean method to maintain data consistency .

Further, the data is normalized using the Min-Max scaling technique so that all values fall within a similar range. This helps the model to learn efficiently. The date-time column is also processed to extract useful features such as hour, which plays an important role in identifying traffic patterns.

Before applying any model, it is important to clean and prepare the dataset properly. The dataset used in this project contains traffic-related details such as date, time, and number of vehicles.

In many real-world datasets, some values may be missing due to errors during data collection. To handle this problem, the missing values are replaced using the mean of the available values. This helps in maintaining consistency in the dataset.

Next, the date and time column is processed to extract useful information like the hour, because traffic patterns mainly depend on time. After that, normalization is applied using Min-Max scaling so that all values are brought into a similar range. This makes it easier for the model to learn patterns effectively.

5.2.1 Code Snippet

```
from sklearn.preprocessing import MinMaxScaler
import pandas as pd
data = pd.read_csv('traffic.csv')
data.fillna(data.mean(), inplace=True)
data['hour'] = pd.to_datetime(data['DateTime']).dt.hour
scaler = MinMaxScaler()
scaled_data = scaler.fit_transform(data[['Vehicles']])
```

5.2.2 Algorithm

- Step 1: Load the dataset
- Step 2: Check for missing values
- Step 3: Replace missing values using mean
- Step 4: Extract hour from DateTime column
- Step 5: Apply normalization
- Step 6: Store processed data

5.3 Sequence Generation

Since traffic data is time-dependent, it cannot be directly used for training. Therefore, a sliding window technique is applied to convert the dataset into sequences. In this method, a group of previous values is used to predict the next value.

This helps the model understand how traffic changes over time and improves prediction accuracy. The generated sequences are then used as input for training the deep learning models.

Traffic data is not independent; it depends on previous values. So, instead of using raw data directly, it is converted into sequences.

A sliding window technique is used for this purpose. In this method, a set of previous values is taken as input, and the next value is used as output. This helps the model understand how traffic changes over time.

5.3.1 Code Snippet

```
def create_sequences(data, time_steps=10):  
    X, y = [], []  
    for i in range(len(data)-time_steps):  
        X.append(data[i:i+time_steps])  
        y.append(data[i+time_steps])  
    return X, y
```

5.3.2 Algorithm: Data Preprocessing

- Step 1: Take normalized data
- Step 2: Select window size
- Step 3: Create input sequences
- Step 4: Assign next value as output
- Step 5: Repeat for entire dataset

5.4 Model Implementation

The system implements three different deep learning models—Simple RNN, GRU, and LSTM—to compare their performance in traffic prediction. All models are developed using the Keras Sequential API.

5.4.1 Simple RNN Implementation

The Simple RNN model is used as the basic model for sequence prediction. It processes data step-by-step and uses previous information to predict future values. In implementation, an RNN layer is added to the model along with a Dense output layer. Although it works well for short-term dependencies, it is not very effective for long sequences due to its limitation in remembering past information.

Code Snippet

```
from keras.models import Sequential
from keras.layers import SimpleRNN, Dense
model = Sequential()
model.add(SimpleRNN(50))
model.add(Dense(1))
model.compile(optimizer='adam', loss='mse')
```

5.4.2 GRU Implementation

The GRU model is an improved version of the Simple RNN. It uses gating mechanisms to control the flow of information, which helps in retaining important data and removing unnecessary information.

Compared to RNN, GRU provides better performance and faster training. It is capable of handling both short-term and medium-term dependencies in the traffic dataset.

Code Snippet

```
from keras.layers import GRU
model = Sequential()
model.add(GRU(50))
```

```
model.add(Dense(1))  
model.compile(optimizer='adam', loss='mse')
```

5.4.3 LSTM Implementation

The LSTM model is the most advanced model used in this project. It is designed to capture long-term dependencies in sequential data. It uses memory cells and gates to store and manage information effectively.

In this implementation, LSTM layers are added along with dropout layers to prevent overfitting. The model is trained for more epochs to learn complex patterns in the data. Among all models, LSTM gives the best performance and highest prediction accuracy.

Code Snippet

```
from keras.layers import LSTM, Dropout  
model = Sequential()  
model.add(LSTM(50, return_sequences=True))  
model.add(Dropout(0.2))  
model.add(LSTM(50))  
model.add(Dense(1))  
model.compile(optimizer='adam', loss='mse')
```

5.5 Model Training

The dataset is divided into training and testing sets to evaluate model performance. Each model is trained using a fixed number of epochs and batch size. The Mean Squared Error (MSE) is used as the loss function, and the Adam optimizer is used for optimization.

During training, the model learns patterns from historical traffic data, which helps in making accurate future predictions.

5.4.1.1 Code Snippet

```
model.fit(X_train, y_train, epochs=20, batch_size=32)
```

5.6 Prediction Process

After training, the LSTM model is selected for final prediction due to its better performance. The trained model takes input sequences and predicts future traffic values. The predicted output represents the expected traffic for a given time interval, which helps in understanding traffic conditions in advance.

5.2.1 Code Snippet

```
predictions = model.predict(X_test)
```

5.2.2 Algorithm

- Step 1: Load trained model
- Step 2: Provide input sequence
- Step 3: Generate prediction
- Step 4: Convert output to actual value
- Step 5: Display result

5.7 Performance Evaluation

To evaluate the performance of the models, error metrics such as Mean Squared Error (MSE) and Root Mean Squared Error (RMSE) are used. The results show that the Simple RNN has higher error compared to GRU and LSTM.

GRU performs better than RNN, but LSTM achieves the lowest error and gives the most accurate predictions. This confirms that LSTM is the most suitable model for traffic flow prediction in this system.

5.8 Web Application Implementation

To make the system easy to use, a web application is developed using Django. The backend handles the model processing, while the frontend allows users to interact with the system.

Users can train models and view predictions through a simple interface.

5.2.1 Code Snippet

```
if __name__ == '__main__':  
    os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'Traffic.settings')  
    execute_from_command_line(sys.argv)
```

5.9 Django Views Implementation

The Django views module handles the core functionality of the web application, including model training, prediction, and result visualization. It processes user requests, interacts with trained models, and returns the output to the frontend

Code:

```
import base64  
from io import BytesIO  
from pathlib import Path  
import re  
  
import matplotlib  
matplotlib.use("Agg")  
import matplotlib.pyplot as plt  
import numpy as np  
import pandas as pd  
from django.shortcuts import render  
from keras.layers import Dense, Dropout, GRU, LSTM, SimpleRNN  
from keras.models import Sequential, model_from_json  
from sklearn.metrics import mean_squared_error  
from sklearn.preprocessing import MinMaxScaler  
  
BASE_DIR = Path(__file__).resolve().parent.parent  
MODEL_DIR = BASE_DIR / "model"  
DATASET_PATH = BASE_DIR / "traffic.csv"  
WINDOW_SIZE = 10  
  
MODEL_DIR.mkdir(exist_ok=True)
```

```

input_scaler = MinMaxScaler(feature_range=(0, 1))
target_scaler = MinMaxScaler(feature_range=(0, 1))

def _load_training_data():
    dataframe = pd.read_csv(DATASET_PATH, nrows=300)
    dataframe["DateTime"] = pd.to_datetime(dataframe["DateTime"])
    dataframe = dataframe.drop(columns=["ID"])
    dataframe["Year"] = dataframe["DateTime"].dt.year
    dataframe["Month"] = dataframe["DateTime"].dt.month
    dataframe["Date_no"] = dataframe["DateTime"].dt.day
    dataframe["Hour"] = dataframe["DateTime"].dt.hour

    feature_frame = dataframe[["Junction", "Year", "Month", "Date_no",
"Hour"]].astype("float32")
    target_frame = dataframe[["Vehicles"]].astype("float32")

    scaled_features = input_scaler.fit_transform(feature_frame.values)
    scaled_targets = target_scaler.fit_transform(target_frame.values)

    x_train = []
    y_train = []
    for index in range(WINDOW_SIZE, len(scaled_features)):
        x_train.append(scaled_features[index - WINDOW_SIZE:index, :])
        y_train.append(scaled_targets[index, 0])

    return (
        dataframe,
        feature_frame,
        np.asarray(x_train, dtype="float32"),
        np.asarray(y_train, dtype="float32"),
    )

TRAFFIC_DATA, FEATURE_FRAME, X_TRAIN, Y_TRAIN =
_load_training_data()

```

```

def _load_saved_model(json_path, weights_path):
    if not json_path.exists() or not weights_path.exists():
        return None

    with json_path.open("r", encoding="utf-8") as json_file:
        loaded_model = model_from_json(json_file.read())

    loaded_model.load_weights(str(weights_path))
    return loaded_model

def _save_model(model, json_path, weights_path):
    model.save_weights(str(weights_path))
    with json_path.open("w", encoding="utf-8") as json_file:
        json_file.write(model.to_json())

def _plot_training_graph(actual_values, predicted_values, title):
    figure, axis = plt.subplots(figsize=(10, 4))
    axis.plot(actual_values, color="#ef476f", linewidth=2, label="Actual")
    axis.plot(predicted_values, color="#06d6a0", linewidth=2, label="Predicted")
    axis.set_title(title)
    axis.set_xlabel("Training samples")
    axis.set_ylabel("Vehicles")
    axis.grid(alpha=0.25)
    axis.legend(loc="upper right")
    figure.tight_layout()

    buffer = BytesIO()
    figure.savefig(buffer, format="png", bbox_inches="tight")
    plt.close(figure)
    return base64.b64encode(buffer.getvalue()).decode("utf-8")

def _plot_forecast_graph(hour_labels, predicted_values, area_name):
    figure, axis = plt.subplots(figsize=(10, 4))

```

```

x_positions = np.arange(len(predicted_values))
    axis.plot(x_positions, predicted_values, color="#118ab2", linewidth=2.5,
marker="o", markersize=4)
    axis.fill_between(x_positions, predicted_values, color="#118ab2", alpha=0.12)
    axis.set_title(f"24-Hour Forecast for {area_name}")
    axis.set_xlabel("Hour")
    axis.set_ylabel("Predicted vehicles")
    tick_positions = list(range(0, len(hour_labels), 3))
    if tick_positions[-1] != len(hour_labels) - 1:
        tick_positions.append(len(hour_labels) - 1)
    axis.set_xticks(tick_positions)
    axis.set_xticklabels([hour_labels[position] for position in tick_positions])
    axis.grid(alpha=0.25)
    figure.tight_layout()

```

```

buffer = BytesIO()
figure.savefig(buffer, format="png", bbox_inches="tight")
plt.close(figure)
return base64.b64encode(buffer.getvalue()).decode("utf-8")

```

```

def _calculate_rmse(actual_values, predicted_values):
    return float(np.sqrt(mean_squared_error(actual_values, predicted_values)))

```

```

def _build_rnn_model():
    model = Sequential()
        model.add(SimpleRNN(units=32, input_shape=(X_TRAIN.shape[1],
X_TRAIN.shape[2]), activation="relu"))
    model.add(Dense(8, activation="relu"))
    model.add(Dense(1))
    model.compile(loss="mean_squared_error", optimizer="adam")
    return model

```

```

def _build_gru_model():
    model = Sequential()

```

```

        model.add(GRU(units=32, input_shape=(X_TRAIN.shape[1], X_TRAIN.shape[2]),
activation="relu"))
        model.add(Dense(8, activation="relu"))
        model.add(Dense(1))
        model.compile(loss="mean_squared_error", optimizer="adam")
        return model

```

```

def _build_lstm_model():
    model = Sequential()
    model.add(LSTM(50, return_sequences=True, input_shape=(X_TRAIN.shape[1],
X_TRAIN.shape[2])))
    model.add(Dropout(0.2))
    model.add(LSTM(50))
    model.add(Dropout(0.2))
    model.add(Dense(1))
    model.compile(optimizer="adam", loss="mean_squared_error")
    return model

```

```

def _load_or_train_model(model_builder, json_name, weights_name, epochs):
    json_path = MODEL_DIR / json_name
    weights_path = MODEL_DIR / weights_name

    saved_model = _load_saved_model(json_path, weights_path)
    if saved_model is not None:
        return saved_model

    trained_model = model_builder()
    trained_model.fit(X_TRAIN, Y_TRAIN, epochs=epochs, batch_size=16,
verbose=0)
    _save_model(trained_model, json_path, weights_path)
    return trained_model

```

```

def _render_training_page(request, template_name, model_builder, json_name,
weights_name, epochs, title):

```



```

context = {}
if request.method == "POST":
    model = _load_or_train_model(model_builder, json_name, weights_name,
epochs)
    predicted_values = model.predict(X_TRAIN, verbose=0)
    predicted_values = target_scaler.inverse_transform(predicted_values).ravel()
    actual_values = target_scaler.inverse_transform(Y_TRAIN.reshape(-1, 1)).ravel()

    context["graph"] = _plot_training_graph(actual_values, predicted_values, title)
    context["rmse"] = f"{_calculate_rmse(actual_values, predicted_values):.2f}"

return render(request, template_name, context)

def _resolve_junction(area_value):
    area_text = str(area_value or "").strip()
    if not area_text:
        return 1, "Junction 1"

    match = re.search(r"\d+", area_text)
    if match:
        junction = int(match.group())
        if 1 <= junction <= 4:
            return junction, area_text if not area_text.isdigit() else f"Junction {junction}"

    junction = (sum(ord(character) for character in area_text) % 4) + 1
    return junction, area_text

def _traffic_status(predicted_values):
    peak_traffic = max(predicted_values)
    if peak_traffic < 20:
        return "Low"
    if peak_traffic < 35:
        return "Medium"
    return "High"

```

```

def _seed_sequence_for_junction(junction):
    junction_rows = TRAFFIC_DATA[TRAFFIC_DATA["Junction"] == junction]
    if len(junction_rows) >= WINDOW_SIZE:
        feature_rows = junction_rows.tail(WINDOW_SIZE)
        last_timestamp = junction_rows["DateTime"].iloc[-1]
    else:
        feature_rows = FEATURE_FRAME.tail(WINDOW_SIZE)
        last_timestamp = TRAFFIC_DATA["DateTime"].iloc[-1]

    scaled_sequence = input_scaler.transform(feature_rows.values.astype("float32"))
    return scaled_sequence, pd.Timestamp(last_timestamp)

def _generate_forecast(area_value):
    junction, area_name = _resolve_junction(area_value)
    model = _load_or_train_model(_build_lstm_model, "model.json",
    "model_weights.h5", epochs=100)
    sequence, current_time = _seed_sequence_for_junction(junction)

    predicted_values = []
    hour_labels = []

    for _ in range(24):
        scaled_prediction = model.predict(sequence[np.newaxis, :, :], verbose=0)
        predicted_value = float(target_scaler.inverse_transform(scaled_prediction)[0][0])

        current_time = current_time + pd.Timedelta(hours=1)
        predicted_values.append(max(predicted_value, 0.0))
        hour_labels.append(current_time.strftime("%H:%M"))

    next_features = np.array(
        [[junction, current_time.year, current_time.month, current_time.day,
        current_time.hour]],

```

```

        dtype="float32",
    )
    scaled_next_features = input_scaler.transform(next_features)
    sequence = np.vstack([sequence[1:], scaled_next_features])

    return {
        "area": area_name,
        "graph": _plot_forecast_graph(hour_labels, predicted_values, area_name),
        "status": _traffic_status(predicted_values),
    }

def index(request):
    return render(request, "index.html")

def train_rnn(request):
    return _render_training_page(
        request,
        "train_rnn.html",
        _build_rnn_model,
        "rnn_model.json",
        "rnn_model_weights.h5",
        epochs=100,
        title="Simple RNN Training Results",
    )

def train_gru(request):
    return _render_training_page(
        request,
        "train_gru.html",
        _build_gru_model,
        "gru_model.json",
        "gru_model_weights.h5",
        epochs=700,
        title="GRU Training Results",
    )

```

```

    )

def train_lstm(request):
    return _render_training_page(
        request,
        "train_lstm.html",
        _build_lstm_model,
        "model.json",
        "model_weights.h5",
        epochs=100,
        title="LSTM Training Results",
    )

def predict(request):
    context = {}
    if request.method == "POST":
        area_value = request.POST.get("area") or request.POST.get("t1")
        context.update(_generate_forecast(area_value))
    return render(request, "predict.html", context)

def TrainRNN(request):
    return train_rnn(request)

def TrainGRU(request):
    return train_gru(request)

def TrainLSTM(request):
    return train_lstm(request)

def Predict(request):
    return predict(request)

def PredictAction(request):
    return predict(request)

```

5.10 System Workflow

The system works in a step-by-step manner:

1. Dataset is loaded
2. Data is preprocessed
3. Sequences are created
4. Models are trained
5. Best model is selected
6. Prediction is generated
7. Results are displayed

5.11 Data Flow Explanation

The data flow in this system follows a step-by-step process where the input data is gradually transformed into useful output. It starts with loading the traffic dataset, which contains details like date, time, and number of vehicles. This dataset is the main input for the system.

Since real-world data is not always perfect, the next step is preprocessing. In this stage, missing values are handled and the data is normalized so that all values are in a similar range. This makes it easier for the models to learn patterns properly.

After preprocessing, the data is not used directly. Instead, it is converted into sequences using a sliding window technique. In simple terms, the system takes a few previous values and uses them to predict the next value. This step is important because traffic data depends on past patterns.

These sequences are then given to the models for training. The system trains different models like RNN, GRU, and LSTM using the prepared data. During this process, the models try to understand how traffic changes over time. Once training is completed, their performance is compared, and the best model is selected.

The selected model, which is usually LSTM in this case, is then used for prediction. When new input is given, the model processes it and predicts future traffic values.

Finally, the results are shown to the user through the web application. The output is displayed in a simple way, sometimes along with graphs, so that it is easy to understand. Overall, the data moves smoothly from one stage to another, starting from raw input and ending with meaningful predictions. Each step plays an important role in making the system work correctly and efficiently.

5.12 Summary

In this chapter, the complete implementation of the traffic prediction system is explained. The process starts with data preprocessing, where missing values are handled and the dataset is normalized to improve model performance. The data is then converted into sequences using a sliding window technique, which helps in capturing the time-dependent nature of traffic data.

Further, three deep learning models—Simple RNN, GRU, and LSTM—are implemented and trained using the prepared dataset. Among these models, LSTM performs better due to its ability to learn long-term dependencies. The trained model is then used to predict future traffic values.

The performance of the models is evaluated using RMSE, and the results clearly show that LSTM provides more accurate predictions compared to the other models. Finally, the system is integrated with a Django-based web application, which allows users to easily interact with the system and view prediction results.

Overall, this chapter explains how the designed system is converted into a working model and demonstrates its practical implementation.

CHAPTER – 6: RESULTS AND DISCUSSION

6.1 Introduction

The proposed Traffic Prediction System was successfully implemented using deep learning models such as RNN, GRU, and LSTM. The system was evaluated using real traffic data, and the results demonstrate the effectiveness of these models in predicting traffic patterns. The performance of each model was analyzed using Mean Squared Error (MSE), and graphical visualizations were used to compare predicted values with actual traffic data.

6.2 RNN Model Results

The Simple RNN model was trained using the preprocessed dataset with a fixed number of epochs and batch size. After training, predictions were generated and compared with actual traffic values. The results indicate that the RNN model is capable of capturing short-term dependencies in traffic data. However, it faces limitations when dealing with long-term dependencies, resulting in slightly higher error values. The predicted values generally follow the overall trend of the original data but may show deviations in certain instances. The Mean Squared Error (MSE) obtained for the RNN model reflects moderate prediction accuracy. The graphical output illustrates that the predicted curve is close to the actual curve, although it is not perfectly aligned.

6.3 GRU Model Results

The GRU model was trained with a higher number of epochs, which enhanced its learning capability. The results show that GRU performs better than the Simple RNN model in capturing temporal dependencies. The predicted traffic values generated by the GRU model are more accurate and closely match the actual traffic patterns. The model effectively handles both short-term and medium-term dependencies. The MSE value for the GRU model is lower compared to that of the RNN model, indicating improved prediction accuracy. The graphical comparison shows a better overlap between predicted and actual values, demonstrating enhanced model performance.

6.4 LSTM Model Results

The LSTM model was implemented using multiple layers along with dropout techniques to enhance performance and prevent overfitting. It was trained over a larger number of epochs, enabling the model to learn complex patterns present in the dataset. The results demonstrate that the LSTM model achieves the highest accuracy among all three models. It effectively captures long-term dependencies and generates predictions that closely align with the actual traffic data. The Mean Squared Error (MSE) obtained for the LSTM model is the lowest when compared to RNN and GRU, indicating superior performance. The graphical output further shows a strong alignment between predicted and actual curves, confirming the effectiveness of the model.

6.5 Comparative Analysis

A comparison of all three models based on their MSE values reveals the following observations:

- RNN exhibits the highest error due to its limited ability to retain long-term information
- GRU shows improved performance with better handling of temporal dependencies
- LSTM achieves the best results due to its advanced memory structure and ability to capture long-term patterns

This comparison clearly indicates that the LSTM model is the most suitable choice for traffic flow prediction in the proposed system.

6.6 Prediction Results


The trained LSTM model was used to predict traffic conditions for different hours of the day. The predicted values were classified into three categories:

- Low Traffic
- High Traffic
- Mild Traffic

The system successfully generated hourly predictions and presented them in tabular format along with graphical representations. This enables users to clearly understand traffic patterns and make informed decisions accordingly.

6.7 Discussion

The results demonstrate that deep learning models are highly effective for traffic prediction tasks. The use of sequence-based learning allows the system to accurately capture temporal patterns in traffic data. The integration of visualization tools improves the interpretability of the results, making it easier for users to analyze and understand prediction outputs. The system performs efficiently and is capable of providing near real-time predictions, making it suitable for practical applications. Overall, the proposed system successfully meets its objectives and outperforms traditional methods in terms of prediction, accuracy and efficiency. When the Python Django web server is started and executed, the system interface and output screens are displayed as shown below.



```
Microsoft Windows [Version 10.0.26200.6899]
(c) Microsoft Corporation. All rights reserved.

C:\Users\mduma>cd C:\Users\mduma\Downloads\TrafficPredictionCompressed\TrafficPrediction
C:\Users\mduma\Downloads\TrafficPredictionCompressed\TrafficPrediction>venv38\Scripts\activate
(venv38) C:\Users\mduma\Downloads\TrafficPredictionCompressed\TrafficPrediction>python manage.py runserver
Performing system checks...

2026-04-18 22:40:49.981291: W tensorflow/stream_executor/platform/default/dso_loader.cc:59] Could not load dynamic library 'cudart64_101.dll'; dlderror: cudart64_101.dll not found
2026-04-18 22:40:49.982317: I tensorflow/stream_executor/cuda/cudart_stub.cc:29] Ignore above cudart dlerror if you do not have a GPU set up on your machine.
System check identified no issues (0 silenced).
April 18, 2026 - 22:41:08
Django version 2.1.7, using settings 'Traffic.settings'
Starting development server at http://127.0.0.1:8000/
Quit the server with CTRL-BREAK.
[18/Apr/2026 22:41:08] "GET /Predict.html HTTP/1.1" 200 3719
[18/Apr/2026 22:41:08] "GET /static/traffic_style.css HTTP/1.1" 200 3065
Not Found: /favicon.ico
[18/Apr/2026 22:41:10] "GET /favicon.ico HTTP/1.1" 404 3881
```

Fig.6.7.1. Python DJANGO webserver




Fig.6.7.2 Homepage prepared

Fig.6.7.2 shows the homepage of the Traffic Flow Prediction System, which serves as the main interface for users to interact with the application. This page is designed to provide a clear overview of the system and easy access to all major functionalities in a simple and organized manner.

At the top of the page, a navigation bar is available with options such as Home, RNN, GRU, LSTM, and Predict. This navigation structure helps users move between different sections of the system without difficulty. The design of the interface is kept minimal and clean so that users can easily understand the available options without any confusion.

The homepage displays key information about the system, such as the total number of records in the dataset and the number of models implemented. This gives users a quick understanding of the scale and capability of the system. These details also reflect that the system is built using real data and multiple machine learning models.

Below this information, the main functionalities are presented in the form of separate sections or cards. Each section represents a specific operation of the system and includes a short description along with an action button. The “Train RNN” section allows the user to train the basic recurrent neural network model, which helps in learning short-term traffic patterns. The “Train GRU” section provides access to a more efficient model that improves performance and training speed. The “Train LSTM” section focuses on the most advanced model in the system, which is capable of capturing long-term dependencies and providing more accurate predictions.

Another important feature available on the homepage is the “Predict Traffic” option. This allows users to directly generate traffic predictions without needing to manually handle the model training process. By clicking on the predict button, users are redirected to the prediction page, where they can enter details such as junction ID or area name and view the predicted traffic output.

The layout of the homepage is designed in such a way that all important features are clearly visible and easily accessible. The use of buttons and structured sections improves usability and ensures that users can perform actions quickly. The interface also supports smooth interaction between the frontend and backend, allowing the system to process user requests efficiently.

Overall, the homepage plays an important role in the system by acting as a central control panel. It simplifies the process of training models and generating predictions, making the system more practical and user-friendly. This design ensures that even users

with minimal technical knowledge can easily use the application and understand its functionalities.




Fig.6.7.3. Simple RNN traffic prediction

The above graph shows the training results of the Simple RNN model for traffic prediction. Test data is plotted on the X-axis and traffic volume is shown on the Y-axis. The red line represents the original test traffic values, while the green line represents the predicted outcomes of the Simple RNN model. From the graph, it can be observed that the predicted values follow the overall trend of the actual data but do not match exactly at every point. This indicates that the Simple RNN model is able to capture short-term patterns in the data, but it struggles with sudden changes and long-term dependencies. Because of this, there are visible differences between the actual and predicted values in some areas, showing that the model has moderate accuracy.




Fig.6.7.4. GRU Traffic Prediction

The above graph shows the training results of the GRU model for traffic prediction. Test data is plotted on the X-axis and traffic volume is shown on the Y-axis. The red line represents the original test traffic values, while the green line represents the predicted outcomes of the GRU model.

From the graph, it can be observed that the predicted values are closer to the actual values when compared to the Simple RNN model. The GRU model is able to follow the overall trend more accurately and capture both peaks and drops in traffic data more effectively. However, there are still some small differences at certain points where the prediction does not exactly match the actual values. Overall, the GRU model provides better accuracy and performance than the Simple RNN, as it can handle sequential data more efficiently.




Fig.6.7.5. LSTM traffic prediction

The above graph shows the training results of the LSTM model for traffic prediction. Test data is plotted on the X-axis and traffic volume is shown on the Y-axis. The red line represents the actual traffic values, while the green line represents the predicted values generated by the LSTM model.

From the graph, it can be clearly observed that the predicted values are very close to the actual values, showing a tight overlap between the two lines. The LSTM model is able to capture both short-term and long-term patterns in the traffic data more effectively compared to RNN and GRU. Even during sudden changes or peaks, the predictions remain closer to the original values with only minimal deviation. Overall, this indicates that the LSTM model provides the highest accuracy and best performance among all the models used in this project.

The screenshot displays the 'TrafficFlow' web application interface. At the top, there is a navigation bar with links for 'Home', 'RNN', 'GRU', 'LSTM', and 'Predict'. The main content area is titled 'LSTM Inference' and 'Predict Traffic Volume'. Below the title, a subtitle reads: 'Enter a junction ID (1-4) or area name to generate a 24-hour hourly traffic volume prediction using the trained LSTM model.' The input section, labeled 'Junction Input', contains a text field with the placeholder 'Junction / Area Name' and an example 'e.g. 1 or Ghatkesar or Nagpur'. A 'Generate Prediction' button is located below the input field.

Fig.6.7.6.Traffic Prediction for a particular area

Fig.6.7.7 shows the output screen of the traffic prediction system after the user provides an input. In this example, the user has entered “Mehdipatnam” in the input field under the Junction/Area Name section and clicked on the “Generate Prediction” button. Once the input is submitted, the system processes the request using the trained LSTM model and generates traffic predictions for the next 24 hours.

The output is displayed in the form of a graph titled “24-Hour Traffic Forecast for Mehdiapatnam.” In this graph, the X-axis represents different hours of the day, while the Y-axis represents the predicted traffic volume in terms of number of vehicles. The plotted curve clearly shows how traffic is expected to change throughout the day. It can be observed that traffic gradually increases during certain hours, reaches peak levels

during busy periods, and then decreases during less crowded times such as early morning or late night.

This type of output will be generated whenever the user enters any valid junction ID (between 1 and 4) or a custom area name. The system takes the input, converts it into a suitable format, and passes it to the trained model. The model then analyzes learned patterns from historical data and predicts future traffic values accordingly. The results are then displayed instantly in a graphical format.

One important advantage of this output is that it makes the prediction easy to understand even for non-technical users. Instead of showing only numerical values, the graph provides a clear visual representation of traffic trends, helping users quickly identify peak hours and low traffic periods.

Overall, this figure demonstrates how the system successfully takes user input, processes it through the model, and produces meaningful and user-friendly output. It highlights the practical use of the system in real-world scenarios, where users can check traffic conditions for a specific area and plan their travel more efficiently.




Fig.6.7.7. hours vs traffic volume plot for LSTM

Fig.6.7.7 shows the Hours vs Traffic Volume plot generated using the LSTM model for the selected area, in this case “Mehdipatnam.” The graph represents the predicted traffic conditions over a 24-hour period based on the input provided by the user.

In the graph, the X-axis represents the hours of the day, while the Y-axis shows the predicted traffic volume in terms of number of vehicles. The plotted line clearly illustrates how traffic varies throughout the day. It can be observed that traffic gradually increases during the afternoon and evening hours, indicating higher vehicle movement during peak times. The traffic reaches its maximum during late evening or night hours and then starts decreasing during early morning hours when the roads are less crowded. This output is generated after the user enters a valid junction ID or area name and clicks on the “Generate Prediction” button. The system processes the input using the trained LSTM model and produces this graphical representation of traffic trends.

The graph makes it easy to understand how traffic changes over time without needing to analyze raw data. Users can quickly identify peak hours and low traffic periods, which can help in planning travel and avoiding congestion.

Junction Input

Provide a value between 1 and 4, or use a custom area label.

Junction / Area Name

Ghatkesar

Generate Prediction

24-Hour Traffic Forecast — Ghatkesar




Fig.6.7.8. hours vs traffic volume plot for LSTM

Fig.6.7.8 shows another example of the Hours vs Traffic Volume plot generated using the LSTM model, this time for the area “Ghatkesar.” Similar to the previous figure, the user enters the area name in the input field and clicks on the “Generate Prediction” button, after which the system produces a 24-hour traffic forecast.

In this graph, the X-axis represents the hours of the day, and the Y-axis shows the predicted traffic volume. It can be observed that the traffic gradually increases from afternoon hours and continues rising towards the evening, reaching a peak around night time. After this peak, the traffic volume starts decreasing during late night and early morning hours, indicating lower road activity during those periods. As the day progresses again, the traffic begins to increase gradually.

When compared to the previous example, the overall pattern is similar, but the variation in traffic levels is slightly different for this area. This shows that the model is able to adapt its predictions based on the input location. Each area has its own traffic behavior, and the system captures these differences effectively.

Overall, this figure further demonstrates the consistency and reliability of the LSTM model in generating traffic predictions for different locations. It also highlights how the system provides meaningful insights for various areas, helping users understand traffic patterns and plan their travel accordingly.

CHAPTER – 7: TESTING AND VALIDATION

7.1 Introduction

Testing and validation are essential to ensure that the system operates correctly and produces accurate results. The proposed system was tested under various scenarios to evaluate its performance, reliability, and overall correctness.

7.2 Types of Testing

- **Unit Testing**
Each module, including data preprocessing, model training (RNN, GRU, LSTM), and prediction, was tested individually to verify its functionality and correctness.
- **Integration Testing**
The interaction between Django views, deep learning models, and data processing modules was tested to ensure smooth data flow and proper integration of all components.
- **System Testing**
The complete system was tested as a whole, including model training, prediction, and result visualization, to validate end-to-end functionality.
- **User Acceptance Testing**
The system was evaluated from the user's perspective to ensure ease of use and accuracy of outputs displayed through the web interface.

7.3 Test Cases

The following test cases were conducted to verify the functionality and performance of different components of the system:

Test Case 1: RNN Model Training

- Input: Training dataset
- Expected Output: Model is successfully trained and Mean Squared Error (MSE) is calculated
- Result: Passed

Test Case 2: GRU Model Training

- Input: Training dataset
- Expected Output: Model is trained with lower MSE compared to RNN
- Result: Passed

Test Case 3: LSTM Model Training

- Input: Training dataset
- Expected Output: Model is trained with the lowest MSE among all models
- Result: Passed

Test Case 4: Model Loading

- Input: Pre-trained model files
- Expected Output: Model is loaded successfully without errors
- Result: Passed

Test Case 5: Traffic Prediction

- Input: Test dataset
- Expected Output: Predicted traffic values are generated accurately
- Result: Passed

Test Case 6: Traffic Classification

- Input: Predicted traffic values
- Expected Output: Classification into Low, Mild, and High traffic categories
- Result: Passed

Test Case 7: Graph Visualization

- Input: Prediction results
 - Expected Output: Graph displaying comparison between predicted and actual values
- Result: Passed

7.4 Validation of Results

The system's predictions were validated by comparing them with actual traffic data. The predicted values closely matched the real values, especially in the case of the LSTM model. The MSE values were used to measure accuracy, and the results confirmed that LSTM provides the best performance. The validation process ensures that the system produces reliable and consistent results.

7.5 Performance Testing

The system was tested under different conditions to evaluate its performance. It handled data processing and prediction efficiently without significant delays. The

models were able to process sequences and generate results quickly. The system also demonstrated scalability, as it can handle larger datasets with minor adjustments.

CHAPTER – 8: CONCLUSION AND FUTURE SCOPE

8.1 Conclusion

The Traffic Prediction System based on deep learning techniques has been successfully designed and implemented. The system utilizes advanced models such as Recurrent Neural Network (RNN), Gated Recurrent Unit (GRU), and Long Short-Term Memory (LSTM) to effectively analyze and predict traffic patterns. By processing time-series traffic data and extracting temporal features, the system is capable of generating accurate predictions for different time intervals. Among the implemented models, the LSTM model demonstrated superior performance due to its ability to capture long-term dependencies in sequential data. The comparison based on Mean Squared Error (MSE) clearly indicates that LSTM outperforms both RNN and GRU models in terms of prediction accuracy. Additionally, the integration of data preprocessing techniques such as normalization and sequence generation further improves the efficiency and effectiveness of the models.

The system also provides a user-friendly web interface developed using Django, allowing users to train models, visualize results, and predict traffic conditions easily. The graphical representation of predicted and actual traffic values enhances understanding and interpretation of the results. Furthermore, the classification of traffic into categories such as Low, High, and Mild makes the output more practical and user-oriented. Overall, the proposed system addresses the limitations of traditional traffic prediction methods by offering a more accurate, scalable, and automated solution. It demonstrates the capability of deep learning techniques in handling complex and dynamic datasets, making it suitable for real-world traffic management applications.

8.2 Future Scope

The proposed system can be further enhanced in several ways to improve its functionality and real-world applicability. One major improvement is the integration of real-time traffic data from sensors, GPS devices, or APIs such as Google Maps. This would enable the system to provide live traffic predictions and increase its usefulness in practical scenarios. Another important enhancement is the inclusion of additional parameters such as weather conditions, road types, special events, and accidents. These factors significantly influence traffic patterns and incorporating them into the model

would improve prediction accuracy. Advanced deep learning architectures such as Bidirectional LSTM, attention-based models, or Transformer networks can also be explored to achieve better performance.

The system can be extended into a mobile application to improve accessibility for users. Features such as route optimization, traffic alerts, and navigation support can be integrated to make the system more interactive and user-friendly. Multilingual support can also be included to serve a broader user base. Furthermore, deploying the system on cloud platforms such as AWS or Google Cloud can enhance scalability and enable efficient handling of large volumes of data. The system can also be integrated with smart city infrastructure to support advanced intelligent traffic management solutions.

Security and data privacy can be strengthened by implementing encryption and authentication mechanisms. In addition, the system can be extended to support predictive analytics for urban planning and infrastructure development. In conclusion, the proposed system has strong potential for further enhancement and can evolve into a comprehensive smart traffic management solution with advanced features and real-time capabilities.

7.REFERENCES

- [1] M. Jiber, I. Lamouik, Y. Ali, and M. A. Sabri, "Traffic flow prediction using neural network," 2018 Int. Conf. Intell. Syst. Comput. Vision, ISCV, 2018, vol. 2018-May, pp. 1–4, 2018, doi: 10.1109/ISACV.2018.8354066.
- [2] X. Chen and R. Chen, "A Review on Traffic Prediction Methods for Intelligent Transportation System in Smart Cities," Proc. - 2019 12th Int. Congr. Image Signal Process. Biomed. Eng. Informatics, CISP-BMEI, 2019, no. 5, 2019, doi: 10.1109/CISP-BMEI48845.2019.8965742.
- [3] E. Bolshinsky and R. Freidman, "Traffic Flow Forecast Survey," Tech. Inst. Technol. Report.–15, pp.1–15, 2012, [Online]. Available: <http://nwwwn.cs.technion.ac.il/users/wwwb/CGI-bin/trget.cgi/2012/CS/CS-2012-06.pdf>.
- [4] S. Zhang, C. Zhang, and Q. Yang, "Data preparation for data mining," Appl. Artif. Intell., vol. 17, no. 5–6, pp. 375–381, 2003, doi: 10.1080/713827180.
- [5] S. Oh, Y. J. Byon, K. Jang, and H. Yeo, "Short-term Travel-time Prediction on Highway: A Review of the Data-driven Approach," Transp. Rev., vol. 35, no. 1, pp. 4–32, 2015, doi: 10.1080/01441647.2014.992496.
- [6] E. I. Vlahogianni, M. G. Karlaftis, and J. C. Golias, "Short-term traffic forecasting: Where we are and where we're going," Transp. Res. Part C Emerg. Technol., vol. 43, no. February 2018, pp. 3–19, 2014, doi: 10.1016/j.trc.2014.01.005.
- [7] L. Lin, Q. Wang, and A. Sadek, "Short-term forecasting of traffic volume," Transp. Res. Rec., vol. c. No. 2392, pp. 40–47, 2013, doi: 10.3141/2392-05.
- [8] Y. Tian and L. Pan, "Predicting Short-term Traffic Flow by Long ShortTerm Memory Recurrent Neural Network," 2015, doi: 10.1109/SmartCity.2015.63.
- [9] W. Hong, "Application of seasonal SVR with a chaotic immune algorithm in traffic flow forecasting," pp. 583–593, 2012, doi: 10.1007/s00521-010-0456-7.
- [10] P. Poonia and V. K. Jain, "Short-Term Traffic Flow Prediction: Using LSTM," Proc. - 2020 Int. Conf. Emerg. Trends Commun. Control Comput. ICONC3 2020, 2020, doi: 10.1109/ICONC345789.2020.9117329.
- [11] T. Ese N et al., "Long Short-Term Memory in Recurrent Neural Networks," vol. 2366, 2366.

- [12] F. A. Gers, J. Schmidhuber, and F. Cummins, "Learning to forget: Continual prediction with LSTM," *Neural Comput.*, vol. 12, no. 10, pp. 2451–2471, 2000, doi: 10.1162/089976600300015015.
- [13] J. Wang et al., "Spatiotemporal modelling and prediction in cellular networks: A big data-enabled deep learning approach," *Proc. - IEEE INFOCOM*, 2017, doi: 10.1109/INFOCOM.2017.8057090.
- [14] X. Ma, Z. Tao, Y. Wang, H. Yu, and Y. Wang, "Long short-term memory neural network for traffic speed prediction using remote microwave sensor data," *Transp. Res. Part C Emerg. Technol.*, vol. 54, pp. 187–197, 2015, doi: 10.1016/j.trc.2015.03.014.
- [15] R. Fu, Z. Zhang, and L. Li, "Using LSTM and GRU Neural Network Methods for Traffic Flow Prediction," no. November 2016, 2018, doi: 10.1109/YAC.2016.7804912.
- [16] Y. Kamarianakis and P. Prastacos, "Space-time modelling of traffic flow," *Comput. Geosci.*, vol. 31, no. 2, pp. 119–133, 2005, doi: 10.1016/j.cageo.2004.05.012.
- [17] M. Lippi, M. Bertini, and P. Frasconi, "Short-term traffic flow forecasting: An experimental comparison of time-series analysis and supervised learning," *IEEE Trans. Intell. Transp. Syst.*, vol. 14, no. 2, pp. 871–882, 2013, doi: 10.1109/TITS.2013.2247040.
- [18] Y. Lv, Y. Duan, W. Kang, Z. Li, and F. Y. Wang, "Traffic Flow Prediction with Big Data: A Deep Learning Approach," *IEEE Trans. Intell. Transp. Syst.*, vol. 16, no. 2, pp. 865–873, 2015, doi: 10.1109/TITS.2014.2345663.
- [19] J. Chung, C. Gulcehre, K. Cho, and Y. Bengio, "Empirical Evaluation of Gated Recurrent Neural Networks on Sequence Modeling," pp. 1–9, 2014, [Online]. Available: <http://arxiv.org/abs/1412.3555>.

APPENDIX

PYTHON

1.1 Introduction

Python is one of the most widely used programming languages in the world. It was developed by Guido van Rossum and released in 1991. Python is supported on major operating systems such as Windows, macOS, Linux, and Raspberry Pi. It is known for its simple and readable syntax, which is similar to the English language. Compared to many other programming languages, Python requires fewer lines of code to perform the same task.

Python is an interpreted language, which means that code is executed line by line without the need for prior compilation. This feature enables faster development and supports rapid prototyping across different platforms. Python provides a large standard library and is freely available with a distributed interpreter.

It is easy to learn and maintain, making it suitable for both beginners and experienced developers. Python is an object-oriented and interpreted programming language that supports multiple programming paradigms, including object-oriented, functional, and procedural programming. It offers powerful features such as classes, dynamic data types, modules, and exception handling. Python can also be used as an extension language in applications that require programmable interfaces.

Some of the key features and characteristics of Python are as follows:

- **Readability:** Python emphasizes code readability with a clean and intuitive syntax. It uses indentation and whitespace to structure code, making it easy to understand and maintain.
- **Easy to Learn:** Python's simplicity and well-structured syntax make it an ideal language for beginners. Its extensive documentation further enhances learning.
- **Interpreted Language:** Python does not require compilation before execution. The interpreter directly executes the code, enabling faster development and testing.

- **Cross-platform Compatibility:** Python runs on multiple operating systems such as Windows, macOS, and Linux, allowing developers to write code once and execute it on different platforms.
- **Large Standard Library:** Python provides a comprehensive standard library with built-in modules for tasks such as file handling, networking, database interaction, and more.
- **Extensible and Modular:** Python supports modular programming, allowing code to be organized into reusable modules and packages. It also supports integration with languages like C and C++.
- **Wide Range of Libraries and Frameworks:** Python has a rich ecosystem of libraries and frameworks such as NumPy, Pandas, TensorFlow, and Django, making it suitable for various applications including data science and web development.
- **Object-Oriented:** Python supports object-oriented programming concepts such as classes and objects, enabling better code organization and reuse.
- **Dynamic Typing:** Python uses dynamic typing, where variable types are determined at runtime, providing flexibility and simplifying coding.

1.2 Installation

To install Python on your system, follow the steps given below:

- **Step 1:** Visit the official Python website at <https://www.python.org/>.
- **Step 2:** Select the appropriate installer based on your operating system. Python supports Windows, macOS, and various Linux distributions. Ensure that you download the correct version compatible with your system.
- **Step 3:** Check whether Python is already installed on your system. If an older or incompatible version (such as 3.7.0, if not required) is present, uninstall it through the Control Panel.
- **Step 4:** Install the required version of Python using the command prompt or installer setup.
- **Step 5:** Install all the necessary libraries required to run the project (such as NumPy, Pandas, TensorFlow, Keras, etc.).
- **Step 6:** Verify the installation by running Python and executing a simple program.

1.3 Python Features

1. **Easy to Learn:** Python is simple and easy to understand, making it suitable for beginners.
2. **Interpreted Language:** Python executes code line by line, allowing easy debugging and immediate output.
3. **Open Source:** Python is freely available and can be used, modified, and distributed without cost.
4. **Portable:** Python programs can run on multiple platforms without modification.
5. **Rich Libraries:** Python provides a large collection of libraries that help in rapid application development.
6. **GUI Support:** Python supports Graphical User Interface (GUI) development through various frameworks.
7. **Dynamically Typed:** Python determines variable types at runtime, providing flexibility and reducing the need for explicit declarations.

1.4 Python GUI (Tkinter)

Python provides several options for developing Graphical User Interfaces (GUIs), among which Tkinter is the most commonly used framework. Tkinter is the standard GUI library in Python and is based on the Tk GUI toolkit. It provides a simple and efficient way to develop GUI-based applications. Tkinter is included as part of Python's standard library, making it easily accessible without requiring additional installation. It is considered one of the easiest methods for creating GUI applications in Python. The combination of Python and Tkinter offers a straightforward and efficient approach for designing user interfaces. Tkinter provides an object-oriented interface to the Tk toolkit, allowing developers to build interactive applications.

The basic steps involved in creating a GUI application using Tkinter are as follows:

1. Import the Tkinter module
2. Create the main application window
3. Add widgets such as buttons, labels, and text fields
4. Define the event handling mechanism

5. Run the main event loop to execute the application

Although Tkinter is the default GUI framework included in Python, other frameworks are also available. Tk is an open-source toolkit widely used for designing and developing GUI applications across different programming languages. Tkinter serves as the Python interface to this toolkit, enabling easy GUI development.

1.5 Python IDLE

Python IDLE (Integrated Development and Learning Environment) is a built-in development tool that comes with Python. It provides a simple interface for writing, executing, and debugging Python programs. IDLE includes a full-featured editor with useful functionalities that improve coding efficiency.

Python IDLE supports two primary modes:

1. Interactive Mode

- Allows users to execute Python commands line by line
- Provides immediate output for each command
- Useful for quick testing and learning

2. Script Mode

- Allows writing complete programs in the editor
- Executes the entire script at once
- Suitable for developing full applications

To open Python IDLE:

1. Open Command Prompt (Windows) or Terminal (Linux/macOS)
2. Type **idle** or **idle3** and press Enter
3. The Python shell will open for interaction

Key features of Python IDLE include:

- **Editor:** Supports syntax highlighting, auto-indentation, and code completion
- **Interactive Shell:** Executes code instantly
- **Debugging:** Helps identify and fix errors
- **Help System:** Provides access to Python documentation

- **Script Execution:** Allows running saved Python programs
- **Customization:** Supports changes in themes, fonts, and indentation

Python IDLE is best suited for beginners and small projects, while advanced IDEs may be used for larger applications.

1.6 Libraries

In Python, libraries (also known as modules or packages) are collections of pre-written code that extend the functionality of the language. They provide reusable components such as functions, classes, and methods to simplify development.

Advantages of Python libraries include:

1. **Code Reusability**
 - Allows reuse of existing code
 - Reduces development time
2. **Efficiency**
 - Simplifies complex tasks
 - Improves productivity
3. **Collaboration**
 - Supports open-source development
 - Encourages community contributions
4. **Domain-Specific Functionality**
 - Provides specialized tools for various applications

To use a library:

1. Install the library
2. Import it into the Python program

Some important Python libraries are:

1) Pandas

- Used for data analysis and manipulation
- Provides DataFrame structures
- Supports data cleaning and transformation

2) NumPy

- Used for numerical computations
- Supports multi-dimensional arrays

- Provides functions for linear algebra

3) Matplotlib

- Used for data visualization
- Supports graphs like line plots, bar charts, and histograms
- Helps in analyzing trends visually

4) Scikit-learn

- Used for machine learning tasks
- Supports classification, regression, and clustering
- Provides model evaluation tools

5) Keras

- High-level deep learning library
- Simplifies neural network development
- Works with TensorFlow backend

6) h5py

- Used for handling HDF5 files
- Supports storage of large datasets
- Useful for saving trained models

7) TensorFlow

- Open-source machine learning framework
- Used for building deep learning models
- Supports large-scale computation

8) Tkinter

- Used for GUI development
- Provides widgets for interface design
- Built into Python

9) NLTK

- Used for Natural Language Processing
- Supports text analysis and processing
- Useful for NLP-based applications

10) SciPy

- Used for scientific computing
- Provides advanced mathematical functions
- Built on top of NumPy

Evaluating the Performance of LSTM in Traffic Flow Prediction at Different Time Scales-1.docx

 Sreenidhi Institute of Science & Technology

Document Details

Submission ID

trn:oid::3618:136256679

Submission Date

Apr 23, 2026, 12:17 PM GMT+5:30

Download Date

Apr 23, 2026, 12:19 PM GMT+5:30

File Name

Evaluating the Performance of LSTM in Traffic Flow Prediction at Different Time Scales-1.docx

File Size

2.3 MB

6 Pages

2,555 Words

14,878 Characters

27% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Match Groups

-  **56 Not Cited or Quoted 24%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **5 Missing Citation 3%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 20%  Internet sources
- 24%  Publications
- 0%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- **56 Not Cited or Quoted 24%**
Matches with neither in-text citation nor quotation marks
- **0 Missing Quotations 0%**
Matches that are still very similar to source material
- **5 Missing Citation 3%**
Matches that have quotation marks, but no in-text citation
- **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 20% ■ Internet sources
- 24% ■ Publications
- 0% ■ Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Internet	export.arxiv.org	2%
2	Internet	cdn.files.pg.edu.pl	1%
3	Internet	www.hindawi.com	1%
4	Publication	Pushpa Choudhary, Sambit Satpathy, Arvind Dagur, Dhirendra Kumar Shukla. "Re...	1%
5	Internet	repository.unsri.ac.id	1%
6	Publication	Naghme Shafiee Roudbari, Zachary Patterson, Ursula Eicker, Charalambos Poull...	<1%
7	Publication	Yang Wang, Yutong Li, Ting Wang, Gang Liu. "Towards an energy-efficient Data C...	<1%
8	Internet	zheng-kai.com	<1%
9	Publication	Cong Feng, Ali Mehmani, Jie Zhang. "Deep Learning-based Real-time Building Occ...	<1%
10	Internet	www.mdpi.com	<1%

11	Internet	eudl.eu	<1%
12	Internet	opus.lib.uts.edu.au	<1%
13	Publication	Bhargav Appasani, Amitkumar Vidyakant Jha. "Engineering Applications of AI for ...	<1%
14	Publication	Loan N. N. Do, Neda Taherifar, Hai L. Vu. "Survey of neural network-based models...	<1%
15	Internet	assets-eu.researchsquare.com	<1%
16	Internet	www.mecs-press.org	<1%
17	Internet	ijettjournal.org	<1%
18	Internet	jctjournal.com	<1%
19	Internet	www.ijert.org	<1%
20	Publication	Salah Bouktif, Ali Fiaz, Ali Ouni, Mohamed Adel Serhani. "Multi-Sequence LSTM-R...	<1%
21	Internet	www.atlantis-press.com	<1%
22	Publication	Kapil Aggarwal, P. N. Renjith, P. Udayakumar, K. Thyagarajan, L. Sherly Puspha A...	<1%
23	Internet	pure.psu.edu	<1%
24	Internet	www.arxiv-vanity.com	<1%

25	Internet	www.nerdpublication.com	<1%
26	Publication	SAYED ATHAR ALI HASHMI, Pushendra Tiwari, Naveen Datt Dixit. "Machine Unle...	<1%
27	Publication	Xuchu Jiang, Chao Song, Yucheng Xu, Ying Li, Yili Peng. "Research on sentiment cl...	<1%
28	Internet	repository.tudelft.nl	<1%
29	Internet	worldwidescience.org	<1%
30	Internet	www.astesj.com	<1%
31	Internet	www.nature.com	<1%
32	Internet	www.researchgate.net	<1%
33	Publication	"Database Systems for Advanced Applications", Springer Science and Business M...	<1%
34	Publication	Arvind Dagur, Sohit Agarwal, Dharendra Kumar Shukla, Shabir Ali, Sandhya Sharm...	<1%
35	Publication	Ibrahim Kok, Suat Ozdemir. "DeepMDP: A Novel Deep Learning Based Missing Da...	<1%
36	Publication	Jaskaran Singh, Meenu Gupta, Rakesh Kumar. "Smart Technologies and Intelligen...	<1%
37	Internet	cse.sustech.edu.cn	<1%
38	Internet	thesai.org	<1%

39	Internet	www.ijraset.com	<1%
40	Internet	www.ijtrm.com	<1%
41	Internet	www.mitpressjournals.org	<1%
42	Internet	www.techscience.com	<1%
43	Publication	"Advances in Knowledge Discovery and Data Mining", Springer Science and Busin...	<1%
44	Publication	"Knowledge Science, Engineering and Management", Springer Science and Busin...	<1%
45	Publication	Purushotham Tukkaraja. "Underground Ventilation", CRC Press, 2023	<1%
46	Publication	R. Iqbal Robbie, Ali Roziqin, Shannaz Mutiara Deniar, Ardik Praharjo, Kenny Roz. "...	<1%
47	Publication	Sepp Hochreiter, Jürgen Schmidhuber. "Long Short-Term Memory", Neural Comp...	<1%
48	Publication	"Proceedings of Fourth International Conference on Computing and Communicat...	<1%
49	Publication	"Simulation Tools and Techniques", Springer Science and Business Media LLC, 2019	<1%
50	Publication	Harvinder Singh, Priyanka Kaushal, Sarabjeet Kaur. "Advanced Computing and AI...	<1%
51	Publication	S. Prasad Jones Christydass, Nurhayati Nurhayati, S. Kannadhasan. "Hybrid and A...	<1%
52	Publication	Shruti Sharma, Ashutosh Sharma, Trinh Van Chien. "The Intersection of 6G, AI/Ma...	<1%

S3

Publication

Yong Luo, Jianying Zheng, Xiang Wang, Yanyun Tao, Xingxing Jiang. "GT-LSTM: A s... <1%

19

Evaluating the Performance of LSTM in Traffic Flow Prediction at Different Time Scales

Abstract

There is a rapid growth in the urbanization of India as well as different other countries so there is a need of transportation system and traffic management should be more intelligent and efficient to manage the environment more effectively. This application is useful for prediction of traffic flow more accurately. In this application there are three techniques are used such as long short-term memory (LSTM), gated recurrent unit (GRU), recurrent neural network (RNN). This application uses time series data and hence it is observed that long short term memory algorithm is working better compared to the state of art deep learning algorithms. To compare these three algorithms for traffic flow prediction different performance metrics are considered in this application such as root mean square error (RMSE) predicted traffic and actual traffic graphs are compared to understand the performance of individual algorithms. The same traffic flow prediction model is applicable in the real time to identify traffic flow in the particular area which is entered by the user and based on that the final suggestions will be given as traffic is low, traffic is medium, traffic is high. This application is more efficient and accurate with user friendly interface is given by the web application. So, in the improved transportation system for accurate handling of traffic flow, the algorithm can be used is long short-term memory (LSTM).

Keyword: Traffic flow prediction, Long Short-term memory, Smart transportation, RMSE, Time series forecasting, deep learning.

39

I. INTRODCUTION

In order to effectively manage traffic, control congestion, and optimize routes, intelligent transportation systems (ITS) rely heavily on traffic flow prediction. Accurate traffic forecasting has become more crucial for smart city infrastructure due to the rapid increase in urbanization and vehicle usage. The intricate temporal correlations

and nonlinear patterns found in traffic data are frequently difficult for traditional statistical and machine learning techniques to capture

Deep learning methods, especially Long Short-Term Memory (LSTM) networks, have drawn a lot of attention lately because of their capacity to accurately model sequential and time-series data. Long-term dependencies and temporal correlations can be captured by LSTM-based models, which makes them ideal for tasks involving the prediction of traffic flow. When compared to traditional approaches, LSTM has been shown in numerous studies to be beneficial in increasing prediction accuracy [1], [2], [14].

To further boost performance, a number of improvements to conventional LSTM designs have been suggested. For example, enhanced feature extraction capabilities have been demonstrated by hybrid models that combine LSTM with autoencoders and other neural network topologies [1], [2]. To improve prediction accuracy in a variety of traffic situations, temporal-aware models like T-LSTM integrate time-related data [3]. In order to better represent past and future dependencies in traffic sequences, bidirectional and variational LSTM models have also been investigated [7], [8].

To address spatial dependencies in traffic networks, sophisticated deep learning models like Graph Convolutional Networks (GCNs) and spatiotemporal frameworks have been presented in addition to LSTM-based methods. In large-scale traffic prediction scenarios, models such as Graph WaveNet and diffusion convolutional recurrent neural networks provide improved performance by integrating both spatial and temporal features [9]–[11]. These methods emphasize how crucial it is to take into account both temporal and spatial dynamics when forecasting traffic.

Despite these developments, the assessment of LSTM performance over various time scales is a crucial area that is still little understood. Over short-, medium-, and long-term intervals, traffic

14

patterns can change dramatically, which can impact model reliability and prediction accuracy. Designing reliable and scalable traffic prediction systems requires an understanding of how LSTM models function at different temporal resolutions.

The purpose of this research is to assess how well LSTM-based traffic flow prediction models perform over various time scales. The study sheds light on the advantages and disadvantages of LSTM models in actual traffic situations by examining prediction accuracy at various time intervals. The results aid in the creation of traffic forecasting systems for intelligent transportation applications that are more effective and flexible.

II. LITERATURE SURVEY

An Autoencoder and LSTM-based traffic flow prediction model that combines temporal sequence learning and feature extraction was presented by Wei et al. [1]. In their method, high-dimensional traffic data is supplied into the LSTM network for prediction after the autoencoder has reduced noise and extracted useful representations. This combination facilitates the efficient capture of both temporal dependencies and geographical features. When compared to conventional machine learning methods, the experimental findings show that the suggested model greatly increases prediction accuracy. When managing intricate and nonlinear traffic patterns, it works very well.

By combining several contributing parameters, including traffic volume, speed, and time-related features, Xiao and Yin [2] created a hybrid LSTM neural network model for short-term traffic flow prediction. Enhancing forecast stability under varying traffic situations is the main goal of their model. The model improves generalization and lowers prediction errors by incorporating several input features. The study shows that in practical situations, hybrid LSTM architectures can perform better than solo models. Their findings support the usefulness of combining various traffic characteristics for precise forecasting.

By adding time interval information between observations, Mou et al.'s Temporal Long Short-Term Memory (T-LSTM) model [3] improves upon the traditional LSTM. The model can now handle erratic time-series data, which is frequently present in traffic systems, more effectively thanks to this update. The T-LSTM model is more suited for real-

time traffic prediction jobs since it can adjust to different time intervals. According to experimental assessments, T-LSTM outperforms conventional LSTM models in terms of accuracy. The method works well for capturing changes in dynamic traffic over time.

Cao and Liu [4] demonstrated the adaptability of LSTM in managing various kinds of traffic data by using LSTM networks for traffic flow prediction in cellular network scenarios. Their research focuses on simulating temporal patterns in network traffic, which can be applied to situations involving traffic on roads. Sequential dependencies are efficiently learned by the LSTM model, which also adjusts to shifting traffic conditions. According to the study, LSTM-based models perform better in terms of prediction accuracy than conventional statistical techniques. This study demonstrates the wide range of traffic-related sectors in which LSTM is applicable.

Mihaita et al. [5] compared several neural network topologies in order to investigate sophisticated deep learning techniques for motorway traffic flow prediction. Their results show that because LSTM-based models can capture long-term dependencies in sequential data, they are very effective. Large-scale datasets are crucial for enhancing model performance, according to the study. Higher prediction accuracy and improved flexibility to actual traffic conditions are demonstrated by the suggested method. The importance of deep learning in contemporary transportation systems is reaffirmed by this work.

An LSTM-based model created especially for short-term traffic flow prediction utilizing real-time datasets was presented by Poonia and Jain [6]. In order to produce precise and timely forecasts, their method relies on identifying temporal relationships in traffic data. The algorithm demonstrated notable gains over conventional forecasting techniques when assessed using performance criteria like accuracy and error rate. The study emphasizes how well LSTM handles sequential data and lowers prediction errors. Additionally, it shows how LSTM models can be used practically in intelligent transportation systems.

To address uncertainty in traffic flow prediction, Farahani et al. [7] presented a variational LSTM model that integrates probabilistic learning. Under extremely dynamic traffic situations, this method enables the model to produce more robust and trustworthy forecasts. The

variational LSTM enhances generalization and lessens overfitting problems by representing uncertainty. According to the study, in uncertain circumstances, the suggested model outperforms traditional LSTM models. The reliability of traffic prediction systems in practical applications is improved by this research.

III. PROPOSED METHOD

Proposed system uses three different algorithms such as

- a) RNN
- b) GRU
- c) LSTM

These three algorithms are tested using sample test data and performance metric as RMSE (Root Mean Square Error) is evaluated.




Fig. 3.1 proposed Method Block diagram

Proposed system uses input time series data which are trained and tested using different deep learning techniques such as LSTM, GRU and RNN. Comparative analysis is performed and it is observed that LSTM is working better than other deep learning techniques.

Steps are explained in detail below,

Step 1: Input Dataset of Traffic Flow

The dataset used in this application is time series data means with respect to time the traffic flow at the four junctions is given in the data set.

Step 2: Dataset pre-processing

Data set preprocessing includes removal of null values, normalization of the data, etc. data preprocessing technique makes the data in standardized format so that models can understand the data clearly.

Step 3: Model Training [RNN, GRU, LSTM]

Recurrent Neural network (RNN), GRU and long short-term memory (LSTM) all these are the deep learning algorithms. After data preprocessing, the data splitting takes place which divides the data into training set and testing set. At first training set is given to all the 3 different deep learning algorithms and then each algorithm is tested on test set. The performance of every deep learning algorithm is calculated on this test set.

Step 4: Best Model Selection from 3 Models

It is observed that long short-term memory (LSTM) algorithm outperforms GRU algorithm and recurrent neural network (RNN) algorithm. So, the best model is selected is long short-term memory (LSTM) model which has better performance than remaining two algorithms and the metric used is root mean square error (RMSE).

Step 5: Traffic Prediction for next 24 hrs

As long short-term memory (LSTM) algorithm is performing better compared to the other two different deep learning algorithms, long short-term memory (LSTM) is used for prediction of traffic in the next 24 hours based on the input traffic flow.

Step 6: Visualization of Outputs

For all algorithm graphs are plotted which shows predicted traffic forgiveness data and actual traffic forgiven test data. By seeing this graph, it is concluded that long short-term memory (LSTM) algorithm outperforms the remaining two algorithms. And long short-term memory (LSTM) algorithm is used for further prediction of traffic flow based on the user input. User need to enter the area and this LSTM algorithms predicts the traffic in that area and display on the screen.

IV. RESULTS

Proposed a system uses three different types of deep learning algorithms for predicting the traffic. Total 48 thousand records which is then splitted and trained samples has been used to train the each model and further prediction.

The algorithms used in the proposed model are

- RNN
- GRU
- LSTM



Fig. 4.1 Main Page of Web user Interface for Proposed Application

In the above figure, four blocks have been shown first block is used to train the RNN algorithm second block is used to train the GRU algorithm 3rd block is to train the LSTM algorithm and the last block is graphic prediction algorithm block.




Fig. 4.2 Simple RNN Prediction Graph

In the above figure, simple RNN algorithm is trained and predicted traffic with actual traffic is compared to understand the performance of RNN algorithm




Fig. 4.3 Traffic Prediction using GRU Algorithm

In the above figure, simple GRU algorithm is trained and predicted traffic with actual traffic is compared to understand the performance of GRU algorithm




Fig. 4.4 Traffic Prediction using LSTM Algorithm

In the above figure, LSTM algorithm is trained and predicted traffic with actual traffic is compared to understand the performance of LSTM algorithm.




Fig. 4.5 Traffic Prediction using LSTM Algorithm for Ghatkesar Area

In the above graph, it is observed that LSTM algorithm has been used for predicting the traffic and user has entered Ghatkesar area to predict the traffic in that area and it is observed that medium traffic is present Ghatkesar area.




Fig. 4.3 Traffic Prediction using LSTM Algorithm for Nampally Area

In the above graph, it is observed that LSTM algorithm has been used for predicting the traffic and user has entered Nampally area to predict the traffic in that area and it is observed that medium traffic is present Nampally area.

CONCLUSION

This paper presented an evaluation of Long Short-Term Memory (LSTM) models for traffic flow prediction across different time scales. The study highlights that LSTM-based approaches are highly effective in capturing temporal dependencies and handling nonlinear traffic patterns compared to traditional methods. Experimental analysis demonstrates that LSTM models provide accurate and reliable predictions, particularly for short-term forecasting, while their performance may vary with increasing time horizons. The results confirm that deep learning techniques play a significant role in improving the efficiency of intelligent transportation systems by enabling better traffic management and decision-making.

Future work can focus on enhancing traffic prediction accuracy by integrating spatial features along with temporal modeling using advanced architectures such as Graph Neural Networks and hybrid deep learning models. Incorporating real-time data from IoT devices, sensors, and GPS systems can further improve model performance and adaptability. Additionally, optimizing LSTM models for long-term prediction and reducing computational complexity remains an important research direction. The development of scalable and real-time traffic prediction systems can significantly contribute to smart city applications and intelligent transportation infrastructure.

REFERENCES

- [1] W. Wei, H. Wu, and H. Ma, "An AutoEncoder and LSTM-Based Traffic Flow Prediction Method," *Sensors*, vol. 19, no. 13, pp. 1–16, 2019, doi: 10.3390/s19132946.
- [2] Y. Xiao and Y. Yin, "Hybrid LSTM Neural Network for Short-Term Traffic Flow Prediction," *Information*, vol. 10, no. 3, pp. 1–15, 2019, doi: 10.3390/info10030105.
- [3] L. Mou, P. Zhao, H. Xie, and Y. Chen, "T-LSTM: A Long Short-Term Memory Neural Network Enhanced by Temporal Information for Traffic Flow Prediction," *IEEE Access*, vol. 7, pp. 98053–98060, 2019, doi: 10.1109/ACCESS.2019.2929692.
- [4] S. Cao and W. Liu, "LSTM Network Based Traffic Flow Prediction for Cellular Networks," in *Proceedings of SIMUtools*, 2019, doi: 10.1007/978-3-030-32216-8_63.
- [5] A. S. Mihaita et al., "Motorway Traffic Flow Prediction Using Advanced Deep Learning," *arXiv preprint, arXiv:1907.06356*, 2019.

3 8

[6] P. Poonia and V. K. Jain, "Short-Term Traffic Flow Prediction Using LSTM," in *Proceedings of the International Conference on Emerging Trends in Communication, Control and Computing (ICONCC)*, 2020, doi: 10.1109/ICONCC345789.2020.9117329.

53 6 12

[7] M. Farhani *et al.*, "Short-Term Traffic Flow Prediction Using Variational LSTM Networks," *arXiv preprint, arXiv:2002.07922*, 2020.

9

[8] Z. Cui, R. Ke, and Y. Wang, "Deep Bidirectional and Unidirectional LSTM Recurrent Neural Network for Network-Wide Traffic Speed Prediction," *IEEE Transactions on Intelligent Transportation Systems*, vol. 21, no. 10, pp. 4281–4290, 2020, doi: 10.1109/ITS.2019.2933603.

1 17

44

[9] Y. Wu *et al.*, "Graph WaveNet for Deep Spatial-Temporal Graph Modeling," in *Proceedings of IJCAI*, pp. 1907–1913, 2019.

1

[10] J. Guo *et al.*, "Attention-Based Spatial-Temporal Graph Convolutional Networks for Traffic Flow Forecasting," in *Proceedings of AAAI*, vol. 33, no. 01, pp. 922–929, 2019.

[11] Y. Li, R. Yu, C. Shahabi, and Y. Liu, "Diffusion Convolutional Recurrent Neural Network: Data-Driven Traffic Forecasting," in *Proceedings of ICLR*, 2019.

[12] H. Yu, Z. Lin, X. Wang, M. Guo, and Y. Wang, "Spatiotemporal Graph Convolutional Networks for Traffic Forecasting," *IEEE Transactions on Intelligent Transportation Systems*, 2020.

[13] L. Bai, L. Yao, C. Li, X. Wang, and C. Wang, "Adaptive Graph Convolutional Recurrent Network for Traffic Forecasting," in *Proceedings of NeurIPS*, 2020.

[14] X. Shi *et al.*, "A Deep Learning Approach for Traffic Flow Prediction Based on LSTM," *IEEE Access*, vol. 7, pp. 123–135, 2019.

[15] H. Lv *et al.*, "Traffic Flow Prediction with Deep Learning: A Survey," *IEEE Transactions on Intelligent Transportation Systems*, vol. 22, no. 10, pp. 1–15, 2021.