

Fake News Detection Using Machine Learning

Major Project Submitted

in

Partial Fulfilment of the requirement of the degree

of

Bachelor of Technology

in

Computer Science and Engineering

By

Md Zafaruddin – 27600122028

Danyal Hussain – 27600122061

Murtuza Ali – 27600122114

Adarsh Raj – 27600122169

Pappu Kumar – 27600122212

Under the guidance of

Professor Trisha Mandal



BUDGE BUDGE INSTITUTE OF TECHNOLOGY

Affiliated to MAKAUT (formerly WBUT) & Approved by AICTE, NAAC
Accredited, Recognized by "UGC section 2f" with AISHE CODE-C-6239 Kolkata -
700 137, West Bengal, India | Phone: 0332 4820676 / 0670

<http://www.bbit.edu.in>



BUDGE BUDGE INSTITUTE OF TECHNOLOGY

(A unit of Jagannath Gupta Family Trust)

Approved by AICTE, Govt. of India and Affiliated to MAKAUT (formerly WBUT)
Nischintapur, Budge Budge, Kolkata - 700 137, West Bengal, | Phone: 0332 4820676 / 0670

Website: www.bbit.edu.in

Certificate

This is to certify that the major project work entitled “ FAKE NEWS DETECTION USING MACHINE LEARNING “ submitted by **Md Zafaruddin, Danyal Hussain, Murtuza Ali, Adarsh Raj and Pappu Kumar**, to the Department of Computer Science & Engineering , Budge Budge Institute of Technology , Kolkata , is a record of bona fide research work carried out under my supervision and is worthy for consideration for the award of B.Tech Degree from Maulana Abul Kalam Azad University of Technology , formerly WBUT

Name and Signature of Guide

Name and Signature of Head of
Department

Date:

Name and Signature of Principal

Forwarded By:

Name and Signature of Head of
Institution

Declaration

We, **Md Zafaruddin, Danyal Hussain, Murtuza Ali, Adarsh Raj and Pappu Kumar**, hereby declare that the Project Report titled “**FAKE NEWS DETECTION USING MACHINE LEARNING**” submitted to **Maulana Abul Kalam Azad University of Technology, West Bengal** in partial fulfilment of the requirement for the award of the degree of **Bachelor of Technology in Computer Science & Engineering (B. Tech)** is our original work. The findings and conclusions are based on data collected and analysed by us and have not been submitted elsewhere for any degree or diploma.

Name and Signature of
Md Zafaruddin
URN: 27600122028

Date:

Place:

Name and Signature of
Danyal Hussain
URN: 27600122061

Name and Signature of
Murtuza Ali
URN: 27600122114

Name and Signature of
Adarsh Raj
URN: 27600122169

Name and Signature of
Pappu Kumar
URN: 27600122212

No-Plagiarism Declaration

Title of the Project: Fake News Detection Using Machine Learning

Name(s) of the learner: Md Zafaruddin, Danyal Hussain, Murtuza Ali, Adarsh Raj and
Pappu Kumar

Name of Project Supervisor: Prof. Trisha Mandal

We declare that this Project Report is the result of our independent work. All sources of information have been duly acknowledged. No portion of this work has been copied or reproduced from any other project or publication. We understand that plagiarism is a serious offence and may result in rejection of Our work and appropriate action against Us.

Signature of Student:

Date:

Place:

Certificate From Supervisor

Date:

This is to certify that the Project Report titled “**FAKE NEWS DETECTION USING MACHINE LEARNING**” submitted by **Md Zafaruddin(URN: 27600122028), Danyal Hussain(URN: 27600122061), Murtuza Ali(URN: 27600122114), Adarsh Raj(URN: 27600122169), and Pappu Kumar(URN: 27600122212)**, is an original work carried out under my direct supervision in partial fulfilment of the requirements for the degree **Bachelor of Technology in Computer Science & Engineering (B. Tech)** at **Budge Budge Institute of Technology**, affiliated to **Maulana Abul Kalam Azad University of Technology, West Bengal**.

To the best of my knowledge, this report has not been submitted for any other award. The student’s performance during the project period has been satisfactory.

Signature

(Name, Designation, Institution)

Acknowledgement

We would like to express our sincere gratitude to our project supervisor, Professor Trisha Mandal, for her invaluable guidance, continuous support, and constructive feedback throughout the development of this project. Her expertise and encouragement were instrumental in shaping the direction and successful completion of this work.

We are also thankful to the Department of Computer Science and Engineering, Budge Budge Institute of Technology, for providing the necessary resources, infrastructure, and academic environment that made this project possible.

We extend our appreciation to the faculty members who offered their insights during the course of this research, and to our friends and classmates for their support and encouragement.

Finally, we are deeply grateful to our families for their constant motivation, patience, and unwavering support throughout our academic journey.

Md Zafaruddin – 27600122028

Danyal Hussain – 27600122061

Murtuza Ali – 27600122114

Adarsh Raj – 27600122169

Pappu Kumar – 27600122212

List of Abbreviations

<u>Abbreviation</u>	<u>Full Form</u>
AI	Artificial Intelligence
ML	Machine Learning
NLP	Natural Language Processing
TF-IDF	Term Frequency–Inverse Document Frequency
SVM	Support Vector Machine
PAC	Passive Aggressive Classifier
LSTM	Long Short-Term Memory
CNN	Convolutional Neural Network
Bi-LSTM	Bidirectional Long Short-Term Memory
BERT	Bidirectional Encoder Representations from Transformers
RoBERTa	Robustly Optimized BERT Pretraining Approach
XLNet	Generalized Autoregressive Pretraining Model
NAAC	National Assessment and Accreditation Council
AICTE	All India Council for Technical Education
UGC	University Grants Commission
ISOT	Information Security and Object Technology (Dataset)
API	Application Programming Interface
RSS	Really Simple Syndication
CSV	Comma-Separated Values
GPU	Graphics Processing Unit
URL	Uniform Resource Locator
UI	User Interface

Abstract

The rapid growth of digital media has made online news and social media platforms the primary source of information for millions of users, but it has also accelerated the spread of fake news and misinformation. Manual fact-checking cannot keep pace with the volume of content published daily, creating a need for automated, intelligent detection systems.

This project presents an AI-powered Fake News Detection System that integrates Machine Learning, Natural Language Processing, semantic similarity analysis, and real-time news verification into a single framework. News text is preprocessed and converted into numerical features using TF-IDF, then classified as real or fake using a Passive Aggressive Classifier trained on the ISOT Fake News Dataset. Rather than relying on classification alone, the system cross-verifies the input against live Google News headlines and applies Sentence Transformer-based semantic similarity to compare contextual meaning rather than exact keyword overlap. The system also performs automatic news category detection (National, International, Sports, Business, Technology, Entertainment, Health, Crime, Education) and combines all outputs into a single credibility score and explainable final verdict, presented through an interactive Gradio-based web interface.

Experimental evaluation shows that combining machine learning prediction with semantic analysis and trusted news verification produces more reliable, transparent, and interpretable results than a standalone classifier, helping users assess the authenticity of online news with supporting evidence rather than a simple binary label.

Contents

Certificate	ii
Declaration	iii
No-Plagiarism Declaration	iv
Certificate from Supervisor	v
Acknowledgement	vi
List of Abbreviations	vii
Abstract	viii
Contents	ix
1 Introduction	1
1.1 Motivation	2
1.2 Literature Review	4
1.3 Research Gap	7
1.4 Research Objectives	10
1.5 Thesis Organization.....	13
2 Objective of the Study	15
2.1 General Objective.....	16
2.2 Specific Objectives.....	17
2.3 Scope of the Study	19
3 Problem Statement	20
3.1 Background of the Problem	21
3.2 Existing Problems	23
3.3 Proposed Solution	25
3.4 Significance of the Study	26

4	Methodology	27
4.1	System Architecture / Research Framework	28
4.2	Tools and Technologies Used.....	29
4.3	Dataset Description	31
4.4	Workflow Diagrams	32
4.5	Methodological Steps.....	34
5	Data Analysis & Interpretation	38
5.1	Dataset Analysis	39
5.2	Data Preprocessing Analysis	40
5.3	Feature Analysis	42
5.4	Data Interpretation	44
6	Discussion and Results	46
6.1	Overview	47
6.2	Model Evaluation	48
6.3	Sample Outputs	50
6.4	Key Findings	53
7	Conclusion	54
7.1	Summary of Findings	55
7.2	Major Contribution.....	57
8	Recommendations & Suggestions	58
8.1	Lessons Learnt	59
8.2	Project Limitation.....	60
8.3	Future Scope.....	62
8.4	Recommendations	63
	References	64

Introduction

This chapter lays the foundation for the research. It begins by outlining the motivation behind the study — how the rapid growth of digital and social media has fuelled the spread of fake news, and why an effective detection system needs more than classification alone, pairing machine learning prediction with real-time Google News verification and semantic similarity analysis. It then reviews the relevant literature, tracing the field's progression from traditional classifiers like Naive Bayes, Logistic Regression, and SVM, through TF-IDF-based feature extraction, to transformer-based models such as BERT and Sentence Transformer, while also surveying the widely used ISOT Fake News Dataset. Building on this review, the chapter identifies key gaps in existing work — heavy reliance on static historical datasets, no real-time verification, limited semantic understanding, and the absence of credibility scoring or category detection — and translates them into concrete objectives: dataset preparation, TF-IDF feature extraction, Passive Aggressive Classifier training, Google News integration, semantic similarity analysis, category detection, credibility scoring, and a Gradio-based interface. The chapter closes with an overview of how the remaining chapters of the report are organized.

1.1 Motivation

The rapid expansion of the internet and digital communication has significantly transformed the way people access and consume news. Social media platforms, online news portals, blogs, and instant messaging applications have become primary sources of information for millions of users worldwide. Although these platforms provide quick access to current events, they have also become major channels for the rapid spread of fake news and misinformation. False information can spread much faster than verified news, creating confusion, panic, social unrest, and even influencing political decisions and public opinion. Therefore, ensuring the authenticity and credibility of online news has become an important challenge in today's digital society.

Traditional methods of verifying news rely heavily on manual fact-checking performed by journalists and media organizations. While these methods are generally reliable, they require significant time and human effort, making them unsuitable for the fast-paced nature of online information sharing. As the volume of digital content continues to increase every day, manual verification alone is no longer sufficient to combat the spread of misinformation. This situation has created the need for intelligent automated systems capable of identifying fake news quickly and accurately.

Recent advancements in Artificial Intelligence (AI), Machine Learning (ML), and Natural Language Processing (NLP) have opened new opportunities for developing automated fake news detection systems. Machine learning models can analyze textual patterns, linguistic features, and writing styles to classify news articles as genuine or fake. However, many existing fake news detection systems depend only on previously collected datasets. Such models often struggle to evaluate newly emerging news because they cannot verify whether similar information has been reported by trusted news organizations.

This limitation motivated the development of the proposed project. Instead of relying solely on machine learning predictions, the proposed system combines multiple verification techniques to improve reliability.

It first preprocesses the news text and applies a trained machine learning classifier to estimate whether the article is likely to be real or fake. The system then performs real-time verification by searching trusted Google News sources and comparing the entered news with similar published headlines. Furthermore, semantic similarity analysis is used to measure how closely the input news matches verified articles, enabling the system to understand contextual meaning rather than relying only on exact keyword matching.

Another motivating factor behind this work is the need to provide users with a clear explanation of the prediction instead of simply displaying a binary "Real" or "Fake" result. The developed system presents a credibility score, category detection, semantic verification, related news headlines, and an overall verdict that helps users understand the reasoning behind the final decision. Such transparency improves user confidence and makes the system more practical for educational and research purposes.

The increasing misuse of digital platforms to spread manipulated information during elections, public emergencies, health crises, and international conflicts further highlights the importance of developing intelligent fact-checking solutions. By integrating machine learning with semantic analysis and trusted news verification, this project aims to provide a more reliable and comprehensive approach to fake news detection. The proposed system demonstrates how multiple AI techniques can work together to improve prediction accuracy while offering meaningful insights into the credibility of online news.

1.2 Literature Review

The problem of fake news detection has received significant attention from researchers due to the rapid growth of online news platforms and social media. The widespread availability of digital information has made it easier to share news instantly, but it has also increased the spread of misinformation. Over the past decade, researchers have proposed various machine learning, natural language processing, and deep learning techniques to automatically identify fake news. This section reviews the major research contributions related to fake news detection and highlights the limitations that motivated the development of the proposed system.

One of the earliest approaches to fake news detection relied on traditional machine learning algorithms such as Naïve Bayes, Logistic Regression, Decision Trees, Random Forest, and Support Vector Machines (SVM). These models used textual features extracted from news articles, including word frequency, sentence structure, and linguistic characteristics. Among these methods, Support Vector Machine and Logistic Regression demonstrated relatively high accuracy for binary classification problems. However, these approaches depended heavily on handcrafted features and required extensive preprocessing before model training.

The introduction of Term Frequency–Inverse Document Frequency (TF-IDF) significantly improved text representation in fake news classification tasks. TF-IDF assigns weights to words based on their importance within a document while reducing the influence of commonly occurring words. Several studies reported that combining TF-IDF with linear classifiers such as Passive Aggressive Classifier and Logistic Regression produced reliable results while maintaining low computational cost. Due to its efficiency and strong performance on textual data, TF-IDF has become one of the most widely used feature extraction techniques in fake news detection.

Recent developments in Natural Language Processing (NLP) have further enhanced the capability of automated fake news detection systems. Researchers have adopted transformer-based language models such as BERT, RoBERTa, XLNet, and Sentence Transformer to capture contextual meaning instead of relying solely on keyword

frequency. Unlike traditional approaches, transformer models understand semantic relationships between words and sentences, allowing them to classify news articles more accurately even when similar information is expressed using different vocabulary. These models have demonstrated superior performance on several benchmark datasets.

Another important direction in fake news research focuses on semantic similarity analysis. Instead of directly predicting whether a news article is fake or real, semantic similarity compares the meaning of an input article with trusted news published by reliable media organizations. Sentence embedding models such as Sentence Transformer convert textual information into numerical vector representations, making it possible to calculate similarity scores between different news articles. This approach helps identify whether an article conveys information consistent with verified news sources, thereby improving prediction reliability.

Researchers have also explored real-time news verification using trusted online sources. Rather than relying exclusively on historical datasets, several systems integrate live news feeds from news portals and search engines to validate whether similar information has been published by credible organizations. This hybrid approach combines machine learning predictions with external verification, reducing false positives and improving user confidence. However, many existing implementations remain limited in terms of scalability, semantic understanding, or user-friendly presentation.

Deep learning approaches such as Long Short-Term Memory (LSTM), Convolutional Neural Networks (CNN), and Bidirectional LSTM have also been applied to fake news detection. These architectures automatically learn complex textual patterns without requiring manual feature engineering. Although they often achieve high classification accuracy, they generally require large labelled datasets, extensive computational resources, and longer training time. Their complexity makes them less suitable for lightweight applications intended for real-time deployment.

Several publicly available datasets have been widely used for evaluating fake news detection models. Among them, the ISOT Fake News Dataset is one of the most popular benchmark datasets because it contains a large collection of labelled fake and genuine news articles collected from multiple reliable sources. Researchers have used this dataset to compare the performance of various machine learning and deep learning models under standardized conditions. The availability of labelled data enables objective evaluation of classification accuracy and model robustness.

Despite these advancements, existing fake news detection systems continue to face several limitations. Many systems rely only on static datasets and cannot effectively evaluate newly emerging news events. Others provide only a binary prediction without explaining the reasoning behind the decision. Some models ignore semantic understanding and depend solely on keyword matching, while others lack integration with trusted news sources for real-time verification. Furthermore, category identification and credibility estimation are often absent, reducing the interpretability of predictions.

The proposed project attempts to overcome these limitations by integrating multiple complementary techniques into a single framework. It combines TF-IDF-based feature extraction, a Passive Aggressive Classifier, Google News verification, semantic similarity using Sentence Transformer, news category detection, credibility score generation, and an interactive Gradio-based user interface. By combining machine learning predictions with semantic analysis and live news verification, the proposed system aims to provide more reliable, explainable, and user-friendly fake news detection than conventional standalone classification models.

Overall, the literature indicates that no single technique is sufficient for accurately detecting fake news in all scenarios. The integration of machine learning, semantic similarity, and trusted news verification offers a more comprehensive solution capable of improving prediction accuracy while increasing user trust. This observation forms the foundation of the proposed research and motivates the design of the AI-powered fake news detection system presented in this project.

1.3 Research Gap

The review of existing literature reveals that significant progress has been made in the field of fake news detection through the application of Machine Learning (ML), Natural Language Processing (NLP), and Deep Learning techniques. Various algorithms have demonstrated promising performance in distinguishing between genuine and fabricated news articles. Despite these advancements, several limitations continue to exist in current fake news detection systems, particularly when dealing with newly emerging news events, real-time verification, and user interpretability. These limitations create opportunities for further research and improvement.

One of the primary research gaps identified is the heavy dependence of existing systems on historical datasets. Most machine learning models are trained using previously collected fake and real news articles. While these models perform well on test datasets, they often struggle to evaluate breaking news or recently published events because such information was not available during the training phase. Consequently, the prediction accuracy decreases when the model encounters completely new topics or evolving real-world situations.

Another important limitation is the lack of real-time verification. Many fake news detection models classify news articles solely based on textual features without checking whether similar information has been reported by trusted media organizations. As a result, the system may incorrectly classify genuine news as fake or vice versa. The absence of live verification significantly reduces the reliability of predictions, particularly during rapidly changing events such as elections, natural disasters, international conflicts, or public health emergencies.

The literature also indicates that numerous existing approaches rely primarily on keyword-based or statistical feature extraction techniques. Although methods such as TF-IDF effectively represent textual information, they do not fully capture the semantic meaning or contextual relationships between sentences. News articles conveying the same information using different wording may therefore receive different predictions.

This limitation reduces the ability of traditional models to understand natural language in a manner similar to human readers.

Although transformer-based language models have considerably improved semantic understanding, many existing implementations utilize these models only for text classification. Very few systems combine semantic similarity analysis with real-time verification from trusted news sources. As a result, users receive only a classification label without understanding whether similar information exists in credible publications. The lack of explainability makes it difficult for users to assess the trustworthiness of the system's prediction.

Another research gap involves the absence of credibility assessment. Most fake news detection applications simply classify news as "Fake" or "Real" without providing any quantitative measure of confidence or reliability. Users are therefore unable to evaluate the certainty of the prediction or understand how strongly the available evidence supports the final decision. Providing a credibility score can significantly improve user confidence and assist decision-making.

The review further shows that news category identification is rarely integrated into fake news detection frameworks. Most studies focus only on binary classification while ignoring the type of news being analyzed. Identifying whether a news article belongs to categories such as National, International, Sports, Technology, Business, Entertainment, Health, Crime, or Education can provide additional contextual information that improves user understanding and system transparency.

Existing systems also pay limited attention to user interface design and result presentation. Many research prototypes generate only textual outputs or prediction labels without presenting supporting evidence. Modern applications require intuitive interfaces that display prediction results, credibility scores, semantic similarity information, related news headlines, and explanatory summaries in a clear and understandable manner. Such visual presentation enhances usability and allows users to make informed judgments regarding the authenticity of news.

Another challenge observed in previous research is the limited integration of multiple AI techniques within a single framework. Most existing systems rely on a single prediction model or a single verification mechanism. Combining machine learning classification, semantic similarity analysis, trusted news verification, category

detection, and credibility estimation within one unified architecture remains relatively uncommon. Integrating these complementary techniques can improve overall system robustness while reducing the weaknesses associated with individual methods.

Based on these identified gaps, the proposed project aims to develop an integrated fake news detection framework that combines Machine Learning, TF-IDF feature extraction, Passive Aggressive Classification, Google News verification, semantic similarity using Sentence Transformer, news category detection, credibility score generation, and an interactive Gradio-based user interface. Unlike many existing systems, the proposed solution not only predicts whether news is fake or real but also verifies the information against trusted online sources, measures semantic similarity, classifies the news category, and presents a credibility score along with supporting evidence. This integrated approach addresses several shortcomings identified in previous studies and contributes towards a more accurate, explainable, and user-friendly fake news detection system.

1.4 Research Objectives

The primary objective of this research is to design and develop an intelligent fake news detection system that can accurately identify whether a news article is genuine or fake by integrating Machine Learning, Natural Language Processing (NLP), semantic similarity analysis, and real-time news verification. The proposed system aims to overcome the limitations of conventional fake news detection approaches by combining multiple verification techniques into a unified framework that enhances prediction accuracy, reliability, and transparency.

Unlike traditional systems that rely solely on historical datasets for classification, the proposed research seeks to incorporate real-time verification using trusted online news sources. This integration enables the system to validate news articles against recent publications and provide users with supporting evidence for every prediction. In addition, the system is designed to generate a credibility score and explanatory analysis so that users can better understand the reasoning behind the final verdict rather than receiving only a binary prediction.

To accomplish the overall objective, the following specific objectives have been identified:

General Objective

The general objective of this research is to develop an AI-powered fake news detection system capable of analyzing news articles using machine learning techniques, semantic similarity analysis, and live news verification to improve the accuracy and reliability of fake news identification.

Specific Objectives

The specific objectives of this research are as follows:

- To collect and preprocess authentic and fake news datasets for training and evaluation purposes.
- To implement efficient text preprocessing techniques, including data cleaning, tokenization, removal of unnecessary characters, and normalization of textual information
- To extract meaningful textual features using the Term Frequency–Inverse Document Frequency (TF-IDF) technique for machine learning classification.
- To train and evaluate a Passive Aggressive Classifier for distinguishing between genuine and fake news articles.
- To integrate Google News verification for identifying related news published by trusted media organizations.
- To perform semantic similarity analysis using Sentence Transformer in order to compare user-provided news with verified online news articles based on contextual meaning.
- To classify news articles into appropriate categories such as National News, International News, Sports News, Business News, Technology News, Entertainment News, Health News, Crime News, and Education News.
- To generate a Credibility Score based on machine learning prediction, semantic similarity, and trusted news verification results.
- To provide an informative and user-friendly interface using Gradio, allowing users to enter news articles and receive detailed prediction results along with supporting evidence.
- To display a comprehensive analysis including machine learning prediction, semantic verification, related Google News headlines, detected news category, and the final credibility-based verdict.
- To improve user confidence by providing explainable results instead of only displaying a "Fake" or "Real" prediction.

- To develop a lightweight, efficient, and scalable system that can be extended with additional news sources, languages, and advanced deep learning models in future research.

The successful achievement of these objectives will contribute to the development of a practical fake news detection system capable of supporting users in identifying misleading information more accurately. By integrating machine learning, semantic analysis, and real-time verification into a single platform, the proposed research aims to provide a comprehensive solution for combating misinformation in today's rapidly evolving digital environment.

1.5 Thesis Organization

This thesis is organized into eight chapters, each focusing on a specific aspect of the proposed AI-Powered Fake News Detection System. The arrangement of these chapters follows a systematic approach, beginning with the introduction of the research problem and concluding with the findings, recommendations, and future scope. This organization enables readers to understand the complete research process in a structured and logical manner.

Chapter 1 – Introduction presents the background of the study, motivation behind the research, literature review, research gap, research objectives, and the overall organization of the thesis. It provides a comprehensive overview of the fake news problem and explains the need for an intelligent detection system that combines machine learning with real-time news verification.

Chapter 2 – Objective of the Study describes the general objective and specific objectives of the research. It also explains the scope of the proposed system, its practical applications, and the boundaries within which the research has been conducted.

Chapter 3 – Problem Statement discusses the existing challenges associated with fake news detection. It explains the shortcomings of traditional approaches, identifies the major issues in current fake news detection systems, and introduces the proposed solution. The chapter also highlights the significance of the study in addressing misinformation and improving digital information reliability.

Chapter 4 – Methodology explains the complete methodology adopted for developing the proposed system. It describes the system architecture, research framework, dataset collection, preprocessing techniques, feature extraction using TF-IDF, machine learning model selection, semantic similarity analysis, Google News verification process, news category detection, credibility score calculation, and the development of the Gradio-based user interface. The workflow of the proposed system is also presented in a step-by-step manner.

Chapter 5 – Data Analysis and Interpretation focuses on the analysis of the dataset used for model training and evaluation. It discusses data preprocessing, feature engineering, dataset visualization, and the interpretation of important statistical observations. The chapter also explains how textual information is transformed into numerical features suitable for machine learning algorithms.

Chapter 6 – Discussion and Results present the experimental results obtained from the proposed system. It evaluates the performance of the machine learning model using appropriate evaluation metrics and demonstrates the effectiveness of semantic similarity analysis, Google News verification, category detection, and credibility score generation. Sample outputs and result analysis are also included to illustrate the practical performance of the developed system.

Chapter 7 – Conclusion summarizes the entire research work and discusses the major contributions of the proposed fake news detection system. It highlights the achievements of the project, evaluates whether the research objectives have been successfully fulfilled, and emphasizes the importance of integrating machine learning with semantic analysis and real-time verification.

Chapter 8 – Recommendations and Suggestions present the limitations of the current system and suggests possible improvements for future research. It discusses opportunities for extending the system through multilingual support, advanced transformer-based language models, integration with additional trusted news sources, enhanced explainable AI techniques, and deployment as a scalable web or mobile application for real-world use.

Finally, the thesis concludes with a comprehensive list of references, including research papers, books, journals, online resources, and official documentation consulted during the development of this project. These references provide the academic foundation of the research and acknowledge the contributions of previous studies in the field of fake news detection, machine learning, and natural language processing.

Objective of the Study

This chapter takes the research direction from the previous chapter and sharpens it into a clear set of goals and limits. It opens by stating the overall aim of the work: building an AI-driven system for detecting fake news that brings together machine learning classification, semantic similarity comparison, and live news verification to make detection more accurate and dependable. This broad aim is then broken down into specific, actionable objectives — collecting and preprocessing the dataset, extracting features through TF-IDF, training a Passive Aggressive Classifier, integrating with Google News, performing semantic comparison using Sentence Transformer, detecting categories across nine distinct news domains, generating a credibility score, and building an interactive interface with Gradio. Finally, the chapter sets clear boundaries for the study, restricting its focus to English-language text-based news articles and the ISOT Fake News Dataset, while framing the resulting system as a decision-support tool for academic purposes rather than a substitute for professional fact-checking.

2.1 General Objective

The primary objective of this research is to design, develop, and evaluate an intelligent fake news detection system capable of accurately identifying whether a news article is genuine or fake by integrating Machine Learning, Natural Language Processing (NLP), semantic similarity analysis, and real-time news verification. The proposed system aims to provide users with a reliable platform that not only predicts the authenticity of news but also validates it through trusted online news sources and contextual semantic analysis.

With the rapid growth of digital media and online news platforms, the volume of misinformation has increased significantly. Traditional manual fact-checking methods are time-consuming and cannot keep pace with the speed at which information spreads across the internet. Therefore, this research focuses on developing an automated system that combines multiple Artificial Intelligence techniques to improve the reliability, transparency, and efficiency of fake news detection.

The developed system utilizes TF-IDF feature extraction and a Passive Aggressive Classifier for textual classification, followed by Google News verification, semantic similarity analysis using Sentence Transformer, news category detection, and credibility score estimation. By integrating these techniques, the system seeks to minimize false predictions while providing users with meaningful explanations and supporting evidence for every prediction.

Another important objective of the study is to develop a user-friendly interface using Gradio, enabling users to interact with the system easily by entering any news article and receiving a detailed analytical report containing prediction results, category detection, semantic verification, credibility score, and relevant news headlines from trusted sources.

Overall, the research aims to demonstrate that combining machine learning with semantic analysis and real-time news verification can significantly improve the effectiveness of fake news detection systems compared to conventional standalone machine learning models.

2.2 Specific Objective

The successful completion of the proposed research requires the achievement of several specific objectives. These objectives collectively contribute towards the development of a comprehensive and intelligent fake news detection framework

.

The specific objectives of the study are as follows:

- To study the characteristics and impact of fake news in modern digital communication systems.
- To collect and prepare a reliable dataset consisting of genuine and fake news articles for training and evaluation.
- To perform efficient text preprocessing including data cleaning, normalization, punctuation removal, stop-word elimination, and text transformation.
- To extract meaningful textual features using the Term Frequency–Inverse Document Frequency (TF-IDF) technique.
- To train and evaluate a Passive Aggressive Classifier for fake news classification.
- To integrate Google News for verifying whether similar news articles exist on trusted news platforms.
- To perform semantic similarity analysis using Sentence Transformer for contextual comparison between user-provided news and verified news headlines.
- To detect the category of the entered news article, including National, International, Sports, Technology, Business, Entertainment, Health, Crime, and Education.
- To calculate a credibility score based on multiple verification factors instead of relying only on machine learning prediction.
- To generate an intelligent final verdict by combining machine learning prediction, semantic similarity, and trusted news verification.
- To develop an interactive web-based interface using Gradio for easy user interaction.

2.2 Specific Objective

Objective of Study

- To display prediction confidence, credibility score, semantic verification results, category information, and supporting Google News headlines in an understandable format.
- To improve transparency by providing explainable AI-based outputs rather than simple binary classification.
- To develop a scalable architecture that can be extended with multilingual support, advanced transformer models, and additional trusted news sources in future research.
- The successful accomplishment of these objectives contributes to building a practical and reliable fake news detection system capable of assisting users in identifying misinformation more effectively.

2.3 Scope of Study

The scope of the proposed research is limited to the development and evaluation of an AI-powered fake news detection system designed for textual news articles written in the English language. The system focuses on identifying whether a news article is genuine or fake by combining machine learning techniques with semantic analysis and real-time verification from trusted online news sources.

The study covers the complete pipeline of fake news detection, including dataset preparation, text preprocessing, feature extraction, machine learning classification, semantic similarity analysis, Google News verification, category detection, credibility score generation, and result visualization through an interactive Gradio-based interface. The proposed system supports multiple news categories, including National News, International News, Sports News, Business News, Technology News, Entertainment News, Health News, Crime News, and Education News. This categorization improves contextual understanding and enhances the interpretability of prediction results.

The project utilizes the ISOT Fake News Dataset for training and evaluating the machine learning model. Feature extraction is performed using TF-IDF, while classification is carried out using a Passive Aggressive Classifier. Semantic similarity is implemented using Sentence Transformer, and real-time verification is achieved through Google News and trusted online news sources.

The system is intended primarily for academic research, educational demonstrations, and awareness regarding fake news detection. Although the developed framework demonstrates effective performance, it is not designed to replace professional fact-checking organizations. Instead, it serves as a decision-support system that assists users by providing evidence-based predictions and credibility assessment.

Furthermore, the architecture has been designed to support future enhancements such as multilingual fake news detection, transformer-based language models, social media integration, image-based misinformation detection, and deployment as a cloud-based web application. These extensions are beyond the scope of the current research but provide promising directions for future work.

Problem Statement

This chapter is on the specific problem the research sets out to solve. It begins with background on how platforms like Facebook, X, WhatsApp, and Telegram have sped up the spread of fake news, particularly during high-stakes moments such as elections, pandemics, and conflicts, and why manual fact-checking simply can't keep up with this pace anymore. It then lays out the shortcomings found in current detection systems — a dependence on historical datasets, no real-time verification, a tendency to rely on keyword matching rather than genuine contextual understanding, limited explainability, no credibility scoring, and weak category identification. Against this backdrop, the chapter introduces the proposed solution: a Gradio-based system that combines TF-IDF and Passive Aggressive classification with Google News verification, semantic similarity through Sentence Transformer, and automatic category detection, producing both a credibility score and an explainable verdict. It closes by discussing why the study matters — both as a practical decision-support tool and as an academic contribution toward explainable, AI-based misinformation detection.

3.1 Background of Problem

The rapid growth of the internet and digital communication technologies has revolutionized the way information is created, shared, and consumed. Today, millions of people rely on online news websites, social media platforms, blogs, and messaging applications to obtain information about current events. The accessibility and speed of these digital platforms have made information available within seconds, allowing news to reach a global audience almost instantly. However, this convenience has also led to the widespread dissemination of fake news, misinformation, and misleading content.

Fake news refers to intentionally fabricated or manipulated information presented as authentic news with the objective of misleading readers. Such misinformation is often designed to influence public opinion, generate financial gain, manipulate political decisions, damage reputations, or create unnecessary panic among society. Due to the enormous volume of information shared every day, it has become increasingly difficult for individuals to distinguish between genuine and fabricated news.

Social media platforms such as Facebook, X (formerly Twitter), Instagram, WhatsApp, Telegram, and YouTube have accelerated the spread of misinformation because users frequently share news without verifying its authenticity. During important national and international events such as elections, pandemics, natural disasters, or military conflicts, fake news spreads rapidly and can produce serious social, economic, and political consequences. Therefore, the development of intelligent systems capable of automatically identifying fake news has become an important area of research.

Traditional fact-checking methods performed by journalists and professional organizations provide reliable verification, but they require considerable human effort and time. Since thousands of news articles are published every hour, manual verification alone cannot effectively address the increasing volume of online misinformation. Consequently, Artificial Intelligence (AI), Machine Learning (ML), and Natural Language Processing (NLP) have emerged as promising technologies for developing automated fake news detection systems.

Machine learning algorithms can analyze textual patterns and classify news articles as genuine or fake based on previously learned examples. However, many existing

systems depend entirely on historical datasets and cannot effectively evaluate newly published news articles that were unavailable during model training. This limitation reduces their effectiveness in real-world applications where new events occur continuously.

To overcome these challenges, the proposed research integrates machine learning prediction with semantic similarity analysis and real-time Google News verification. Rather than relying solely on statistical classification, the developed system compares user-provided news with trusted online sources, analyzes contextual similarity, estimates credibility, identifies the news category, and generates an explainable final verdict. This integrated approach aims to improve the reliability and transparency of fake news detection while providing users with meaningful supporting evidence.

3.2 Existing Problems

Although numerous fake news detection systems have been proposed in recent years, several important limitations continue to reduce their effectiveness in practical applications.

The first limitation is the heavy dependence on historical datasets. Most machine learning models are trained using previously collected fake and genuine news articles. These models perform well on known datasets but often struggle to classify breaking news because they have never encountered similar information during training.

Another significant limitation is the absence of real-time verification. Most systems classify news solely on the basis of textual features without checking whether similar information has already been published by trusted news organizations. Consequently, users receive predictions without any supporting evidence regarding the credibility of the news.

Many existing approaches also rely on keyword-based analysis rather than contextual understanding. Keyword-based systems may incorrectly classify news articles when the same information is expressed using different words or writing styles. They frequently fail to capture the semantic meaning of sentences, leading to inaccurate predictions.

Another issue is the lack of explainability. Existing systems usually display only "Fake" or "Real" labels without explaining why a particular decision was made. Users therefore have limited confidence in the prediction because they cannot examine the reasoning or supporting information behind the classification.

Most available fake news detection applications do not provide a credibility score. A binary prediction alone does not indicate the confidence level of the model or the amount of supporting evidence available. Credibility estimation enables users to better understand the reliability of prediction results.

Another limitation is the absence of news category identification. Most systems ignore contextual information such as whether the article belongs to National, International, Sports, Business, Technology, Entertainment, Health, Crime, or Education. Category detection improves the interpretability of predictions and provides additional context for users.

Furthermore, many research prototypes offer limited user interaction and poor visualization. They generally lack intuitive graphical interfaces capable of presenting prediction results, semantic similarity, verification status, credibility score, and related news headlines in a user-friendly manner.

These limitations indicate that there is still considerable scope for developing more intelligent fake news detection systems capable of combining multiple verification techniques within a unified framework.

3.3 Proposed Solution

To address the limitations identified in existing fake news detection systems, this research proposes an integrated AI-powered fake news detection framework that combines machine learning, semantic similarity analysis, and trusted online news verification into a single platform.

The proposed system begins by accepting a news article from the user through an interactive Gradio interface. The entered text undergoes preprocessing, including cleaning and normalization, before meaningful textual features are extracted using the TF-IDF technique. These features are then supplied to a Passive Aggressive Classifier trained on the ISOT Fake News Dataset to generate an initial prediction regarding whether the news is likely to be fake or genuine.

Instead of relying solely on machine learning prediction, the system performs an additional verification step using Google News. It searches trusted news sources for similar headlines and determines whether related information has been published by reliable media organizations. This real-time verification significantly improves the credibility of the final prediction.

The proposed framework also utilizes Sentence Transformer-based semantic similarity analysis to compare the contextual meaning of the user-provided news with verified news articles. Unlike simple keyword matching, semantic similarity allows the system to identify conceptually similar information even when different words are used.

Another important component of the proposed system is automatic news category detection. The system identifies whether the entered news belongs to categories such as National, International, Sports, Business, Technology, Entertainment, Health, Crime, or Education. This additional contextual information improves user understanding and supports better interpretation of prediction results.

Finally, the outputs generated by machine learning prediction, semantic similarity, Google News verification, and category detection are combined to calculate a credibility score and generate an explainable final verdict. The result is displayed through an interactive Gradio interface together with supporting headlines, prediction confidence, category information, and analysis summary.

3.4 Significance of the Study

The significance of this research lies in its contribution towards combating the growing problem of fake news through the application of Artificial Intelligence and Machine Learning techniques. By integrating multiple verification mechanisms into a single framework, the proposed system provides a more comprehensive approach to fake news detection than traditional standalone classifiers.

The developed system assists users in evaluating the credibility of online news before sharing or believing it. This capability contributes to reducing the spread of misinformation across digital platforms and encourages responsible information consumption.

From an academic perspective, the project demonstrates the practical application of Machine Learning, Natural Language Processing, semantic similarity analysis, and real-time news verification within a single research framework. It provides an effective case study for students and researchers interested in AI-based misinformation detection. The research also contributes to explainable artificial intelligence by presenting credibility scores, semantic verification, category detection, and supporting Google News headlines instead of simply providing binary predictions. Such transparency improves user trust and facilitates informed decision-making.

Furthermore, the modular architecture adopted in this project enables future enhancements such as multilingual support, transformer-based language models, integration with additional trusted news sources, social media verification, and deployment as a cloud-based web application. Consequently, the proposed research serves as a strong foundation for future investigations into intelligent misinformation detection systems.

Methodology

This chapter walks through how the proposed system was actually designed and built. It starts by describing the overall system architecture, tracing the path from Gradio-based user input through preprocessing, TF-IDF feature extraction, Passive Aggressive classification, retrieval from Google News, semantic comparison via Sentence Transformer, and category detection, all the way to the final credibility score. It then introduces the tools and technologies behind the implementation — Python, Google Colab, Scikit-learn, Pandas, NumPy, Sentence Transformer, Google News RSS, News API, Feedparser, Gradio, and Joblib. The chapter goes on to describe the ISOT Fake News Dataset, covering the True.csv and Fake.csv files and explaining how they were merged, labelled, and cleaned ahead of training. This is followed by workflow diagrams that trace a news article's journey from submission through preprocessing, classification, verification, and final result presentation. The chapter ends by breaking the overall process down into eleven methodological steps — spanning dataset collection and preprocessing, feature extraction, model training, prediction, Google News verification, semantic similarity analysis, category detection, credibility score generation, verdict generation, and result visualization.

4.1 System Architecture

The proposed AI-Powered Fake News Detection System follows a systematic methodology that integrates Machine Learning, Natural Language Processing, semantic similarity analysis, and real-time news verification to determine the authenticity of news articles. The overall framework has been designed to improve prediction accuracy while providing transparency through credibility scoring, category detection, and supporting evidence from trusted news sources.

The system begins with user interaction through a Gradio-based graphical interface. The user enters a news article and selects the appropriate news category. Before classification, the news text undergoes preprocessing to remove unwanted characters, normalize text, and prepare the input for machine learning analysis. Feature extraction is then performed using the TF-IDF technique, converting textual information into numerical vectors suitable for machine learning algorithms.

The processed feature vector is passed to the trained Passive Aggressive Classifier, which predicts whether the news article is likely to be genuine or fake. Simultaneously, the system generates a search query and retrieves related headlines from Google News. These headlines are further analyzed using Sentence Transformer-based semantic similarity to determine how closely the user-provided news matches verified news published by trusted media organizations.

The framework also performs semantic category detection to classify the entered news into categories such as National, International, Sports, Technology, Business, Entertainment, Health, Crime, and Education. Finally, the outputs from machine learning prediction, semantic similarity analysis, category detection, and Google News verification are combined to calculate a credibility score and generate the final verdict. The result is displayed through an interactive Gradio interface, allowing users to understand both the prediction and the supporting evidence behind it.

The overall architecture ensures that multiple verification mechanisms work together instead of relying solely on machine learning classification, thereby improving the robustness and reliability of fake news detection.

4.2 Tools and Technologies Used

The successful implementation of the proposed system required the integration of several software tools, machine learning libraries, APIs, and development platforms. Each technology was selected based on its efficiency, reliability, and compatibility with the project requirements.

Python

Python serves as the primary programming language due to its simplicity, extensive machine learning ecosystem, and strong support for natural language processing. It provides an efficient environment for implementing data preprocessing, model training, API integration, and user interface development.

Google Colab

Google Colaboratory was used as the primary development environment. It provides cloud-based execution, GPU support, and easy integration with machine learning libraries without requiring complex local setup.

Scikit-learn

Scikit-learn was utilized for machine learning implementation, including TF-IDF feature extraction, Passive Aggressive Classifier training, model evaluation, and performance analysis.

Pandas

Pandas was used for loading, cleaning, and manipulating the Fake.csv and True.csv datasets. It simplifies data preprocessing and structured data management.

NumPy

NumPy provides efficient numerical computation and supports vector operations required during feature extraction, probability calculation, and model prediction.

Sentence Transformer

Sentence Transformer was integrated for semantic similarity analysis and semantic category detection. The model converts textual information into sentence embeddings, enabling contextual comparison instead of simple keyword matching.

Google News RSS

Google News RSS was used for real-time verification of news articles. The retrieved headlines provide supporting evidence regarding whether similar information has been published by trusted news organizations.

News API

News API was integrated as an additional verification source to obtain news articles from multiple reliable publishers and improve verification accuracy.

Feed parser

Feed parser was used to parse RSS feeds retrieved from Google News and extract relevant news headlines.

Gradio

Gradio provides an interactive web-based graphical interface that allows users to enter news articles and receive prediction results along with category detection, credibility score, semantic analysis, and Google News verification.

Joblib

Joblib was used for saving and loading the trained machine learning model and TF-IDF vectorizer, reducing retraining time during deployment.

4.3 Dataset Description

The proposed fake news detection system was trained and evaluated using the ISOT Fake News Dataset, one of the most widely used benchmark datasets for fake news classification research. The dataset consists of two separate CSV files containing genuine and fake news articles collected from various online news sources.

The True.csv file contains authentic news articles obtained from trusted media organizations, while the Fake.csv file consists of fabricated and misleading news articles collected from unreliable websites. Each record contains the news title, article text, subject category, and publication date. These labeled datasets provide sufficient diversity for training supervised machine learning models capable of distinguishing between genuine and fake news.

Before training, both datasets were merged into a unified dataset. Binary labels were assigned, where genuine news articles were represented by one class and fake news articles by the other. Duplicate entries, missing values, and irrelevant attributes were removed during preprocessing to improve data quality and model performance.

The cleaned dataset was then divided into training and testing subsets. The training data was used to train the Passive Aggressive Classifier, while the testing data was used to evaluate model performance and prediction accuracy.

The ISOT dataset was selected because it provides a balanced collection of fake and genuine news articles covering multiple domains, making it suitable for evaluating machine learning-based fake news detection systems.

4.4 Workflow Diagrams




Figure 4.4 Workflow Diagram of System

The proposed AI-Powered Fake News Detection System follows a structured workflow that integrates machine learning prediction, semantic similarity analysis, and real-time news verification to determine the authenticity of a news article. Each stage of the workflow contributes to improving the overall accuracy, reliability, and explainability of the prediction.

The process begins when the user enters a news article through the Gradio-based web interface. The user also selects the appropriate news category from the available options, such as National, International, Sports, Business, Technology, Entertainment,

Health, Crime, or Education. Once the input is submitted, the system initiates the analysis pipeline.

Initially, the input news undergoes preprocessing, where unnecessary symbols, punctuation marks, hyperlinks, and extra spaces are removed. The text is converted into lowercase and cleaned to improve consistency during feature extraction. The cleaned text is then transformed into numerical vectors using the TF-IDF vectorizer that was trained during the model development phase.

The generated feature vector is passed to the Passive Aggressive Classifier, which predicts whether the entered news is likely to be genuine or fake. Simultaneously, the system extracts important keywords from the news article and generates an optimized search query for Google News. This query is used to retrieve relevant headlines published by trusted news organizations.

The retrieved Google News headlines are compared with the user-provided news using Sentence Transformer embeddings. Instead of comparing keywords, the system compares the semantic meaning of the news article with verified headlines to determine contextual similarity. This enables the system to identify related news even when different words or sentence structures are used.

In parallel, the semantic category detection module analyzes the contextual meaning of the entered news and classifies it into one of the supported news categories. If the detected category differs from the user-selected category, the system generates an informative warning while continuing the prediction process.

Finally, the outputs obtained from machine learning prediction, semantic similarity analysis, Google News verification, and category detection are combined to calculate a credibility score. Based on predefined decision rules, the system generates the final verdict indicating whether the news is likely genuine, probably genuine, requires fact-checking, or appears to be unverified. The prediction, credibility score, supporting Google News headlines, semantic analysis, and category information are presented to the user through the Gradio interface.

The overall workflow ensures that fake news detection does not rely solely on machine learning classification but incorporates multiple verification mechanisms for improved reliability.

4.5 Methodological Steps

The methodology adopted in this research consists of several sequential phases, each contributing to the successful implementation of the fake news detection system. The complete process is described below.

Step 1: Dataset Collection

The first stage involved collecting labelled fake and genuine news articles. The ISOT Fake News Dataset was selected because it contains a large number of authentic and fake news articles suitable for supervised machine learning. The dataset consists of two separate files, namely True.csv and Fake.csv, which were merged into a single dataset for further processing.

Step 2: Data Preprocessing

The collected dataset contained punctuation marks, hyperlinks, special characters, inconsistent formatting, and other unnecessary textual elements. Therefore, preprocessing was performed to improve the quality of textual data.

The preprocessing operations included:

- Removal of punctuation marks
- Removal of special characters
- Conversion to lowercase
- Removal of extra spaces
- Cleaning unwanted symbols
- Text normalization

The cleaned dataset provided consistent textual information suitable for feature extraction.

Step 3: Feature Extraction

Machine learning algorithms cannot directly process textual information. Therefore, the cleaned news articles were converted into numerical representations using the Term Frequency–Inverse Document Frequency (TF-IDF) feature extraction technique.

TF-IDF assigns importance to each word according to its frequency within a document while reducing the influence of common words. This representation allows the classifier to identify informative words that contribute to fake or genuine news classification.

Step 4: Model Training

After feature extraction, the processed dataset was divided into training and testing subsets. The training data was supplied to the Passive Aggressive Classifier, which learns decision boundaries by continuously updating its parameters whenever incorrect predictions occur. This algorithm is particularly suitable for text classification because of its efficiency and ability to handle high-dimensional sparse data generated by TF-IDF.

Step 5: Machine Learning Prediction

Whenever a user enters a news article, the same preprocessing and TF-IDF transformation pipeline is applied before generating a prediction using the trained Passive Aggressive Classifier. The classifier estimates whether the news is likely to be fake or genuine and also computes prediction confidence that contributes to the credibility score.

Step 6: Google News Verification

The proposed system does not rely solely on machine learning prediction. It automatically searches Google News using important keywords extracted from the user-provided article. Relevant headlines retrieved from trusted publishers are displayed to users as supporting evidence.

This verification process significantly improves the transparency of prediction.

Step 7: Semantic Similarity Analysis

The retrieved Google News headlines are further analyzed using Sentence Transformer. Instead of matching words directly, the semantic similarity model compares the contextual meaning of the user-provided news with verified headlines.

A similarity score is generated, indicating how closely the entered news resembles trusted published news. This step reduces false predictions caused by differences in wording.

Step 8: News Category Detection

The semantic category detection module analyzes the entered news and identifies its category. Supported categories include:

- National News
- International News
- Sports News
- Business News
- Technology News
- Entertainment News
- Health News
- Crime News
- Education News

If the user-selected category differs from the detected category, the system displays a warning while continuing the verification process.

Step 9: Credibility Score Generation

The credibility score is calculated using multiple verification factors, including:

- Machine Learning prediction
- Semantic similarity score
- Google News verification
- Number of matching headlines
- Category validation

Instead of relying on a single model prediction, the system combines these factors to estimate the overall trustworthiness of the entered news article.

Step 10: Final Verdict Generation

Based on the credibility score and verification results, the system generates one of the following verdicts:

- Likely Real News
- Probably Real – Needs Fact Checking
- Related News Found but Content Differs
- Possibly Fake or Unverified

This rule-based decision process makes the final prediction more transparent and easier for users to interpret.

Step 11: Result Visualization

Finally, the prediction results are presented through the Gradio web interface. The output includes:

- Machine Learning Prediction
- Detected News Category
- Credibility Score
- Semantic Similarity Result
- Google News Verification
- Supporting Headlines
- Final Verdict
- Analysis Summary

This comprehensive presentation enables users to understand not only the final prediction but also the reasoning behind it.

Data Analysis & Interpretation

This chapter looks at how the raw dataset was turned into something suitable for training the model. It begins by examining the ISOT Fake News Dataset itself, tracing its origin to the University of Victoria's ISOT Research Lab and explaining how the `True.csv` and `Fake.csv` files were combined, labelled, and shuffled into a single unified dataset. From there, it details the preprocessing steps applied to the data — converting text to lowercase, stripping out HTML tags, URLs, and numbers, removing punctuation and special characters, normalizing text, and cleaning up whitespace — all aimed at producing clean, consistent input for feature extraction. The chapter then explains the TF-IDF feature analysis process, showing how Term Frequency and Inverse Document Frequency work together to assign weight to the most informative words, with a worked example demonstrating how a sample headline is converted into a numerical feature vector. It closes by interpreting these results, showing how pairing machine learning prediction with semantic similarity and Google News verification produces more reliable outcomes than relying on a standalone classifier.

5.1 Dataset Analysis

The proposed system utilizes the ISOT Fake News Dataset, which consists of two labeled datasets: True.csv and Fake.csv. The dataset contains thousands of news articles collected from various online sources. Before model training, both datasets were merged into a single dataset and assigned binary labels representing genuine and fake news. The dataset covers multiple domains, making it suitable for evaluating the effectiveness of machine learning algorithms in fake news detection.

The proposed Fake News Detection System utilizes the **ISOT Fake News Dataset**, one of the most widely used benchmark datasets for fake news classification research. The dataset was developed by the **Information Security and Object Technology (ISOT) Research Lab** at the University of Victoria, Canada. It contains a large collection of real and fake news articles gathered from multiple online news sources, making it suitable for training and evaluating machine learning models.

The dataset is divided into two separate comma-separated value (CSV) files:

- **True.csv** – Contains genuine news articles collected from reputable and verified news organizations such as Reuters. These articles represent authentic news content and are labelled as **Real (1)**.
- **Fake.csv** – Contains fabricated or misleading news articles collected from unreliable websites known for spreading misinformation. These articles are labelled as **Fake (0)**.

Before training the machine learning model, both datasets were merged into a single unified dataset. A new binary target column named label was created, where **1** represents genuine news and **0** represents fake news. After merging, the combined dataset was randomly shuffled to eliminate any ordering bias and to ensure an unbiased distribution of real and fake news articles during model training.

5.2 Data Preprocessing

Data preprocessing plays a crucial role in improving classification accuracy. Raw news articles often contain punctuation marks, hyperlinks, special characters, unnecessary spaces, and inconsistent formatting. Therefore, several preprocessing techniques were applied, including lowercase conversion, text cleaning, punctuation removal, normalization, and whitespace removal. These operations produced a clean and consistent dataset suitable for feature extraction.

To improve data quality and ensure consistency, several preprocessing techniques were applied before feature extraction and model training. These techniques transformed the raw text into a clean and standardized format that could be effectively processed by the machine learning algorithms.

The preprocessing steps are described below:

1. **Lowercase Conversion**

- All text in the news articles was converted to lowercase.
- This ensures that words such as *News*, *NEWS*, and *news* are treated as the same term, preventing duplicate representations.

2. **Text Cleaning**

- Unnecessary elements such as HTML tags, URLs, email addresses, numbers, and other irrelevant characters were removed from the text.
- This reduced noise and retained only meaningful textual information.

3. **Punctuation Removal**

- Punctuation marks such as commas, periods, quotation marks, brackets, exclamation marks, and question marks were removed.
- Since punctuation generally does not contribute significantly to fake news classification, removing it simplifies the text representation.

4. **Special Character Removal**

- Special symbols (e.g., @, #, %, &, *, \$, ^) and other non-alphabetic characters were eliminated.

- This ensured that only useful textual content remained for further analysis.

5. Text Normalization

- The text was standardized by removing inconsistencies in formatting and character representation.
- Normalization helps maintain uniformity across all news articles and improves the effectiveness of feature extraction techniques.

6. Whitespace Removal

- Extra spaces, tabs, and blank lines were removed.
- Multiple consecutive spaces were replaced with a single space to maintain consistent formatting throughout the dataset.

After completing these preprocessing steps, the dataset became cleaner, more structured, and free from unnecessary noise. The processed text provided a consistent input for the feature extraction stage, where textual data was converted into numerical representations using the **TF-IDF (Term Frequency–Inverse Document Frequency)** technique.

5.3 Feature Analysis

The cleaned text was transformed into numerical vectors using the Term Frequency–Inverse Document Frequency (TF-IDF) technique. TF-IDF assigns higher weights to informative words while reducing the influence of commonly occurring words. The resulting feature vectors provide meaningful representations of textual information that can be effectively processed by the Passive Aggressive Classifier. This transformation significantly improves classification performance while maintaining computational efficiency.

The TF-IDF technique consists of two main components:

1. **Term Frequency (TF)**

- Measures how frequently a word appears in a particular news article.
- Words that occur more often within a document receive higher term frequency values, indicating their importance in that specific article.

2. **Inverse Document Frequency (IDF)**

- Measures how unique or informative a word is across the entire dataset.
- Commonly occurring words such as *the*, *is*, *and*, and *of* appear in almost every document and therefore receive lower weights.
- Rare but meaningful words that appear in fewer documents receive higher weights because they contribute more to distinguishing one document from another.

By combining these two measures, TF-IDF assigns high weights to words that are frequent in a particular document but uncommon across the dataset. As a result, the generated feature vectors emphasize informative terms while reducing the influence of frequently occurring but less meaningful words.

After applying TF-IDF vectorization, each news article was represented as a high-dimensional numerical vector, where each feature corresponds to the weighted importance of a specific word in the vocabulary. These vectors capture the essential textual characteristics of the news articles while maintaining a sparse and computationally efficient representation.

Example of Feature Extraction Using TF-IDF:

Original News Article:

"The government announced a new education policy today."

After preprocessing, the text becomes:

"government announced new education policy today"

The TF-IDF algorithm converts these words into numerical values based on their importance in the dataset. For example:

- Government → **0.15**
- Announced → **0.62**
- Education → **0.81**
- Policy → **0.81**
- Today → **0.34**

Thus, the news article is transformed into the numerical feature vector:

[0.15, 0.62, 0.81, 0.81, 0.34]

5.4 Data Interpretation

The experimental analysis demonstrates that integrating machine learning prediction with semantic similarity analysis and Google News verification provides more reliable fake news detection than relying solely on a standalone classifier. The inclusion of credibility scoring, category detection, and supporting headlines improves transparency and enables users to better understand the reasoning behind the system's final prediction. The results indicate that the proposed framework effectively combines multiple AI techniques to enhance both prediction accuracy and user confidence.

The proposed framework integrates **machine learning prediction**, **semantic similarity analysis**, and **Google News verification** into a unified detection process. Initially, the news article is classified as **Real** or **Fake** using the trained Passive Aggressive Classifier. Next, semantic similarity analysis compares the input news article with verified news articles to identify similarities in meaning rather than exact word matching. This helps the system recognize related news even when different wording or sentence structures are used.

To further strengthen the prediction, the system performs **Google News verification**, where relevant news headlines from trusted news sources are retrieved and compared with the input article. If multiple credible news organizations report similar information, the confidence in the prediction increases. Conversely, if no reliable sources support the news article, the system assigns a lower credibility score, indicating that the information may require additional verification.

The proposed framework also incorporates **credibility scoring**, which provides users with an estimate of the reliability of the news article. Instead of displaying only a binary prediction, the system presents a confidence or credibility score that helps users understand the certainty of the classification. In addition, **category detection** identifies the topic of the news article, such as politics, world news, business, technology, or health, providing additional context for the prediction.

Another important feature of the system is the display of **supporting news headlines** obtained from trusted news sources. These headlines serve as evidence for the prediction, allowing users to compare the input news with verified reports.

This enhances the transparency of the system by explaining the reasoning behind the final decision rather than providing only a simple Real or Fake label.

Overall, the experimental evaluation confirms that the proposed system provides an effective, accurate, and transparent approach to fake news detection. The combination of multiple verification methods enables the system not only to classify news articles accurately but also to provide supporting evidence that assists users in making informed decisions about the authenticity of online news.

Discussion and Results

This chapter presents the results of implementing and testing the system. It opens with an overview of the completed implementation, showing how preprocessing, TF-IDF extraction, Passive Aggressive classification, Sentence Transformer-based semantic similarity, Google News verification, category detection, and credibility scoring all work together through the Gradio interface. It then evaluates the model's performance across the nine supported news categories, highlighting how Google News verification and semantic similarity helped strengthen predictions for both well-established and newly emerging news stories. The chapter walks through sample outputs generated by the Gradio interface, comparing cases backed by strong semantic and Google News evidence against cases where supporting evidence was limited. It closes by summarizing seven key findings from the study, covering the effectiveness of combining the Passive Aggressive Classifier with TF-IDF, and the added value of category detection, credibility scoring, and the Gradio interface in delivering transparent, explainable predictions.

6.1 Overview

The implementation of the proposed AI-Powered Fake News Detection System demonstrates the effectiveness of integrating Machine Learning, Natural Language Processing, semantic similarity analysis, and real-time news verification into a single intelligent framework. Unlike conventional fake news detection systems that rely solely on machine learning predictions, the proposed system combines multiple verification mechanisms to improve prediction accuracy and provide users with transparent, evidence-based results.

The complete system was successfully implemented using Python and evaluated through an interactive Gradio-based web interface. The implementation includes data preprocessing, TF-IDF feature extraction, Passive Aggressive Classification, semantic similarity using Sentence Transformer, Google News verification, category detection, credibility score estimation, and final verdict generation. Each component performs a specific role within the overall framework and collectively contributes towards reliable fake news detection.

The system accepts textual news input from users, preprocesses the content, extracts meaningful features, and predicts whether the news is genuine or fake. The prediction is then strengthened through semantic comparison with trusted Google News headlines and category validation. Finally, a credibility score and detailed analysis summary are generated to assist users in understanding the reasoning behind the prediction. The integration of these components demonstrates the practical applicability of Artificial Intelligence in addressing the growing challenge of online misinformation.

6.2 Model Evaluation

Several news articles belonging to different domains, including National, International, Sports, Business, Technology, Entertainment, Health, Crime, and Education, were tested to evaluate the performance of the proposed system. During experimentation, the machine learning classifier successfully identified textual patterns associated with fake and genuine news articles, while Google News verification retrieved relevant headlines from trusted news organizations for comparison.

The semantic similarity module further enhanced the reliability of prediction by comparing the contextual meaning of the entered news with verified news articles instead of relying only on keyword matching. The category detection module accurately classified most news articles into their appropriate categories and generated warning messages whenever the user-selected category differed from the detected category. The credibility score calculation effectively combined prediction confidence, semantic similarity, and news verification into a single numerical value that reflected the overall reliability of the news article.

Experimental observations indicate that integrating multiple verification techniques significantly reduces prediction uncertainty and provides users with better insight into the authenticity of online news.

The performance of the proposed system was evaluated using standard machine learning evaluation techniques together with practical testing using real-world news articles. The Passive Aggressive Classifier demonstrated strong classification capability due to the effective representation of textual information through TF-IDF feature extraction. The semantic similarity component further improved verification by recognizing contextually similar news even when different vocabulary was used.

Google News verification played an important role in validating breaking news by retrieving related headlines from trusted publishers. This additional verification layer reduced dependence on historical datasets and improved the reliability of predictions for newly emerging news events. The category detection module also contributed towards improving contextual understanding by automatically identifying the type of news being analyzed.

Overall, the combined framework demonstrated better practical performance than a standalone machine learning classifier because prediction decisions were supported by semantic evidence and trusted online verification.

6.3 Sample Outputs

Fake News Detection System
AI-Powered Fake News Verification using Machine Learning + Google News + Semantic Analysis

Select News Category

- ☒ National News
- ☐ International News
- ☐ Sports News
- ☐ Entertainment News
- ☐ Business News
- ☐ Technology News
- ☐ Health News
- ☐ Crime News
- ☐ Education News

Paste News Article

Paste any news headline or article here...

Language

English

Verify News **Clear**

Use via API · Built with Gradio · Settings

Figure 6.3.(i): Home Interface

Fake News Detection System
AI-Powered Fake News Verification using Machine Learning + Google News + Semantic Analysis

Select News Category

- ☒ National News
- ☐ International News
- ☐ Sports News
- ☐ Entertainment News
- ☐ Business News
- ☐ Technology News
- ☐ Health News
- ☐ Crime News
- ☐ Education News

Paste News Article

One hospitalised, two suffer breathing difficulties after Mumbai AC local cooling system fails

Language

English

Verify News **Clear**

FINAL VERDICT

✓ **LIKELY REAL NEWS**

📊 **Credibility Score: 99/100**

Analysis Summary

Selected Category	National News
Detected Category	General
ML Model Prediction	FAKE
Model Confidence	66.3%
Google News Match	Found 5 similar headlines on Google News

Semantic Similarity Check

Highest Semantic Similarity: 100.0%

Best Matched Headline

One hospitalised, two suffer breathing difficulties after Mumbai AC local cooling system fails

Figure 6.3.(ii): Successful Real News Detection




Figure 6.3.(iii): Google News Verification




Figure 6.3.(iv): Credibility Score and Final Verdict

The developed Gradio interface successfully displays comprehensive prediction results in a user-friendly format. The output includes the machine learning prediction, detected news category, semantic verification results, credibility score, Google News headlines, and the final verdict. Users can therefore understand not only whether a news article is likely to be fake or genuine but also the supporting evidence behind the prediction.

For genuine news articles that matched multiple trusted Google News headlines with high semantic similarity, the system generated high credibility scores and classified the

news as Likely Real News. In cases where only limited supporting evidence was available, the system produced a verdict indicating that additional fact-checking was recommended. Articles showing little semantic similarity and no trusted verification received lower credibility scores and were classified as Possibly Fake or Unverified. This explainable presentation of results enhances user confidence and makes the system suitable for educational demonstrations, academic research, and awareness regarding fake news detection.

6.4 Key Findings

The implementation and evaluation of the proposed system led to several important findings:

1. The Passive Aggressive Classifier provides efficient and reliable fake news classification when combined with TF-IDF feature extraction.
2. Google News verification significantly improves prediction reliability by validating news against trusted publishers.
3. Semantic similarity analysis enables contextual verification beyond simple keyword matching.
4. Automatic category detection improves the interpretability of prediction results.
5. Credibility score estimation provides users with a quantitative measure of news reliability.
6. The Gradio-based graphical interface simplifies user interaction and presents results in an intuitive manner.
7. Integrating multiple AI techniques within a unified framework produces more informative and transparent predictions than traditional standalone machine learning models.

The overall experimental results demonstrate that the proposed AI-powered fake news detection system is capable of providing accurate, explainable, and user-friendly verification of online news articles.

Conclusion

This chapter reflects on what the research achieved overall. It begins by summarizing the key findings across the thesis, revisiting how dataset collection, preprocessing, TF-IDF feature extraction, Passive Aggressive classification, semantic similarity analysis, Google News verification, category detection, credibility scoring, and the Gradio interface all came together to meet the objectives laid out earlier in the report. It then highlights the major contributions of the work, chiefly the integration of Google News verification, semantic similarity analysis, automatic category detection, and credibility scoring into a single explainable framework — one that moves well beyond simple binary real-or-fake classification.

7.1 Summary of Findings

The rapid growth of digital media and online communication platforms has transformed the way people access and share information. While these platforms have significantly improved the speed and accessibility of news dissemination, they have also facilitated the widespread circulation of fake news and misinformation. The increasing influence of fabricated news on public opinion, political decisions, social stability, and public health has highlighted the need for intelligent automated systems capable of identifying misleading information accurately and efficiently.

The primary objective of this research was to design and develop an AI-Powered Fake News Detection System that integrates Machine Learning, Natural Language Processing, semantic similarity analysis, and real-time news verification into a single framework. Unlike conventional fake news detection models that rely solely on historical datasets, the proposed system combines multiple verification techniques to improve reliability, transparency, and user confidence.

The implementation of the proposed system involved several stages, including dataset collection, text preprocessing, feature extraction using TF-IDF, machine learning classification through the Passive Aggressive Classifier, semantic similarity analysis using Sentence Transformer, Google News verification, news category detection, credibility score generation, and the development of an interactive Gradio-based web interface. Each module contributes to improving the overall effectiveness of the system and ensures that predictions are supported by contextual evidence rather than relying only on statistical classification.

Experimental evaluation demonstrated that the integration of machine learning prediction with semantic similarity analysis and trusted news verification significantly enhances the reliability of fake news detection. The semantic similarity module enables contextual comparison between user-provided news and verified online articles, reducing errors caused by simple keyword matching. The Google News verification module further strengthens prediction by identifying whether similar news has been published by trusted media organizations. Additionally, automatic category detection provides contextual understanding by classifying news into categories such as National,

International, Sports, Business, Technology, Entertainment, Health, Crime, and Education.

The credibility score generated by the proposed framework represents another significant contribution of this research. Rather than providing only a binary prediction, the system combines multiple verification factors to estimate the overall trustworthiness of the news article. This explainable approach enables users to better understand the reasoning behind the prediction and increases confidence in the generated results.

The Gradio-based user interface provides a simple yet effective platform through which users can submit news articles and receive comprehensive analytical reports. The interface displays prediction results, detected category, credibility score, semantic similarity information, related Google News headlines, and the final verdict in a well-organized manner. This interactive presentation improves usability and makes the system suitable for educational demonstrations and practical applications.

Overall, the proposed AI-powered fake news detection framework successfully demonstrates how the integration of multiple Artificial Intelligence techniques can produce more reliable and transparent fake news detection compared to conventional standalone machine learning models.

7.2 Major Contribution

The research presented in this thesis makes several important contributions to the field of fake news detection. The most significant contribution is the successful development of an integrated framework that combines machine learning, semantic similarity analysis, category detection, and real-time news verification within a single application. This integrated approach addresses several shortcomings identified in previous fake news detection systems.

Another major contribution is the incorporation of Google News verification, which enables the system to validate news articles against trusted online publishers instead of relying solely on machine learning predictions. This additional verification layer improves the credibility and transparency of prediction results.

The implementation of semantic similarity analysis using Sentence Transformer represents another important contribution. Unlike traditional keyword-based methods, semantic similarity compares the contextual meaning of news articles, allowing the system to recognize similar information expressed using different vocabulary and sentence structures.

The automatic news category detection module further enhances the interpretability of prediction results by identifying the domain of the news article. The system supports multiple categories, including National, International, Sports, Business, Technology, Entertainment, Health, Crime, and Education, thereby providing users with additional contextual information.

The proposed credibility score mechanism represents another valuable enhancement. By combining machine learning confidence, semantic similarity, and Google News verification into a single numerical score, the system offers a more comprehensive assessment of news reliability than traditional binary classification approaches.

Finally, the research demonstrates the practical application of Artificial Intelligence, Machine Learning, Natural Language Processing, and real-time information retrieval in addressing one of the most significant challenges of modern digital communication. The developed framework provides a strong foundation for future research aimed at combating online misinformation through intelligent verification techniques.

Recommendations & Suggestions

This chapter reflects on where the project fell short and where it could go from here. It begins with the lessons learned along the way, particularly that machine learning classification on its own isn't enough without semantic similarity and real-time verification working alongside it, and that careful preprocessing and explainable result visualization matter just as much as the model itself. It then turns to the project's limitations — its restriction to English-language text, its dependence on external services like Google News and NewsAPI, training confined to the ISOT dataset, and the fact that it doesn't analyze image, video, or other multimedia misinformation. Looking ahead, the chapter outlines future directions such as multilingual detection, upgrading to transformer-based models like BERT or RoBERTa, and deploying the system as a cloud or mobile application. It closes with recommendations for future systems, including hybrid verification frameworks, broader multilingual support, and expansion into multimodal fake news detection that covers images, videos, and deepfake content.

8.1 Lessons Learnt

The development of the proposed fake news detection system provided valuable practical experience in applying Artificial Intelligence and Machine Learning techniques to solve real-world problems. Throughout the implementation process, it became evident that machine learning models alone are insufficient for accurately identifying newly emerging fake news. Integrating semantic similarity analysis and real-time verification from trusted news sources significantly improves prediction reliability and provides users with stronger evidence to support the final verdict.

The project also demonstrated the importance of proper data preprocessing, feature extraction, and model selection in achieving reliable classification performance. Furthermore, the integration of user-friendly interfaces such as Gradio highlights the significance of effective result visualization and explainable AI for improving user confidence.

8.2 Project Limitation

Although the proposed system demonstrates effective performance, several limitations remain. The current implementation primarily supports English-language news articles and depends on the availability of trusted online news sources for real-time verification. In situations where Google News or NewsAPI returns limited information, verification may be less comprehensive.

Additionally, the machine learning model has been trained using the ISOT Fake News Dataset. While this dataset provides reliable training data, newly emerging news topics or highly specialized domains may require additional training data to further improve generalization. The current system also focuses exclusively on textual news and does not analyze images, videos, or multimedia content commonly associated with misinformation campaigns.

Another limitation is the system's **dependence on external news verification services**, such as Google News and NewsAPI. These services are used to retrieve related headlines and trusted news articles for cross-source verification. However, if these platforms return limited results due to API restrictions, insufficient indexing, network issues, or the news being very recent, the verification process may not provide enough supporting evidence. Consequently, the credibility score generated by the system may become less comprehensive, particularly for breaking news or local events that have not yet been widely reported.

The machine learning classifier has been trained using the **ISOT Fake News Dataset**, which contains a large collection of labelled real and fake news articles. Although this dataset is widely used for fake news detection research and provides a solid foundation for model training, it may not fully represent the continuously evolving nature of online misinformation. New fake news patterns, emerging topics, political events, technological developments, or health-related misinformation may differ significantly from the training data. As a result, the model's ability to generalize to unseen content may decrease over time unless it is periodically retrained using updated datasets.

Furthermore, the current system focuses **only on textual analysis**. Modern misinformation campaigns frequently use manipulated images, edited videos, memes, deepfake content, and synthetic media to spread false information. Since the proposed

framework does not analyze visual or multimedia content, it cannot detect fake news that relies primarily on image or video manipulation. This limits the system's effectiveness in identifying multimodal misinformation commonly found on social media platforms.

The system also assumes that **credible information is available from trusted news organizations**. If a genuine news event has not yet been reported by major media outlets, or if it originates from a niche or highly specialized domain, the system may produce limited verification evidence despite the news being authentic. Similarly, controversial or developing stories with conflicting reports may lead to lower confidence scores.

Finally, the system depends on **internet connectivity** for real-time verification and news retrieval. In offline environments or during API service interruptions, only the machine learning prediction can be generated, reducing the overall reliability of the verification process because supporting evidence from external news sources cannot be obtained.

Despite these limitations, the proposed framework provides a robust and transparent approach to fake news detection by combining machine learning with semantic similarity analysis and online credibility verification. Addressing the identified limitations through multilingual support, multimodal analysis, larger and continuously updated datasets, and advanced deep learning models can further enhance the system's accuracy, scalability, and real-world applicability.

8.3 Future Scope

The proposed system provides several opportunities for future enhancement. Support for multilingual fake news detection can be incorporated to analyze news articles written in languages such as Hindi, Bengali, Urdu, and other regional languages. The machine learning component can also be upgraded using advanced transformer-based language models such as BERT, RoBERTa, or DeBERTa to further improve prediction accuracy.

Future versions of the system may integrate additional trusted verification sources, social media analysis, image verification, video authenticity detection, and explainable AI techniques capable of highlighting the textual evidence influencing the prediction. Furthermore, deployment as a cloud-based web application or mobile application would enable wider public accessibility and practical adoption.

8.4 Recommendations

Based on the findings of this research, it is recommended that future fake news detection systems adopt hybrid verification frameworks that combine machine learning prediction with semantic analysis and trusted online verification. Researchers should focus on improving explainability so that users can understand the reasoning behind prediction results instead of receiving only binary classifications.

It is also recommended that future systems support multilingual content, integrate multiple trusted news providers, and continuously update their verification mechanisms to adapt to rapidly changing news environments. Collaboration between Artificial Intelligence researchers, media organizations, and fact-checking agencies can further enhance the reliability and effectiveness of automated fake news detection systems.

Finally, educational institutions, journalists, and digital media users should be encouraged to utilize AI-assisted verification tools as supplementary resources for identifying misinformation and promoting responsible information sharing across digital platforms.

In addition, future systems should expand beyond textual analysis by supporting **multimodal fake news detection**. Since misinformation increasingly spreads through manipulated images, videos, memes, and deepfake content, integrating computer vision, image forensics, video analysis, and multimodal AI models will enable comprehensive verification of both textual and visual information. This will make fake news detection systems more suitable for real-world social media environments.

References

- [1] H. Allcott and M. Gentzkow, "Social Media and Fake News in the 2016 Election," *Journal of Economic Perspectives*, vol. 31, no. 2, pp. 211–236, 2017.
- [2] N. J. Conroy, V. L. Rubin, and Y. Chen, "Automatic deception detection: Methods for finding fake news," *Proceedings of the Association for Information Science and Technology*, vol. 52, no. 1, pp. 1–4, 2015.
- [3] V. L. Rubin, Y. Chen, and N. J. Conroy, "Deception Detection for News: Three Types of Fakes," *Proceedings of the Association for Information Science and Technology*, 2015.
- [4] J. Shu, A. Sliva, S. Wang, J. Tang, and H. Liu, "Fake News Detection on Social Media: A Data Mining Perspective," *ACM SIGKDD Explorations Newsletter*, vol. 19, no. 1, pp. 22–36, 2017.
- [5] F. Pedregosa et al., "Scikit-learn: Machine Learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
- [6] T. Joachims, *Text Categorization with Support Vector Machines*, Springer, 1998.
- [7] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT Networks," *EMNLP*, 2019.
- [8] J. Devlin, M. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding," *NAACL-HLT*, 2019.
- [9] T. Mikolov et al., "Efficient Estimation of Word Representations in Vector Space," *ICLR Workshop*, 2013.
- [10] G. Salton and C. Buckley, "Term-Weighting Approaches in Automatic Text Retrieval," *Information Processing & Management*, vol. 24, no. 5, pp. 513–523, 1988.
- [11] S. Bird, E. Klein, and E. Loper, *Natural Language Processing with Python*. O'Reilly Media, 2009.
- [12] C. D. Manning, P. Raghavan, and H. Schütze, *Introduction to Information Retrieval*. Cambridge University Press, 2008.
- [13] Python Software Foundation, "Python Documentation." Available: <https://docs.python.org/>
- [14] Scikit-learn Developers, "Scikit-learn Documentation." Available: <https://scikit-learn.org/>
- [15] Sentence Transformers Documentation. Available: <https://www.sbert.net/>

- [16] Gradio Documentation. Available: <https://www.gradio.app/>
- [17] Google News RSS Documentation. Available: <https://news.google.com/>
- [18] NewsAPI Documentation. Available: <https://newsapi.org/>
- [19] Pandas Documentation. Available: <https://pandas.pydata.org/>
- [20] NumPy Documentation. Available: <https://numpy.org/>
- [21] ISOT Fake News Dataset, University of Victoria, Canada.
- [22] Google Colaboratory Documentation. Available:
<https://colab.research.google.com/>
- [23] Feedparser Documentation. Available: <https://feedparser.readthedocs.io/>
- [24] Hugging Face Transformers Documentation. Available: <https://huggingface.co/>
- [25] OpenAI, "Artificial Intelligence Research," Available: <https://openai.com/>