

# COMP2002 - Artificial Intelligence

## Week 3 - Neural Network Exercises

### Introduction

The aim of this sheet of exercises is to get you started with implementing machine learning software. You should complete the exercises ahead of the week 4 seminar session. The model answers will be published shortly after, giving you enough time to re-attempt the exercises after the demonstration in the seminar. You should complete the exercises in a Jupyter Notebook. You can either install Jupyter on your own device or use the version available in the labs.

### Activities

Your task is to go through the following tasks. Please note, you are expected to complete some work on this outside of the timetabled sessions.

### Exercise 1 - Classify the Iris Data

The first task this week is to use a neural network to classify the iris data. Begin by loading the data and then use the `MLPClassifier` class to train a classifier for the data.

Once you have trained the neural network, compare the results with the `confusion_matrix` function and plot the result with the Matplotlib `imshow` function.

### Exercise 2 - Regression with Neural Networks

Having tried a classification problem, this exercise requires you to train a neural network to solve a regression problem – the California house price data we discussed in the lecture. Begin by loading the data as follows:

```
from sklearn.datasets import fetch_california_housing
# Load the data.
data = fetch_california_housing()
inputs = data["data"]
targets = data["target"]
```

Once you've loaded the data, plot any two of the columns against each other as follows:

```
import matplotlib.pyplot as plt

# Plot columns 0 and 1 (can replace with any pair of inputs).
plt.scatter(inputs[:,0], inputs[:,1], c=targets, cmap="viridis")
plt.savefig("california_data.pdf", bbox_inches="tight")
plt.show()
```

### Exercise 3 - Normalise the Data

You've loaded the data, it's now time to pre-process the data by normalising. Use the `MinMaxScaler` to normalise the input values lie between 0 and 1.

Once you've normalised the values you can use the `ptp` method to print the difference between the maximum and minimum values for each input as follows:

```
# Print the range of the variables to show the normalisation effect.  
print(inputs.ptp(axis=0))  
print(scaled.ptp(axis=0))
```

## Exercise 4 - Train the Model

The data is now pre-processed and ready for modelling. Use the *MLPRegressor* as shown in the lecture to train a neural network that predicts house prices.