



Semester : VI

Subject : DAV

Academic Year: 2023-2024

REPRESENTING TEXT :-

* It includes phases 3 and phase 4 of Data Analytics Life cycle.

* Tokenization is the task of separating (also called tokenizing) words from the body of text.

* Raw text is converted into collections of tokens after the tokenization, where each token is generally a word.

A common approach is tokenizing on spaces. For example, with the tweet shown previously:

I ~~only~~ once had a gf back in the day. Then the bPhone came out lol.

tokenization based on spaces would output a list of tokens.

{I, once, had, a, gf, back, in, the, day,

Then, the, bPhone, came, out, lol}

Note that token "day." contains a period. This is the result of only using space as the separator. Therefore, tokens "day." and "day" would be considered different terms in the downstream analysis unless an additional lookup table is provided.

The problems faced:

Can't → Can't should be written as can and t

We'll → We'll should be ^{written} we and ll

Wi-Fi → Wi-Fi should be written wi and Fi.

Text Normalization Technique - Case Folding:

It reduces all letters to lowercase (or the opposite if applicable). For the previous tweet, after case folding the text would become this:

Subject Incharge: Prof. Sarala Mary Page No. 1

Department of CSE-Data Science | APSIT





Semester: VI

Subject: DAV

Academic Year: 2023 2024

I once had a gf back in the day, then the bphone came out lol.

Problems faced:

For example,
General motor → The gGeneral motor can be ~~was~~ will be interpreted as general and motor.

WHO → WHO stands for World Health Organization but here WHO changes to who.

Text Normalization Technique - Stopwords

- Stop words are a set of commonly used words in a language.
- Examples of stop words in English are 'a', 'the', 'is', 'are' etc.
- It is used to eliminate words that are so widely used that they carry very little useful information.

Example:

```
import nltk
from nltk.corpus import stopwords
nltk.download('stopwords')
print(stopwords.words('english'))
```

Output:

['i', 'me', 'myself', 'we', 'our', 'ours', 'ourselves', ...].

Example: Stopwords

Sample text with Stop Words	Without Stop Words
GreekforGeeks - A Computer science Portal for Geeks. Can listening be exhausting? I like reading, so I read	GreekforGeeks, Computer Science, Portal, Geeks. Listening, Exhausting. Like, Reading, read.



Semester : VI

Subject : DAV

Academic Year: 2023-2024

Bag of Words (BOW) model in NLP:

Bag of Words model is used to preprocess the text by converting it into a bag of words, which keeps a count of a total occurrences of most frequently used words.

This model can be visualized using a table, which contains the count of words corresponding to the word itself.

Example:

Let us consider the three sentences:

- (1) Hello and Welcome everyone.
- (2) John loves teaching.
- (3) John loves to play cricket.

Let's do Bag of words for the following sentences:
We have to generate vectors for these sentences. We will consider the unique words in the corpus given.

	Hello	and	welcome	everyone	John	loves	teaching	to	play	cricket
(1)	1	1	1	1	0	0	0	0	0	0
(2)	0	0	0	0	1	1	1	0	0	0
(3)	0	0	0	0	1	1	0	1	1	1

remove stopword

For every sentences, we substitute with 1 and 0 according to the occurrence of the word:

To reduce the size, we remove the stopwords from the given table. In the given example "and" and "to" is stopword. Let us remove it and we get 8 words. This is how bag of words model work.