



Module 3

What Is the Naive Bayes Algorithm?

It is a classification technique based on Bayes' Theorem with an independence assumption among predictors. In simple terms, a Naive Bayes classifier assumes that the presence of a particular feature in a class is unrelated to the presence of any other feature.

The Naïve Bayes classifier is a popular supervised machine learning algorithm used for classification tasks such as text classification. It belongs to the family of generative learning algorithms, which means that it models the distribution of inputs for a given class or category. This approach is based on the assumption that the features of the input data are conditionally independent given the class, allowing the algorithm to make predictions quickly and accurately.

In statistics, naive Bayes classifiers are considered as simple probabilistic classifiers that apply Bayes' theorem. This theorem is based on the probability of a hypothesis, given the data and some prior knowledge. The naive Bayes classifier assumes that all features in the input data are independent of each other, which is often not true in real-world scenarios. However, despite this simplifying assumption, the naive Bayes classifier is widely used because of its efficiency and good performance in many real-world applications.

Moreover, it is worth noting that naive Bayes classifiers are among the simplest Bayesian network models, yet they can achieve high accuracy levels when coupled with kernel density estimation. This technique involves using a kernel function to estimate the probability density function of the input data, allowing the classifier to improve its performance in complex scenarios where the data distribution is not well-defined. As a result, the naive



Bayes classifier is a powerful tool in machine learning, particularly in text classification, spam filtering, and sentiment analysis, among others.

For example, a fruit may be considered to be an apple if it is red, round, and about 3 inches in diameter. Even if these features depend on each other or upon the existence of the other features, all of these properties independently contribute to the probability that this fruit is an apple and that is why it is known as 'Naive'.

An NB model is easy to build and particularly useful for very large data sets. Along with simplicity, Naive Bayes is known to outperform even highly sophisticated classification methods.

Bayes theorem provides a way of computing posterior probability $P(c|x)$ from $P(c)$, $P(x)$ and $P(x|c)$. Look at the equation below:

$$P(c|x) = \frac{P(x|c)P(c)}{P(x)}$$

$$P(c|X) = P(x_1|c) \times P(x_2|c) \times \dots \times P(x_n|c) \times P(c)$$

Above,

- $P(c|x)$ is the posterior probability of *class* (c , *target*) given *predictor* (x , *attributes*).
- $P(c)$ is the prior probability of *class*.
- $P(x|c)$ is the likelihood which is the probability of the *predictor* given *class*.
- $P(x)$ is the prior probability of the *predictor*.



Sample Project to Apply Naive Bayes

Problem Statement

HR analytics is revolutionizing the way human resources departments operate, leading to higher efficiency and better results overall. Human resources have been using analytics for years.

However, the collection, processing, and analysis of data have been largely manual, and given the nature of human resources dynamics and HR KPIs, the approach has been constraining HR. Therefore, it is surprising that HR departments woke up to the utility of machine learning so late in the game. Here is an opportunity to try predictive analytics in identifying the employees most likely to get promoted.

How Do Naive Bayes Algorithms Work?

Time needed: 1 minute.

Let's understand it using an example. Below I have a training data set of weather and corresponding target variable 'Play' (suggesting possibilities of playing). Now, we need to classify whether players will play or not based on weather condition. Let's follow the below steps to perform it.

1. Convert the data set into a frequency table

In this first step data set is converted into a frequency table

2. Create Likelihood table by finding the probabilities



Create Likelihood table by finding the probabilities like Overcast probability = 0.29
and probability of playing is 0.64.

Weather	Play
Sunny	No
Overcast	Yes
Rainy	Yes
Sunny	Yes
Sunny	Yes
Overcast	Yes
Rainy	No
Rainy	No
Sunny	Yes
Rainy	Yes
Sunny	No
Overcast	Yes
Overcast	Yes
Rainy	No

Frequency Table		
Weather	No	Yes
Overcast		4
Rainy	3	2
Sunny	2	3
Grand Total	5	9

Likelihood table		
Weather	No	Yes
Overcast		4
Rainy	3	2
Sunny	2	3
All	5	9
	=5/14	=9/14
	0.36	0.64

3. Use Naive Bayesian equation to calculate the posterior probability

Now, use Naive Bayesian equation to calculate the posterior probability for each class.

The class with the highest posterior probability is the outcome of the prediction.

Problem: Players will play if the weather is sunny. Is this statement correct?

We can solve it using the above-discussed method of posterior probability.

$$P(\text{Yes} \mid \text{Sunny}) = P(\text{Sunny} \mid \text{Yes}) * P(\text{Yes}) / P(\text{Sunny})$$

Here $P(\text{Sunny} \mid \text{Yes}) * P(\text{Yes})$ is in the numerator, and $P(\text{Sunny})$ is in the denominator.

Here we have $P(\text{Sunny} \mid \text{Yes}) = 3/9 = 0.33$, $P(\text{Sunny}) = 5/14 = 0.36$, $P(\text{Yes}) = 9/14 = 0.64$

Now, $P(\text{Yes} \mid \text{Sunny}) = 0.33 * 0.64 / 0.36 = 0.60$, which has higher probability.



The Naive Bayes uses a similar method to predict the probability of different class based on various attributes. This algorithm is mostly used in [text classification](#) (nlp) and with problems having multiple classes.

What Are the Pros and Cons of Naive Bayes?

Pros:

- It is easy and fast to predict class of test data set. It also perform well in multi class prediction
- When assumption of independence holds, the classifier performs better compared to other [machine learning models](#) like [logistic regression](#) or decision tree, and requires less training data.
- It perform well in case of categorical input variables compared to numerical variable(s). For numerical variable, normal distribution is assumed (bell curve, which is a strong assumption).

Cons:

- If categorical variable has a category (in test data set), which was not observed in training data set, then model will assign a 0 (zero) probability and will be unable to make a prediction. This is often known as “Zero Frequency”. To solve this, we can use the smoothing technique. One of the simplest smoothing techniques is called Laplace estimation.
- On the other side, [Naive Bayes](#) is also known as a bad estimator, so the probability outputs from predict_proba are not to be taken too seriously.



- Another limitation of this algorithm is the assumption of independent predictors. In real life, it is almost impossible that we get a set of predictors which are completely independent.

Applications of Naive Bayes Algorithms

- **Real-time Prediction:** Naive Bayesian classifier is an eager learning classifier and it is super fast. Thus, it could be used for making predictions in real time.
- **Multi-class Prediction:** This algorithm is also well known for multi class prediction feature. Here we can predict the probability of multiple classes of target variable.
- **Text classification/ Spam Filtering/ Sentiment Analysis:** Naive Bayesian classifiers mostly used in text classification (due to better result in multi class problems and independence rule) have higher success rate as compared to other algorithms. As a result, it is widely used in Spam filtering (identify spam e-mail) and [Sentiment Analysis](#) (in social media analysis, to identify positive and negative customer sentiments)
- **Recommendation System:** Naive Bayes Classifier and [Collaborative Filtering](#) together builds a [Recommendation System](#) that uses machine learning and data mining techniques to filter unseen information and predict whether a user would like a given resource or not.