

# Fake news: an algorithmic perspective on fact-checking

Martijn B.J. Schouten  
11295562

Bachelor thesis  
Credits: 12 EC

Bachelor's degree Information Science

University of Amsterdam  
Faculty of Science  
Science Park 904  
1098 XH Amsterdam

*Supervisor*  
Dr. M. J. Marx

ILPS, IvI  
Faculty of Science  
University of Amsterdam  
Science Park 904  
1098 XH Amsterdam

2019-06

Add a  
final date

20

## Abstract

21

Add an  
abstract

22	<b>Contents</b>	
23	<b>1 Introduction</b>	<b>4</b>
24	<b>2 Related Work</b>	<b>5</b>
25	2.1 Automatic fake news detection . . . . .	5
26	2.2 Pooling . . . . .	5
27	2.3 Padding . . . . .	6
28	2.4 Neural text classifiers . . . . .	6
29	<b>3 Methodology</b>	<b>7</b>
30	3.1 Description of the data . . . . .	7
31	3.2 Charts . . . . .	7
32	3.3 Methods . . . . .	7
33	3.3.1 RQ1 . . . . .	7
34	3.3.2 RQ2 . . . . .	7
35	3.3.3 RQ3 . . . . .	7
36	<b>4 Evaluation</b>	<b>7</b>
37	4.1 RQ1 . . . . .	7
38	4.2 RQ2 . . . . .	7
39	4.3 RQ3 . . . . .	8
40	<b>5 Conclusions</b>	<b>9</b>
41	5.1 Acknowledgements . . . . .	9

# 1 Introduction

The ability to broadcast information on a large scale has been in the hands of large publishing organizations in the pre-Internet era, but nowadays everyone can share news via social media [7]. This introduces risks on validity and authenticity of news, as social media and digital platforms can speed up the spread of falsehoods without much effort from the author [5].

As a matter of fact, 63% of adults in the United States prefer to read their news on the Internet. Young adults take the lead: 76% of adults between the ages 18 and 49 get their primary news consumption via the web, compared to just 43% for adults of 50 years and older [13]. As time passes by, social media is slowly becoming the primary source of news for more and more people.

The main danger of this development is that human perception is often skewed with regards to objectivity of facts. Naïve realism let consumers of news believe that their perception is right, while other's perceptions are uninformed. Furthermore, confirmation bias results in consumers preferring information that confirms beliefs they already have [19]. This makes consumers vulnerable for the spread of misinformation or fake news.

According to the European Commission, "*disinformation - or fake news - consists of verifiably false or misleading information that is created, presented and disseminated for economic gain or to intentionally deceive the public, and may cause public harm*" [5]. The answer to the problem of fake news as of recently has been to manually fact-check statements on validity, but, as Shu et al. underlines, one of the downsides to this approach is that fake news typically relates to newly emerging, time-critical events. This means the real news may not be fully verified by proper knowledge bases due to a lack of contradicting claims [19]. An automated approach would both help in solving the problem of human subjectivity and the speed at which false information is spread in the current news spreading landscape.

Natural language processing has been in rapid development over the past years. With the releases of OpenAI's GPT-2 model in February of this year and Google's BERT in the autumn of 2018, state-of-the-art pre-trained textual embedding techniques have shown promising results on various classification tasks [15][6]. Although fake news classification has been attempted before [21][9], performance has been rather low. However, these new pre-trained textual embeddings have not yet been used in the fight against disinformation.

This thesis is focussed on the following research question: *what is the performance of combinations of pre-trained embedding techniques with machine learning algorithms when classifying fake news?* This main question will be answered through the results of the following subquestions:

**RQ1** Which way of pooling vectors to a fixed length works best for classifying fake news?

**RQ2** At what padding sequence length do neural networks hold the highest accuracy when classifying fake news?

**RQ3** How well do neural network classification architectures classify fake news compared to non-neural classification algorithms?

Add an  
overview  
of thesis  
section

## 2 Related Work

### 2.1 Automatic fake news detection

There have been several attempts in the past to create classifiers for automatic detection of lies and fake news. Wang used both linear and neural classifiers to classify statements from the Liar dataset into 6 possible gradations of truthfulness. Furthermore, he added speaker metadata to improve the result of his classifications [21].

From the same dataset, Khurana extracted linguistic features such as n-grams, sentiment, number of capital letters and POS tags to classify the data into 3 labels instead of the original 6 labels. For classification, she used a set of non-neural classifiers [9].

The British factchecking organization Full Fact has developed an architecture that is able to monitor and factcheck statements from the British Parliament and major media outlets in the United Kingdom. It can automatically factcheck the accuracy of statistical claims, for example [3]. For detecting factual claims from texts, the organization uses InferSent, which is a way of transfer learning that has been proved to perform well for the use case of Full Fact [11].

Various tools with regards to fake news detection are also available. Faker Fact is a tool which can classify texts into a set of categories ranging from satire to agenda-driven, the former identifying humorous intent, the later identifying manipulation [1]. Hoaxy, on the other hand, allows for the visualization of unverified claims through Twitter networks [17].

### 2.2 Pooling

Linear classifiers need data in a two-dimensional shape to be able to perform calculations. In the case of raw text data, sentences in the dataset have variable word lengths, resulting in a different vector length when turning the text into a vector representation. To turn the vector representations into a uniform length, we can either cut off the vectors at a fixed length (*padding*), or we can perform calculations to reduce the length of the vectors (*pooling*).

In computer vision, feature pooling is used to reduce noise in data. The goal of this step is to transform joint feature representations into a new, more usable one that preserves important information while discarding irrelevant details. Pooling techniques such as max pooling and average pooling perform mathematical operations to reduce several numbers into one [4]. In the case of transforming the shape of the data, we can reduce vectors to the smallest vector in the dataset to create a uniform shape.

Scherer et al. compared performance of two pooling operations on a convolutional neural network architecture. The first pooling method extracted maximums and the second one was primarily based on working with averages. They have shown that a max pooling operation is vastly superior for capturing invariances in image-like data [16].

Shen et al. noted that in text classification, only a small number of key words contribute to the final prediction. As a result, simple pooling operations are surprisingly effective for representing documents [18]. Lai et al., Hu et al. and Zhang et al. use a max pooling layer in a (recurrent) convolutional neural

133 network for identifying key features in text classification [12][8][23]. In the case  
134 of text classification, max pooling strategies seem to be the most popular.

## 135 **2.3 Padding**

136 When padding a sequence, a list of sequences is transformed to a specific length.  
137 Sequences longer than the desired length will be truncated to fit the requirement,  
138 while sequences shorter than the desired length will be padded by a specified  
139 value [2]. To fill the sequences, a value of zero is often used. Hu et al. also use  
140 zero values for padding their sequences [8].

141 Apart from controlling the size of the feature dimension, padding has other  
142 uses as well. Simard et al. make use of sequence padding for convolutional  
143 neural networks to center feature units, and concluded it did not impact the  
144 performance of the classifier significantly [20]. Wen et al. apply padding to  
145 convolutional network models to prevent dimension loss [22].

## 146 **2.4 Neural text classifiers**

147 Wang has shown that neural networks perform slightly better on classifying fake  
148 news than linear classifiers. In his research, he compared accuracies on support  
149 vector machines, logistic regressions, bidirectional LSTMs and convolutional  
150 neural networks with each other. With his 6 label classification, his support  
151 vector machine implementation was the best performing linear classifier, but  
152 the performance was slightly worse than the best performing neural network  
153 (0.258 for the former, and 0.260 for the latter) [21].

154 Wang used two neural network architectures both well known for their  
155 robustness and performance when it comes to text classification. The first  
156 model, the bidirectional Long Short Term Memory (LSTM) networks, are specifically  
157 tailored at keeping track of information for a long period of time. This makes  
158 those models able to keep track of the context in a more intelligent way when  
159 compared to a standard non-neural classification algorithm [14].

160 The second architecture, the convolutional neural network, apply a set of  
161 filters in its layers to local features. These models are shown to be effective in  
162 numerous natural language processing applications, such as semantic parsing,  
163 search query retrieval, sentence modeling and other traditional NLP tasks [10].

## 164 3 Methodology

### 165 3.1 Description of the data

### 166 3.2 Charts

### 167 3.3 Methods

#### 168 3.3.1 RQ1

#### 169 3.3.2 RQ2

#### 170 3.3.3 RQ3

## 171 4 Evaluation

### 172 4.1 RQ1

173 **Which way of pooling vectors to a fixed length works best for classifying**  
174 **fake news?**

175 The answer to this question will be given by comparing accuracy of a logistic  
176 regression with different pooling strategies (max, min, average).




Figure 1: Comparing different pooling strategies.

### 177 4.2 RQ2

178 **At what padding sequence length do neural networks hold the highest**  
179 **accuracy when classifying fake news?**

180 The answer to this question will be given by comparing accuracy of a bidirectional  
181 LSTM architecture with variable padding lengths.

182 By comparing all embedding techniques, I plan on getting a peak padding  
183 length with the best overall performance shared by all embedding methods. At  
184 this moment, the optimal length averages at around a length of 22.




Figure 2: Comparing different maximum padding lengths.

### 4.3 RQ3

**How well do neural network classification architectures classify fake news compared to non-neural classification algorithms?**

The answer of this question will be given by comparing two linear classifiers with two neural classifiers.




Figure 3: Comparing linear classifiers with neural classifiers.



## 190 **5 Conclusions**

### 191 **5.1 Acknowledgements**

## 192 References

- 193 [1] About fakerfact.
- 194 [2] Sequence preprocessing.
- 195 [3] Mevan Babakar and Will Moy. The state of automated factchecking.  
196 Technical report, Full Fact, 2016.
- 197 [4] Y-Lan Boureau, Jean Ponce, and Yann LeCun. A theoretical analysis  
198 of feature pooling in visual recognition. In *Proceedings of the 27th*  
199 *international conference on machine learning (ICML-10)*, pages 111–118,  
200 2010.
- 201 [5] European Commission. Fake news and online disinformation. [https://ec.](https://ec.europa.eu/digital-single-market/en/fake-news-disinformation)  
202 [europa.eu/digital-single-market/en/fake-news-disinformation](https://ec.europa.eu/digital-single-market/en/fake-news-disinformation),  
203 2018. Retrieved on 8th of April, 2019.
- 204 [6] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert:  
205 Pre-training of deep bidirectional transformers for language understanding.  
206 *arXiv preprint arXiv:1810.04805*, 2018.
- 207 [7] Lee Howell et al. Digital wildfires in a hyperconnected world. *WEF Report*,  
208 3:15–94, 2013.
- 209 [8] Baotian Hu, Zhengdong Lu, Hang Li, and Qingcai Chen. Convolutional  
210 neural network architectures for matching natural language sentences. In  
211 *Advances in neural information processing systems*, pages 2042–2050, 2014.
- 212 [9] Urja Khurana. The linguistic features of fake news headlines and  
213 statements, 2017.
- 214 [10] Yoon Kim. Convolutional neural networks for sentence classification. *arXiv*  
215 *preprint arXiv:1408.5882*, 2014.
- 216 [11] Lev Konstantinovskiy. Sentence embeddings for automated factchecking -  
217 lev konstantinovskiy.
- 218 [12] Siwei Lai, Liheng Xu, Kang Liu, and Jun Zhao. Recurrent convolutional  
219 neural networks for text classification. In *Twenty-ninth AAAI conference*  
220 *on artificial intelligence*, 2015.
- 221 [13] Amy Mitchell and Hannah Klein. Americans still prefer watching to reading  
222 the news – and mostly still through television. 2018.
- 223 [14] Christopher Olah. [https://colah.github.io/posts/2015-08-understanding-](https://colah.github.io/posts/2015-08-understanding-lstms/)  
224 [lstms/](https://colah.github.io/posts/2015-08-understanding-lstms/), August 2015.
- 225 [15] Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya  
226 Sutskever. Language models are unsupervised multitask learners. 2019.
- 227 [16] Dominik Scherer, Andreas Müller, and Sven Behnke. Evaluation of  
228 pooling operations in convolutional architectures for object recognition.  
229 In *International conference on artificial neural networks*, pages 92–101.  
230 Springer, 2010.

- 231 [17] Chengcheng Shao, Giovanni Luca Ciampaglia, Alessandro Flammini, and  
232 Filippo Menczer. Hoaxy: A platform for tracking online misinformation.  
233 In *Proceedings of the 25th International Conference Companion on World*  
234 *Wide Web*, WWW '16 Companion, pages 745–750, Republic and Canton  
235 of Geneva, Switzerland, 2016. International World Wide Web Conferences  
236 Steering Committee.
- 237 [18] Dinghan Shen, Guoyin Wang, Wenlin Wang, Martin Renqiang Min,  
238 Qinliang Su, Yizhe Zhang, Chunyuan Li, Ricardo Henao, and Lawrence  
239 Carin. Baseline needs more love: On simple word-embedding-based models  
240 and associated pooling mechanisms. *CoRR*, abs/1805.09843, 2018.
- 241 [19] Kai Shu, Amy Sliva, Suhang Wang, Jiliang Tang, and Huan Liu. Fake  
242 news detection on social media: A data mining perspective. *CoRR*,  
243 abs/1708.01967, 2017.
- 244 [20] Patrice Y Simard, David Steinkraus, John C Platt, et al. Best practices  
245 for convolutional neural networks applied to visual document analysis. In  
246 *Icdar*, volume 3, 2003.
- 247 [21] William Yang Wang. "liar, liar pants on fire": A new benchmark dataset  
248 for fake news detection. *CoRR*, abs/1705.00648, 2017.
- 249 [22] L. Wen, X. Li, L. Gao, and Y. Zhang. A new convolutional neural network-  
250 based data-driven fault diagnosis method. *IEEE Transactions on Industrial*  
251 *Electronics*, 65(7):5990–5998, July 2018.
- 252 [23] Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional  
253 networks for text classification. In *Advances in neural information*  
254 *processing systems*, pages 649–657, 2015.