



Longest Substring with Distinct Characters (hard)

We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
 - Time Complexity
 - Space Complexity

Problem Statement#

Given a string, find the **length of the longest substring**, which has all **distinct characters**.

Example 1:

Input: String="aabccbb"

Output: 3

Explanation: The longest substring with distinct characters is "abc".

Example 2:

Input: String="abbbb"

Output: 2



Explanation: The longest substring with distinct characters



Example 3:

Input: String="abccde"

Output: 3

Explanation: Longest substrings with distinct characters are "abc" & "cde".

Try it yourself#

Try solving this question here:



C++



```
using namespace std;

#include <iostream>
#include <string>
#include <unordered_map>

class NoRepeatSubstring {
public:
    static int findLength(const string& str) {
        int maxLength = 0;
        // TODO: Write your code here
        return maxLength;
    }
};
```



Solution#



This problem follows the **Sliding Window** pattern, and we can use a dynamic sliding window strategy as discussed in [Longest Substring with K Distinct Characters](#). We can use a **HashMap** to remember the last index of each character we have processed. Whenever we get a duplicate character, we will shrink our sliding window to ensure that we always have distinct characters in the sliding window.

Code#

Here is what our algorithm will look like:

C++

```
using namespace std;

#include <iostream>
#include <string>
#include <unordered_map>

class NoRepeatSubstring {
public:
    static int findLength(const string& str) {
        int windowStart = 0, maxLength = 0;
        unordered_map<char, int> charIndexMap;
        // try to extend the range [windowStart, windowEnd]
        for (int windowEnd = 0; windowEnd < str.length(); windowEnd++) {
            char rightChar = str[windowEnd];
            // if the map already contains the 'rightChar', shrink the window from
            // we have only one occurrence of 'rightChar'
            if (charIndexMap.find(rightChar) != charIndexMap.end()) {
                // this is tricky; in the current window, we will not have any 'rightChar'
                // previous index and if 'windowStart' is already ahead of the last
                // we'll keep 'windowStart'
                windowStart = max(windowStart, charIndexMap[rightChar] + 1);
            }
            charIndexMap[rightChar] = windowEnd; // insert the 'rightChar' into the map
            maxLength = max(maxLength, windowEnd - windowStart + 1); // remember the maximum length
        }
    }
};
```



Time Complexity#

The above algorithm's time complexity will be $O(N)$, where 'N' is the number of characters in the input string.

Space Complexity#

The algorithm's space complexity will be $O(K)$, where K is the number of distinct characters in the input string. This also means $K \leq N$, because in the worst case, the whole string might not have any duplicate character, so the entire string will be added to the **HashMap**. Having said that, since we can expect a fixed set of characters in the input string (e.g., 26 for English letters), we can say that the algorithm runs in fixed space $O(1)$; in this case, we can use a fixed-size array instead of the **HashMap**.

[< Back](#)[Next >](#)[Fruits into Baskets \(medium\)](#)[Longest Substring with Same Letters ...](#)[Mark as Completed](#)[Report an Issue](#)