



CS 412 Intro. to Data Mining

Chapter 2. Getting to Know Your Data

Jiawei Han, Computer Science, Univ. Illinois at Urbana-Champaign, 2017





Chapter 2. Getting to Know Your Data

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization
- Measuring Data Similarity and Dissimilarity
- Summary



Types of Data Sets: (1) Record Data


- Relational records
 - Relational tables, highly structured
- Data matrix, e.g., numerical matrix, crosstabs

	China	England	France	Japan	USA	Total
Active Outdoors Crochet Glove		12.00	4.00	1.00	240.00	257.00
Active Outdoors Lycra Glove		10.00	6.00		323.00	339.00
InFlux Crochet Glove	3.00	6.00	8.00		132.00	149.00
InFlux Lycra Glove		2.00			143.00	145.00
Triumph Pro Helmet	3.00	1.00	7.00		333.00	344.00
Triumph Vertigo Helmet		3.00	22.00		474.00	499.00
Xtreme Adult Helmet	8.00	8.00	7.00	2.00	251.00	276.00
Xtreme Youth Helmet		1.00			76.00	77.00
Total	14.00	43.00	54.00	3.00	1,972.00	2,086.00

- Transaction data

TID	Items
1	Bread, Coke, Milk
2	Beer, Bread
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Coke, Diaper, Milk

- Document data: Term-frequency vector (matrix) of text documents




team	coach	y	pla	ball	score	game	n	wi	lost	timeout	season
Document 1	3	0	5	0	2	6	0	2	0	2	
Document 2	0	7	0	2	1	0	0	3	0	0	
Document 3	0	1	0	0	1	2	2	0	3	0	


Text Analytics

Types of Data Sets: (2) Graphs and Networks


□ Transportation network



□ World Wide Web



□ Molecular Structures



□ Social or information networks


Types of Data Sets: (3) Ordered Data

- ## ▢ Video data: sequence of images



sapatiotemporal

- ## ☐ Temporal data: time-series




- ## ❑ Sequential Data: transaction sequences

- ## Genetic sequence data

	Start	
Human	GTTTGAGG	- - ATGTCACAAATGCTCCCTTCATTCTCTATTAACAGACCTGCCGCA
Chimpanzee	GTTTGAGG	- - ATGTCACAAATGCTGCTTCACTCTCTATTAACAGACCTGCCGCA
Macaque	GTTTGAGG	- - ATGCTCACAAATGCTCCCTTCATTCTCCATTACAACCTGCCGCA
Human	GACAATTCTGCTAGCAGCCTTGTGCTATTATCTGTTTCTAAACCTAGTAATTGAGTGT	
Chimpanzee	GACAATTCTGCTAGCAGCCTTGTGCTATTATCTGTTTCTAAACCTAGTAATTGAGTGT	
Macaque	GACAATTCTGCTAGCAGCCTTGTGCTATTATCTGTTTCTAAACCTAGTAATTGAGTGT	
	↓	
Human	GATCTGGAGACTAA-CTCTGAAATAAAAGCTGATTATTATTATTATTCTCAAAAACAA	
Chimpanzee	GATCTGGAGACTAAACTCTGAAATAAAAGCTGATTATTATTATTATTCTCAAAAACAA	
Macaque	TATCTGGAGACTAAACTCTGAAATAAAAGCTGATTATTATTATTCTCAAAAACAA	
Human	CAGAATACGATTAGCAAATTACTTCTTAAGATATTATTTACATTCTATATTCTCCTA	
Chimpanzee	CAGAATACGATTAGCAAATTACTTCTTAAGATACTATTTCACATTCTATATTCTCCTA	
Macaque	CAGAATATGATTAGCAAATTACCTCTTAAGATATTATTTGCACATTCTATATTCTCCTA	
Human	CCCTGAGTTGATGTGTGAGCAATATGTCACCTTCATAAAGCCAGGTATACA- - - TTATG	
Chimpanzee	CCCTGAGTTGATGTGTGAGCCGTATGTCACCTTCATAAAGCCAGGTATACA- - - TTATG	
Macaque	CCCTGAGTTGATGTGTGAGCAATATGTCACCTTCACAAAGCCAGGTATATACATTACG	
	H I I Y S T F L S K	
Human	GACAGGTAAGTAAAAAACATATTATTATTCTACGTTTGTCCAAAATTTAAATTTC	
Chimpanzee	GACAGGTAAGTAAAAAACATATTATTATTCTACGTTTGTCCAAAATTTAAATTTC	
Macaque	GACAGGTAAGTAAAAA-CATATTATTATTCTAGGTTTGTCCAAAAGAGTTTAAATTTC	
Human	AACTGTTGCGCGTGTGTGGTAA- - - TGTAACACAAACTCAAGTACA	
Chimpanzee	AACTGTTGCGCGTGTGTGGTAA- - - TGTAACACAAACTCAAGTACA	
Macaque	AACTGTTGCGCATGTGTGGTAA- - - CGTAAACACAAATTCAGTACA	

Types of Data Sets: (4) Spatial, image and multimedia Data

- Spatial data: maps



- Image data:

- Video data:

Important Characteristics of Structured Data

- ສີເກີດສິນ (Attribute ສີເກີດ)

 - Dimensionality
 - Curse of dimensionality
 - Sparsity → ແກ້ໄຂ Missing → ຖະແຈກຮັບໃຈ }
 - Only presence counts
 - Resolution → ຕົວລະບຸ ພາຍໃນລະບຸ/ພາຍໃນລະບຸ
 - Patterns depend on the scale ⇒ Normalization
 - Distribution → ດຽວຢາງ ຂາດປັບປຸງ → Normal Year?
 - Centrality and dispersion

Data Objects

- Data sets are made up of data objects
- A **data object** represents an entity
 - ↳ Data point : ફોરા 1 મુ
- Examples:
 - sales database: customers, store items, sales
 - medical database: patients, treatments
 - university database: students, professors, courses
- Also called *samples*, *examples*, *instances*, *data points*, *objects*, *tuples*
- Data objects are described by **attributes**
- Database rows → data objects; columns → attributes

data object
entity
Data point

Attributes

- **Attribute (or dimensions, features, variables)**
 - A data field, representing a characteristic or feature of a data object.
 - *E.g., customer_ID, name, address*
- **Types:**
 - Nominal (e.g., red, blue)
 - Binary (e.g., {true, false}) → *student_ID, 1,0 → nominal 2 d*
 - Ordinal (e.g., {freshman, sophomore, junior, senior})
 - Numeric: quantitative
 - Interval-scaled: 100°C is interval scales
 - Ratio-scaled: 100°K is ratio scaled since it is twice as high as 50°K
 - Q1: Is student ID a nominal, ordinal, or interval-scaled data?
 - Q2: What about eye color? Or color in the color spectrum of physics?

Attribute Types

- **Nominal:** categories, states, or “names of things”
 - *Hair_color* = {*auburn, black, blond, brown, grey, red, white*}
 - marital status, occupation, ID numbers, zip codes
- **Binary**
 - Nominal attribute with only 2 states (0 and 1)
 - Symmetric binary: both outcomes equally important
 - e.g., gender
 - Asymmetric binary: outcomes not equally important.
 - e.g., medical test (positive vs. negative)
 - Convention: assign 1 to most important outcome (e.g., HIV positive)
- **Ordinal**
 - Values have a meaningful order (ranking) but magnitude between successive values is not known
 - *Size* = {*small, medium, large*}, grades, army rankings

Numeric Attribute Types

- Quantity (integer or real-valued)
- **Interval**
 - Measured on a scale of **equal-sized units**
 - Values have order
 - E.g., *temperature in C° or F°, calendar dates*
 - No true zero-point
- **Ratio**
 - Inherent **zero-point**
 - We can speak of values as being an order of magnitude larger than the unit of measurement (10 K° is twice as high as 5 K°).
 - e.g., *temperature in Kelvin, length, counts, monetary quantities*

Discrete vs. Continuous Attributes

Discrete Attribute

- Has only a finite or countably infinite set of values
 - E.g., zip codes, profession, or the set of words in a collection of documents
- Sometimes, represented as integer variables
- Note: Binary attributes are a special case of discrete attributes

Continuous Attribute

- Has real numbers as attribute values
 - E.g., temperature, height, or weight
- Practically, real values can only be measured and represented using a finite number of digits
- Continuous attributes are typically represented as floating-point variables


Chapter 2. Getting to Know Your Data

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization
- Measuring Data Similarity and Dissimilarity
- Summary



Basic Statistical Descriptions of Data

- Motivation
 - To better understand the data: central tendency, variation and spread
- Data dispersion characteristics
 - Median, max, min, quantiles, outliers, variance, ...
- Numerical dimensions correspond to sorted intervals
 - Data dispersion:
 - Analyzed with multiple granularities of precision
 - Boxplot or quantile analysis on sorted intervals
- Dispersion analysis on computed measures
 - Folding measures into numerical dimensions
 - Boxplot or quantile analysis on the transformed cube



Measuring the Central Tendency: (1) Mean

- Mean (algebraic measure) (sample vs. population):

Note: n is sample size and N is population size.

$$\bar{x} = \frac{1}{n} \sum_{i=1}^n x_i \quad \mu = \frac{\sum x}{N}$$

- Weighted arithmetic mean:

$$\bar{x} = \frac{\sum_{i=1}^n w_i x_i}{\sum_{i=1}^n w_i}$$

- Trimmed mean:

- Chopping extreme values (e.g., Olympics gymnastics score computation)

Measuring the Central Tendency: (2) Median

- Median:

- Middle value if odd number of values, or average of the middle two values otherwise
- Estimated by interpolation (for *grouped data*):

age	frequency
1–5	200
6–15	450
16–20	300
21–50	1500
51–80	700
81–110	44

Approximate
median



Sum before the median interval

Interval width ($L_2 - L_1$)

$$\text{median} = L_1 + \left(\frac{n/2 - (\sum \text{freq})_l}{\text{freq}_{\text{median}}} \right) \text{width}$$

Low interval limit


Measuring the Central Tendency: (3) Mode

- Mode: Value that occurs most frequently in the data

- Unimodal


- Empirical formula:

$$\text{mean} - \text{mode} = 3 \times (\text{mean} - \text{median})$$





- Multi-modal

- Bimodal




- Trimodal




Symmetric vs. Skewed Data

- Median, mean and mode of symmetric, positively and negatively skewed data


symmetric



positively skewed




negatively skewed



Properties of Normal Distribution Curve

← — — — — Represent data dispersion, spread — — — — →



Measures Data Distribution: Variance and Standard Deviation

- ❑ Variance and standard deviation (*sample: s, population: σ*)

- ❑ **Variance:** (algebraic, scalable computation)

- ❑ Q: Can you compute it incrementally and efficiently?

$$s^2 = \frac{1}{n-1} \sum_{i=1}^n (x_i - \bar{x})^2 = \frac{1}{n-1} \left[\sum_{i=1}^n x_i^2 - \frac{1}{n} \left(\sum_{i=1}^n x_i \right)^2 \right]$$

$$\sigma^2 = \frac{1}{N} \sum_{i=1}^n (x_i - \mu)^2 = \frac{1}{N} \sum_{i=1}^n x_i^2 - \mu^2$$


- ❑ **Standard deviation s (or σ)** is the square root of variance s^2 (or σ^2)

Graphic Displays of Basic Statistical Descriptions


- **Boxplot:** graphic display of five-number summary
- **Histogram:** x-axis are values, y-axis repres. frequencies
- **Quantile plot:** each value x_i is paired with f_i indicating that approximately $100 f_i \%$ of data are $\leq x_i$
- **Quantile-quantile (q-q) plot:** graphs the quantiles of one univariant distribution against the corresponding quantiles of another
- **Scatter plot:** each pair of values is a pair of coordinates and plotted as points in the plane

Measuring the Dispersion of Data: Quartiles & Boxplots

- **Quartiles:** Q_1 (25^{th} percentile), Q_3 (75^{th} percentile)
- **Inter-quartile range:** $\text{IQR} = Q_3 - Q_1$
- **Five number summary:** min, Q_1 , median, Q_3 , max
- **Boxplot:** Data is represented with a box
 - Q_1 , Q_3 , IQR: The ends of the box are at the first and third quartiles, i.e., the height of the box is IQR
 - Median (Q_2) is marked by a line within the box
 - Whiskers: two lines outside the box extended to Minimum and Maximum
 - Outliers: points beyond a specified outlier threshold, plotted individually
 - **Outlier:** usually, a value higher/lower than $1.5 \times \text{IQR}$




Visualization of Data Dispersion: 3-D Boxplots




Histogram Analysis

↳
Histogram

- ❑ Histogram: Graph display of tabulated frequencies, shown as bars
- ❑ Differences between histograms and bar charts
 - ❑ Histograms are used to show distributions of variables while bar charts are used to compare variables
 - ❑ Histograms plot binned quantitative data while bar charts plot categorical data
 - ❑ Bars can be reordered in bar charts but not in histograms
 - ❑ Differs from a bar chart in that it is the area of the bar that denotes the value, not the height as in bar charts, a crucial distinction when the categories are not of uniform width




Olympic Medals of all Times (till 2012 Olympics)




Bar chart

Histograms Often Tell More than Boxplots





- The two histograms shown in the left may have the same boxplot representation
- The same values for: min, Q1, median, Q3, max
- But they have rather different data distributions






Scatter plot

- ❑ Provides a first look at bivariate data to see clusters of points, outliers, etc.
- ❑ Each pair of values is treated as a pair of coordinates and plotted as points in the plane




Positively and Negatively Correlated Data



- The left half fragment is positively correlated
- The right half is negative correlated

Uncorrelated Data



Chapter 2. Getting to Know Your Data

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization 
- Measuring Data Similarity and Dissimilarity
- Summary





Data Visualization

- Why data visualization?
 - Gain insight into an information space by mapping data onto graphical primitives
 - Provide qualitative overview of large data sets
 - Search for patterns, trends, structure, irregularities, relationships among data
 - Help find interesting regions and suitable parameters for further quantitative analysis
 - Provide a visual proof of computer representations derived
- Categorization of visualization methods:
 - Pixel-oriented visualization techniques
 - Geometric projection visualization techniques
 - Icon-based visualization techniques
 - Hierarchical visualization techniques
 - Visualizing complex data and relations

box plot
กราฟกล่อง บุณฑ์กราฟล็อก
-> ถนนที่ว่าไฟต่อไป

Pixel-Oriented Visualization Techniques

- ❑ For a data set of m dimensions, create m windows on the screen, one for each dimension
- ❑ The m dimension values of a record are mapped to m pixels at the corresponding positions in the windows
- ❑ The colors of the pixels reflect the corresponding values



ລາຄາ → ສ້າງ
ເງິນ → ພືບ


ສະກາດ
ສະຫຼິບ
transaction
ນັບ

Parallel Coordinates


Dimension 1
2 vs 1 & 4 vs 3/r

- n equidistant axes which are parallel to one of the screen axes and correspond to the attributes
- The axes are scaled to the [minimum, maximum]: range of the corresponding attribute
- Every data item corresponds to a polygonal line which intersects each of the axes at the point which corresponds to the value for the attribute

Parallel coordinate plot, Fisher's Iris data



Parallel Coordinates of a Data Set




អាជីវកម្មស៊ូល, ទំនើបនុវត្តស៊ូល


Tree-Map

Ex. A- ធនានេតិ៍រងគួង

- Screen-filling method which uses a hierarchical partitioning of the screen into regions depending on the attribute values
- The x- and y-dimension of the screen are partitioned alternately according to the attribute values (classes)




Schneiderman@UMD: Tree-Map of a File System




Schneiderman@UMD: Tree-Map to support large data sets of a million items

Visualizing Complex Data and Relations: Tag Cloud

- ❑ Tag cloud: Visualizing user-generated tags
 - ❑ The importance of tag is represented by font size/color
 - ❑ Popularly used to visualize word/phrase distributions




KDD 2013 Research Paper Title Tag Cloud




Newsmap: Google News Stories in 2005

Visualizing Complex Data and Relations: Social Networks


- Visualizing non-numerical data: social and information networks




A typical network structure



A social network




organizing
information networks



Chapter 2. Getting to Know Your Data

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization
- Measuring Data Similarity and Dissimilarity
- Summary

วิดีโอนี้สอน, ทำา ของ Data
เพื่อจัดการคุณภาพ



Similarity, Dissimilarity, and Proximity

- **Similarity measure or similarity function** Attribute یعنی اندیکا
 - A real-valued function that quantifies the similarity between two objects
 - Measure how two data objects are alike: The higher value, the more alike
 - Often falls in the range [0,1]: 0: no similarity; 1: completely similar
 - **Dissimilarity (or distance) measure** Attribute یعنی اندیکا
ul style="list-style-type: none;"> - Numerical measure of how different two data objects are
 - In some sense, the inverse of similarity: The lower, the more alike
 - Minimum dissimilarity is often 0 (i.e., completely similar)
 - Range [0, 1] or [0, ∞), depending on the definition
- **Proximity** usually refers to either similarity or dissimilarity

Data Matrix and Dissimilarity Matrix

- Data matrix

- A data matrix of n data points with l dimensions

- Dissimilarity (distance) matrix

- n data points, but registers only the distance $d(i, j)$ (typically metric)

- Usually symmetric, thus a triangular matrix

- **Distance functions** are usually different for real, boolean, categorical, ordinal, ratio, and vector variables

- Weights can be associated with different variables based on applications and data semantics

$$D = \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1l} \\ x_{21} & x_{22} & \dots & x_{2l} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{nl} \end{pmatrix}$$

$$\begin{array}{ccccc} & 0 & & & \\ & d(2,1) & 0 & & \\ & \vdots & \vdots & \ddots & \\ & d(n,1) & d(n,2) & \dots & 0 \end{array}$$

Standardizing Numeric Data

- Z-score:

$$z = \frac{x - \mu}{\sigma}$$

- X: raw score to be standardized, μ : mean of the population, σ : standard deviation
- the distance between the raw score and the population mean in units of the standard deviation
- negative when the raw score is below the mean, “+” when above
- An alternative way: Calculate the mean absolute deviation


$$s_f = \frac{1}{n}(|x_{1f} - m_f| + |x_{2f} - m_f| + \dots + |x_{nf} - m_f|)$$

where

$$m_f = \frac{1}{n}(x_{1f} + x_{2f} + \dots + x_{nf})$$

- standardized measure (z-score):
$$z_{if} = \frac{x_{if} - m_f}{s_f}$$
- Using mean absolute deviation is more robust than using standard deviation

Example: Data Matrix and Dissimilarity Matrix



Data Matrix

point	attribute1	attribute2
x_1	1	2
x_2	3	5
x_3	2	0
x_4	4	5

* ការបង្កើតរបស់វគ្គ Data Mining

នៅពេល Classification,

Cluster ត្រូវបានដោះស្រាយជា Scale តុលាក់

↓

ក្រោមភាព Normalization,
standardization
($\mu = 0, \sigma = 1$)

និងបានការ
បញ្ចូនចំណាំ
តាមរយៈរាយ
ស្ថាបី
រួម 0, 1

Dissimilarity Matrix (by Euclidean Distance)

	x_1	x_2	x_3	x_4
x_1	0			
x_2	3.61	0		
x_3	2.24	5.1	0	
x_4	4.24	1	5.39	0

$$\frac{x - x_{\min}}{x_{\max} - x_{\min}}$$

Distance on Numeric Data: Minkowski Distance

- **Minkowski distance:** A popular distance measure

$$d(i, j) = \sqrt[p]{|x_{i1} - x_{j1}|^p + |x_{i2} - x_{j2}|^p + \dots + |x_{il} - x_{jl}|^p}$$

where $i = (x_{i1}, x_{i2}, \dots, x_{il})$ and $j = (x_{j1}, x_{j2}, \dots, x_{jl})$ are two l -dimensional data objects, and p is the order (the distance so defined is also called L- p norm)

- Properties
 - $d(i, j) > 0$ if $i \neq j$, and $d(i, i) = 0$ (Positivity)
 - $d(i, j) = d(j, i)$ (Symmetry)
 - $d(i, j) \leq d(i, k) + d(k, j)$ (Triangle Inequality)
- A distance that satisfies these properties is a **metric**
- Note: There are nonmetric dissimilarities, e.g., set differences

Special Cases of Minkowski Distance

- $p = 1$: (L_1 norm) Manhattan (or city block) distance
 - E.g., the Hamming distance: the number of bits that are different between two binary vectors

$$d(i, j) = |x_{i1} - x_{j1}| + |x_{i2} - x_{j2}| + \cdots + |x_{il} - x_{jl}|$$

ເຕັກສິນ classification,
clustering

- $p = 2$: (L_2 norm) Euclidean distance

$$d(i, j) = \sqrt{|x_{i1} - x_{j1}|^2 + |x_{i2} - x_{j2}|^2 + \cdots + |x_{il} - x_{jl}|^2}$$

- $p \rightarrow \infty$: (L_{\max} norm, L_∞ norm) “supremum” distance
 - The maximum difference between any component (attribute) of the vectors


$$d(i, j) = \lim_{p \rightarrow \infty} \sqrt[p]{|x_{i1} - x_{j1}|^p + |x_{i2} - x_{j2}|^p + \cdots + |x_{il} - x_{jl}|^p} = \max_{f=1}^l |x_{if} - x_{jf}|$$

ຮະຢະຈາກຫຍວ່າ ທີ່ມາດກໍ່ສູງ
ເຕັກສິນທີ່ກໍ່ສູງຂະໜາດຂອງ
ເລີດ

Example: Minkowski Distance at Special Cases

☞ Հայոց լեզու կենսագործություն

point	attribute 1	attribute 2
x1	1	2
x2	3	5
x3	2	0
x4	4	5



Manhattan (L_1)

L	x1	x2	x3	x4
x1	0			
x2	5	0		
x3	3	6	0	
x4	6	1	7	0

Euclidean (L_2)

L2	x1	x2	x3	x4
x1	0			
x2	3.61	0		
x3	2.24	5.1	0	
x4	4.24	1	5.39	0

Supremum (L_∞)

L_∞	x1	x2	x3	x4
x1	0			
x2	3	0		
x3	2	5	0	
x4	3	1	5	0

Proximity Measure for Binary Attributes

- A contingency table for binary data

		Object <i>j</i>		
		1	0	sum
Object <i>i</i>	1	q	r	$q + r$
	0	s	t	$s + t$
sum		$q + s$	$r + t$	p

- Distance measure for symmetric binary variables

$$d(i, j) = \frac{r + s}{q + r + s + t}$$

- Distance measure for asymmetric binary variables:

$$d(i, j) = \frac{r + s}{q + r + s}$$

- Jaccard coefficient (*similarity* measure for

asymmetric binary variables):

$$sim_{Jaccard}(i, j) = \frac{q}{q + r + s}$$

- Note: Jaccard coefficient is the same as

(a concept discussed in Pattern Discovery)

$$coherence(i, j) = \frac{sup(i, j)}{sup(i) + sup(j) - sup(i, j)} = \frac{q}{(q + r) + (q + s) - q}$$

Example: Dissimilarity between Asymmetric Binary Variables

Name	Gender	Fever	Cough	Test-1	Test-2	Test-3	Test-4
Jack	M	Y	N	P	N	N	N
Mary	F	Y	N	P	N	P	N
Jim	M	Y	P	N	N	N	N

- Gender is a symmetric attribute (not counted in)
- The remaining attributes are asymmetric binary
- Let the values Y and P be 1, and the value N be 0
- Distance: $d(i, j) = \frac{r + s}{q + r + s}$

$$d(jack, mary) = \frac{0+1}{2+0+1} = 0.33$$

$$d(jack, jim) = \frac{1+1}{1+1+1} = 0.67$$

$$d(jim, mary) = \frac{1+2}{1+1+2} = 0.75$$

		Mary		
		1	0	Σ_{row}
Jack		1	2	0
0		1	3	4
Σ_{col}		3	3	6

		Jim		
		1	0	Σ_{row}
Jack		1	1	2
0		1	3	4
Σ_{col}		2	4	6

		Mary		
		1	0	Σ_{row}
Jim		1	1	2
0		2	2	4
Σ_{col}		3	3	6

Proximity Measure for Categorical Attributes

- Categorical data, also called nominal attributes
 - Example: Color (red, yellow, blue, green), profession, etc.
- Method 1: Simple matching
 - m : # of matches, p : total # of variables

$$d(i, j) = \frac{p - m}{p}$$

- Method 2: Use a large number of binary attributes
 - Creating a new binary attribute for each of the M nominal states

Ordinal Variables

- An ordinal variable can be discrete or continuous
- Order is important, e.g., rank (e.g., freshman, sophomore, junior, senior)
- Can be treated like interval-scaled
 - Replace *an ordinal variable value* by its rank: $r_{if} \in \{1, \dots, M_f\}$
 - Map the range of each variable onto [0, 1] by replacing *i*-th object in the *f*-th variable by
$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$
- Example: freshman: 0; sophomore: 1/3; junior: 2/3; senior 1
 - Then distance: $d(\text{freshman}, \text{senior}) = 1$, $d(\text{junior}, \text{senior}) = 1/3$
- Compute the dissimilarity using methods for interval-scaled variables

Attributes of Mixed Type

- A dataset may contain all attribute types
 - Nominal, symmetric binary, asymmetric binary, numeric, and ordinal
- One may use a weighted formula to combine their effects:

$$d(i, j) = \frac{\sum_{f=1}^p w_{ij}^{(f)} d_{ij}^{(f)}}{\sum_{f=1}^p w_{ij}^{(f)}}$$

- If f is numeric: Use the normalized distance
- If f is binary or nominal: $d_{ij}^{(f)} = 0$ if $x_{if} = x_{jf}$; or $d_{ij}^{(f)} = 1$ otherwise
- If f is ordinal
 - Compute ranks z_{if} (where $z_{if} = \frac{r_{if} - 1}{M_f - 1}$)
 - Treat z_{if} as interval-scaled

Cosine Similarity of Two Vectors

- A **document** can be represented by a bag of terms or a long vector, with each attribute recording the *frequency* of a particular term (such as word, keyword, or phrase) in the document

Document	team	coach	hockey	baseball	soccer	penalty	score	win	loss	season
Document1	5	0	3	0	2	0	0	2	0	0
Document2	3	0	2	0	1	1	0	1	0	1
Document3	0	7	0	2	1	0	0	3	0	0
Document4	0	1	0	0	1	2	2	0	3	0

- Other vector objects: Gene features in micro-arrays
- Applications: Information retrieval, biologic taxonomy, gene feature mapping, etc.
- Cosine measure: If d_1 and d_2 are two vectors (e.g., term-frequency vectors), then

$$\cos(d_1, d_2) = \frac{d_1 \bullet d_2}{\|d_1\| \times \|d_2\|}$$


where \bullet indicates vector dot product, $\|d\|$: the length of vector d

Example: Calculating Cosine Similarity

- Calculating Cosine Similarity:

$$\cos(d_1, d_2) = \frac{d_1 \bullet d_2}{\|d_1\| \times \|d_2\|}$$

$$sim(A, B) = \cos(\theta) = \frac{A \cdot B}{\|A\| \|B\|}$$



where • indicates vector dot product, ||d||: the length of vector d

- Ex: Find the **similarity** between documents 1 and 2.

$$d_1 = (5, 0, 3, 0, 2, 0, 0, 2, 0, 0) \quad d_2 = (3, 0, 2, 0, 1, 1, 1, 0, 1, 0)$$

- First, calculate vector dot product

$$d_1 \bullet d_2 = 5 \times 3 + 0 \times 0 + 3 \times 2 + 0 \times 0 + 2 \times 1 + 0 \times 1 + 0 \times 1 + 2 \times 1 + 0 \times 0 + 0 \times 1 = 25$$

- Then, calculate $\|d_1\|$ and $\|d_2\|$

$$\|d_1\| = \sqrt{5 \times 5 + 0 \times 0 + 3 \times 3 + 0 \times 0 + 2 \times 2 + 0 \times 0 + 0 \times 0 + 2 \times 2 + 0 \times 0 + 0 \times 0} = 6.481$$

$$\|d_2\| = \sqrt{3 \times 3 + 0 \times 0 + 2 \times 2 + 0 \times 0 + 1 \times 1 + 1 \times 1 + 0 \times 0 + 1 \times 1 + 0 \times 0 + 1 \times 1} = 4.12$$

- Calculate cosine similarity: $\cos(d_1, d_2) = 25 / (6.481 \times 4.12) = 0.94$

Chapter 2. Getting to Know Your Data

- Data Objects and Attribute Types
- Basic Statistical Descriptions of Data
- Data Visualization
- Measuring Data Similarity and Dissimilarity
- Summary



Summary

- Data attribute types: nominal, binary, ordinal, interval-scaled, ratio-scaled
- Many types of data sets, e.g., numerical, text, graph, Web, image.
- Gain insight into the data by:
 - Basic statistical data description: central tendency, dispersion, graphical displays
 - Data visualization: map data onto graphical primitives
 - Measure data similarity
- Above steps are the beginning of data preprocessing
- Many methods have been developed but still an active area of research

References

- W. Cleveland, Visualizing Data, Hobart Press, 1993
- T. Dasu and T. Johnson. Exploratory Data Mining and Data Cleaning. John Wiley, 2003
- U. Fayyad, G. Grinstein, and A. Wierse. Information Visualization in Data Mining and Knowledge Discovery, Morgan Kaufmann, 2001
- L. Kaufman and P. J. Rousseeuw. Finding Groups in Data: an Introduction to Cluster Analysis. John Wiley & Sons, 1990.
- H. V. Jagadish et al., Special Issue on Data Reduction Techniques. Bulletin of the Tech. Committee on Data Eng., 20(4), Dec. 1997
- D. A. Keim. Information visualization and visual data mining, IEEE trans. on Visualization and Computer Graphics, 8(1), 2002
- D. Pyle. Data Preparation for Data Mining. Morgan Kaufmann, 1999
- S. Santini and R. Jain," Similarity measures", IEEE Trans. on Pattern Analysis and Machine Intelligence, 21(9), 1999
- E. R. Tufte. The Visual Display of Quantitative Information, 2nd ed., Graphics Press, 2001
- C. Yu, et al., Visual data mining of multimedia data for social and behavioral studies, Information Visualization, 8(1), 2009

