

# Computer Vision - 2025

## Week #13. Multi-Modal Data Processing. Part II: Generalization

Lectures by Alexei Kornaev <sup>1,2,3</sup>

Practical sessions by Kirill Yakovlev <sup>2</sup>


<sup>1</sup>AI Institute, Innopolis University (IU), Innopolis

<sup>2</sup>Robotics & CV Master's Program, IU, Innopolis

<sup>3</sup>Dept. of  $M^2R$ , Orel State University, Orel

<sup>4</sup>RC for AI, National RC for Oncology, Moscow

April 14, 2025



# Agenda

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

- 1 Recap: CLIP architecture and loss
- 2 Current state of VLMs
- 3 Optimization of VLMs
- 4 Fine-Tuning of LMs
- 5 Prospects
- 6 VLM + Control System = VLAM
- 7 Outcomes
- 8 Contrastive Language-Image Pre-training (CLIP)
- 9 Fine-Tuning of Large Models
- 10 Other Types of Multimodalities
- 11 Meta-Learning

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

# Section 1. Recap: CLIP architecture and loss

# CLIP Loss: Core Mechanism

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Definition

Align image-text pairs in a shared space using symmetric contrastive loss:

$$\mathcal{L}_{\text{CLIP}} = -\frac{1}{2N} \sum_{i=1}^N \left[ \log \frac{e^{s_{ii}/\tau}}{\sum_j e^{s_{ij}/\tau}} + \log \frac{e^{s_{ii}/\tau}}{\sum_j e^{s_{ji}/\tau}} \right]$$

where  $s_{ij} = \cos\_sim(I_i, T_j)$  for image and text embeddings,  $\tau$  is the temperature parameter (learned or fixed) to scale logits.




Figure: Contrastive Language-Image Pre-training (CLIP) [Radford et al., 2021]

# Pre-test: CLIP Loss Example with a Small Batch (N=2)

CV-2025

## Setup

A.Kornaev,  
K.Yakovlev

Batch size  $N = 2$ , temperature  $\tau = 0.07$ ; **image embeddings**:  $l_1 = [0.8, 0.6]$ ,  $l_2 = [0.6, 0.8]$ ; **text embeddings**:  $T_1 = [0.7, 0.7]$ ,  $T_2 = [0.7, -0.7]$ ; normalized embeddings:  $\|l\| = \|T\| = 1$ ; **similarity Matrix**:

Recap: CLIP  
architecture  
and loss

$$S = \begin{bmatrix} l_1 \cdot T_1 & l_1 \cdot T_2 \\ l_2 \cdot T_1 & l_2 \cdot T_2 \end{bmatrix} = \begin{bmatrix} 0.98 & 0.14 \\ 0.98 & -0.14 \end{bmatrix}.$$

Current state  
of VLMs

Step 1: Image  $\rightarrow$  Text Loss (for  $l_1$ )

Optimization  
of VLMs

$$\text{Softmax}_{\tau}(S_{l_1}) = \frac{e^{X.XX/X.XX}}{e^{X.XX/X.XX} + e^{X.XX/X.XX}} \approx 1.0,$$

Fine-Tuning of  
LMs

$$\mathcal{L}_{CE}(l_1) = -\log(1.0) \approx 0.$$

Prospects

Step 2: Text  $\rightarrow$  Image Loss (for  $T_2$ )

VLM +  
Control  
System =  
VLAM

$$\text{Softmax}_{\tau}(S_{T_2}) = \frac{e^{X.XX/X.XX}}{e^{X.XX/X.XX} + e^{X.XX/X.XX}} \approx 0.018,$$

$$\mathcal{L}_{CE}(T_2) = -\log(0.018) \approx 4.0.$$

Outcomes

Total Loss

Contrastive  
Language-  
Image

$$\mathcal{L}_{CLIP} = \frac{1}{2 \times 2} (0 + 4.0 + \dots) \quad (\text{Sum over all pairs}).$$

# Pre-test: CLIP Loss Example with a Small Batch (N=2)

CV-2025

## Setup

A.Kornaev,  
K.Yakovlev

Batch size  $N = 2$ , temperature  $\tau = 0.07$ ; **image embeddings**:  $I_1 = [0.8, 0.6]$ ,  $I_2 = [0.6, 0.8]$ ; **text embeddings**:  $T_1 = [0.7, 0.7]$ ,  $T_2 = [0.7, -0.7]$ ; normalized embeddings:  $\|I\| = \|T\| = 1$ ; **similarity Matrix**:

Recap: CLIP  
architecture  
and loss

$$S = \begin{bmatrix} I_1 \cdot T_1 & I_1 \cdot T_2 \\ I_2 \cdot T_1 & I_2 \cdot T_2 \end{bmatrix} = \begin{bmatrix} 0.98 & 0.14 \\ 0.98 & -0.14 \end{bmatrix}.$$

Current state  
of VLMs

Step 1: Image  $\rightarrow$  Text Loss (for  $I_1$ )

Optimization  
of VLMs

$$\text{Softmax}_{\tau}(S_{I_1}) = \frac{e^{0.98/0.07}}{e^{0.98/0.07} + e^{0.14/0.07}} = \frac{e^{14}}{e^{14} + e^2} \approx 1.0,$$

Fine-Tuning of  
LMs

$$\mathcal{L}_{CE}(I_1) = -\log(1.0) \approx 0.$$

Prospects

Step 2: Text  $\rightarrow$  Image Loss (for  $T_2$ )

VLM +  
Control  
System =  
VLAM

$$\text{Softmax}_{\tau}(S_{T_2}) = \frac{e^{-0.14/0.07}}{e^{0.14/0.07} + e^{-0.14/0.07}} = \frac{e^{-2}}{e^2 + e^{-2}} \approx 0.018,$$

Outcomes

$$\mathcal{L}_{CE}(T_2) = -\log(0.018) \approx 4.0.$$

Contrastive  
Language-  
Image

Total Loss

$$\mathcal{L}_{\text{CLIP}} = \frac{1}{2 \times 2} (0 + 4.0 + \dots) \quad (\text{Sum over all pairs}).$$

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 2. Current state of VLMs

CV-2025

A.Korinaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image



CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 3. Optimization of VLMs

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 4. Fine-Tuning of LMs

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 5. Prospects

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 6. VLM + Control System = VLAM

# RT-2: Vision-Language-Action Model

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Core Mechanism

Unifies vision, language, and action via tokenization:  $\text{Action} = \text{Decode}\left(\text{Transformer}\left(\left[\underbrace{\mathcal{V}(I)}_{\text{Visual Tokens}}; \underbrace{\mathcal{T}(C)}_{\text{Language Tokens}}\right]\right)\right)$

where:  $\mathcal{V}$ : vision tokenizer (ViT + Action Quantizer);  $\mathcal{T}$ : language tokenizer (PaLI-style); actions discretized as  $\langle \text{cmd}, x, y, z, \theta \rangle$  tokens.

## Key Innovations

- **Action Chunking:** Predicts action sequences autoregressively
- **Cross-Modal Attention:**  $\text{Attention}(Q_{\text{action}}, K_{\text{vision} + \text{lang}}, V_{\text{vision} + \text{lang}})$
- **Chain-of-Thought:** "Plan  $\rightarrow$  Verify  $\rightarrow$  Execute" token prediction




Figure: RT-2's unified architecture [Brohan et al., 2023]



# Hands-on Coding with CLIP models (again)

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

CLIP + CLIPSeg = prerequisite for Action

- Get an Image (scene) + text (instruction from a human to a robot)
- Define a set of discrete robot skills (actions) and scene objects, and distractors
- use CLIPSeg for object segmentation and position detection
- use CLIP for skill prediction (VLAM Concept)

The code is available via the [link #1](#).

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

# Core Concepts in Multimodal Learning

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Key Technical Challenges

- **Embedding Alignment:** Map modalities to a shared space (e.g., CLIP's image/text encoders).
- **Cross-Modal Attention:** Dynamically fuse modalities (e.g., Flamingo's Perceiver Resampler).
- **Scaling Laws:** Training with massive datasets (LAION-5B, RT-1).

## Contrastive Learning Formulation

$$\mathcal{L}_{\text{contrast}} = -\log \frac{e^{s(I, T) / \tau}}{\sum_{j=1}^N e^{s(I, T_j) / \tau}}$$

- $s(I, T)$ : Cosine similarity between image  $I$  and text  $T$ .
- $\tau$ : Temperature parameter (learned in CLIP).

## Cross-Modal Attention

$$\text{Attention}(Q_{\text{text}}, K_{\text{image}}, V_{\text{image}}) = \text{softmax}\left(\frac{QK^T}{\sqrt{d}}\right) V$$

# Modern VLMs and Applications

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Architectures

- **Flamingo** [Alayrac, 2022]: Processes interleaved images/text for few-shot learning.
- **LLaVA** [Liu, 2023]: Connects vision encoder to LLM via projection layers.
- **BLIP-2** [Li, 2023]: Q-Former bridges frozen encoders (ViT + LLM).

## Robotics Applications

- **PALM-E** [Driess, 2023]: Embodied LLM for planning with vision-language-action.
- **RT-2**: VLMs for robotic control ("pick up the banana").
- **Instruction Following**: Grounding language commands to sensorimotor actions.

Modality	Robot Input	Embedding Technique
Vision	Camera frames	ViT/ResNet
Language	Commands	BERT/GPT
Actions	Joint angles	MLP

Table: Multimodal Inputs in Robotics

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 7. Outcomes

# Outcomes

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

This week's lecture on Multimodal Data Processing introduces foundational concepts in vision-language alignment for robotic systems. By the end of this session, students will be able to:

- 1 Explain contrastive learning principles and cross-modal attention mechanisms in Vision-Language Models (VLMs).
- 2 Implement zero-shot inference using CLIP for robotic object recognition and scene understanding.
- 3 Critically evaluate architectural choices in modern VLMs (e.g., Flamingo [Alayrac, 2022], LLaVA [Liu, 2023]).

**Key Takeaway:** Multimodal alignment bridges perception (vision) and reasoning (language), forming the foundation for embodied AI systems like PALM-E [Driess, 2023] in robotics.

# VLAM: Vision-Language-Action Models

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Key Components

- Multimodal encoder (vision + language)
- Policy network for action generation
- Integration with reinforcement learning [Driess, 2023]

## Policy Gradient Theorem

$$\nabla_{\theta} \mathcal{J}(\theta) = \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(a|s) \cdot A(s, a)]$$

Component	Implementation
Multimodal Encoder	Transformer Fusion
Policy Network	MLP/Transformer Decoder
Action Space	Continuous (RL) / Discrete (IL)

Table: VLAM Architecture Components

# LLM Training: From Scratch vs Pretrained

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Decision Factors

- **Pretrained:** 99% of use cases (low-resource adaptation)
- **From Scratch:** Specialized domains, novel architectures

## Parameter-Efficient Fine-Tuning

- LoRA:  $\Delta W = BA$  where  $B \in \mathbb{R}^{d \times r}$ ,  $A \in \mathbb{R}^{r \times k}$
- QLoRA: 4-bit quantization + LoRA

Metric	From Scratch	Pretrained
Data Needs	1B+ tokens	1k-100k tokens
Compute Cost	\$100k+	\$100-\$1k
Training Time	Weeks	Hours

Table: Training Strategy Comparison



CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

# Section 8. Contrastive Language-Image Pre-training (CLIP)

# CLIP Loss: Core Mechanism

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Definition

Align image-text pairs in a shared space using symmetric contrastive loss:

$$\mathcal{L}_{\text{CLIP}} = -\frac{1}{2N} \sum_{i=1}^N \left[ \log \frac{e^{s_{ii}/\tau}}{\sum_j e^{s_{ij}/\tau}} + \log \frac{e^{s_{ii}/\tau}}{\sum_j e^{s_{ji}/\tau}} \right]$$

where  $s_{ij} = \cos\_sim(I_i, T_j)$  for image and text embeddings,  $\tau$  is the temperature parameter (learned or fixed) to scale logits.



Figure: Contrastive Language-Image Pre-training (CLIP) [Radford et al., 2021]

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 9. Fine-Tuning of Large Models

# Fine-Tuning Strategies for LMs

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Comparison of Parameter-Efficient Methods

Method	Added Params	Modifies Forward Pass	Key Advantage
Full FT	100%	$h = (W_0 + \Delta W)x$	Highest accuracy
LoRA	$\sim 0.1\%$	$h = W_0x + BAx$	Balance of efficiency/performance
Adapter	$\sim 1\%$	$h = W_0x + W_2(\sigma(W_1x))$	Modular
Prefix Tuning	$\sim 0.5\%$	$[P; x] \rightarrow \text{Attention}$	No backbone changes
BitFit	$\sim 0.01\%$	$h = W_0x + b$	Only biases updated

## Mathematical Forms

- **Adapter:**  $W_2 \in \mathbb{R}^{d \times r}$ ,  $W_1 \in \mathbb{R}^{r \times d}$
- **Prefix Tuning:**  $P \in \mathbb{R}^{l \times d}$  (prepended tokens)
- **BitFit:**  $b \in \mathbb{R}^d$  (bias terms only)

## When to Use LoRA?

- Need high parameter efficiency ( $r \leq 64$ )
- Preserve original model architecture
- Balance between compute and accuracy

# LoRA: Low-Rank Adaptation [Hu et al., 2021]

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Key Mathematical Formulation

For a pretrained weight matrix  $W_0 \in \mathbb{R}^{d \times k}$ :

$$W = W_0 + \underbrace{BA}_{\text{Low-rank update}} \quad \begin{cases} B \in \mathbb{R}^{d \times r} \\ A \in \mathbb{R}^{r \times k} \\ r \ll \min(d, k) \end{cases}$$

## Example: 1024x1024 Layer with Rank=8

- Original params:  $1024 \times 1024 = 1,048,576$
- LoRA params:  $8 \times (1024 + 1024) = 16,384$
- Reduction:  $\frac{16,384}{1,048,576} \approx 1.56\%$

# LoRA in Action

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Forward Pass Computation

For input  $x \in \mathbb{R}^k$ :

$$h = W_0 x + \underbrace{B(Ax)}_{\text{Rank-constrained update}}$$

## Gradient Flow

- Frozen weights:  $\nabla_{W_0} \mathcal{L} = 0$
- Adaptor gradients:

$$\nabla_B \mathcal{L} = (\nabla_h \mathcal{L}) x^\top A^\top \quad \nabla_A \mathcal{L} = B^\top (\nabla_h \mathcal{L}) x^\top$$

## Why This Works

- Preserves pretrained knowledge ( $W_0$  fixed)
- Efficient training (only update  $B, A$ )
- Low-rank bottleneck prevents overfitting

# Blog reading

CV-2025

A.Korinaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Vision Language Action Models (VLA) Overview: LeRobot Policies Demo

The advent of Generative AI, has fundamentally transformed robotic intelligence, enabling significant strides in how advanced humanoid robots perceive, reason and act in the physical world. This huge progress is primarily attributed in terms of decision making, thanks to LLM and VLMs generalization due to their large scale pre-training. Instead of relying on traditional complex policies which has to be carefully handcrafted for individual low level tasks for fine grained actions, VLA allows robotic control combining vision and language knowledge for better reasoning.

# Paper reading

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## RT-2: Vision-Language-Action Models Transfer Web Knowledge to Robotic Control

We study how vision-language models trained on Internet-scale data can be incorporated directly into end-to-end robotic control to boost generalization and enable emergent semantic reasoning. Our goal is to enable a single end-to-end trained model to both learn to map robot observations to actions and enjoy the benefits of large-scale pretraining on language and vision-language data from the web. To this end, we propose to co-fine-tune state-of-the-art vision-language models on both robotic trajectory data and Internet-scale vision-language tasks, such as visual question answering. In contrast to other approaches, we propose a simple, general recipe to achieve this goal: in order to fit both natural language responses and robotic actions into the same format, we express the actions as text tokens and incorporate them directly into the training set of the model in the same way as natural language tokens. We refer to such category of models as vision-language-action models (VLA) and instantiate an example of such a model, which we call RT-2. Our extensive evaluation (6k evaluation trials) shows that our approach leads to performant robotic policies and enables RT-2 to obtain a range of emergent capabilities from Internet-scale training. This includes significantly improved generalization to novel objects, the ability to interpret commands not present in the robot training data (such as placing an object onto a particular number or icon), and the ability to perform rudimentary reasoning in response to user commands (such as picking up the smallest or largest object, or the one closest to another object). We further show that incorporating chain of thought reasoning allows RT-2 to perform multi-stage semantic reasoning, for example figuring out which object to pick up for use as an improvised hammer (a rock), or which type of drink is best suited for someone who is tired (an energy drink) [Brohan et al., 2023].



# Paper reading

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Vision-Language Models for Vision Tasks: A Survey

Most visual recognition studies rely heavily on crowd-labelled data in deep neural networks (DNNs) training, and they usually train a DNN for each single visual recognition task, leading to a laborious and time-consuming visual recognition paradigm. To address the two challenges, Vision-Language Models (VLMs) have been intensively investigated recently, which learns rich vision-language correlation from web-scale image-text pairs that are almost infinitely available on the Internet and enables zero-shot predictions on various visual recognition tasks with a single VLM. This paper provides a systematic review of visual language models for various visual recognition tasks, including: (1) the background that introduces the development of visual recognition paradigms; (2) the foundations of VLM that summarize the widely-adopted network architectures, pre-training objectives, and downstream tasks; (3) the widely-adopted datasets in VLM pre-training and evaluations; (4) the review and categorization of existing VLM pre-training methods, VLM transfer learning methods, and VLM knowledge distillation methods; (5) the benchmarking, analysis and discussion of the reviewed methods; (6) several research challenges and potential research directions that could be pursued in the future VLM studies for visual recognition. [Zhang et al., 2024].

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

# Section 10. Other Types of Multimodalities

# Other Types of Multimodalities

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## The Five Senses Analogy

Sense	Data Modality	ML Example
Vision	Images/Video	CNNs, ViTs
Auditory	Audio/Waveforms	Spectrogram Transformers
Tactile	Pressure/Texture	Tactile Sensors in Robotics
Olfactory	Chemical Sensors	e-Nose Gas Detection
Gustatory	Molecular Data	Flavor Prediction Models

## Emerging Sensor Fusion

- LiDAR+RGB: Autonomous vehicles
- IMU+Vision: Human pose estimation
- Spectrograms+Text: Audio captioning

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Section 11. Meta-Learning

# Multimodal Optimization Challenges

CV-2025

A.Kornaev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

## Physics-Informed Neural Networks (PINNs)

$$\mathcal{L}_{\text{PINN}} = \underbrace{\lambda_d \|u_\theta(x_i) - u_i\|^2}_{\text{Data Loss}} + \underbrace{\lambda_p \|\mathcal{N}[u_\theta](x_j)\|^2}_{\text{Physics Loss}} + \underbrace{\lambda_r \|\theta\|^2}_{\text{Regularization}}$$

- Multi-objective: Data fitting + PDE residuals [Raissi et al., 2017]
- Loss landscape modality gaps cause training instabilities

## Multi-Task Tradeoffs

- Pareto optimality in joint losses
- Gradient conflict quantification:

$$\cos(\nabla_\theta \mathcal{L}_i, \nabla_\theta \mathcal{L}_j) < 0$$

- Solution: Uncertainty weighting [Kendall et al., 2018]

# Bibliography

## CV-2025

A.Kor-naev,  
K.Yakovlev

Recap: CLIP  
architecture  
and loss

Current state  
of VLMs

Optimization  
of VLMs

Fine-Tuning of  
LMs

Prospects

VLM +  
Control  
System =  
VLAM

Outcomes

Contrastive  
Language-  
Image

Jean-Baptiste et al. Alayrac. Flamingo: a visual language model for few-shot learning. **NeurIPS**, 2022.

Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Xi Chen, Krzysztof Choromanski, Tianli Ding, Danny Driess, Avinava Dubey, Chelsea Finn, Pete Florence, Chuyuan Fu, Montse Gonzalez Arenas, Keerthana Gopalakrishnan, Kehang Han, Karol Hausman, Alexander Herzog, Jasmine Hsu, Brian Ichter, Alex Irpan, Nikhil Joshi, Ryan Julian, Dmitry Kalashnikov, Yuheng Kuang, Isabel Leal, Lisa Lee, Tsang-Wei Edward Lee, Sergey Levine, Yao Lu, Henryk Michalewski, Igor Mordatch, Karl Pertsch, Kanishka Rao, Krista Reymann, Michael Ryoo, Grecia Salazar, Pannag Sanketi, Pierre Sermanet, Jaspiar Singh, Anikait Singh, Radu Soricut, Huong Tran, Vincent Vanhoucke, Quan Vuong, Ayzaan Wahid, Stefan Welker, Paul Wohlhart, Jialin Wu, Fei Xia, Ted Xiao, Peng Xu, Sichun Xu, Tianhe Yu, and Brianna Zitkovich. Rt-2: Vision-language-action models transfer web knowledge to robotic control, 2023. URL <https://arxiv.org/abs/2307.15818>.

Danny et al. Driess. Palm-e: An embodied multimodal language model. **ICML**, 2023.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL <https://arxiv.org/abs/2106.09685>.

Alex Kendall, Yarin Gal, and Roberto Cipolla. Multi-task learning using uncertainty to weigh losses for scene geometry and semantics. In **Proceedings of the IEEE conference on computer vision and pattern recognition**, pages 7482–7491, 2018.

Junnan et al. Li. Blip-2: Bootstrapping vision-language pre-training with frozen image encoders and llms. **arXiv:2301.12597**, 2023.

Haotian et al. Liu. Visual instruction tuning. **NeurIPS**, 2023.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision, 2021. URL <https://arxiv.org/abs/2103.00020>.

Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Physics informed deep learning (part i): Data-driven solutions of nonlinear partial differential equations, 2017. URL <https://arxiv.org/abs/1711.10561>.

Jingyi Zhang, Jiaying Huang, Sheng Jin, and Shijian Lu. Vision-language models for vision tasks: A survey, 2024. URL <https://arxiv.org/abs/2304.00685>.