Development of an Optical Tracking System for Real-time Robotic Applications

Shannon Pitman

Author: Shannon Pitman
Supervisor: Arnold Pretorius
Date: September 2025

MechatronicsSystems.Group
Department of Mechanical Engineering
University of Cape Town

Submitted in partial fulfilment of the requirements for the degree of
°

Abstract

Engineering students often need a clear, practical model for writing dissertations; this document provides an overview tailored to final-year mechatronics projects and demonstrates effective use of a LaTeX thesis template. Many student reports lack consistent structure, rigorous scoping, and appropriate use of figures, tables, code listings, and citations, which impedes readability and assessment.

This work contributes an exemplar that explains what each report section should contain, offers typical subheadings, and embeds working examples of template elements to copy and adapt. The document is implemented in XeLaTeX using the `memoir` class with chapters for Introduction, Literature Review, Methodology, Results, Discussion, Conclusions, Recommendations, and Appendices, along with acronyms and bibliography support; the result is a shareable guide that doubles as a starting point for students to produce professional, evidence-based engineering reports.

How to write an abstract in 5 minutes?

Answer the following questions in narrative form with no more than two sentences per question:

- *What is the background to the project?*
- *What is the problem that is being solved?*
- *What is the contribution of the project to this problem?*
- *What is the main conclusion of the project?*

Contents

List of Figures **v**

List of Tables **vi**

Acronyms **vii**

1 Introduction **1**
1.1 Background and Motivation 1
1.2 Context and Related Work 1
1.3 Aims, Objectives and Contributions 1
1.4 Project Scope and Limitations 1
1.5 Report Outline 1

2 Literature Review **2**
2.1 Introduction 2
2.2 Overview of Motion Capture 2
2.3 Survey of Optical Motion Capture 2
2.4 Applications of Optical Motion Capture 2
2.5 Limitations of Existing Approaches 2
2.6 Summary 2

3 System Specifications **3**
3.1 Introduction 3
3.2 Overall System Architecture 3
3.3 OCP Subsystem Requirements 3
3.3.1 Performance Requirements 3
3.3.2 Functional Requirements 3
3.4 OMC Subsystem Requirements 3
3.4.1 Performance Requirements 3
3.4.2 Functional Requirements 3
3.5 Constraints and Assumptions 3

4 Optical Motion Capture **4**
4.1 Literature Review 4
4.1.1 Estimation Algorithms 4
4.1.2 Hardware Considerations for Camera-Based Sensing 4
4.2 Camera Selection and System Integration 4

4.3 Theory Development 4
4.3.1 Rigid-body Motion 4
4.3.2 Image Acquisition and Formation 4
4.3.3 Camera Calibration 5
4.3.4 Image Processing 5
4.3.5 Triangulation 5
4.3.6 State Estimation 5
4.4 Tracking Algorithm Design 5
4.4.1 Software Architecture 5
4.5 Implementation 5
4.5.1 Calibration Procedure 5
4.5.2 Graphical User Interface 5
4.6 Experimental Testing Setup 5
4.6.1 Physical Configuration 5
4.6.2 Reference System and Ground Truth 5
4.6.3 Test Trajectories 5
4.6.4 Data Acquisition and Processing Pipeline 5
4.7 Results and Discussion 6
4.7.1 Calibration Accuracy 6
4.7.2 Static Localisation Performance 6
4.7.3 Dynamic Tracking Performance 6
4.7.4 Filter Comparison 6
4.7.5 Real-time Performance 6
4.7.6 System Limitations and Failure Analysis 6

5 Optimal Camera Placement 7
5.1 Literature Review 8
5.1.1 Background of OCP 8
5.1.2 Motivation for Optimal Placement 8
5.1.3 Optimisation Approaches for Sensor Placement 9
5.1.4 Modelling the Problem 10
5.1.5 Summary 10
5.2 Theoretical Framework 11
5.2.1 Genetic Algorithm Terminology 11
5.2.2 Encoding Schemes 12
5.2.3 Selection Methods 12
5.2.4 Crossover Techniques 12
5.2.5 Convergence Analysis 12
5.3 Methodology 12
5.3.1 Algorithm Configuration 12
5.3.2 Cost Function 12
5.3.3 Termination Criteria 12
5.4 Results and Discussion 12
5.4.1 Convergence Behaviour 12
5.4.2 Cost Function Evaluation 12
5.4.3 Parameter Sensitivity Analysis 12
5.4.4 Optimal Placement Configurations 12

5.4.5 System Limitations 12

6 Conclusion and Future Work **13**
6.1 Summary of Contributions 13
6.2 Key Findings 13
6.3 Limitations 13
6.4 Recommendations for Future Work 13

References **14**

List of Figures

List of Tables

5.1 Comparison of biological and genetic algorithm terminology. 11

Acronyms

AGP Art Gallery Problem 8, 10

DNA deoxyribonucleic acid 11

FOV Field of View 8

MoCap Motion Capture 10

NP-hard Non-deterministic Polynomial-time hard 7

OCP Optimal Camera Placement 7, 8

PSO Particle Swarm Optimisation 7

Introduction 1

1.1 Background and Motivation

1.2 Context and Related Work

1.3 Aims, Objectives and Contributions

1.4 Project Scope and Limitations

1.5 Report Outline

Literature Review 2

2.1 Introduction

2.2 Overview of Motion Capture

2.3 Survey of Optical Motion Capture

2.4 Applications of Optical Motion Capture

2.5 Limitations of Existing Approaches

2.6 Summary

System Specifications 3

3.1 Introduction

3.2 Overall System Architecture

Block Diagram

3.3 OCP Subsystem Requirements

3.3.1 Performance Requirements

3.3.2 Functional Requirements

3.4 OMC Subsystem Requirements

3.4.1 Performance Requirements

3.4.2 Functional Requirements

3.5 Constraints and Assumptions

Optical Motion Capture 4

4.1 Literature Review

4.1.1 Estimation Algorithms

4.1.2 Hardware Considerations for Camera-Based Sensing

4.1.2.1 Camera Capabilities

Resolution, latency, iframe rate, microcontroller...

4.1.2.2 Communication Architectures

Wired vs wireless: PoE, Wi-Fi, Bluetooth Synchronous vs Asynchronous

4.2 Camera Selection and System Integration

4.3 Theory Development

4.3.1 Rigid-body Motion

4.3.1.1 Reference Frames

4.3.1.2 Representing Pose

4.3.2 Image Acquisition and Formation

Computer vision, light and colour, image formation

4.3.2.1 Colour Spaces

4.3.2.2 Camera Model and Projection

4.3.3 Camera Calibration

4.3.4 Image Processing

4.3.4.1 Marker Design and Detection

4.3.5 Triangulation

4.3.6 State Estimation

4.3.6.1 The Kalman Filter

4.3.6.2 The Extended Kalman Filter

4.3.6.3 The Invariant Extended Kalman Filter

4.3.6.4 The Two-Frames Group In-EKF

4.4 Tracking Algorithm Design

4.4.1 Software Architecture

4.5 Implementation

4.5.1 Calibration Procedure

4.5.2 Graphical User Interface

4.6 Experimental Testing Setup

4.6.1 Physical Configuration

4.6.2 Reference System and Ground Truth

4.6.2.1 Spatial and Temporal Alignment

How the system's coordinate frame was aligned with OptiTRack - will camera be in their optimised position versus OptiTrack's ad hoc arrangement? How the two data streams would be temporarily aligned

4.6.3 Test Trajectories

4.6.4 Data Acquisition and Processing Pipeline

flow chart

4.7 Results and Discussion

4.7.1 Calibration Accuracy

4.7.2 Static Localisation Performance

4.7.3 Dynamic Tracking Performance

4.7.4 Filter Comparison

4.7.5 Real-time Performance

4.7.6 System Limitations and Failure Analysis

Optimal Camera Placement 5

The quality of a multi-camera localisation system is determined as much by the geometric arrangement as by hardware. Sensor noise, calibration accuracy, and algorithmic performance all matter; yet even a perfectly calibrated, high-quality camera system running a sophisticated algorithm can still fail to localise the target if its cameras are arranged poorly. Determining the Optimal Camera Placement (OCP) requires both a model of how error arises and subsequently propagates, and an effective optimsation formulation that is capable of navigating a large search space timeously.

When the sensor placement is suboptimal, the inaccuracy tends to compound in two ways. The first results from the geometric measurement uncertainty. Cameras discretise their worldview into pixels; the target is projected onto a finite grid of pixels, and its position is inferred from this quantised image (as explained in 4.3.2.2). The further a target is from a camera, the fewer pixels it subtends, reducing the spatial resolution and increasing the resulting position estimate's variance. Moreover, when two cameras observe a target from nearly parallel viewing angles, small pixel-level uncertainties preclude triangulation [1]. The resulting depth estimate becomes ill-conditioned, degrading the tracking prediction. Hence, in these avoidable configurations, the limitation of the tracking system is not the sensor itself but the geometry.

The second degrading source is visibility loss. Intuitively a camera cannot measure what it cannot see. Occlusion, whether caused by invariant static obstacles in the environment or dynamically occurring by the target itself reduce the number of measurements [2]. Similarly, limited coverage may result in area's being unobserved. Therefore, it may be necessary to optimise for an arrangement that rewards redundant views whilst still ensuring that most of the flight space is observable [3]. Thus, the arrangement of the sensors can exacerbate localisation error beyond the intrinsic noise characteristics of the cameras themselves.

Optimising placement, however, is combinatorially explosive, and classified as Non-deterministic Polynomial-time hard (NP-hard) [4]. As the number of inputs (camera, candidate placements, and workspace size) grow, the number of possible configurations grows exponentially; consequently, an exhaustive search becomes intractable. In this context, NP-hard denotes that the problem becomes increasingly computationally challenging to find a guaranteed global solution with a multitude of inputs. The literature suggests that heuristic- or metaheauristic-based algorithms, such as genetic algorithms, greedy methods, or Particle Swarm Optimisation (PSO) approaches, are adopted because of their proficiency in exploring large, unsmooth, multi-objective search spaces efficiently [Citation needed]. Alternatives, like integer

and mixed-integer programming attempt to find globally optimal solutions but under more heavily imposed constraints. Therefore, each optimisation technique reflects a tradeoff between optimality guarantees, scalability, efficiency and modelling fidelity.

5.1 Literature Review

Optimising camera placement is not optional; it should be a prerequisite for accurate tracking. This section reviews the literature on the OCP problem. First, the optimisation strategies employed to search the ill-defined, non-convex search space in sufficiently good time are examined. Second, an examination of how the sources of measurement uncertainty, quantisation, triangulation geometry, and occlusion, have been characterized and modelled is provided. Together, this provides the state of the art in designing geometrically valid and computationally reasonable multi-camera tracking systems.

5.1.1 Background of OCP

OCP descends from the well-studied Art Gallery Problem (AGP), which established the combinatorial foundations of visibility-based sensor placement but was formulated under idealised assumptions which is too limiting for physical sensors. The AGP found the minimum number of omnidirectional guards required to observe an entire 2D polygon with n vertices. Fisk proved, via triangulation and 3-colouring, that $\lfloor \frac{n}{3} \rfloor$ guards are always sufficient for covering any simple polygon, as demonstrated in Figure The AGP usefulness is bounded by its assumptions: where guard are endowed with unlimited sensing range for 360 $\circ$ Field of View (FOV), and perfect visibility. Real cameras violate these assumptions; where physical sensors have a limited range of marker detection and resolution that degrades with distance, a finite FOV, and the target's may be occluded during observation. [Look into this paper: O'Rourke (1987) Art Gallery Theorems and Algorithms AGP complexity is NP-hard->OCP is also NP-hard]

(maybe make this part of the caption: In this example, a polygon with $n = 13$ vertices is first triangulated, then each vertex is assigned one of three colours such that no triangle shares two vertices of the same colour; placing guards at all vertices of the least frequent colour guarantees complete coverage.)

Therefore, although the OCP inherits the NP-hard combinatorial structure of the AGP it is necessary for the optimisation to account for the sensor's limitations, favour double coverage for triangulation, and to quantify the observational quality spatially rather than described as a binary visibility test.

5.1.2 Motivation for Optimal Placement

These constraints are motivated by diverse applications, such as: surveillance and monitoring [5], motion capture [3, 6], augmented and virtual reality [2], and autonomous driving [7]. In such visual sensor networks, accurate localisation requires that each marker or feature be visible to at least two cameras, enabling 3D position recovery through triangulation [3, 6]. Most papers emphasise that sensor placement

(including amount, location, orientation, and arrangement to the other sensors in the network) significantly affects system coverage and tracking performance [8]. However, the OCP is NP-hard and combinatorial; this means that the search space grows explosively with the number of candidate positions and orientations, rendering exhaustive search intractable. Consequently, most investigators resort to heuristic-based approximation algorithms as they offer a practical path to reach acceptable solutions within reasonable computation time.

Generally, the OCP can be stated as follows: given a set of candidate camera locations and orientations, find the configuration that maximises 3D reconstruction quality of a target within a defined workspace, subject to practical constraints such as mounting options and budget. Solving this problem requires balancing trade-offs among coverage, accuracy, and computational efficiency. Without the aid of an optimisation algorithm, the sensors are arranged in an ad-hoc configuration by the designer, which requires expertise or trial and error, which can be time-consuming or sacrificial if a sub-par arrangement is settled on with no mathematical quantitative guidance. Thus, the resulting localisation error is neither calculated nor considered mathematically. Here lies the need to optimise the camera network based on metrics that minimise degrading effects like resolution uncertainty and probabilistic occlusion even if the trajectory of the target is not known exactly beforehand.

5.1.3 Optimisation Approaches for Sensor Placement

Recent research has diverged into avenues of how to formulate the problem, when to conclude that an optimal solution has been found, and what consitutes success as a benchmark. Two primary classes of optimisation methods have emerged: heuristic algorithms and integer programming. The problem formulation typically depends of defining a specific objective function, sensor model, and workspace representation. Eventhough the search space is continuous it is typical of designers to discretise both the workspace and the possible camera locations to make the problem more computable. Depending on the application, available resources, and workspace constraints, different optimisation objectives have been prioritised in the literature. Broadly, these can be categorised into coverage-based objectives and accuracy-based objectives. In terms of coverage-based objectives, the goal is to maximise the visible area of the workspace, and sometimes going further to handle aspects of occlusion both static and dynamic and hence usually ensuring a two-cover coverage. This is particularly relevant in surveillance applications where ensuring that all regions are monitored is critical [5]. Conversely, accuracy-based objectives focus on minimising localisation error, which is crucial in motion capture and augmented reality applications where precise tracking is required and more than one camera arranged sufficiently non-parallel is needed to ensure triangulation is possible [2, 3]. Wu, Sharma, and Huang proposed another accuracy-based metric of placement which assessed how the limited camera intrinsics and quantisation lead to inaccurate measurements exacerbated by the placement of two cameras [1]. Many studies have proposed hybrid objectives that balance the trade-off of accuracy with coverage [6, 8]. Some works have also considered additional constraints such as budget limits and physical mounting options [3, 7, 9].

5.1.3.1 Optimisation Objectives

The configuration quality for 3D marker tracking and trinagulation is mostly affected by two main sources of error: marker visibility and triangulation accuracy. In terms of the application being Motion Capture (MoCap), a marker should not be occluded by any obstacle, including itself, the marker must be within the cameras field of view, vissible given the camera's resolution and range of capture. These are necessary to ensure consistent and continual tracking. Furthermore, at least two cameras should be arranged sufficiently non-parallel so that triangulation is well-conditioned. Sometimes, the easy answer is just to throw more cameras at the problem as that does give redundant views and ensures we can place camera pairs to cover the scene in a sufficently non-parallel format but in most research situationships, it is not prudent to over-exhaust the budget and hence it may be a desirable goal to asses the least amount of cameras required to achieve a level of accuracy/ coverage to minimise cost.

Provided below is a summary table of the different optimisation qualities found across papers in the literature (insert table with rows indication paper citation and application and columns of optimsation objectives)

5.1.4 Modelling the Problem

As mentioned earlier due to the large search space which is made so large becaus ethe problem is combinatorial (meaning additonal combinations of different aspects like position and roientation of each camera) which is NP-hard and increases expeonently with each additonal sensor added to the network it becomes necessary to make some simplifications as an exhaustive search especially for a room-sized scale search simply becomes intractable and computationally inefficent. This is often why the search-space is dicsretised both in the flight-space arena and in the possible mounting locations of the camera.

5.1.5 Summary

The measurement uncertainty attributed to the spatial relationship between the target and the cameras can be modelled based on the distance between the target and camera which can excerbated pixel resolution and the orientation between camera's view vectors where the increasingly more parallel these vectors are results in ill-conditioned triangulation geometry, culminating in poor pose estimates and hence poor tracking

As seen there have been a plethora of proposed methodologies for optimising camera placement in the literature which are summarised in the timeline below where they have been broadly categorised as heuristic optimisation or binary integer programming and their objectives have also been listed based on thematic colour rings indicated in the key.

The optimal camera placement problem extends the AGP foundation by introducing constraints that reflect the true capabilities and limitations of physical sensors.

5.2 Theoretical Framework

5.2.1 Genetic Algorithm Terminology

The language used to describe genetic algorithms borrows heavily from evolutionary biology. Table 5.1 defines these terms in both domains to clarify the analogy and establish consistent vocabulary for the sections that follow.

Table 5.1: Comparison of biological and genetic algorithm terminology.

Term	Biological Meaning	Genetic Algorithm Meaning
Chromosome	A structure of DNA carrying genetic information	A complete candidate solution encoded in some representation, e.g bit strings
Gene	A unit of heredity determining a specific trait	A single element or parameter within the candidate solution, e.g a bit
Population	A group of interbreeding individuals of the same species	The set of candidate solutions existing at a given iteration
Fitness	An organism's ability to survive and reproduce in its environment	An objective function quantifying how well a candidate solution achieves the desired goal
Generation	All individuals born and living at approximately the same time	One complete iteration of the algorithm producing a new population
Selection	Differential survival and reproduction due to heritable trait variation	An operator that chooses higher-performing individuals to serve as parents
Crossover	Exchange of genetic material between homologous chromosomes during meiosis	An operator that combines portions of two parent solutions to create offspring
Mutation	A random, heritable change in genetic sequence, ususally caused by a erroneous DNA replication	An operator that randomly perturbs one or more genes in a solution

This biological analogy provides useful intuition: just as natural selection refines a species over generations by favouring advantageous traits, genetic algorithms iteratively improve a population of solutions by favouring those with higher fitness. While genetic algorithms lack the biological complexity of true evolution, they do provide a productive conceptual framework. The effectiveness of this process depends on how solutions are represented, this is often reffered to as the encoding.

5.2.2 Encoding Schemes

5.2.3 Selection Methods

5.2.4 Crossover Techniques

5.2.5 Convergence Analysis

5.3 Methodology

5.3.1 Algorithm Configuration

5.3.1.1 Parameter Selection

5.3.1.2 Initial Population

5.3.1.3 Tournament Selection

5.3.1.4 Double Point Crossover

5.3.1.5 Mutation

5.3.1.6 Elitism

5.3.2 Cost Function

5.3.2.1 Resolution Uncertainty Cost Function

5.3.2.2 Dynamic Occlusion Cost Function

5.3.2.3 Combined Cost Function

5.3.3 Termination Criteria

5.4 Results and Discussion

5.4.1 Convergence Behaviour

5.4.2 Cost Function Evaluation

5.4.3 Parameter Sensitivity Analysis

5.4.4 Optimal Placement Configurations

Different Modalities Random Placement, ad hoc placement

5.4.5 System Limitations

?

Conclusion and Future Work 6

6.1 Summary of Contributions

6.2 Key Findings

6.3 Limitations

includes scope constraints outlined in intro

6.4 Recommendations for Future Work

closed-loop robotic control Benchmark GA against other metaheuristic like PSO or SA to see if better solutions existan assess convergence performance

References

[1] R. Sharma, 'Analysis of uncertainty bounds due to quantization for three-dimensional position estimation using multiple cameras,' *Optical Engineering*, vol. 37, no. 1, p. 280, Jan. 1998, ISSN: 0091-3286. DOI: 10.1117/1.601615. Accessed: 22nd Aug. 2025.

[2] P. Rahimian and J. K. Kearney, 'Optimal Camera Placement for Motion Capture Systems,' *IEEE Transactions on Visualization and Computer Graphics*, vol. 23, no. 3, pp. 1209–1221, Mar. 2017, ISSN: 1941-0506. DOI: 10.1109/TVCG.2016.2637334. Accessed: 30th Jun. 2025.

[3] A. Aissaoui, A. Ouafi, P. Pudlo, C. Gillet, Z.-E. Baarir and A. Taleb-Ahmed, 'Designing a camera placement assistance system for human motion capture based on a guided genetic algorithm,' *Virtual Reality*, vol. 22, no. 1, pp. 13–23, Mar. 2018, ISSN: 1434-9957. DOI: 10.1007/s10055-017-0310-7. Accessed: 9th Jul. 2025.

[4] N. Kirchhof, 'Optimal placement of multiple sensors for localization applications,' in *International Conference on Indoor Positioning and Indoor Navigation*, Oct. 2013, pp. 1–10. DOI: 10.1109/IPIN.2013.6817862. Accessed: 14th Aug. 2025.

[5] R. Bodor, A. Drenner, P. Schrater and N. Papanikolopoulos, 'Optimal Camera Placement for Automated Surveillance Tasks,' *Journal of Intelligent and Robotic Systems*, vol. 50, no. 3, pp. 257–295, Oct. 2007, ISSN: 0921-0296, 1573-0409. DOI: 10.1007/s10846-007-9164-7. Accessed: 12th Aug. 2025.

[6] J. Ziegler, H. Gattringer and A. Müller, 'Optimal Camera Placement for Maximized Motion Capture Volume and Marker Visibility,' in *Advances in Service and Industrial Robotics*, T. Petrič, A. Ude and L. Žlajpah, Eds., Cham: Springer Nature Switzerland, 2023, pp. 45–52, ISBN: 978-3-031-32606-6. DOI: 10.1007/978-3-031-32606-6_6.

[7] V. A. Puligandla and S. Lončarić, 'A Multiresolution Approach for Large Real-World Camera Placement Optimization Problems,' *IEEE Access*, vol. 10, pp. 61 601–61 616, 2022, ISSN: 2169-3536. DOI: 10.1109/ACCESS.2022.3176817. Accessed: 14th Aug. 2025.

[8] J. Zhou, H. Deng, Z. Zhao, Y. Zou and X. Wang, *Sensor Placement Optimization of Visual Sensor Networks for Target Tracking Based on Multi-Objective Constraints*, https://www.mdpi.com/2076-3417/14/5/1722, Feb. 2024. Accessed: 14th Aug. 2025.

[9] X. Dai, 'Optimal Camera Configuration for Large-Scale Motion Capture Systems,'