

Actuators



Electric Linear Actuator	
Specification	Value
Voltage	12V / 24V DC
Power Output	50 W
Continuous Current	3A
Max Load / Force	2500N
Speed Range	5–100 mm/s
Stroke Length	20–1000 mm (Customizable)
Motor Type	Brush DC, Permanent Magnet
Rated RPM	4000 RPM
Duty Cycle	10%
IP Rating	IP67 (Waterproof)
End Limit	Built-in Limit Switches
Feedback Option	No Feedback / Hall Sensor
Mounting	Flange Mount
Frame Size	32 mm



Electric Linear Actuator	
Specification	Value
Voltage	DC 12V / 24V
Power Output	100 W
Continuous Current	5.5A / 20A
Max Load / Force	12,000N
Speed Range	6.5–38 mm/s
Stroke Length	20–1000 mm
Motor Type	Brush DC, Permanent Magnet
Rated RPM	Not Specified (Gear Motor)
Duty Cycle	10% (Max 2 min ON, 18 min OFF)
IP Rating	IP65 (Waterproof)
End Limit	Built-in Limit Switches
Feedback Option	Not Available / Not Specified
Mounting	Flange Mount
Frame Size	32 mm



3 Stages Telescopic Linear Actuator	
Specification	Value
Voltage	DC 12V / 24V
Power Output	50 W
Continuous Current	Custom (Not specified)
Max Load / Force	750–2000N (75–200 kg / 165–440 lbs)
Speed Range	5–42 mm/s (0.2"–1.68"/s)
Stroke Length	20–1000 mm (0.8"–40")
Motor Type	Brush DC, Permanent Magnet (Gear Motor)
Rated RPM	Custom (Not specified)
Duty Cycle	25% (Max 2 min ON, 18 min rest)
IP Rating	IP43 / IP54 / IP65 (Customizable)
End Limit	Built-in Limit Switch
Feedback Option	Limit Switch / Hall Effect (Hall Sensor)
Mounting	Flange Mount
Frame Size	32 mm



Heavy Duty Electric Linear Actuator	
Specification	Value
Voltage	DC 12V / 24V
Power Output	50 W
Continuous Current	3A
Max Load / Force	1200N (120 kg)
Speed Range	3–40 mm/s (Rated speed: 40 mm/s)
Stroke Length	25 mm or Customized
Motor Type	Brush DC, Permanent Magnet
Rated RPM	300 RPM
Duty Cycle	10%
IP Rating	IP68 (Waterproof)
End Limit	Built-in Dual Limit Switches
Feedback Option	Not specified / No sensor listed
Mounting	Flange Mount
Frame Size	32 mm

The motor can be designed &manufactured with customized request.

Actuators



Heavy Duty Solar Panels Linear Actuator High Torque	
Specification	Value
Voltage	12V / 24V / 36V / 48V DC
Continuous Current	0.9A / 6.5A
Max Load / Force	24,000N
Speed Range	2 mm/s
Stroke Length	100–1000 mm
Retracted Length	Stroke + 309 mm
Motor Type	Brush DC, Permanent Magnet
Duty Cycle	10% (2 min ON, 18 min OFF)
IP Rating	IP66
End Limit	Built-in Limit Switch
Inner Tube Material	Stainless Steel



Hospital Medical Bed Electric Actuator	
Specification	Value
Voltage	12V DC / 24V DC
Power Output	100 W
Continuous Current	4.5A / 9A
Max Load / Force	6000N
Speed Range	5–40 mm/s
Stroke Length	20–1000 mm
Motor Type	Gear Motor, Brush, Permanent Magnet
Rated RPM	4200 RPM
Duty Cycle	25% (2 min ON / 18 min Rest)
IP Rating	IP66
End Limit	Built-in Limit Switch
Feedback Option	–
Mounting	Panel Mount
Frame Size	32 mm



High Quality Linear Actuator Motor	
Specification	Value
Voltage	12V / 24V / 36V / 48V DC
Power Output	50 W
Continuous Current	3A
Max Load / Force	900N (≈ 90 kg / 198 lbs)
Speed Range	5 mm/s or 90 mm/s (Customizable)
Stroke Length	25 mm (Customizable)
Motor Type	Brush Motor, Permanent Magnet
Rated RPM	4000 RPM
Duty Cycle	10%
IP Rating	Waterproof
End Limit	Built-in Limit Switch
Feedback Option	Available (Signal Feedback Options)
Mounting	Flange Mount
Frame Size	32 mm

The motor can be designed &manufactured with customized request.