


Turnout — spatial clusters

local Moran's I, delegation level · Benjamini-Hochberg $q = 0.05$

- LISA class
- high turnout among high — HH (0)
 - low among low — LL (10)
 - high among low — HL (1)
 - not significant (248)
 - below the coverage floor (5)

259 mapped units



Global Moran's $I = +0.451$ ($p < 0.0001$, 9,999 permutations), so turnout is clustered in space beyond chance — but less strongly than vote choice: the candidates' shares run $+0.556/+0.552/+0.375$ at delegation level and $+0.599/+0.591/+0.399$ at imada, against $+0.451$ here, and the gap widens at the finer level. Whom people voted for is more spatially organised than whether they voted at all. The map localises that: a class is assigned only where a unit's own neighbourhood beats 9,999 random ones, after correction across all 259 units (threshold applied: $p \leq 0.0017$); 43 reach an uncorrected $p \leq 0.05$.

5 unit(s) are excluded entirely for thin coverage, so they contribute no value and no neighbourhood. 2 island group(s) are bridged to the mainland by their shortest link.

The registered count is the only field in this dataset that no identity on the form checks — the one field read by classifier alone — so turnout is a certified numerator over an uncertified denominator, and is weaker evidence than any candidate figure mapped elsewhere in this directory.

Source: ISIE procès-verbaux · boundaries OCHA/HDX COD-AB (CC BY-IGO) · turnout is voters over registered, on the stations where both figures survived the read