




# Reinforcement Learning 2

Sutton and Barto, Chapter 6.1, 6.2, 6.5  
AIMA Chapter 21

Slides courtesy of Dan Klein and Pieter Abbeel  
University of California, Berkeley



# Reinforcement Learning 2



Slides courtesy of Dan Klein and Pieter Abbeel – University of California, Berkeley


[These slides were created by Dan Klein and Pieter Abbeel for CS188 Intro to AI at UC Berkeley. All CS188 materials are available at <http://ai.berkeley.edu>.]

# Review: Reinforcement Learning


- We still assume an MDP:
  - A set of states  $s \in S$
  - A set of actions (per state)  $A$
  - A model  $T(s,a,s')$
  - A reward function  $R(s,a,s')$
- Still looking for a policy  $\pi(s)$
- New twist: don't know  $T$  or  $R$ , so must try out actions
- Big idea: Compute all averages over  $T$  using sample outcomes




# Review: Model-Free Learning




# Review: Passive Reinforcement Learning



# Review: Passive Reinforcement Learning

- **Simplified task: policy evaluation**
    - Input: a fixed policy  $\pi(s)$
    - You don't know the transitions  $T(s,a,s')$
    - You don't know the rewards  $R(s,a,s')$
    - **Goal: learn the state values**
  - **In this case:**
    - Learner is “along for the ride”
    - No choice about what actions to take
    - Just execute the policy and learn from experience
    - This is NOT offline planning! You actually take actions in the world.
- 




# Review: Direct Evaluation

- Goal: Compute values for each state under  $\pi$
- Idea: Average together observed sample values
  - Act according to  $\pi$
  - Every time you visit a state, write down what the sum of discounted rewards turned out to be
  - Average those samples
- This is called direct evaluation



# Review: Example: Direct Evaluation

Input Policy  $\pi$



Assume:  $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 2

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 3

E, north, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 4

E, north, C, -1  
C, east, A, -1  
A, exit, x, -10

Output Values

	-10 A	
+8 B	+4 C	+10 D
	-2 E	



# Review: Problems with Direct Evaluation

- What's good about direct evaluation?
  - It's easy to understand
  - It doesn't require any knowledge of  $T$ ,  $R$
  - It eventually computes the correct average values, using just sample transitions
- What bad about it?
  - It wastes information about state connections
  - Each state must be learned separately
  - So, it takes a long time to learn

## Output Values

	-10 A	
+8 B	+4 C	+10 D
	-2 E	

*If B and E both go to C under this policy, how can their values be different?*


# Review: Why Not Use Policy Evaluation Instead?

- Simplified Bellman updates calculate  $V$  for a fixed policy:

- Each round, replace  $V$  with a one-step-look-ahead layer over  $V$

$$V_0^\pi(s) = 0$$

$$V_{k+1}^\pi(s) \leftarrow \sum_{s'} T(s, \pi(s), s') [R(s, \pi(s), s') + \gamma V_k^\pi(s')]$$



- This approach fully exploited the connections between the states
  - Unfortunately, we need  $T$  and  $R$  to do it!
- Key question: how can we do this update to  $V$  without knowing  $T$  and  $R$ ?
    - In other words, how to we take a weighted average without knowing the weights?


# Review: Temporal Difference Learning

- Big idea: learn from every experience!

- Update  $V(s)$  each time we experience a transition  $(s, a, s', r)$
- Likely outcomes  $s'$  will contribute updates more often

- Temporal difference learning of values

- Policy still fixed, still doing evaluation!
- Move values toward value of whatever successor occurs: running average



Sample of  $V(s)$ :  $sample = R(s, \pi(s), s') + \gamma V^\pi(s')$

Update to  $V(s)$ :  $V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + (\alpha)sample$

Same update:  $V^\pi(s) \leftarrow V^\pi(s) + \alpha(sample - V^\pi(s))$

# Review: Exponential Moving Average

- Exponential moving average

- The running interpolation update:  $\bar{x}_n = (1 - \alpha) \cdot \bar{x}_{n-1} + \alpha \cdot x_n$

- Makes recent samples more important:

$$\bar{x}_n = \frac{x_n + (1 - \alpha) \cdot x_{n-1} + (1 - \alpha)^2 \cdot x_{n-2} + \dots}{1 + (1 - \alpha) + (1 - \alpha)^2 + \dots}$$

- Forgets about the past (distant past values were wrong anyway)

- Decreasing learning rate (alpha) can give converging averages

# Example: Temporal Difference Learning

States

	A	
B	C	D
	E	

Assume:  $\gamma = 1$ ,  $\alpha = 1/2$

Observed Transitions

B, east, C, -2

	0	
0	0	8
	0	

C, east, D, -2

	0	
-1	0	8
	0	

	0	
-1	3	8
	0	

$$V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + \alpha [R(s, \pi(s), s') + \gamma V^\pi(s')]$$


# Review: Problems with TD Value Learning

- TD value learning is a model-free way to do policy evaluation, mimicking Bellman updates with running sample averages
- However, if we want to turn values into a (new) policy, we're sunk:

$$\pi(s) = \arg \max_a Q(s, a)$$



$$Q(s, a) = \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V(s')]$$

- Idea: learn Q-values, not values
- Makes action selection model-free too!




# Active Reinforcement Learning

---



# Active Reinforcement Learning

- Full reinforcement learning: optimal policies (like value iteration)
  - You don't know the transitions  $T(s,a,s')$
  - You don't know the rewards  $R(s,a,s')$
  - You choose the actions now
  - Goal: learn the optimal policy / values
- In this case:
  - Learner makes choices!
  - Fundamental tradeoff: exploration vs. exploitation
  - This is NOT offline planning! You actually take actions in the world and find out what happens...





# Q-Learning

- Q-Learning: sample-based Q-value iteration

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') \left[ R(s, a, s') + \gamma \max_{a'} Q_k(s', a') \right]$$


- Learn  $Q(s,a)$  values as you go

- Receive a sample  $(s,a,s',r)$
- Consider your old estimate:  $Q(s, a)$
- Consider your new sample estimate:

$$sample = R(s, a, s') + \gamma \max_{a'} Q(s', a')$$


- Incorporate the new estimate into a running average:

$$Q(s, a) \leftarrow (1 - \alpha)Q(s, a) + (\alpha) [sample]$$



# Q-Learning Properties

- Amazing result: Q-learning converges to optimal policy -- even if you're acting suboptimally!
- This is called **off-policy learning**
- Caveats:
  - You have to explore enough
  - You have to eventually make the learning rate small enough
  - ... but not decrease it too quickly
  - Basically, in the limit, it doesn't matter how you select actions (!)



# Review: Reinforcement Learning

- We still assume an MDP:
  - A set of states  $s \in S$
  - A set of actions (per state)  $A$
  - A model  $T(s,a,s')$
  - A reward function  $R(s,a,s')$
- Still looking for a policy  $\pi(s)$
- New twist: don't know  $T$  or  $R$ , so must try out actions
- Big idea: Compute all averages over  $T$  using sample outcomes



# The Story So Far: MDPs and RL

## Known MDP: Offline Solution

### Goal

Compute  $V^*$ ,  $Q^*$ ,  $\pi^*$

Evaluate a fixed policy  $\pi$

### Technique

Value / policy iteration

Policy evaluation

## Unknown MDP: Model-Based

### Goal

Compute  $V^*$ ,  $Q^*$ ,  $\pi^*$

Evaluate a fixed policy  $\pi$

### Technique

VI/PI on approx. MDP

PE on approx. MDP

## Unknown MDP: Model-Free

### Goal

Compute  $V^*$ ,  $Q^*$ ,  $\pi^*$

Evaluate a fixed policy  $\pi$

### Technique

Q-learning

Value Learning


# Model-Free Learning

- Model-free (temporal difference) learning

- Experience world through episodes

$$(s, a, r, s', a', r', s'', a'', r'', s'''' \dots)$$

- Update estimates each transition  $(s, a, r, s')$
- Over time, updates will mimic Bellman updates



# Q-Learning

- We'd like to do Q-value updates to each Q-state:

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') \left[ R(s, a, s') + \gamma \max_{a'} Q_k(s', a') \right]$$

- But can't compute this update without knowing T, R

- Instead, compute average as we go

- Receive a sample transition (s,a,r,s')
- This sample suggests


$$Q(s, a) \approx r + \gamma \max_{a'} Q(s', a')$$

- But we want to average over results from (s,a) (Why?)
- So keep a running average


$$Q(s, a) \leftarrow (1 - \alpha)Q(s, a) + (\alpha) \left[ r + \gamma \max_{a'} Q(s', a') \right]$$

# Q-Learning Properties

- Amazing result: Q-learning converges to optimal policy -- even if you're acting suboptimally!
- This is called **off-policy learning**
- Caveats:
  - You have to explore enough
  - You have to eventually make the learning rate small enough
  - ... but not decrease it too quickly
  - Basically, in the limit, it doesn't matter how you select actions (!)



# Exploration vs. Exploitation





# How to Explore?

- Several schemes for forcing exploration
  - Simplest: random actions ( $\epsilon$ -greedy)
    - Every time step, flip a coin
    - With (small) probability  $\epsilon$ , act randomly
    - With (large) probability  $1-\epsilon$ , act on current policy



# How to Explore?

- Several schemes for forcing exploration
  - Simplest: random actions ( $\epsilon$ -greedy)
    - Every time step, flip a coin
    - With (small) probability  $\epsilon$ , act randomly
    - With (large) probability  $1-\epsilon$ , act on current policy
  - Problems with random actions?
    - You do eventually explore the space, but keep thrashing around once learning is done
    - One solution: lower  $\epsilon$  over time
    - Another solution: exploration functions



# Exploration Functions

- When to explore?

- Random actions: explore a fixed amount
- Better idea: explore areas whose badness is not (yet) established, eventually stop exploring

- Exploration function

- Takes a value estimate  $u$  and a visit count  $n$ , and returns an optimistic utility, e.g.  $f(u, n) = u + k/n$

Regular Q-Update:  $Q(s, a) \leftarrow_{\alpha} R(s, a, s') + \gamma \max_{a'} Q(s', a')$


Modified Q-Update:  $Q(s, a) \leftarrow_{\alpha} R(s, a, s') + \gamma \max_{a'} f(Q(s', a'), N(s', a'))$

- Note: this propagates the “bonus” back to states that lead to unknown states as well!




# Regret

- Even if you learn the optimal policy, you still make mistakes along the way
- Regret is a measure of your total mistake cost: the difference between your (expected) rewards, including youthful suboptimality, and optimal (expected) rewards
- Minimizing regret goes beyond learning to be optimal – it requires optimally learning to be optimal
- Example: random exploration and exploration functions both end up optimal, but random exploration has higher regret




# Approximate Q-Learning

---



# Generalizing Across States

- Basic Q-Learning keeps a table of all q-values
- In realistic situations, we cannot possibly learn about every single state!
  - Too many states to visit them all in training
  - Too many states to hold the q-tables in memory
- Instead, we want to generalize:
  - Learn about some small number of training states from experience
  - Generalize that experience to new, similar situations
  - This is a fundamental idea in machine learning, and we'll see it over and over again



# Linear Value Functions

---

- Using a feature representation, we can write a q function (or value function) for any state using a few weights:

$$V(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

$$Q(s, a) = w_1 f_1(s, a) + w_2 f_2(s, a) + \dots + w_n f_n(s, a)$$

- Advantage: our experience is summed up in a few powerful numbers
- Disadvantage: states may share features but actually be very different in value!

# Approximate Q-Learning

$$Q(s, a) = w_1 f_1(s, a) + w_2 f_2(s, a) + \dots + w_n f_n(s, a)$$

- Q-learning with linear Q-functions:

$$\text{transition} = (s, a, r, s')$$

$$\text{difference} = \left[ r + \gamma \max_{a'} Q(s', a') \right] - Q(s, a)$$

$$Q(s, a) \leftarrow Q(s, a) + \alpha [\text{difference}]$$

$$w_i \leftarrow w_i + \alpha [\text{difference}] f_i(s, a)$$


Exact Q's

Approximate Q's

- Intuitive interpretation:


- Adjust weights of active features
- E.g., if something unexpectedly bad happens, blame the features that were on: disprefer all states with that state's features

- Formal justification: online least squares






# Q-Learning and Least Squares




# Linear Approximation: Regression\*



Prediction:

$$\hat{y} = w_0 + w_1 f_1(x)$$




Prediction:

$$\hat{y}_i = w_0 + w_1 f_1(x) + w_2 f_2(x)$$

# Optimization: Least Squares\*


$$\text{total error} = \sum_i (y_i - \hat{y}_i)^2 = \sum_i \left( y_i - \sum_k w_k f_k(x_i) \right)^2$$



# Minimizing Error\*

Imagine we had only one point  $x$ , with features  $f(x)$ , target value  $y$ , and weights  $w$ :

$$\begin{aligned}\text{error}(w) &= \frac{1}{2} \left( y - \sum_k w_k f_k(x) \right)^2 \\ \frac{\partial \text{error}(w)}{\partial w_m} &= - \left( y - \sum_k w_k f_k(x) \right) f_m(x) \\ w_m &\leftarrow w_m + \alpha \left( y - \sum_k w_k f_k(x) \right) f_m(x)\end{aligned}$$



Approximate q update explained:


$$w_m \leftarrow w_m + \alpha \left[ \underbrace{r + \gamma \max_a Q(s', a')}_{\text{"target"}} - \underbrace{Q(s, a)}_{\text{"prediction"}} \right] f_m(s, a)$$

“target”

“prediction”


# Overfitting: Why Limiting Capacity Can Help\*

---



# Policy Search

---



# Policy Search

---

- Problem: often the feature-based policies that work well (win games, maximize utilities) aren't the ones that approximate  $V$  /  $Q$  best
  - E.g. your value functions from project 2 were probably horrible estimates of future rewards, but they still produced good decisions
  - Q-learning's priority: get Q-values close (modeling)
  - Action selection priority: get ordering of Q-values right (prediction)
  - We'll see this distinction between modeling and prediction again later in the course
- Solution: learn policies that maximize rewards, not the values that predict them
- Policy search: start with an ok solution (e.g. Q-learning) then fine-tune by hill climbing on feature weights

# Policy Search

---

- Simplest policy search:
  - Start with an initial linear value function or Q-function
  - Nudge each feature weight up and down and see if your policy is better than before
- Problems:
  - How do we tell the policy got better?
  - Need to run many sample episodes!
  - If there are a lot of features, this can be impractical
- Better methods exploit look ahead structure, sample wisely, change multiple parameters...



# Term Project

---

- Pick a topic from the class, and write a program to demonstrate how it can apply to your robots. Short write-up or video to describe what you did.
- Teams of up to 5 people.
- Examples:
  - 8 Puzzle to sort grid of robots into ascending order by ID
  - Adversarial search for a game between R2D2 and R2Q5
  - Natural language processing for robots (translate commands into code)
- Alternate: do one of last year's homework assignments (on your own, not with a team).

# In class exercise: Robot Navigation with A\*

```
1 import sys
2 import time
3 import r2d2_client
4 import courses
5 import a_star
6 import maneuver
7
8
9 # connect to Sphero
10 r2d2 = r2d2_client.R2D2Client('127.0.0.1', 1337)
11
12 # get course, find path
13 G = courses.grid_1
14 start = (0,0)
15 goal = (3,0)
16 path = a_star.A_star(G, start, goal)
17
18 # ☑=start node, ☒=goal node
19 # □=□ □=□
20 # || || || ||
21 # □ □=□ □
22 # || || || ||
23 # □=□ □=□
24 # || || || ||
25 # ☑ □=□ ☒
26
27 # traverse path
28 speed = 0x88 # half speed
29 maneuver.follow_path(r2d2, path, speed, dist_constant=0.75)
30 r2d2.animate(10)
31 r2d2.quit()
```

<https://www.youtube.com/watch?v=qjlhtkhbPT8>