

This is a set of queries that may be performed over the created models

They follow the AQL language, which is a subset of OCL
[#https://eclipse.dev/acceleo/documentation/](https://eclipse.dev/acceleo/documentation/)

Note that the editingContextId of each query needs to be changed by the specific ID of the project, which is the UUID after the /project/ element in the URL

<http://localhost:8080/projects/8489727c-cb5f-41bd-a911-bfb2a23009da/edit/6f5909d7-49b0-4f49-80ed-8dba1e867444>

Return the classe name with applied stereotype Sensor

```
query Viewer {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()->select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'Sensor') ") {
        queryBasedString(query: "aql:self.name")
      }
    }
  }
}
```

Return all the stereotypes applied in a class with applied stereotype Sensor

```
query AvailableSensors {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()->select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'Sensor')") {
        queryBasedString(query: "aql:self.getStereotypeApplications()")
      }
    }
  }
}
```

Return the kind of the Services available from all classes

```
query AvailableServices {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()->select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'Service') ") {
        queryBasedString(query: "aql:self.getStereotypeApplications()->collect (sa |
sa.kind)")
      }
    }
  }
}
```

Return all the stereotypes applied in a class with applied stereotype Information

```
query AvailableInformation {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()->select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'Information') ") {
        queryBasedString(query: "aql:self.getStereotypeApplications()")
      }
    }
  }
}
```

Returns all the applied Component profile

```
query IoMTcomponent {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()-f>select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'IoMTcomponent') ") {
        queryBasedString(query: "aql:self.getStereotypeApplications()")
      }
    }
  }
}
```

Returns all the supportedFeatures for all classes

```
query IoMTcomponentCollectFeatures {
  viewer {
    editingContext(editingContextId: "8489727c-cb5f-41bd-a911-bfb2a23009da") {
      queryBasedObject(query: "aql:editingContext.allContents()->select(e |
e.getAppliedStereotypes()->exists( st | st.name = 'IoMTcomponent') ") {
        queryBasedString(query: "aql:self.getStereotypeApplications()->select(sa |
sa.supportedFeatures->size() >= 1 )->collect (sa | sa.supportedFeatures)")
      }
    }
  }
}
```