

**Medha Madhusudhan**

**1BM19CS230**

**CSE - 4A**

**DBMS Lab Programs for Lab Test - 1**

**Lab Program - 1**

```
create database Insurance;
```

```
use Insurance;
```

```
create table Person(  
    driver_id varchar(20) not null,  
    driver_name varchar(20) not null,  
    address varchar(20) not null,  
    primary key(driver_id)  
);
```

```
create table Car(  
    reg_num varchar(20) not null,  
    model varchar(20) not null,  
    year_purchase int not null,  
    primary key(reg_num)  
);
```

```
create table Accident(  
    report_num int not null,  
    accident_date date not null,  
    location varchar(20) not null,  
    primary key(report_num)
```

```
);
```

```
create table Owns(
    driver_id varchar(20) not null,
    reg_num varchar(20) not null,
    primary key(driver_id,reg_num),
    foreign key(driver_id) references Person(driver_id),
    foreign key(reg_num) references Car(reg_num)
);
```

```
create table Participated(
    driver_id varchar(20) not null,
    reg_num varchar(20) not null,
    report_num int not null,
    damage_amount int not null,
    primary key(driver_id,reg_num,report_num),
    foreign key(driver_id) references Person(driver_id),
    foreign key(reg_num) references Car(reg_num),
    foreign key(report_num) references Accident(report_num)
);
```

```
insert into Person(driver_id,driver_name,address)
values ('A01','Richard','Srinivas Nagar'),
       ('A02','Pradeep','Rajajinagar'),
       ('A03','Smith','Ashok Nagar'),
       ('A04','Venu','NR Colony'),
       ('A05','Jhon','Hanumanth Nagar');
```

```
insert into Car(reg_num,model,year_purchase)
values ('KA052250','Indica',1990),
       ('KA031181','Lancer',1957),
       ('KA095477','Toyota',1998),
       ('KA053408','Honda',2008),
       ('KA041702','Audi',2005);
```

```
insert into Owns(driver_id,reg_num)
values ('A01','KA052250'),
       ('A02','KA053408'),
       ('A03','KA031181'),
       ('A04','KA095477'),
       ('A05','KA041702');
```

```
insert into Accident(report_num,accident_date,location)
values (11,'2003-01-01','Mysore Road'),
       (12,'2004-02-02','South End Circle'),
       (13,'2003-01-21','Bull Temple Road'),
       (14,'2008-02-17','Mysore Road'),
       (15,'2005-03-04','Kanakpura Road');
```

```
insert into Participated(driver_id,reg_num,report_num,damage_amount)
values ('A01','KA052250',11,10000),
       ('A02','KA053408',12,50000),
       ('A03','KA095477',13,25000),
       ('A04','KA031181',14,3000),
       ('A05','KA041702',15,5000);
```

-- demonstrate how you update damage amount to 25000 for reg number 'KA053408' and report num 12

update Participated

set damage\_amount = 25000 where reg\_num = 'KA053408' and report\_num = 12;  
select \* from Participated;

	driver_id	reg_num	report_num	damage_amount
▶	A01	KA052250	11	10000
	A02	KA053408	12	25000
	A03	KA095477	13	25000
	A04	KA031181	14	3000
	A05	KA041702	15	5000

-- add a new accident to the database

insert into Accident values (16,'2007-07-08','Jayanagar');  
select \* from Accident;

	report_num	accident_date	location
▶	11	2003-01-01	Mysore Road
	12	2004-02-02	South End Circle
	13	2003-01-21	Bull Temple Road
	14	2008-02-17	Mysore Road
	15	2005-03-04	Kanakpura Road
	16	2007-07-08	Jayanagar

-- find the total no. of people who owned cars involved in accident in 2008

select count(\*) as accidents\_2008 from Accident where accident\_date between '2008-01-01' and '2008-12-31';

	accidents_2008
▶	1

-- find the number of accidents in which cars belonging to model 'Lancer' were involved

```
select count(p.report_num) from Participated p,Car c  
where p.reg_num = c.reg_num and c.model = 'Lancer';
```

	count(p.report_num)
▶	1

## Lab Program - 2

```
create database banking;
```

```
use banking;
```

```
create table Branch(  
    branch_name varchar(20) not null,  
    branch_city varchar(20) not null,  
    assets real not null,  
    primary key(branch_name)  
);
```

```
create table BankAccount(  
    accno int not null,  
    branch_name varchar(20) not null,  
    balance real not null,  
    primary key(accno),  
    foreign key(branch_name) references Branch(branch_name)  
);
```

```
create table BankCustomer(  
    customer_name varchar(20) not null,  
    customer_street varchar(20) not null,  
    customer_city varchar(20) not null,  
    primary key(customer_name)  
);
```

```
create table Depositor(  
    customer_name varchar(20) not null,
```

```
accno int not null,  
primary key(customer_name,accno),  
foreign key(customer_name) references BankCustomer(customer_name),  
foreign key(accno) references BankAccount(accno)  
);
```

```
create table Loan(  
    loanno int not null,  
    branch_name varchar(20) not null,  
    amount real not null,  
    primary key(loanno),  
    foreign key(branch_name) references Branch(branch_name)  
);
```

```
insert into Branch(branch_name,branch_city,assets)  
values ('SBI_Chamrajpet','Bangalore',50000),  
       ('SBI_ResidencyRoad','Bangalore',10000),  
       ('SBI_ShivajiRoad','Bombay',20000),  
       ('SBI_ParliamentRoad','Delhi',10000),  
       ('SBI_Jantarmanatar','Delhi',20000);
```

```
insert into BankAccount(accno,branch_name,balance)  
values (1,'SBI_Chamrajpet',2000),  
       (2,'SBI_ResidencyRoad',5000),  
       (3,'SBI_ShivajiRoad',6000),  
       (4,'SBI_ParliamentRoad',9000),  
       (5,'SBI_Jantarmanatar',8000),  
       (6,'SBI_ShivajiRoad',4000),
```

```
(8,'SBI_ResidencyRoad',4000),  
(9,'SBI_ParliamentRoad',3000),  
(10,'SBI_ResidencyRoad',5000),  
(11,'SBI_Jantarmanatar',2000);
```

```
insert into BankCustomer(customer_name,customer_street,customer_city)  
values ('Avinash','Bull_Temple_Road','Bangalore'),  
       ('Dinesh','Bannerghatta_Road','Bangalore'),  
       ('Mohan','NationalCollege_Road','Bangalore'),  
       ('Nikil','Akbar_Road','Delhi'),  
       ('Ravi','Prithviraj_Road','Delhi');
```

```
insert into Depositor(customer_name,accno)  
values ('Avinash',1),  
       ('Dinesh',2),  
       ('Nikil',4),  
       ('Ravi',5),  
       ('Avinash',8),  
       ('Nikil',9),  
       ('Dinesh',10),  
       ('Nikil',11);
```

```
insert into Loan(loanno,branch_name,amount)  
values (1,'SBI_Chamrajpet',1000),  
       (2,'SBI_ResidencyRoad',2000),  
       (3,'SBI_ShivajiRoad',3000),  
       (4,'SBI_ParliamentRoad',4000),  
       (5,'SBI_Jantarmanatar',5000);
```



-- Branch,BankAccount,BankCustomer,Depositor,Loan

-- find all the customers who have at least two accounts at the  
'SBI\_ResidencyRoad'

```
select distinct d.customer_name from Depositor d,BankAccount ba,Branch b
where d.accno = ba.accno and ba.branch_name = b.branch_name and
ba.branch_name = 'SBI_ResidencyRoad'
and 2 <= (select count(accno) from Depositor where customer_name =
d.customer_name);
```

	customer_name
▶	Dinesh
	Avinash

-- find all the customers who have an account at all branches in Delhi

```
select d.customer_name from Depositor d,BankAccount ba,Branch b
where d.accno = ba.accno and b.branch_name = ba.branch_name and
b.branch_city = 'Delhi'
group by d.customer_name
having count(d.accno) >= (select count(branch_name) from Branch where
branch_city = 'Delhi');
```

	customer_name
▶	Nikil

-- demonstrate how you delete all account tuples at every branch located at a  
Bombay

```
delete from BankAccount
```

where branch\_name in (select branch\_name from Branch where branch\_city = 'Bombay');

select \* from BankAccount;

	accno	branch_name	balance
►	1	SBI_Chamrajpet	2000
	2	SBI_ResidencyRoad	5000
	4	SBI_ParliamentRoad	9000
	5	SBI_Jantarantar	8000
	8	SBI_ResidencyRoad	4000
	9	SBI_ParliamentRoad	3000
	10	SBI_ResidencyRoad	5000
	11	SBI_Jantarantar	2000

### Lab Program - 3

```
create database supplierdb;
```

```
use supplierdb;
```

```
create table Suppliers(  
    sid int not null,  
    sname varchar(20) not null,  
    address varchar(20) not null,  
    primary key(sid)  
);
```

```
create table Parts(  
    pid int not null,  
    pname varchar(20) not null,  
    color varchar(20) not null,  
    primary key(pid)  
);
```

```
create table Catalog(  
    sid int not null,  
    pid int not null,  
    cost real not null,  
    primary key(sid,pid),  
    foreign key(sid) references Suppliers(sid),  
    foreign key(pid) references Parts(pid)  
);
```

```
insert into Suppliers(sid,sname,address)
```

```

values (10001,'Acme Widget','Bangalore'),
       (10002,'Johns','Kolkata'),
       (10003,'Vimal','Mumbai'),
       (10004,'Reliance','Delhi');

```

```

insert into Parts(pid,pname,color)
values (20001,'Book','Red'),
       (20002,'Pen','Red'),
       (20003,'Pencil','Green'),
       (20004,'Mobile','Green'),
       (20005,'Charger','Black');

```

```

insert into Catalog(sid,pid,cost)
values (10001,20001,10),
       (10001,20002,10),
       (10001,20003,30),
       (10001,20004,10),
       (10001,20005,10),
       (10002,20001,10),
       (10002,20002,20),
       (10003,20003,30),
       (10004,20003,40);

```

-- find the pnames of parts for which there is some supplier

```
select distinct p.pname from Parts p,Catalog c
```

```
where p.pid = c.pid and exists (select 'X' from Catalog where pid = p.pid);
```

	pname
▶	Book
	Pen
	Pencil
	Mobile
	Charger

-- find the snames of suppliers who supply every part

```
select s.sname from Suppliers s,Catalog c
where s.sid = c.sid
group by s.sname
having count(c.pid) = (select count(*) from Parts);
```

	sname
▶	Acme Widget

-- find the snames of suppliers who supply every red part

```
select s.sname from Suppliers s,Parts p,Catalog c
where s.sid = c.sid and p.pid = c.pid
and p.color = 'Red'
group by s.sname
having count(c.pid) = (select count(*) from Parts where color = 'Red');
```

	sname
▶	Acme Widget
	Johns

-- find the pname of parts supplied by acme widget and no one else

```
select p.pname from Parts p,Catalog c
where p.pid = c.pid
and p.pid not in (select pid from Catalog where sid in (select sid from Suppliers
where sname <> 'Acme Widget'));
```

	pname
▶	Mobile
	Charger

-- find the sids of suppliers who charge more for some part than average cost of that part

select distinct c.pid,c.sid from Catalog c

where c.cost > (select avg(c1.cost) from Catalog c1 where c1.pid = c.pid);

	pid	sid
▶	20002	10002
	20003	10004
✱	NULL	NULL

-- for each part, find the sname of supplier who charges most for that part

select p.pname,s.sname from Parts p,Suppliers s,Catalog c

where p.pid = c.pid and s.sid = c.sid

and c.cost = (select max(cost) from Catalog where pid = p.pid);

	pname	sname
▶	Book	Acme Widget
	Mobile	Acme Widget
	Charger	Acme Widget
	Book	Johns
	Pen	Johns
	Pencil	Reliance

## Lab Program - 4

```
create database studentfaculty;  
use studentfaculty;
```

```
create table Student(  
    snum int not null,  
    sname varchar(10) not null,  
    major varchar(2) not null,  
    lvl varchar(2) not null,  
    age int not null,  
    primary key(snum)  
);
```

```
create table Faculty(  
    fid int not null,  
    fname varchar(10) not null,  
    deptid int not null,  
    primary key(fid)  
);
```

```
create table Class(  
    cname varchar(10) not null,  
    meetsat time not null,  
    room varchar(10) not null,  
    fid int not null,  
    primary key(cname),  
    foreign key(fid) references Faculty(fid)  
);
```

```
create table Enrolled(  
    snum int not null,  
    cname varchar(10) not null,  
    primary key(snum,cname),  
    foreign key(snum) references Student(snum),  
    foreign key(cname) references Class(cname)  
);
```

```
insert into Student(snum,sname,major,lvl,age)  
values (1,'Jhon','CS','Sr',19),  
       (2,'Smith','CS','Jr',20),  
       (3,'Jacob','CV','Sr',20),  
       (4,'Tom','CS','Jr',20),  
       (5,'Rahul','CS','Jr',20),  
       (6,'Rita','CS','Sr',21);
```

```
insert into Faculty(fid,fname,deptid)  
values (11,'Harish',1000),  
       (12,'MV',1000),  
       (13,'Mira',1001),  
       (14,'Shiva',1002),  
       (15,'Nupur',1000);
```

```
insert into Class(cname,meetsat,room,fid)  
values ('Class1','10:15:16','R1',14),  
       ('Class10','10:15:16','R128',14),  
       ('Class2','10:15:20','R2',12),
```



```

('Class3','10:15:25','R3',11),
('Class4','20:15:20','R4',14),
('Class5','20:15:20','R3',15),
('Class6','13:20:20','R2',14),
('Class7','10:10:10','R3',14);

```

```

insert into Enrolled(snum,cname)
values (1,'Class1'),
       (2,'Class1'),
       (3,'Class3'),
       (4,'Class3'),
       (5,'Class4');

```

```

insert into Enrolled(snum,cname)
values (1,'Class5'),
       (2,'Class5'),
       (3,'Class5'),
       (4,'Class5'),
       (5,'Class5');

```

-- find names of all juniors who are enrolled in a class taught by 'Harish'

```

select s.sname from Student s,Enrolled e
where s.snum = e.snum
and s.lvl = 'Jr'
and e.cname in (select cname from Class where fid = (select fid from Faculty
where fname = 'Harish'));

```

	sname
▶	Tom

-- find the name of all classes that either meet in room128 or have  $\geq 5$  students

select c.cname from Class c

where c.room = 'R128'

union

select distinct e.cname from Enrolled e

where  $5 \leq (\text{select count(snum) from Enrolled where cname = e.cname});$

	cname
▶	Class10
	Class5

-- find the names of all students who are enrolled in two classes that meet at the same time

select distinct s.sname from Student s,Class c,Enrolled e

where s.snum = e.snum and c.cname = e.cname

and exists (select 'X' from Class c1,Enrolled e1 where c1.cname = e1.cname and c1.meetsat = c.meetsat and e1.snum = e.snum and c1.cname  $\neq$  e.cname);

	sname
▶	Rahul

-- find the names of faculty who teach in every room in which class is taught

select f.fname from Faculty f,Class c

where f.fid = c.fid

group by f.fid

having count(f.fid) = (select count(distinct room) from Class);

	fname
▶	Shiva

-- find the names of faculty members for whom combined enrollment of courses that they teach is less than five

```
select distinct f.fname
from Class c, Faculty f
where c.fid = f.fid
and 5 > (select count(snum) from enrolled where cname in (select cname from
Class where Class.fid = c.fid));
```

	fname
▶	Harish
	MV
	Shiva

-- find the names of students who are not enrolled in any class

```
select s.sname from Student s
where not exists (select 'X' from Enrolled where snum = s.snum);
```

	sname
▶	Rita

-- for each age value that appears in Students, find the level that appears the most

```
select s.age,s.lvl from Student s
where s.lvl = 'Jr'
group by s.age
having count(s.lvl) > (select count(lvl) from Student where lvl = 'Sr' and age = s.age)
union
select s.age,s.lvl from Student s
where s.lvl = 'Sr'
group by s.age
having count(s.lvl) > (select count(lvl) from Student where lvl = 'Jr' and age = s.age);
```

	age	lvl
►	20	Jr
	19	Sr
	21	Sr

## Lab Program - 5

```
create database airlinesdb;
```

```
use airlinesdb;
```

```
create table Flights(  
    flno int not null,  
    from_loc varchar(20) not null,  
    to_loc varchar(20) not null,  
    distance int not null,  
    departs time not null,  
    arrives time not null,  
    price int not null,  
    primary key(flno)  
);
```

```
create table Aircraft(  
    aid int not null,  
    aname varchar(20) not null,  
    cruisingrange int not null,  
    primary key(aid)  
);
```

```
create table Employees(  
    eid int not null,  
    ename varchar(20) not null,  
    salary int not null,  
    primary key(eid)  
);
```

```
create table Certified(  
    eid int not null,  
    aid int not null,  
    primary key(eid,aid),  
    foreign key(eid) references Employees(eid),  
    foreign key(aid) references Aircraft(aid)  
);
```

```
insert into Flights(flno,from_loc,to_loc,distance,departs,arrives,price)  
values (101,"Bangalore","Delhi",2500,"07:15:31","12:15:31",5000),  
       (102,"Bangalore","Lucknow",3000,"07:15:31","11:15:31",6000),  
       (103,"Lucknow","Delhi",500,"12:15:31","17:15:31",3000),  
       (107,"Bangalore","Frankfurt",8000,"07:15:31","22:15:31",60000),  
       (104,"Bangalore","Frankfurt",8500,"07:15:31","23:15:31",75000),  
       (105,"Kolkata","Delhi",3400,"07:15:31","09:15:31",7000);
```

```
insert into Flights(flno,from_loc,to_loc,distance,departs,arrives,price)  
values (106,"Delhi","Kolkata",3400,"12:15:35","14:20:00",7000);
```

```
insert into Aircraft(aid,aname,cruisingrange)  
values (101,"747",3000),  
       (102,"Boeing",900),  
       (103,"647",800),  
       (104,"Dreamliner",10000),  
       (105,"Boeing",3500),  
       (106,"707",1500),  
       (107,"Dream",12000);
```

```
insert into Employees(eid,ename,salary)
values (701,'A',50000),
(702,'B',100000),
(703,'C',150000),
(704,'D',90000),
(705,'E',40000),
(706,'F',60000),
(707,'G',90000);
```

```
insert into Certified(eid,aid)
values (701,101),
(701,102),
(701,106),
(701,105),
(702,104),
(703,104),
(704,104),
(702,107),
(703,107),
(704,107),
(702,101),
(703,105),
(704,105),
(705,103);
```

-- Find the names of aircraft such that all pilots certified to operate them have salaries more than Rs.80,000.

select distinct a.aname from Aircraft a, Employees e, Certified c  
 where a.aid = c.aid and e.eid = c.eid and e.salary > 80000;

	aname
▶	747
	Dreamliner
	Boeing
	Dream

-- For each pilot who is certified for more than three aircrafts, find the eid and the maximum cruisingrange of the aircraft for which she or he is certified.

select e.eid, e.ename, max(a.cruisingrange) from Employees e, Certified c, Aircraft a  
 where e.eid = c.eid and a.aid = c.aid group by e.ename having count(c.aid) > 3;

	eid	ename	max(a.cruisingrange)
▶	701	A	3500

-- Find the names of pilots whose salary is less than the price of the cheapest route from Bengaluru to Frankfurt.

select e.ename from Employees e where salary < (select min(price) from Flights  
 where from\_loc = "Bangalore" and to\_loc = "Frankfurt");

	ename
▶	A
	E

-- For all aircraft with cruisingrange over 1000 Kms, find the name of the aircraft and the average salary of all pilots certified for this aircraft.

select a.aname, a.cruisingrange, avg(e.salary)  
 from Aircraft a, Employees e, Certified c  
 where c.eid = e.eid and c.aid = a.aid  
 group by a.aname having a.cruisingrange > 1000 ;



	aname	cruisingrange	avg(e.salary)
▶	747	3000	75000.0000
	Dreamliner	10000	113333.3333
	707	1500	50000.0000
	Dream	12000	113333.3333

-- Find the names of pilots certified for some Boeing aircraft.

select distinct e.ename from Employees e,Certified c,Aircraft a  
where e.eid = c.eid and a.aid = c.aid and aname like "Boeing";

	ename
▶	A
	C
	D

-- Find the aids of all aircraft that can be used on routes from Bengaluru to New Delhi.

select a.aid from aircraft a where a.cruisingrange >= (select distance from Flights  
where from\_loc = "Bangalore" and to\_loc = "Delhi");

	aid
▶	101
	104
	105
	107
•	NULL

-- A customer wants to travel from bangalore to kolkata with no more than two changes of flight

-- List the choice of departure times if a customer wants to arrive by 6 p.m.

select f.from\_loc,f.to\_loc,f.arrives from Flights f  
where (f.from\_loc = "Bangalore" and f.to\_loc = (select from\_loc from Flights  
where to\_loc = "Kolkata")) or f.to\_loc = "Kolkata";

	from_loc	to_loc	arrives
►	Bangalore	Delhi	12:15:31
	Delhi	Kolkata	14:20:00