



F1-24 Hydraulic Ram

If flowing water is suddenly brought to rest in a long pipe, a phenomenon known as water hammer occurs, which produces a pressure wave that travels along the pipe.

This principle is used in the hydraulic ram to pump water.

PRODUCT CODE: F1-24

Categories: Educational, F1 Series Fluid Mechanics, F1-24 - Hydraulic Ram

Tags: Armfield , Cyclic Fluctuations , Delivery Head , F1-24 , Flow Characteristics , Fluid Mechanics , Hydraulic Ram , Pressure Characteristics , Pump Water , Supply Head , Water Hammer

DESCRIPTION

The Hydraulic Ram comprises an acrylic base incorporating pulse and non-return valves and a supply reservoir on a stand which is fed by the hydraulics bench. An air vessel above the valve chamber smooths cyclic fluctuations from the ram delivery.

The weights supplied may be applied to the pulse valve to change the closing pressure and thus the operating characteristics.

TECHNICAL SPECIFICATIONS

Supply head: 300-700mm variable

Delivery head: 750-1500mm variable

Requires Hydraulics Bench Service unit F1-10/F1-10-2

FEATURES & BENEFITS

Experimental content

- To demonstrate the operating principles of the hydraulic ram
- Establishing flow/pressure characteristics and determining efficiency of the hydraulic ram

Dimensions

Length: 0.75m
Width: 0.33m
Height: 1.62m

Order Codes

F1-24

YOU MAY ALSO LIKE...



**F1-10
HYDRAULICS
BENCH**

[Read more](#)



**C11-MKII PIPE
NETWORKS**

[Read more](#)

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781

