



FT15 Disc Bowl Centrifuge

The Armfield Disc Bowl Centrifuge is designed to provide practical training in the technique of separating a heavy phase liquid from a lighter phase liquid with particular emphasis on the separation of cream from milk. Throughputs of up to 125 litres/hour are possible and 12 motor speeds between 8,500 – 10,000rpm are selectable.

PRODUCT CODE: FT15

Categories: Armfield Educational Food Technology, Armfield Liquid Foods, FT Series - Educational Food Technology, FT15 Disc Bowl Centrifuge, IFT Industrial Food Technology, IFT Series - Industrial Food Technology

Tags: Centrifuge , Collecting Vessel , Cream , Dairy , Disc Bowl Centrifuge , Disk Bowl , Milk , Phase Liquid , Separation , Vessel

DESCRIPTION

A supporting framework intended for bench mounting houses the separator, complete with its variable speed drive control unit, food reservoir and the necessary ancilliary equipment.

The feed reservoir, positioned over the centrifuge, is made from grey anodised aluminium and contains a polypropylene on/off valve. The separator bowl assembly is made up of stainless steel disks and an anodised aluminium casing with nitrile rubber sealing ring, housed in a polypropylene shroud which incorporates the cream and skimmed milk outlets.

A motor, directly coupled to the separator bowl, is mounted vertically in a cast aluminium casing with cushioned clamping feet. The casing acts as the support for the separator.

Ancillary equipment to facilitate a thorough investigation into this type of separation consists of:

- Optical tachometer
- Product collecting vessels
- Stop clock
- Tools

The backboard includes a sectioned diagram detailing the component parts of the separator bowl and describing its mode of operation.

ADDITIONAL INFORMATION

Weight	60 kg
Dimensions	.6 × .6 × .4 m

TECHNICAL SPECIFICATIONS

- A self-contained centrifugal separator training unit which allows thorough investigation of the separation of a heavy phase liquid from a lighter phase liquid
- Using milk as the process fluid, cream having a fat content from 12-55% can be obtained. Accessories are included to allow variation and measurement of bowl speed and throughput rate measurement. Ease of stripdown to component parts is facilitated by tools included in the supply
- Throughput up to 125 l/hr can be obtained from a 10l capacity feed tank, which can be continuously replenished
- Materials in contact with the process fluid are anodised aluminium, stainless steel, nitrile rubber and polypropylene
- 12 motor speeds between 8,500 and 10,000rpm are selectable
- Accessories mounted on the framework include:
 - Optical tachometer
 - Stop clock
 - Product collecting vessels
 - Tools
- A comprehensive instruction manual is included in the supply detailing installation, commissioning and operation
- Separator bowl incorporates 19 discs
- 12 motor speeds between 8,500 and 10,000rpm are selectable by switch on the motor control housing
- The tachometer has a five-digit display and a measuring range of 60-19,999rpm
- Resolution 1 rpm
- Two graduated sample collecting vessels, glass, 1.0l and 0.4l
- One stop clock, 100mm dial, 30-hour spring driven movement with start/stop and reset push buttons

FEATURES & BENEFITS

The centrifuge provides practical instruction exercises in all aspects of cream/milk separation including:

- Production of a variety of creams having milk fat contents from 12%-55%
- Demonstration of the effect of temperature and bowl speed on separator performance
- Demonstration of the effect of product type on throughput
- Learning the importance of cleanliness and hygiene in food processing
- Understanding the mode of operation of this type of centrifuge, using instructive diagrams and ease of stripdown to component parts

Requirements

FT15-A: 220-240V/1ph/50Hz


FT15-B: 120V/1ph/60Hz

FT15-G: 220-240V/1ph/60Hz

Shipping Specifications

OVERALL DIMENSIONS

Height: 0.60m



Width: 0.60m
Depth: 0.40m

SHIPPING SPECIFICATION

Volume: 0.4m3
Gross weight: 60kg

YOU MAY ALSO LIKE...



**FT25 SCRAPED
SURFACE HEAT
EXCHANGER
SERIES**

[Read more](#)



**FT74XA
HTST/UHT
SYSTEM**

[Read more](#)

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781

