



FT22 Rising Film Evaporator

The Armfield Rising Film Evaporator is a floor-standing unit, designed to provide practical training for the operation of large modern evaporator equipment in industry.

PRODUCT CODE: FT22

Categories: Armfield Dairy, Armfield Educational Food Technology, Armfield Flavours And Fragrances, Armfield Ingredients, Armfield Liquid Foods, FT Series - Educational Food Technology, FT22 Rising Film Evaporator, IFT Industrial Food Technology, IFT Series - Industrial Food Technology

Tags: Evaporation , FT22 , Gas Separator , Liquid Separator , Organoleptic , Rising Film Evaporator

DESCRIPTION

The single tube-in-jacket evaporator replicates industrial units which often contain scores of much longer tubes within the steam space. The component parts of the industrial process have been scaled down, feed tank, vapour/liquid separator, condenser, concentrate tank, condensate tank, CIP pump and vacuum pump, all manufactured from hygienic materials such as stainless steel, PTFE and glass.

The system is supported within a stainless steel framework and requires only a connection to suitable steam, electrical and water services for operation.

Only 0.65m² of floor space is required to install the evaporator and it has been designed to fit easily into a room of standard height.

TECHNICAL SPECIFICATIONS

Evaporator tube length: 1.36m

Heat transfer area: 0.06m²

Max evaporation rate: 10 l/h

Max steam consumption: 15 Kg/h

Max steam pressure (working): 1.7 bar

Condenser area: 0.17m²

Feed tank capacity max: 30L

Concentrate collecting tank capacity: 5L

Condensate collecting tank capacity: 5L

CIP pump (flexible impeller): 8 L/min @ 20ft H₂O

System vacuum: 225mm Hg ABS (increased when pump heads in series)

FEATURES & BENEFITS

- Small quantities of liquid products can be concentrated
- Easily cleaned and maintained
- Low product usage eases the disposal of waste
- Nominal throughput only 10 L/h

Features

- Single-tube heat exchanger
- Integral CIP system
- Integral control console
- Data logging and analysis included

Applications

- Juices (fruit and vegetable)
- Milk and milk products
- Extracts (non-flammable)
- Effluents

Related products

- UOP10
- FT17
- FT18-MKII
- FT20
- FT25
- FT27
- FT36
- FT51
- FT52
- FT74XA
- FT80-81
- FT83
- FT84-12
- FT85
- FT90-91
- FT94X
- FT94LT
- FT102XA
- FT110DP
- FT111X



- FT140
- FT174X

Optional Accessories

UOP10 Steam Generator

Provides an adequate supply of steam as the heat transfer medium.

Armfield UOP10 Laboratory steam generator

Requirements

ELECTRICITY SUPPLY

FT22-A: 220-240V / 1ph / 50Hz / 3kW

FT22-B: 120V / 1ph / 60Hz / 3kW

FT22-G: 220-240V/60Hz, (3kW)

Data logger: A computer running Windows 98 or above, with a USB port.

Shipping Specifications

Volume: 2.40m³

Gross weight: 330kg

Dimensions

Height: 2.60m

Width: 0.78m

Depth: 0.65m

Order Codes

FT22-A

FT22-B

YOU MAY ALSO LIKE...



**UOP3 –
DISTILLATION
COLUMNS**

[Read more](#)



**FT74XA
HTST/UHT
SYSTEM**

[Read more](#)

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781