



FT28 Oil Extraction Screw Press

This oil extraction screw press has been developed to meet an increasing demand for a relatively unsophisticated small-capacity press, suitable for laboratory work.

It is designed to press seeds, nuts or other fine biomass to extract the oil. In addition a cake is formed which can be further purified down stream.

PRODUCT CODE: FT28

Categories: Armfield Edible And Essential Oils, Armfield Educational Food Technology, FT Series - Educational Food Technology, FT28 Oil Extraction Screw Press, IFT Industrial Food Technology, IFT Series - Industrial Food Technology

Tags: FT28 , Oil Cake , Oil Extraction , Screw Press

DESCRIPTION

Seed or ground meal is gravity-fed to the press from an integral feed hopper fitted with a manually operated shut-off slide. The thickness of the press cake may be varied. The press is driven at the discharge end through a single-reduction helical gearbox.

The power source is a 4kW, four-pole, three-phase electric motor. Typical throughput data for various seeds is shown in the table below.

TECHNICAL SPECIFICATIONS

FT28-E version:

Screw press, having barrel constructed from separate cast rings spaced apart by shims. 60mm diameter bore, 155mm drainage length with single-piece wormshaft driven at the discharge end through a single-reduction helical gearbox. Complete with feed hopper, manual feed chute, oil discharge chute and suitable base plate. Includes: one 4kW, four-pole motor, 1,450rpm with starter.

- Oil extraction screw press suitable for use in the laboratory
- Complete with feed hopper, manual feed chute and oil discharge
- 4kW electric motor
- Suitable for use with a wide range of seeds or ground meals

FEATURES & BENEFITS

- Very simple controls
- Robust design
- Self-lubricating shaft in product contact areas
- Removable panels for viewing process and safety
- Quiet processing

Press Capabilities

		FIRST PRESS		SECOND PRESS	
Seed	Pre-treat-ment	Through put Kg/hr	% Oil in cake	Through put (1st press cake) Kg/hr	% Oil in cake
Sunflower	Clean	35/40	15/28	40	12
Rape	Clean	35/40	17/20	40	13
Linseed	Clean	28	20	40	12
Copra	Clean and break to 10/12mm pieces	40	30	40	12
Palm kernels	Clean and grind to 8 mesh	35/40	20	35	12
Macadamia kernels	Clean	30 (60% kenels/ 40%cake)	20/24	30	14/16

Armfield-FT28-PressTable

Requirements

ELECTRICAL SUPPLY:

FT28-C: 415V / 3ph / 50Hz / 25 amp

FT28-D: 208V / 3ph / 60Hz / 25 amp

FT28-E: 380V / 3ph / 50Hz / 25 amp

FT28-F: 220-240V / 3ph / 60Hz / 25 amp

Shipping Specifications

PACKED AND CRATED SHIPPING SPECIFICATIONS

Gross Weight: 320Kg

Volume: 1.10m³

Dimensions

OVERALL DIMENSIONS

Height: 1.09m

Width: 0.99m

Depth: 1.20m

Ordering Codes

FT28-C

FT28-D

FT28-E

FT28-F

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781

