



FT63 Laboratory Process Chiller

The FT63 is a recirculating process chiller, providing a continuous supply of chilled liquid to serve as the cooling fluid when used with an Armfield miniature-scale processing unit. It is particularly suitable for use with an Armfield Heat Treatment and Filtration Systems (FT174, FT74XA and FT18).

PRODUCT CODE: **FT63**

Categories: Armfield Dairy, Armfield Educational Food Technology, FT Series - Educational Food Technology, FT63 Laboratory Process Chiller, IFT Industrial Food Technology, IFT Series - Industrial Food Technology

Tags: Chiller , Compressor , Cooling Fluid , Evaporator , Freeze , FT63 , FT64 , Glycol , Heat Exchanger , Laboratory Process Chiller

DESCRIPTION

The FT63 contains a reservoir of cooled fluid, which is pumped through the external process to be cooled (eg heat exchanger system).

The cooling fluid can be water or a mixture of glycol and water depending on the output temperature required. This fluid is cooled by the integral refrigeration system. A high-pressure pump is used to pump the fluid through the process. A bypass valve facility enables the fluid to be recirculated independently of the process conditions.

Compressor Reciprocating hermetically sealed compressor with a refrigerant cooled motor. Evaporator Packaged coil type, made of copper tubes and aluminum fins. Condenser Single air-cooled condenser manufactured from aluminium fins mechanically bonded to refrigeration-grade copper tubes. The condenser fan is of a low-noise axial type. Fan blades are fully enclosed by a safety grill.

TECHNICAL SPECIFICATIONS

COOLING CAPACITY

The cooling capacity of a chiller is dependent on its operating conditions, particularly the liquid temperature and concentration.

The FT63 has a typical cooling capacity of 2kW with an outlet temperature of 0°C, using a 20% glycol solution (typical FT174X application). For other applications please consult Armfield.

Refrigerant: R407C Freon

Max ambient temp: 32°C

PROCESS PUMP

Head: 6 bar max

Flow rate: 4.8 m³/hr at 3.7 bar

Reservoir capacity: 25 litres

FEATURES & BENEFITS

- Low refrigerant charge
- Low running costs
- Easily cleaned and maintained
- Continuously recirculating glycol solutions for cold chilled liquid temperatures
- Temperature controller on chilled liquid outlet enables stable processing
- High cooling capacity
- Integral high capacity liquid pump
- Mobile unit
- Washable control panel
- Stainless steel casing



Armfield-FT63 Washable-Digital-Control-Panel

Requirements

Electricity supply: Single phase (see ordering codes)

Shipping Specifications

PACKED AND CREATED SHIPPING SPECIFICATIONS

Volume: 0.7m³

Gross weight: 160Kg

Dimensions

Length: 0.80m


Width: 0.70m

Height: 0.97m

Order Codes

- **FT63SS-A:** Laboratory Process Chiller 230V / 1ph / 50Hz / 15A
- **FT63SS-G:** Laboratory Process Chiller 220V / 1ph / 60Hz / 16

YOU MAY ALSO LIKE...




**FT74XA
HTST/UHT
SYSTEM**

[Read more](#)



**FT18-MKII
MODULAR
CROSS FLOW
FILTRATION**

[Read more](#)



**FT174 –
MODULAR
MINIATURE
SCALE
HTST/UHT
PROCESS
SYSTEM**

[Read more](#)

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781