



H1-1/H1-2/H1-3 – Vernier Hook & Point Gauges

The measurement of steady state water surface position is frequently needed during hydraulic investigations.

This is done by using a small point or hook manually adjusted to touch the water surface, and a reading is taken of the vertical movement using a scale or vernier.

PRODUCT CODE: H1-1, H1-3

Categories: Educational, H Series - Hydraulic Instruments

Tags: Gauging Rod , H Series , Hydraulic Investigations , Hydraulic Measurement Instruments , Vernier , Vernier Hook & Point Gauges

DESCRIPTION

The measurement of steady state water surface position is frequently needed during hydraulic investigations.

This is done by using a small point or hook manually adjusted to touch the water surface, and a reading is taken of the vertical movement using a scale or vernier.

A mounting frame is clamped to a suitable support structure and a gauging rod is free to slide up and down over the water surface. A stainless steel hook or point is attached to the bottom end of the rod and is used to locate the water surface.

Gauging is carried out by means of a primary scale attached to the mounting frame and a vernier scale attached to the rod. The scales are in edge contact.

The rod is held in a screwed collar for fine adjustment and can be released for large, rapid changes of position. Zero can be reset by a locking screw positioned on the vernier scale.

TECHNICAL SPECIFICATIONS

Ranges:

- **H1-1:** 150mm
- **H1-2:** 300mm
- **H1-3:** 450mm

Resolution: $\pm 0.10\text{mm}$

Typical accuracy: $\pm 0.20\text{mm}$

Repeatability: $\pm 0.10\text{mm}$

FEATURES & BENEFITS

Demonstration Capabilities

- Location of air-water surface boundaries with high resolution
- Measurement of slowly changing water levels in flumes and hydraulic models
- Measurement of mechanical deformation

Accessories

H1-10: Tripod stand

Ordering specification

- A rugged low cost gauge for measurement of water surface position to $\pm 0.20\text{mm}$
- Mounting frame in enamelled cast aluminium
- Gauging rod and adjusting mechanism in bright plated brass
- Supplied complete with stainless steel hook and point

Shipping Specifications

PACKED AND CRATED SHIPPING SPECIFICATIONS

H1-1 (150mm)

- **Volume:** 0.01m^3
- **Gross Weight:** 1.2Kg

H1-1 (300mm)

- **Volume:** 0.01m^3
- **Gross Weight:** 1.5Kg

H1-1 (450mm)

- **Volume:** 0.01m^3
- **Gross Weight:** 1.7Kg

Dimensions

H1-1 (150mm)

- **Length:** 0.265m
- **Width:** 0.75m
- **Height:** 0.5m

H1-2 (300mm)

- **Length:** 0.415m



- **Width:** 0.75m
- **Height:** 0.5m

H1-3 (450mm)

- **Length:** 0.565m
- **Width:** 0.75m
- **Height:** 0.5m

Order Codes

- **H1-1**
- **H1-2**
- **H1-3**

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781

