



H1-7 – H1-8 – Digital Hook & Point Gauges

A range of digital hook and point gauges which includes a liquid crystal display which indicates the movement of the gauging rod.

A push button sets the display to zero at any position, allowing the measurement of movement relative to a datum.

PRODUCT CODE: H1-7, H1-8

Categories: Educational, H Series - Hydraulic Instruments, H1-7 – H1-8 - Digital Hook & Point Gauges

Tags: Digital Hook & Point Gauges , H Series , Hydraulic Measurement Instruments , LCD , Liquid Crystal Electronic Display

DESCRIPTION

A range of digital hook and point gauges which includes a liquid crystal display which indicates the movement of the gauging rod.

A push button sets the display to zero at any position, allowing the measurement of movement relative to a datum.

A mounting plate is clamped to a suitable support structure and a flat vertical shaft retained by the gauging unit is free to slide up and down over the water surface.

A steel point or hook is attached to the bottom end of the shaft and is used to locate the water surface.

The gauging unit consists of a liquid crystal electronic display which indicates the movements of the shaft.

A quick-release mechanism permits large changes to be rapidly accommodated, and a screw adjustment is provided for accurate final positioning.

A push button sets the display to zero at any position, so that relative movements compared with a datum can be easily measured.

This gauge is easy to use and minimises potential errors resulting from reading vernier scales.

TECHNICAL SPECIFICATIONS

Ranges:

- H1-7: 300mm
- H1-8: 500mm

Resolution: $\pm 0.01\text{mm}$

Typical accuracy: $\pm 0.03\text{mm}$

Repeatability: $\pm 0.01\text{mm}$

Operating temperature range: 5°C to 40°C

Note: The gauge is powered continuously by a small cell battery with a life in excess of 6 months. (No 'on/off' switch improves reliability)

FEATURES & BENEFITS

Demonstration Capabilities

- Measurement of steady state of water with digital display

Accessories

- H1-11: Adjustable Tripod stand with mountings

Ordering specification

- A direct indicating gauge which eliminates observation errors due to vernier and scale reading
- Can be set to zero anywhere in the operating range to permit easy relative level checking
- The liquid crystal display is easy to read and has a resolution of $\pm 0.01\text{mm}$
- A push button gives immediate change to inches from millimetres if required
- A quick-release mechanism permits rapid changes of position

Shipping Specifications

PACKED AND CRATED SHIPPING SPECIFICATIONS

H1-7 (300mm)

Volume: 0.01m^3

Gross Weight: 2Kg

H1-8 (500mm)

Volume: 0.03m^3

Gross Weight: 2.5Kg

Dimensions

H1-7 (300mm):

- **Length:** 4.50m
- **Width:** 0.75m
- **Height:** 0.40m



H1-8 (500mm):

- **Length:** 6.50m
- **Width:** 0.75m
- **Height:** 0.40m

Order Codes

- H1-7
- H1-8

Armfield Limited. Unit 10 Headlands Business Park, Salisbury Road, Ringwood, Hampshire BH24 3PB.
England. Tel: +44(0) 1425 478781

