

```

#include <iostream>
#include <cstring>

#define SIZE 100

using namespace std;

class Stack
{
public:
    Stack()
    {
        top = 0;
    }
    int push(int data)
    {
        if (top >= SIZE - 1) // Check if the stack is full
        {
            return 0; // Stack overflow
        }
        top++; // Move top pointer
        this->data[top] = data; // Add data to stack
        return 1; // Success
    }

    int *pop()
    {
        if (top < 0) // Check if the stack is empty
        {
            return NULL; // Stack underflow
        }
        return &data[top--];
    }
private:
    int data[SIZE];
    int top;
};

int main()
{
    int data, *temp;
    char command[50];
    Stack *stack = new Stack();
    while(1)
    {
        cin>>command;
        if(strcmp(command, "exit") == 0)
        {
            break;
        }
        else if(strcmp(command, "push") == 0)
        {
            cout<<"Please input a integer data:";
            cin>>data;
            if(stack->push(data) == 1)
            {
                cout<<"Successfully push data "<<data<<" into stack.\n";
            }
        }
        else
        {
        }
    }
}

```

```
        cout<<"Failed to push data into stack.\n";
    }
}
else if(strcmp(command, "pop") == 0)
{
    temp = stack->pop();
    if(temp == NULL)
    {
        cout<<"Failed to pop a data from stack.\n";
    }
    else
    {
        cout<<"Pop data "<<*temp<<" from stack.\n"<<endl;
    }
}
}
}
```