

```

#include <stdio.h>
#include <string.h>
#include <limits.h> // Used to access the limits of integer types (determines various properties of
the various variable types.)

int ans[10001]; // Array to represent the skyline

int main()
{
    int right_side = 0, left_side = INT_MAX; // Initializing variables to track the rightmost and leftmost
    sides of buildings
    memset(ans, 0, sizeof(ans)); // Initializing the skyline array with zeros
    char s[100]; // String to store input lines

    // Reading input until EOF
    while (fgets(s, sizeof(s), stdin) != NULL)
    {
        int l, h, r;
        sscanf(s, "%d %d %d", &l, &h, &r); // Parsing input line into left, height, and right variables
        right_side = (r > right_side) ? r : right_side; // Updating the rightmost side of buildings
        left_side = (l < left_side) ? l : left_side; // Updating the leftmost side of buildings

        // Iterating through the skyline for each building to determine the skyline heights
        for (int i = l; i < r; i++)
        {
            if (ans[i] < h)
            {
                ans[i] = h; // Storing the maximum height for each position of the skyline
            }
        }
    }

    // Printing the skyline representation
    for (int i = left_side; i < right_side; i++)
    {
        if (ans[i] != ans[i - 1])
        {
            // Checking for changes in skyline height
            if (ans[i] == 0)
            {
                printf("%d %d ", i, 0); // Printing the position and height of the skyline
            }
            else
            {
                printf("%d %d ", i, ans[i]); // Printing the position and height of the skyline
            }
        }
    }

    printf("%d %d\n", right_side, 0); // Printing the last position of the skyline as 0 height

    return 0;
}

```