

```

#include <stdio.h>

#define SIZE 100
#define FLOODED -1
#define WALL 1
#define SPACE 0

int findPath(int (*arr)[SIZE], int n);

int main()
{
    int maze[SIZE][SIZE], n, i, j, answer;

    scanf("%d", &n);

    for (i = 0; i < n; i++)
        for (j = 0; j < n; j++)
            scanf("%d", &maze[i][j]);

    answer = findPath(maze, n);
    if (answer)
        printf("Yes");
    else
        printf("No");

    return 0;
}

int findPath(int (*maze)[SIZE], int n)
{
    maze[0][0] = FLOODED;
    int flag = 1, i, j;

    while(flag)
    {
        flag = 0;
        for (i = 0; i < n; i++)
        {
            for (j = 0; j < n; j++)
            {
                if (maze[i][j] == SPACE)
                {
                    if (i > 0 && maze[i - 1][j] == FLOODED ||
                        i < n - 1 && maze[i + 1][j] == FLOODED ||
                        j > 0 && maze[i][j - 1] == FLOODED ||
                        j < n - 1 && maze[i][j + 1] == FLOODED)
                    {
                        maze[i][j] = FLOODED;
                        flag = 1;
                    }
                }
            }
        }
    }

    return (maze[n - 1][n - 1] == FLOODED);
}

```