RAGVIDENCE · EVIDENCE RETRIEVAL REPORT

bm25-body → bm25-heading_context

One controlled retrieval comparison · 12 questions · 10 answerable · k=2

60% → 90%

Evidence sufficiency improved from 60% to 90%.

3 questions recovered 0 regressions 1 unresolved failure

Generated 2026-10-13T11:18:05+00:00 Artifact schema v1

Baseline versus intervention

Success means every required evidence ID appeared within the recorded retrieval depth.

Baseline · bm25-body

60%

6 / 10 answerable questions sufficient

Strategy: BM25 · Representation: body · k=2

Index time: 131.3 ms (secondary run metadata)

Intervention · bm25-heading_context

90%

9 / 10 answerable questions sufficient

Strategy: BM25 · Representation: heading context · k=2

Index time: 0.8 ms (secondary run metadata)

+30.0 percentage points in evidence sufficiency

Change analysis

Review regressions first, then unresolved failures. Stable successes are grouped later.

0
Pass → Fail · Regressions

1
Fail → Fail · Unresolved

3
Fail → Pass · Recovered

6
Pass → Pass · Stable

2 N/A cases are excluded from the answerable success-rate denominator.

Evidence-backed diagnosis

> **Observed facts**
>
> 3 failed queries passed after enrichment with no regressions.

> **Diagnostic interpretation**
>
> **Observed pattern:** Missing structural context in the baseline representation
>
> **Recommended next experiment:** Repeat on a frozen slice of your own corpus and inspect every changed rank.
>
> **Confidence:** medium
>
> **Limitation:** This rule identifies correlation in a small labeled comparison, not universal causation.

Regressions

No questions in this group.

Unresolved failures

▶ **DEV-04** Required: E-ORION-41-RESET, E-ORION-42-RESET

Fail → Fail Split: dev Fail · Insufficient evidence Coverage: 0% → 50% First relevant rank: N/A → 2

> **Required evidence gained:** E-ORION-41-RESET
>
> **Required evidence lost:** None
>
> **Still missing:** E-ORION-42-RESET

Baseline

Fail · Insufficient evidence

Evidence coverage: 0% First relevant rank: N/A

Reciprocal rank: 0.000 Precision@k: 0.000

Retrieved hits: 2

Required evidence: E-ORION-41-RESET, E-ORION-42-RESET

Found required evidence: None

Missing required evidence: E-ORION-41-RESET, E-ORION-42-RESET

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 4.861 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-LYRA-30-GUEST

Retriever score: 1.293 · Evidence IDs: E-LYRA-30-GUEST

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

Intervention

Fail · Insufficient evidence

Evidence coverage: 50% First relevant rank: 2

Reciprocal rank: 0.500 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-41-RESET, E-ORION-42-RESET

Found required evidence: E-ORION-41-RESET

Missing required evidence: E-ORION-42-RESET

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 3.002 · Evidence IDs: None

Controller Migration Notes > Comparing reset workflows

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the instal

#2 · SEC-ORION-41-RESET

Retriever score: 1.847 · Evidence IDs: E-ORION-41-RESET

Orion DeskHub > Firmware 4.1 > Pairing reset

Hold the side button for five seconds. Release it when the status ring flashes blue once. This procedure clears the current controller pairing.

Improvements

▶ **DEV-01** Required: E-ORION-42-RESET

Fail → Pass Split: dev Pass · Sufficient evidence Coverage: 0% → 100% First relevant rank: N/A → 1

> **Required evidence gained:** E-ORION-42-RESET
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Fail · Insufficient evidence

Evidence coverage: 0% First relevant rank: N/A

Reciprocal rank: 0.000 Precision@k: 0.000

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: None

Missing required evidence: E-ORION-42-RESET

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 3.986 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-LYRA-30-GUEST

Retriever score: 1.818 · Evidence IDs: E-LYRA-30-GUEST

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: E-ORION-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-42-RESET

Retriever score: 2.442 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

#2 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.097 · Evidence IDs: None

Controller Migration Notes > Comparing reset workflows

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the instal

▶ **DEV-03** Required: E-ORION-42-RECOVERY

Fail → Pass Split: dev Pass · Sufficient evidence Coverage: 0% → 100%

First relevant rank: N/A → 2

> **Required evidence gained:** E-ORION-42-RECOVERY
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Fail · Insufficient evidence

Evidence coverage: 0% First relevant rank: N/A

Reciprocal rank: 0.000 Precision@k: 0.000

Retrieved hits: 2

Required evidence: E-ORION-42-RECOVERY

Found required evidence: None

Missing required evidence: E-ORION-42-RECOVERY

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 3.495 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-ORION-42-RESET

Retriever score: 1.303 · Evidence IDs: E-ORION-42-RESET

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 2

Reciprocal rank: 0.500 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RECOVERY

Found required evidence: E-ORION-42-RECOVERY

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-42-RESET

Retriever score: 1.988 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

#2 · SEC-ORION-42-RECOVERY

Retriever score: 1.795 · Evidence IDs: E-ORION-42-RECOVERY

Orion DeskHub > Firmware 4.2 > Interrupted update recovery

Disconnect power for twenty seconds, reconnect the adapter, and wait until the status ring becomes steady white before reopening the control application.

▶ **HOLD-04** Required: E-ATLAS-42-RESET

Fail → Pass Split: heldout Pass · Sufficient evidence Coverage: 0% → 100%

First relevant rank: N/A → 2

> **Required evidence gained:** E-ATLAS-42-RESET
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Fail · Insufficient evidence

Evidence coverage: 0% First relevant rank: N/A

Reciprocal rank: 0.000 Precision@k: 0.000

Retrieved hits: 2

Required evidence: E-ATLAS-42-RESET

Found required evidence: None

Missing required evidence: E-ATLAS-42-RESET

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.867 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-ORION-41-RESET

Retriever score: 0.787 · Evidence IDs: E-ORION-41-RESET

Hold the side button for five seconds. Release it when the status ring flashes blue once. This procedure clears the current controller pairing.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 2

Reciprocal rank: 0.500 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ATLAS-42-RESET

Found required evidence: E-ATLAS-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.175 · Evidence IDs: None

Controller Migration Notes > Comparing reset workflows

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the instal

#2 · SEC-ATLAS-42-RESET

Retriever score: 1.993 · Evidence IDs: E-ATLAS-42-RESET

Atlas Dock > Firmware 4.2 > Pairing reset

Press the recessed rear switch for three seconds, then release it when the two port indicators blink together. Existing display preferences are retained.

Stable results

▶ **DEV-02** Required: E-ORION-42-RESET

Pass → Pass Split: dev Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 2 → 1

> **Required evidence gained:** None
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 2

Reciprocal rank: 0.500 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: E-ORION-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.687 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-ORION-42-RESET

Retriever score: 1.967 · Evidence IDs: E-ORION-42-RESET

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: E-ORION-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-42-RESET

Retriever score: 3.184 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

#2 · SEC-ORION-41-RESET

Retriever score: 2.142 · Evidence IDs: E-ORION-41-RESET

Orion DeskHub > Firmware 4.1 > Pairing reset

Hold the side button for five seconds. Release it when the status ring flashes blue once. This procedure clears the current controller pairing.

▶ **DEV-05** Required: E-LYRA-30-GUEST

Pass → Pass Split: dev Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 1 → 1

> **Required evidence gained:** None
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-LYRA-30-GUEST

Found required evidence: E-LYRA-30-GUEST

Missing required evidence: None

Ranked evidence

#1 · SEC-LYRA-30-GUEST

Retriever score: 7.268 · Evidence IDs: E-LYRA-30-GUEST

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

#2 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 0.707 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-LYRA-30-GUEST

Found required evidence: E-LYRA-30-GUEST

Missing required evidence: None

Ranked evidence

#1 · SEC-LYRA-30-GUEST

Retriever score: 7.582 · Evidence IDs: E-LYRA-30-GUEST

Lyra Travel Router > Firmware 3.0 > Guest network reset

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

#2 · SEC-NOVA-20-CALIBRATION

Retriever score: 0.568 · Evidence IDs: E-NOVA-20-CALIBRATION

Nova Room Sensor > Firmware 2.0 > Manual calibration

Keep the sensor on a level surface and hold both arrow buttons for twelve seconds. Calibration is complete when the display shows a solid square.

▶ **HOLD-01** Required: E-ORION-42-RESET

Pass → Pass Split: heldout Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 1 → 1

> **Required evidence gained:** None
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: E-ORION-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-42-RESET

Retriever score: 2.421 · Evidence IDs: E-ORION-42-RESET

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

#2 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.196 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-42-RESET

Found required evidence: E-ORION-42-RESET

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-42-RESET

Retriever score: 3.652 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

#2 · SEC-ORION-41-RESET

Retriever score: 1.173 · Evidence IDs: E-ORION-41-RESET

Orion DeskHub > Firmware 4.1 > Pairing reset

Hold the side button for five seconds. Release it when the status ring flashes blue once. This procedure clears the current controller pairing.

▶ **HOLD-02** Required: E-ORION-41-RECOVERY

Pass → Pass Split: heldout Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 2 → 1

Required evidence gained: None

Required evidence lost: None

Still missing: None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 2

Reciprocal rank: 0.500 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-41-RECOVERY

Found required evidence: E-ORION-41-RECOVERY

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 1.930 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-ORION-41-RECOVERY

Retriever score: 1.070 · Evidence IDs: E-ORION-41-RECOVERY

Leave the adapter connected and hold the rear recovery switch for three seconds. The status ring turns white when recovery is complete.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-ORION-41-RECOVERY

Found required evidence: E-ORION-41-RECOVERY

Missing required evidence: None

Ranked evidence

#1 · SEC-ORION-41-RECOVERY

Retriever score: 1.845 · Evidence IDs: E-ORION-41-RECOVERY

Orion DeskHub > Firmware 4.1 > Interrupted update recovery

Leave the adapter connected and hold the rear recovery switch for three seconds. The status ring turns white when recovery is complete.

#2 · SEC-ORION-42-RESET

Retriever score: 1.059 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

▶ **HOLD-03** Required: E-NOVA-20-CALIBRATION

Pass → Pass Split: heldout Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 1 → 1

> **Required evidence gained:** None
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-NOVA-20-CALIBRATION

Found required evidence: E-NOVA-20-CALIBRATION

Missing required evidence: None

Ranked evidence

#1 · SEC-NOVA-20-CALIBRATION

Retriever score: 2.886 · Evidence IDs: E-NOVA-20-CALIBRATION

Keep the sensor on a level surface and hold both arrow buttons for twelve seconds. Calibration is complete when the display shows a solid square.

#2 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 1.119 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-NOVA-20-CALIBRATION

Found required evidence: E-NOVA-20-CALIBRATION

Missing required evidence: None

Ranked evidence

#1 · SEC-NOVA-20-CALIBRATION

Retriever score: 5.347 · Evidence IDs: E-NOVA-20-CALIBRATION

Nova Room Sensor > Firmware 2.0 > Manual calibration

Keep the sensor on a level surface and hold both arrow buttons for twelve seconds. Calibration is complete when the display shows a solid square.

#2 · SEC-ORION-42-RESET

Retriever score: 0.500 · Evidence IDs: E-ORION-42-RESET

Orion DeskHub > Firmware 4.2 > Pairing reset

If the hub remains paired to an unavailable controller, hold the side button for eight seconds. Release it after the status ring flashes amber twice. The saved network settings remain unchanged.

▶ **HOLD-05** Required: E-LYRA-30-GUEST

Pass → Pass Split: heldout Pass · Sufficient evidence Coverage: 100% → 100%

First relevant rank: 1 → 1

> **Required evidence gained:** None
> **Required evidence lost:** None
> **Still missing:** None

Baseline

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-LYRA-30-GUEST

Found required evidence: E-LYRA-30-GUEST

Missing required evidence: None

Ranked evidence

#1 · SEC-LYRA-30-GUEST

Retriever score: 6.525 · Evidence IDs: E-LYRA-30-GUEST

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

#2 · SEC-ORION-42-RECOVERY

Retriever score: 0.802 · Evidence IDs: E-ORION-42-RECOVERY

Disconnect power for twenty seconds, reconnect the adapter, and wait until the status ring becomes steady white before reopening the control application.

Intervention

Pass · Sufficient evidence

Evidence coverage: 100% First relevant rank: 1

Reciprocal rank: 1.000 Precision@k: 0.500

Retrieved hits: 2

Required evidence: E-LYRA-30-GUEST

Found required evidence: E-LYRA-30-GUEST

Missing required evidence: None

Ranked evidence

#1 · SEC-LYRA-30-GUEST

Retriever score: 7.515 · Evidence IDs: E-LYRA-30-GUEST

Lyra Travel Router > Firmware 3.0 > Guest network reset

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

#2 · SEC-ORION-41-RESET

Retriever score: 0.993 · Evidence IDs: E-ORION-41-RESET

Orion DeskHub > Firmware 4.1 > Pairing reset

Hold the side button for five seconds. Release it when the status ring flashes blue once. This procedure clears the current controller pairing.

Unanswerable / N/A cases

▶ **DEV-06** Unanswerable question

Not applicable Split: dev N/A · Unanswerable Coverage: N/A → N/A

First relevant rank: N/A → N/A

> **Required evidence gained:** None
>
> **Required evidence lost:** None
>
> **Still missing:** None

Baseline

N/A · Unanswerable

Evidence coverage: N/A First relevant rank: N/A

Reciprocal rank: N/A Precision@k: N/A

Retrieved hits: 2

Required evidence: None

Found required evidence: None

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.864 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-LYRA-30-GUEST

Retriever score: 0.525 · Evidence IDs: E-LYRA-30-GUEST

On the Lyra Travel Router running firmware 3.0, select Guest Network, choose Reset Access Code, and confirm the prompt. Connected guest devices are disconnected.

Intervention

N/A · Unanswerable

Evidence coverage: N/A

First relevant rank: N/A Reciprocal rank: N/A

Precision@k: N/A Retrieved hits: 2

Required evidence: None

Found required evidence: None

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 0.759 · Evidence IDs: None

Controller Migration Notes > Comparing reset workflows

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the instal

#2 · SEC-ORION-42-RECOVERY

Retriever score: 0.725 · Evidence IDs: E-ORION-42-RECOVERY

Orion DeskHub > Firmware 4.2 > Interrupted update recovery

Disconnect power for twenty seconds, reconnect the adapter, and wait until the status ring becomes steady white before reopening the control application.

▶ **HOLD-06** Unanswerable question

Not applicable Split: heldout N/A · Unanswerable Coverage: N/A → N/A

First relevant rank: N/A → N/A

> **Required evidence gained:** None
> **Required evidence lost:** None
> **Still missing:** None

Baseline

N/A · Unanswerable

Evidence coverage: N/A First relevant rank: N/A

Reciprocal rank: N/A Precision@k: N/A

Retrieved hits: 2

Required evidence: None

Found required evidence: None

Missing required evidence: None

Ranked evidence

#1 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 2.967 · Evidence IDs: None

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the installed device and version.

#2 · SEC-ORION-41-RECOVERY

Retriever score: 0.662 · Evidence IDs: E-ORION-41-RECOVERY

Leave the adapter connected and hold the rear recovery switch for three seconds. The status ring turns white when recovery is complete.

Intervention

N/A · Unanswerable

Evidence coverage: N/A

First relevant rank: N/A Reciprocal rank: N/A

Precision@k: N/A Retrieved hits: 2

Required evidence: None

Found required evidence: None

Missing required evidence: None

Ranked evidence

#1 · SEC-ATLAS-42-RESET

Retriever score: 1.493 · Evidence IDs: E-ATLAS-42-RESET

Atlas Dock > Firmware 4.2 > Pairing reset

Press the recessed rear switch for three seconds, then release it when the two port indicators blink together. Existing display preferences are retained.

#2 · SEC-MIGRATION-RESET-COMPARISON

Retriever score: 1.440 · Evidence IDs: None

Controller Migration Notes > Comparing reset workflows

Teams moving from Orion DeskHub firmware 4.2 to Atlas Dock firmware 4.2 should not assume that the pairing-reset workflows are identical. Use the procedure in the manual for the instal

Reproducibility

Keep the same reviewed dataset and retrieval depth when comparing runs. Run identifiers and configuration refer to the recorded artifacts.

Baseline · bm25-body

Run ID

ee71bf462992

Run created

2026-10-13T11:18:05+00:00

Dataset hash

f7702c7d14e97c796385410be045449a8eccf8c5a7550656071eae0dcaed2d56

Product version

0.1.0

Python version

3.12.14

Platform

Linux-6.18.33.2-microsoft-standard-WSL2-x86_64-with-glibc2.43

Model

Not configured

Provider

Not configured

Intervention · bm25-heading_context

Run ID

515f2f28ad90

Run created

2026-10-13T11:18:05+00:00

Dataset hash

f7702c7d14e97c796385410be045449a8eccf8c5a7550656071eae0dcaed2d56

Product version

0.1.0

Python version

3.12.14

Platform

Linux-6.18.33.2-microsoft-standard-WSL2-x86_64-with-glibc2.43

Model

Not configured

Provider

Not configured

Limitations

- Constructed teaching data and a small reviewed question set.

- Retrieval evaluation does not prove generated-answer correctness.
- Results apply to the recorded strategy, representation, dataset and k.

This report evaluates retrieved evidence; it does not establish causation or generated-answer correctness. Source previews can contain confidential content. Review before sharing.

Printing includes every question and ranked evidence item, including closed disclosures. Navigation is omitted. Use this complete view when exporting to PDF.