

# 1. Description

## 1.1. Project

Project Name	ProjektZespolowy
Board Name	NUCLEO-H743ZI2
Generated with:	STM32CubeMX 6.5.0
Date	05/25/2022


## 1.2. MCU

MCU Series	STM32H7
MCU Line	STM32H743/753
MCU name	STM32H743ZITx
MCU Package	LQFP144
MCU Pin number	144

## 1.3. Core(s) information

Core(s)	ARM Cortex-M7

# 2. Pinout Configuration



# 3. Pins Configuration


Pin Number LQFP144	Pin Name (function after	Pin Type	Alternate Function(s)	Label
	reset)		, ,	
3	PE4	I/O	DCMI_D4	
4	PE5	I/O	DCMI_D6	
5	PE6	I/O	DCMI_D7	
6	VBAT	Power		
7	PC13 *	I/O	GPIO_Input	B1 [Blue PushButton]
8	PC14-OSC32_IN (OSC32_IN)	I/O	RCC_OSC32_IN	
9	PC15-OSC32_OUT (OSC32_OUT) **	I/O	RCC_OSC32_OUT	
16	VSS	Power		
17	VDD	Power		
23	PH0-OSC_IN (PH0)	I/O	RCC_OSC_IN	
24	PH1-OSC_OUT (PH1)	I/O	RCC_OSC_OUT	
25	NRST	Reset		
30	VDD	Power		
31	VSSA	Power		
33	VDDA	Power		
36	PA2	I/O	USART2_TX	
37	PA3	I/O	USART2_RX	
38	VSS	Power		
39	VDD	Power		
40	PA4	I/O	DCMI_HSYNC	
42	PA6	I/O	DCMI_PIXCLK	
46	PB0 *	I/O	GPIO_Output	LD1 [Green Led]
51	VSS	Power		
52	VDD	Power		
56	PG0 *	I/O	GPIO_Input	ResetG0
57	PG1 *	I/O	GPIO_Output	PWDNPG1
61	VSS	Power		
62	VDD	Power		
71	VCAP	Power		
72	VDD	Power		
75	PB14 *	I/O	GPIO_Output	LD3 [Red Led]
77	PD8	I/O	USART3_TX	STLINK_RX
78	PD9	I/O	USART3_RX	STLINK_TX
79	PD10 *	I/O	GPIO_Output	USB_OTG_FS_PWR_EN

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
83	VSS	Power		
84	VDD	Power		
92	PG7	I/O	GPIO_EXTI7	USB_OTG_FS_OVCR
94	VSS	Power		
95	VDD33_USB	Power		
96	PC6	I/O	DCMI_D0	
97	PC7	I/O	DCMI_D1	
99	PC9	I/O	RCC_MCO_2	
106	VCAP	Power		
107	VSS	Power		
108	VDD	Power		
117	PD3	I/O	DCMI_D5	
120	VSS	Power		
121	VDD	Power		
126	PG11	I/O	DCMI_D3	
130	VSS	Power		
131	VDD	Power		
136	PB6	I/O	I2C1_SCL	
137	PB7	I/O	DCMI_VSYNC	
138	воото	Boot		
140	PB9	I/O	I2C1_SDA	
141	PE0	I/O	DCMI_D2	
143	PDR_ON	Reset		
144	VDD	Power		

<sup>\*</sup> The pin is affected with an I/O function

<sup>\*\*</sup> The pin is affected with a peripheral function but no peripheral mode is activated

# 4. Clock Tree Configuration



# 5. Software Project

## 5.1. Project Settings

Name	Value	
Project Name	ProjektZespolowy	
Project Folder	C:\Users\bttle\STM32CubeIDE\workspace_1.9.0\ProjektZespolowy	
Toolchain / IDE	STM32CubeIDE	
Firmware Package Name and Version	STM32Cube FW_H7 V1.10.0	
Application Structure	Advanced	
Generate Under Root	Yes	
Do not generate the main()	No	
Minimum Heap Size	0x200	
Minimum Stack Size	0x400	

## 5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	Yes
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	No

## 5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_DMA_Init	DMA
4	MX_USART3_UART_Init	USART3
5	MX_USART2_UART_Init	USART2
6	MX_DCMI_Init	DCMI
7	MX_I2C1_Init	I2C1
8	MX_JPEG_Init	JPEG

# 6. Power Consumption Calculator report

### 6.1. Microcontroller Selection

Series	STM32H7
Line	STM32H743/753
MCU	STM32H743ZITx
Datasheet	DS12110_Rev8

## 6.2. Parameter Selection

Temperature	25
Vdd	3.0

## 6.3. Battery Selection

Battery	Alkaline(9V)	
Capacity	625.0 mAh	
Self Discharge	0.3 %/month	
Nominal Voltage	9.0 V	
Max Cont Current	200.0 mA	
Max Pulse Current	0.0 mA	
Cells in series	1	
Cells in parallel	1	


## 6.4. Sequence

	1	
Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	VOS0: Scale0-High	SVOS5: System-Scale5
D1 Mode	DRUN/CRUN	DSTANDBY
D2 Mode	DRUN	DSTANDBY
D3 Mode	DRUN	DSTOP
Fetch Type	ITCM	NA
CPU Frequency	480 MHz	0 Hz
Clock Configuration	HSE BYP PLL	Flash-OFF
Clock Source Frequency	24 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	148 mA	150 µA
Duration	0.1 ms	0.9 ms
DMIPS	1027.0	0.0
Ta Max	105.46	124.98
Category	In DS Table	In DS Table

## 6.5. Results

Sequence Time	1 ms	Average Current	14.94 mA
Battery Life	1 day, 17 hours	Average DMIPS	1027.2001
			DMIPS

## 6.6. Chart



# 7. Peripherals and Middlewares Configuration

#### 7.1. DCMI

**DCMI: Slave 8 bits External Synchro** 

#### 7.1.1. Parameter Settings:

#### **Mode Config:**

Pixel clock polarity Active on Falling edge

Vertical synchronization polarity Active Low Horizontal synchronization polarity Active Low

Frequency of frame capture All frames are captured

JPEG mode Enabled \*

#### **Interface Capture Config:**

Byte Select Mode Interface captures all received bytes
Line Select Mode Interface captures all received lines

## 7.2. I2C1 I2C: I2C

#### 7.2.1. Parameter Settings:

#### Timing configuration:

Custom Timing Disabled
I2C Speed Mode Standard Mode

I2C Speed Frequency (KHz)100Rise Time (ns)0Fall Time (ns)0Coefficient of Digital Filter0

Analog Filter Enabled

Timing **0x10606BA1** \*

#### **Slave Features:**

Clock No Stretch Mode Disabled
General Call Address Detection Disabled
Primary Address Length selection 7-bit
Dual Address Acknowledged Disabled
Primary slave address 0

#### 7.3. JPEG

mode: Activated

#### 7.3.1. Parameter Settings:

Version:

JPEG version jpeg1\_v1\_0

JPEG Software options:

ENCODE Enabled
DECODE Enabled

RGB\_FORMAT JPEG\_ARGB8888

JPEG\_SWAP\_RG

#### 7.4. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator Low Speed Clock (LSE): BYPASS Clock Source

mode: Master Clock Output 2

#### 7.4.1. Parameter Settings:

#### **Power Parameters:**

SupplySource PWR\_LDO\_SUPPLY

Power Regulator Voltage Scale Power Regulator Voltage Scale 2

**RCC Parameters:** 

TIM Prescaler Selection Disabled
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000
CSI Calibration Value 16
HSI Calibration Value 32

**System Parameters:** 

VDD voltage (V) 3.3

Flash Latency(WS) 1 WS (2 CPU cycle)

Product revision rev.Y

**PLL range Parameters:** 

PLL1 clock Input range Between 8 and 16 MHz
PLL1 clock Output range Wide VCO range

#### 7.5. SYS

### **Timebase Source: SysTick**

#### **7.6. USART2**

### **Mode: Asynchronous**

#### 7.6.1. Parameter Settings:

#### **Basic Parameters:**

Baud Rate 9600 \*

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

**Advanced Parameters:** 

Data Direction Receive and Transmit

Over Sampling 16 Samples
Single Sample Disable
ClockPrescaler 1

Fifo Mode Disable

Txfifo Threshold 1 eighth full configuration
Rxfifo Threshold 1 eighth full configuration

**Advanced Features:** 

Auto Baudrate Disable TX Pin Active Level Inversion Disable **RX Pin Active Level Inversion** Disable Disable **Data Inversion** TX and RX Pins Swapping Disable Overrun Enable Enable DMA on RX Error MSB First Disable

#### **7.7. USART3**

#### **Mode: Asynchronous**

#### 7.7.1. Parameter Settings:

#### **Basic Parameters:**

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

#### **Advanced Parameters:**

Data Direction Receive and Transmit

Over Sampling 16 Samples
Single Sample Disable
ClockPrescaler 1

Fifo Mode Disable

Txfifo Threshold 1 eighth full configuration
Rxfifo Threshold 1 eighth full configuration

#### **Advanced Features:**

Auto Baudrate Disable TX Pin Active Level Inversion Disable Disable **RX Pin Active Level Inversion** Data Inversion Disable Disable TX and RX Pins Swapping Overrun Enable DMA on RX Error Enable MSB First Disable

#### \* User modified value

# 8. System Configuration

## 8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull	Max	User Label
DOM:	55.4	DOM: D4	Ali . 5 5 . 5 . 5 . 1	down	Speed	
DCMI	PE4	DCMI_D4	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PE5	DCMI_D6	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PE6	DCMI_D7	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA4	DCMI_HSYNC	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA6	DCMI_PIXCLK	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC6	DCMI_D0	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC7	DCMI_D1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PD3	DCMI_D5	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PG11	DCMI_D3	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PB7	DCMI_VSYNC	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PE0	DCMI_D2	Alternate Function Push Pull	No pull-up and no pull-down	Low	
I2C1	PB6	I2C1_SCL	Alternate Function Open Drain	No pull-up and no pull-down	Low	
	PB9	I2C1_SDA	Alternate Function Open Drain	No pull-up and no pull-down	Low	
RCC	PC14- OSC32_IN (OSC32_IN)	RCC_OSC32_IN	n/a	n/a	n/a	
	PH0- OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
	PH1- OSC_OUT (PH1)	RCC_OSC_OUT	n/a	n/a	n/a	
	PC9	RCC_MCO_2	Alternate Function Push Pull	No pull-up and no pull-down	Low	
USART2	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA3	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low	
USART3	PD8	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low	STLINK_RX
	PD9	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low	STLINK_TX
Single Mapped Signals	PC15- OSC32_OU T	RCC_OSC32_O UT	n/a	n/a	n/a	
GPIO	PC13	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	B1 [Blue PushButton]
	PB0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD1 [Green Led]
	PG0	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	ResetG0
	PG1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	PWDNPG1
	PB14	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD3 [Red Led]
	PD10	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	USB_OTG_FS_PWR_EN

IP	Pin	Signal	GPIO mode	GPIO pull/up pull	Max	User Label
				down	Speed	
	PG7	GPIO_EXTI7	External Interrupt Mode with	No pull-up and no pull-down	n/a	USB_OTG_FS_OVCR
			Rising edge trigger detection			

## 8.2. DMA configuration

DMA request	Stream	Direction	Priority
USART2_RX	DMA1_Stream0	Peripheral To Memory	Low
USART2_TX	DMA1_Stream1	Memory To Peripheral	Low
DCMI	DMA1_Stream2	Peripheral To Memory	Low

#### USART2\_RX: DMA1\_Stream0 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Byte
Memory Data Width: Byte

#### USART2\_TX: DMA1\_Stream1 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Byte
Memory Data Width: Byte

#### DCMI: DMA1\_Stream2 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Word \*

## 8.3. BDMA configuration

nothing configured in DMA service

8.4.	<b>MDMA</b>	confia	uration
<b>v</b>		909	4.4.5.

nothing configured in DMA service

## 8.5. NVIC configuration

# 8.5.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority	
Non maskable interrupt	true	0	0	
Hard fault interrupt	true	0	0	
Memory management fault	true	0	0	
Pre-fetch fault, memory access fault	true	0	0	
Undefined instruction or illegal state	true	0	0	
System service call via SWI instruction	true	0	0	
Debug monitor	true	0	0	
Pendable request for system service	true	0	0	
System tick timer	true	0	0	
DMA1 stream0 global interrupt	true	0	0	
DMA1 stream1 global interrupt	true	0	0	
DMA1 stream2 global interrupt	true	0	0	
USART2 global interrupt	true	0	0	
PVD and AVD interrupts through EXTI line 16		unused		
Flash global interrupt		unused		
RCC global interrupt		unused		
EXTI line[9:5] interrupts		unused		
I2C1 event interrupt		unused		
I2C1 error interrupt		unused		
USART3 global interrupt		unused		
DCMI global interrupt		unused		
FPU global interrupt		unused		
JPEG global interrupt		unused		
HSEM1 global interrupt	unused			

## 8.5.2. NVIC Code generation


Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
DMA1 stream0 global interrupt	false	true	true
DMA1 stream1 global interrupt	false	true	true
DMA1 stream2 global interrupt	false	true	true
USART2 global interrupt	false	true	true

<sup>\*</sup> User modified value

# 9. System Views


- 9.1. Category view
- 9.1.1. Current



Power Domain view

Category view

## 9.1.2. Without filters



## 9.2. Power Domain view

Category view Power Domain view



## 10. Docs & Resources

Type Link

Presentations https://www.st.com/resource/en/product\_presentation/microcontrollers\_st

m32h7\_series\_product\_overview.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_embedded\_software\_solutions.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_eval-

tools\_portfolio.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_stm8\_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_software\_development\_tools.pdf

Training Material https://www.st.com/resource/en/sales\_guide/sg\_sc2154.pdf

Training Material https://www.st.com/resource/en/training\_certification/faecp\_stm32h7\_dual

core\_edr.pdf

Training Material https://www.st.com/resource/en/training\_certification/faecp\_stm32h7\_edr.

pdf

Brochures https://www.st.com/resource/en/brochure/brstm32h7.pdf

Brochures https://www.st.com/resource/en/brochure/brstm32h7vl.pdf

Flyers https://www.st.com/resource/en/flyer/flnucleolrwan.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Flyers https://www.st.com/resource/en/flyer/flpowerstbd.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2639-soldering-

recommendations-and-package-information-for-leadfree-ecopack-mcus-

- and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2834-how-to-get-the-best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2867-oscillator-design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4230-stm32-microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4539-hrtim-cookbook-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4635-minimization-of-power-consumption-using-lpuart-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-

- applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4838-managing-memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4839-level-1-cache-on-stm32f7-series-and-stm32h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4861-lcdtft-display-controller-ltdc-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4936-migration-of-microcontroller-applications-from-stm32f7-series-to-stm32h743753-line-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4938-getting-started-with-stm32h74xig-and-stm32h75xig-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4990-getting-started-with-sigmadelta-digital-interface-on-applicable-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4996-hardware-jpeg-

- codec-peripheral-in-stm32f7677xxx-andstm32h743534555475750a3b3b0xx-microcontrollersstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5020-digital-camera-interface-dcmi-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5200-getting-started-with-stm32h7-series-sdmmc-host-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5224-stm32-dmamux-the-dma-request-router-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5293-migration-guide-from-stm32f7-series-and-stm32h743753-line-to-stm32h7a37b3-and-stm32h7b0-value-line-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5312-migration-from-revy-to-revv-for-stm32h743753-and-stm32h750-value-line-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5337-stm32h7-series-lifetime-estimates-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5342-error-correction-code-ecc-management-for-internal-memories-protection-on-stm32h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5348-fdcan-

peripheral-on-stm32-devices-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5354-getting-started-with-the-stm32h7-series-mcu-16bit-adc-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5405-fdcan-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4899-stm32-microcontroller-gpio-configuration-for-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5690-vrefbuf-peripheral-applications-and-trimming-technique-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4760-quadspiinterface-on-stm32-microcontrollers-and-microprocessors-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1202\_freertos\_guidefor related Tools freertos-guide-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an1602\_semihosting\_in for related Tools \_truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an1801\_stm32cubeprog for related Tools rammer\_in\_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/atollic\_editing\_keyboard for related Tools \_shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/iar\_to\_atollic\_truestudio for related Tools \_migration\_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/stm32cubemx\_installatio

for related Tools n in truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2606-stm32-for related Tools microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4502-stm32-for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4635-minimization-of-

for related Tools power-consumption-using-lpuart-for-stm32-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4657-stm32-

for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4891-stm32h72x-for related Tools stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-

& Software performance-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5001-stm32cube-for related Tools expansion-package-for-stm32h7-series-mdma-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5014-stm32h7x3-

for related Tools smart-power-management-expansion-package-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5033-stm32cube-

for related Tools mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5426-migrating-for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5534-stm32h735gdk-

for related Tools firmware-upgrade-for-atbased-emw3080-wifi-module-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4865-lowpower-timer-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Design Notes & https://www.st.com/resource/en/design\_tip/dt0117-microphone-array-

Tips beamforming-in-the-pcm-and-pdm-domain-stmicroelectronics.pdf

Errata Sheets https://www.st.com/resource/en/errata\_sheet/es0392-stm32h742xig-and-

stm32h743xig-device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00387108.pdf

Programming https://www.st.com/resource/en/programming\_manual/pm0253-stm32f7-Manuals series-and-stm32h7-series-cortexm7-processor-programming-manual-

stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference\_manual/rm0433-stm32h742-

Manuals stm32h743753-and-stm32h750-value-line-advanced-armbased-32bit-

mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf