

Client-side Technologies

Eng. Niveen Nasr El-Den
SD & Gaming CoE
iTi

The background features a large, dark blue trapezoidal shape on the left side, which tapers towards the right. To the right of this shape is a white area. At the bottom, there is a horizontal orange bar that also tapers towards the right. The overall design is minimalist and geometric.


Day 1



World Wide Web


- The *World Wide Web* (*Web*) is a network of information resources.
- The **Web** relies on three **mechanisms** to make these resources readily available to the widest possible audience:
 - ▷ A uniform naming scheme for locating resources on the Web (e.g., **URLs**).
 - ▷ Protocols, for access to named resources over the Web (e.g., **HTTP**).
 - ▷ Hypertext, for easy navigation among resources (e.g., **HTML**).

Website




Client-side technologies used to create web sites.


Client-Server Model




Client-Server Model



Client-Server Model



Client-Server Model



Essential Technologies of WWW



HTML

Content & Structure.



CSS

Presentation



JavaScript

Behavior

HTML

The Mother Tongue of The Browser

HTML Background

- HTML stands for “Hyper Text Mark-up Language”.
- The language used to design Web Page.
- HTML was invented in 1990 by a scientist called Tim Berners-Lee. The purpose was to make it easier for scientists at different universities to gain access to each other's research documents.
- HTML standards are organized by W3C :
<http://www.w3.org/MarkUp/>

Hyper-Text-Markup-Language

- **Hyper** is the method by which you move around on the web.
- **Text** is self-explanatory.
- **Mark-up** is what **HTML tags** do to the text inside them.
- **Language** is what HTML is. It uses many English words.

Rough Timeline of Web Technologies

- 1991 HTML
- 1994 HTML 2
- 1996 CSS 1 + JavaScript
- 1997 HTML 4
- 1998 CSS 2
- 2000 XHTML 1
- 2002 Tableless Web Design
- 2005 AJAX
- 2006 jQuery
- 2009 HTML 5

<http://webdirections.org/history/>


HTML

- HTML is used for creating **static** web pages.
- It is designed to **display** data & focus on how data looks.
- HTML's role on the web is to tell the browser **how** a document should **appear**.

HTML Functionalities

- HTML gives authors the means to:
 - ▷ Publish online **documents** with headings, text, tables, lists, photos, etc.
 - Include video clips, sound clips, and other applications directly in their documents.
 - ▷ Link information via hypertext **links**, at the click of a button.
 - ▷ Design **forms** for conducting transactions with remote services, for use in searching for information, making reservations, ordering products, etc.

Sample Webpage



Sample Webpage HTML Structure

```
<!DOCTYPE HTML>
```

```
<html>
```

```
<head>
```

```
<title>First Demo</title>
```

```
</head>
```

```
<body>
```

```
<p>Welcome all</p>
```


```
<!-- The content of the document -->
```

```
</body>
```

```
</html>
```

Title tags

Body tags



HTML Document Basic Structure


- HTML documents contain text and various tags that define elements .
- HTML document contains `<html>` element that wraps
 - ▷ **head** section
 - The **title** of the document appears in the head along with other information about the document related to browser & search engine.
 - ▷ **body** section
 - The content of the document appears in the body.

Example!

Sample HTML Tags Example

- `<p>This is a paragraph.</p>`
- `Hello world`
- `Hi <i>Ahmed</i> Ali`
- `< a href="http://www.gamingegypt.com">`
click here
``
- `<i>Hello</i> world`
- `<hr/>`
- etc...

HTML Element Syntax



HTML Element Syntax

```
<start_of_tag attribute_name="attribute value">  
    Content  
</end_of_tag>
```

- An HTML element consists of an opening tag, a closing tag and the content inside.
- Tags tell the browser how it should display content on screen.
- Tags can have attributes, some tags have obligatory attributes.

HTML Element Syntax

```
<start_of_tag attribute_name="attribute value">  
    Content  
</end_of_tag>
```

- Attributes provide **additional information** about the element to configure and adjust the behavior of tag.
- Attributes are always specified in **the start tag**.
- Attributes come in name/value pairs like:
name="value".

HTML Element Syntax

- Each element has a number of properties associated with it:
 - ▷ starts with a **start tag / opening tag**, begins with a (<) and ends with a (>).
 - ▷ ends with an **end tag / closing tag**, begins with a (</) and ends with a (>).
 - ▷ The **element content** is everything between the start and the end tag.
 - ▷ Some HTML elements have **empty content**.
 - ▷ Empty elements are **closed in the start tag**.
 - ▷ Most HTML elements can have **attributes**.
 - ▷ HTML documents consist of nested HTML elements.
 - Most elements can contain other HTML elements.

General Element Attributes



- Core Attributes

- ▷ Used on the majority of HTML elements (although not all)
- ▷ Not valid in base, head, html, meta, script, style, and title elements.

Attribute	Value	Description
class	<i>classname</i>	Specifies a classname for an element
id	<i>id</i>	Specifies a unique id for an element
style	<i>style_definition</i>	Specifies an inline style for an element
title	<i>text</i>	Specifies extra information about an element. It is often displayed as a tooltip or while the element is loading.

HTML Document Elements Hierarchy

HTML page is like a tree, series of nested elements (tags)



<head> Element

- 1st Child of <html> element
- Many elements may be nested as a child for <head>

Child Tag	Description
<title>	defines the title of the document, its required.
<style>	Defines style information for a document
<script>	Used to define a Client-Side script. Either contains scripting statements or points to an external file
<link>	Defines the relationship between a document and an external resource
<meta>	provides metadata about the HTML document, like page description, keywords, author of the document, last modified
<base>	specifies a default address or a default target for all links on a page

<title> Tag

- Defines the title of the document
- Shown in Tab
- Used in adding the page to favorite or bookmark list

```
<html>  
  <head>  
    <title>Trial Demo</title>  
  </head>  
</html>
```

<meta> Tag

- Meta tags are used to store information usually relevant to browsers and search engines.
 - ▷ Provides additional information about the page; for example, which character encoding the page uses, a summary of the page's content, instructions to search engines about whether or not to index content, and so on.
 - ▷ Define the author of the document as well as the content of the webpage.

```
<meta name="description" content="an html tutorial" />
```

```
<meta name="keywords" content="html, webdesign, javascript" />
```

```
<meta name="author" content="bill gates" />
```

```
<meta http-equiv="refresh" content="5; url=http://www.abc.com" />
```

<!-- --> Tag

- <!-- --> is the comment tag of html.
- Its used to insert comments in the source code, either as head child or body child.
- Comments are not displayed in the browsers.

- Example:

```
<html>  
  <head>  
    <!--This is a comment in head section-->  
  </head>  
  <body>  
    <!--This is a comment in body section-->  
    <p>This is a paragraph.</p>  
  </body>  
</html>
```

<body> Element

- Last Child of <html> element
- The <body> element defines the document's body.
- Many elements may be nested as a child for <body>
- Inside <body> Section:
 - **Text**
 - ▷ Formatting
 - ▷ Resizing
 - ▷ Layout
 - ▷ Listing
 - **Links**
 - ▷ To local pages
 - ▷ To pages at other sites
 - ▷ To bookmarks
 - **Forms**
 - **Tables**
 - **Images**
 - ▷ Inserting images (GIF & jpg)
 - ▷ Adding a link to an image

Text Format Appearance

Tag	Description
<code>text</code>	writes text as bold
<code><i>text</i></code>	writes text in italics
<code><u>text</u></code>	writes underlined text
<code>text</code>	defines emphasized text
<code><sub>text</sub></code>	lowers text and makes it smaller
<code><sup>text</sup></code>	lifts text and makes it smaller
<code>text</code>	defines text that has been deleted from a document.
<code><ins>text</ins></code>	defines text that has been inserted into a document.
<code><strike>text</strike></code>	strikes a line through the text
<code>text</code>	usually makes text bold

Text Size Appearance

Tag	Description
<code><big>text</big></code>	increase the size by one
<code><small>text</small></code>	decrease the size by one
<code><h1>text</h1></code>	writes text in biggest heading
<code><h6>text</h6></code>	writes text in smallest heading

Text Layout

Tag	Description
<code><p>text</p></code>	Adds a paragraph break after the text.
<code><p align="left center right"> text </p></code>	Directs the alignment of text in paragraph.
<code><pre>text</pre></code>	writes text exactly as it is, including spaces.
<code><center>text</center></code>	Center text.
<code><div> text</div></code>	Defines a section in a document
<code>text</code>	

Example!

Block vs. Inline Elements

- Block elements

- ▷ Container elements for grouping other elements.
- ▷ May contain other block elements & inline elements.
- ▷ Normally start (and end) with a new line when displayed in a browser.
e.g. `<div>`, `<p>`, `<h1>`..`<h6>` etc.

- Inline elements

- ▷ Container for text and other inline elements.
- ▷ Normally displayed without starting a new line.
e.g. ``, ``, `<td>`, `<a>`, `<i>` etc.

<div> vs.

- **<div>** Defines a section in a document (block-level)
 - ▷ creates logical divisions within a page
- **** Defines a section in a document (inline)
 - ▷ Useful for modifying a specific portion of text
- HTML elements can be grouped together with **<div>** and ****.
- Useful with CSS

Example!

Text breaking and white space

- Whitespace generally ignored in block and inline
- `<pre>`
 - ▷ whitespace is respected
- `
`
 - ▷ Explicit line break
- `<hr />`
 - ▷ Horizontal rule
- Use Character entities
 - entities for HTML markup characters.

Special Character Entities

- Entities are used to implement reserved characters or to express characters that cannot easily be entered with the keyboard.
- Syntax:
`&entity_name` or `&#entity_num`

Special Character Entities

Name	Symbol	HTML Equivalent
Ampersand	&	& or &
cent sign	¢	¢ or ¢
copyright symbol	©	© or ©
degree sign	°	° or °
greater than	>	> or >
less than	<	< or <
non-breaking space		 or
registered trademark	®	® or ®

Special Character Entities

Name	Symbol	HTML Equivalent
trademark	™	™ or ™
quotation mark	“	" or "
apostrophe	‘	' or '
Euro	€	€ or €
British Pound	£	£ or £
Japanese Yen	¥	¥ or ¥
Cent sign	¢	¢ or ¢

HTML Lists

- HTML supports
 - ▷ ordered “Numbered” lists,
 - ▷ unordered “Bulleted” lists, &
 - ▷ definition lists.

Numbered List

- An ordered list starts with the `` tag.
- `` tag to define list items.

Attribute	Value	Description
Start	Number (default) Capital letter	Use styles instead. Specifies the start point in a list
Type	Small letter Capital Roman # Small Roman #	Use styles instead. Specifies which kind of bullet points will be used

```
<ol start="5">  
  <li>text</li>  
  <li>text</li>  
</ol>
```

```
<ol type="A">  
  <li>text</li>  
  <li>text</li>  
</ol>
```

Bulleted Lists

- An unordered list starts with the `` tag.
- `` tag to define list items.
- You have the following bullet options as a value for *type* attribute:
 - ▷ **disc** (default)
 - ▷ **circle**
 - ▷ **square**

```
<ul type="circle">  
  <li>text</li>  
  <li>text</li>  
</ul>
```

```
<ul type="disc">  
  <ul type="circle">  
    <ul type="square">
```

Example!

Definition List

- An definition list starts with the `<dl>` tag.
- `<dt>` definition term tag present the item in the list to be defined.
- `<dd>` definition description tag is used to describe an item in a definition list.

```
<dl>  
  <dt>Coffee</dt>  
    <dd>- black hot drink</dd>  
  <dt>Milk</dt>  
    <dd>- white cold drink</dd>  
</dl>
```

Example!

HTML Links

```
<a href="url" target="">Link text</a>
```

Click [here](http://www.yahoo.com) to go to yahoo.

- Image link content

```
<a href="myfile.htm"></a>
```

- Link Within a Page

- ▷ To link to an anchor you need to:

- Create a link pointing to the anchor
- Create the anchor itself.

```
< tag id|name="top"></tag>
```

```
<a href="#top">Top</a>
```

- Link to email

```
<a href="mailto:email@hotmail.com?subject=SweetWords  
&body=Please send me a copy of your new program!">  
Email Me
```

```
</a>
```

HTML Images

```
<img src="" width="" height="" alt="" />
```

- Images commonly types used in browsers are : GIFs, JPEGs, & PNGs

```

```

```

```

- Alternative Text

```

```

- Resizing

```

```

Image Map

- Image maps are images, that have been divided into regions.
- Clicking in a region of the image cause the web surfer to be connected to a new URL.
- Image maps are graphical form of creating links between pages

Image Map

- Possible shapes for areas inside image are

```
<img src="" usemap= "#example" />
```



```
<map name= "example">  
  <area shape=rect coords= "x1,y1,x2,y2"  
    href="http://www.abc.com" />
```

```
  <area shape=circle coords= "x1,y1,x2,y2"  
    href="http://www.abc.com" />
```

```
  <area shape=polygon coords= "x1,y1,x2,y2,... xn,yn"  
    href="http://www.abc.com" />
```


.....

```
</map>
```



Cascading Style Sheets

*the sister technology to HTML that is
used to style your web pages*



Designed to separate presentation from content

CSS

- CSS stands for Cascading Style Sheets.
- CSS was developed by the W3C.
- CSS is a style sheet language used to describe the **presentation** of a document written in a markup language.
- Its most common application is to style web pages written in HTML, XHTML and **any** kind of XML document.
- Styles define **how to display** HTML elements (font face, size, color, alignment, ...etc)
- Styles are normally stored in *Style Sheets*
- The term **cascading** derives from the fact that multiple style sheets can be applied to the same Web page.
- Due to CSS, all HTML presentation **tags** and attributes are **deprecated**, e.g. **font**, **center**, etc

CSS Benefits

- With CSS we have the following benefits:

1. The Separation of Structure and Presentation

2. Managing Style at Large Sites

- ▷ Easy maintenance.

3. Improved performance

- ▷ Page load faster.

4. Decreased production work

- ▷ Saves time.

5. Rich design and layout

CSS Features

- Provides precise control over margins, line spacing, element placement, colors, font faces, and font sizes.
- Removes the need to re-type HTML style tags each time a new style is needed.
- Ensures every user sees the same view regardless of the ways in which the browser's size and colors are configured.
- Provides the ability to change the overall look of a Web page or even an entire site by changing a single style sheet.


CSS Versions

- Cascading Style Sheets 1 (CSS1)
 - ▷ Features: Fonts, Colors, Alignment, Spacing
- Cascading Style Sheets 2 (CSS2-CSS2.1)
 - ▷ Features: Layout, Positioning... (CSS-P)
- Cascading Style Sheets 3 (CSS 3)
 - ▷ Features: Effect, Sizing...

CSS Syntax

- A style sheet consists of the style rules that tell your browser **how** to present a document.
- The CSS syntax rule is made up of 5 parts:
 - 1.selector 4. declaration block
 - 2.property 5. declaration
 - 3.value
- **selector** is a pattern to be affected; separated by commas.
- **property** and **value** describe the appearance of that pattern; separated by colons; building a **declaration**.
- **declarations** are property-value pair; separated by semicolons; building a **declaration block**.
- Style rules are formed as follows:
selector {property: value}

CSS Rule



Implementing CSS

- CSS can be linked to an HTML document as:
 1. Embedding in `<head>` section using `<style>`
 2. Linking to an external style sheet file using
 - ▷ `<link>` element within head section
 - ▷ `@import` rule within style tag in the head section
 3. Inline style using `style` attribute
- Using external files is highly recommended

1. Embedding in a Style Tag

- Embedded, or **internal** styles are used for the whole page.
- You define internal styles in the **head** section by using the `<style>` tag
- An embedded (internal) style sheet should be used when a single document has a unique style.

<head>

<style type="text/css">

h1 { color: blue; }

h2 { color: red; }

</ style >

</head>

H1 header with blue color

H2 header with red color

Example!

2. Linking to an External Style Sheet File

- An external style sheet is ideal when the style is applied to many pages.
- With an external style sheet, you can change the look of an entire Web site by changing one file.
- Using `<link>` tag.
 - ▷ Basically links an external style sheet to the document.
 - ▷ The `<link>` tag goes inside the `head` section.

`<head>`

`<link rel=stylesheet type="text/css" href="style.css">`

`</head>`

Example!

2. Linking to an External Style Sheet File

■ Using **@import** rule

- ▷ Another way to link external CSS files
- ▷ Basically imports one style sheet into another.
- ▷ Placed at the top of the <style> or in external style sheets.
- ▷ Must come before any other declaration

```
<style type="text/css">
```

```
    @import url("styles1.css");
```

```
    /*same as*/
```

```
    @import "style1.css";
```

```
    p {color: yellow }
```

```
</style>
```

3. In-line Style

- In-line styles are plunked straight into the HTML tags using the **style** attribute.
- In-line style loses many of the advantages of style sheets by mixing content with presentation.
- In-line style should be avoided wherever possible

- Example:

<p style="color: red; font-family: 'Arial' ">

This paragraph is styled in red with the Arial font, if available.

</p>

Example!

CSS Comments

```
<style type="text/css">
```

```
/*
```

```
h1 { color: red; font-family: "Calibri";}
```

```
*/
```

```
</style>
```

Cascading Order

- “**Cascading** ” reflects the way styles are applied to the elements in a document, because style declarations cascade down to elements from many origins.
- Styles will be applied to HTML in the following order:
 1. Browser default
 2. External style sheet
 3. Internal style sheet (in head)
 4. Inline style
- When styles conflict, the “nearest” (most recently applied) style wins.

Grouping

- Grouping selectors is done by separating each selector with a comma to give the same properties to a number of selectors without having to repeat

h1,h2,h3,h4,h5,h6 { color: green; font-family: "Arial" }

Selectors



Example:

h1 { font-family: "sans-serif" }
h2 { font-family: "sans-serif" }
h3 { font-family: "sans-serif" }

is equivalent to:

h1, h2, h3 { font-family: "sans-serif" }

Example of Cascading Order

- External Style sheet

```
h3 {  color: red;  
      text-align: left;  
      font-size: 8pt  }
```

- Internal Style sheet

```
h3 {  text-align: right;  
      font-size: 20pt;  
      text-decoration: underline  
      }
```

- Resultant attributes

```
color: red;  
text-align: right;  
font-size: 20pt;  
text-decoration: underline
```

Example!

CSS Selectors

- Selectors determine which element the rule applies to:
 - ▷ All elements of specific type (tag)
 - ▷ Those that match a specific attribute (id, class)
 - ▷ Elements may be matched depending on how they are nested in the document tree (HTML)
 - ▷ Examples:
 - `.header{ color: green }`
 - `#menu{ padding-top: 8px }`

CSS Selectors

- Several types of selectors are defined for use when implementing Style Sheets:
 1. Simple Basic Selectors
 2. Attribute selectors
 3. Combinators
 4. Pseudo-Classes
 5. Pseudo-Elements
- A selector can contain a chain of one or more simple selectors separated by combinators, optionally followed by attribute selectors, ID selectors, or pseudo-classes. but it can contain only one pseudo-element, which must be appended to the last simple selector in the chain

1. Simple Basic Selectors

1. **Type Selector**
2. **IDs**
3. **Classes**
4. **Universal Selector**

1.1 Type Selector

- In general, **STYLE** attribute can be added to any HTML element.
- Example:

```
<span style = ' font-family: "sans serif "; color: blue; text-align: center '>  
Hello There!  
</span>
```
- Type selector selects an element of the HTML document: P, H1, BODY, etc.
- Example:

```
h1 {color: blue;}
```

1.2 ID Selector

- The ID attribute is used to define a unique style for an element.

- Example:

- ✓ In the CSS

#id1 {color: red}

- ✓ In the HTML

<div id="id1">

**This is the div with the id.
</div>**

1.2 ID Selector

- Example2:

- ✓ In the CSS

- `div#id1 {color: red}`

- ✓ In the HTML

- `<div id="id1">`

- `This is the div with the id.`

- `</div>`

1.3 Classes Selector

- Classes allow you to define a style which can be applied to multiple elements on your page.
- Example 1:
 - To apply one class over more than one different HTML element:
 - ✓ In the CSS
 - `.bold { font-weight: bold }`**
 - ✓ In the HTML
 - `<p class="bold">`**
 - This paragraph will be Bold.`</p>`**
 - ``**
 - This SPAN will be Bold too.``**
- Both the paragraph & the span elements will be styled by the class "bold".

1.3 Classes Selector

- Example 2:

- To apply more than one class per given element:

- ✓ In the CSS

.bold { font-weight: bold }

.large { font-size: 20pt }

- ✓ In the HTML

<p class="bold large">

This paragraph will be Bold & very large.

</p>

- The paragraph above will be styled by the class "bold" AND the class "large".

1.3 Classes Selector

■ Example 3:

- Say that you would like to have two types of paragraphs in your document: one right-aligned paragraph, and one center-aligned paragraph. Here is how you can do it with styles:

✓ In the CSS

```
p.right {text-align: right}
```

```
p.center {text-align: center}
```

✓ In the HTML

```
<p class="right">This paragraph will be right-aligned. </p>
```

```
<p class="center">
```

```
  This paragraph will be center-aligned.
```

```
</p>
```

Example!

HTML Online References

- www.w3schools.com
- www.tutorialspoint.com
- www.quackit.com
- www.htmlcodetutorial.com
- www.htmlquick.com
- www.htmldog.com
- <https://developer.mozilla.org/en-US/docs/Web/HTML/Element>
- www.tutorialehtml.com/en/index.php



Assignments