21CY681- Internet Protocol lab -10

Name: Meera E Thimothy

Roll No: CB.EN.P2CYS22002

<u>Title:</u> Analyzing bit torrent and BHT protocols using wireshark

Open Wireshark in the background by choosing the appropriate interface.

- 3. Then open your torrent file and start the download at least 20%. Stop the capture and document the answers to the following questions:
- a. Give a detailed study about the working of BitTorrent in your downloading scenario.

BitTorrent peer-to-peer (P2P) protocol finds users with files other users want and then downloads pieces of the files from those users simultaneously.

Once connected, a BitTorrent client downloads bits of the files in the torrent in small pieces, downloading all the data it can get. Once the BitTorrent client has some data, it can then begin to upload that data to other BitTorrent clients in the swarm. In this way, everyone downloading a torrent is also uploading the same torrent. This speeds up everyone's download speed.

b. Working of BitTorrent.

BitTorrent is a peer-to-peer protocol, which means that the computers in a BitTorrent "swarm" (a group of computers downloading and uploading the same torrent) transfer data between each other without the need for a central server.

c. Protocol Level Analysis

BITTORENT -


0.		Time	Source	Destination	Protocol	Lengt	Info
c	1	0.000000	192.168.251.101	46.139.90.206	BitTorre	122	Handshake
	2	0.049250	192.168.251.101	95.54.143.159	BitTorre	122	Handshake
	3	0.238092	46.139.90.206	192.168.251.101	BitTorre	350	Handshake Extended Have All Unchoke
	671	21.001734	192.168.251.101	94.181.246.57	BitTorre	122	Handshake
	672	21.299328	94.181.246.57	192.168.251.101	BitTorre	146	Handshake
	676	21.451330	192.168.251.101	5.137.116.142	BitTorre	122	Handshake
	704	22.233648	5.137.116.142	192.168.251.101	BitTorre	359	Handshake Extended Have All Port Unchoke
	819	23.746221	192.168.251.101	192.168.251.59	BitTorre	122	Handshake
	2423	68.340296	192.168.251.101	95.54.143.159	BitTorre	122	Handshake
	2509	71.735390	192.168.251.101	192.168.251.59	BitTorre	122	Handshake
	2511	72.742086	2409:4072:2e0c:d03d:e5e4:5cb9:c5	2409:4072:2e0c:d03d:92f	BitTorre	142	Handshake
	2512	72.747143	2409:4072:2e0c:d03d:450:aa14:ded	2409:4072:2e0c:d03d:e26	BitTorre	142	Handshake
	2513	72.747364	2409:4072:2e0c:d03d:92f1:aa15:9d	2409:4072:2e0c:d03d:e5e	BitTorre	158	Handshake
	2515	72.748146	2409:4072:2e0c:d03d:e267:b981:b8	2409:4072:2e0c:d03d:450	BitTorre	182	Handshake
	4848	115.276935	2409:4072:8ea1:ca02:4db9:49fa:791	2409:4072:2e0c:d03d:e5e	BitTorre	142	Handshake
	6613	140.158541	192.168.251.101	95.54.143.159	BitTorre	122	Handshake
	6615	140.525812	95.54.143.159	192.168.251.101	BitTorre	163	Handshake
	8679	182.199835	2409:4072:8ea1:ca02:c50f:10d3:7e6	2409:4072:2e0c:d03d:e26	BitTorre	142	Handshake
1	3005	244.310414	2409:4072:2e0c:d03d:e5e4:5cb9:c5	2a03:ec00:b97c:e06f:45e	BitTorre	142	Handshake
	2000	244240002	2400 4072 2 0 102 1 5 45 10 5	2 02 001 440 4 7 104	DUT	***	., ., .

> [SEQ/ACK analysis]

ODED ON DE DE 52 41 40 96 de 40 40 60 h0 Ed 26 51 4E 16 1004 Au Tu




DHT






d. Tracker's status.




Here we can be able to see that the name of the tracker is i-6000.b-46591.ut.bench.utorrent.com

e. DHT status




Here we can see that while downloading the torrent file the DHT status is set to working.



Here while seeding the DHT status is set as disabled.

f. Identify other peers involved in the communication

From the below screenshot we can see that there are sevreral nodes which represents a peer and it sip address and port number is shown



g. Try to identify the name of the file downloded

bt-dht.bencoded.string == 25f241c88bdc49c9b05da6f145164018a22f050a

```
v info hash: 25f241c88bdc49c9b05da6f145164018a22f050a
       Key: info hash
        Value: 25f241c88bdc49c9b05da6f145164018a22f050a
∨ BitTorrent DHT Protocol
  Request arguments: Dictionary...
        Key: a

→ Value: Dictionary...
        v id: dff503d6ae529049f1f1bbe9ebb3a6db3c870ce1
             Key: id
             Value: dff503d6ae529049f1f1bbe9ebb3a6db3c870ce1
        v implied_port: 1
             Key: implied_port
             Terminator: e
             Value: 1
        v info_hash: 25f241c88bdc49c9b05da6f145164018a22f050a
             Key: info hash
             Value: 25f241c88bdc49c9b05da6f145164018a22f050a
          name: Minecraft
             Key: name
             Value: Minecraft
```

- 4. Try to export the 20% of data you have captured as traffic in Wireshark while downloading files in Torrent.
- 5. After the Download completes and when it starts seeding, open the Wireshark and analyze the information being transferred in that traffic. Document the difference in Network traffic.

2320 2022/344 09:20:37.449239 2409:4072:e95:dba2:	55082 2404:6800:4007:819:	443 TCP	86 [TCP Dup ACK 2318#1] 55082 + 443 [ACK] Seg=3 Ack=74 Win=510 Len=0 SLE=1 SRE=74
2321 2022/344 09:20:37.459217 192.168.137.150	27835 176.96.249.117	37076 BT-uTP	62 Connection ID:57312 [Fin] Seq=27001 Ack=26484 Win=50000 Len=0
2322 2022/344 09:20:37.461204 35.213.12.39	443 192.168.137.150	55233 TLSv1.2	85 Encrypted Alert
2323 2022/344 09:20:37.461204 35.213.12.39	443 192.168.137.150	55233 TCP	54 443 + 55233 [FIN, ACK] Seq=560 Ack=1535 Win=501 Len=0
2324 2022/344 09:20:37.461293 192.168.137.150	55233 35.213.12.39	443 TCP	54 55233 + 443 [ACK] Seq=1535 Ack=561 Win=510 Len=0
2325 2022/344 09:20:37.461493 2404:6800:4007:819:	443 2409:4072:e95:dba2:_	55082 TCP	74 443 + 55082 [FIN, ACK] Seq=74 Ack=3 Win=282 Len=0
2326 2022/344 09:20:37.461555 2409:4072:e95:dba2:	55082 2404:6800:4007:819:	443 TCP	74 55082 + 443 [ACK] Seq=3 Ack=75 Win=510 Len=0
2327 2022/344 09:20:37.509723 138.199.14.86	443 192.168.137.150	55009 TCP	66 [TCP Dup ACK 332#5] 443 + 55009 [ACK] Seq=2 Ack=1 Win=501 Len=0 SLE=0 SRE=1
2328 2022/344 09:20:38.262704 192.168.137.150	55374 91.232.158.75		66 [TCP Retransmission] [TCP Port numbers reused] 55374 → 11327 [SYN] Seq=0 Win=64240 Len=0 MSS=146

Here we didn't get any packets for seeding. Since there wasn't any seeding done by our system.