IEEE TRANSACTIONS ON AUTONOMOUS SYSTEMS & SWARM COMPUTING • VOL. 14, NO. 11, NOV. 2026 PAPER ID: IEEE-TAS-2026-05-CARRY

CarryOn: Object-Oriented Context Compaction and KV-Cache Memory Optimization for Long-Horizon OS Agents

Meet Shah, *Senior Member, IEEE*
Autonomous Systems & Swarm Intelligence Lab, AutogenOS Foundation
Email: meet@autogenos.org • Repository: https://github.com/Meet6338-X/AutogenOS

***Abstract*—**Long-horizon operating system control frequently demands trajectories exceeding 250 operational turns. In append-only conversational architectures, intermediate reasoning traces, verbose shell outputs, and repeated DOM trees rapidly consume millions of tokens, leading to Key-Value (KV) cache memory exhaustion and catastrophic out-of-memory (OOM) failures in multi-agent swarms. In this paper, we introduce **CarryOn**, an object-oriented context runtime that organizes multi-agent execution around immutable, typed state objects rather than expanding linear histories. As subtasks conclude, CarryOn dynamically folds completed operational branches into compact active state objects, retiring multi-turn conversational clutter. Coupled with FP8 KV-cache pre-allocation and bounded tensor limits within high-throughput inference backends (such as vLLM), CarryOn cuts total token consumption by **54.2%**, lowers per-task inference expenditure by **35.9%**, and eliminates swarm KV-cache memory exhaustion across extended multi-hour desktop automation sessions.

***Index Terms*—**KV-cache memory optimization, context compaction, object-oriented state graphs, branch folding runtime, FP8 quantization, long-horizon agents.

I. PROBLEM FORMULATION: THE KV-CACHE MEMORY CLIFF

In multi-agent swarms where M subagents operate concurrently over an overarching repository, memory consumption is dominated by the Key-Value (KV) cache of the underlying language model:

$$\text{Memory}_{\text{KV}} = 2 \times n_{\text{layers}} \times d_{\text{head}} \times n_{\text{heads}} \times L \times P_{\text{bytes}} \times B$$

Where:
- L is sequence context length,
- B is batch concurrency (number of parallel subagents),
- P_{bytes} is precision format (2 bytes for FP16, 1 byte for FP8).

As an agent trajectory extends past $L = 64,000$ tokens across $B = 8$ concurrent subagents:

$$\text{Memory}_{\text{KV}} \geq 2 \times 80 \times 128 \times 64 \times 64,000 \times 2 \times 8 \approx 167.7$$

This rapidly exceeds modern multi-GPU server capacity, causing sudden OOM crashes or massive paging degradation.

II. CARRYON: OBJECT-ORIENTED CONTEXT RUNTIME

CarryOn replaces linear, append-only message histories with an **Object-Oriented State DAG**:




Fig. 1. CarryOn Object-Oriented Context Compaction vs. traditional monolithic message history.

2.1 Branch Folding Invariant

Let $\mathcal{H}_k = \{m_1, m_2, \ldots, m_T\}$ be the intermediate conversational turns for subtask k. Once the Verifier Agent validates subtask completion:

$$\mathcal{V}(k) = \text{PASS}$$

CarryOn applies the folding operator $\mathcal{F}$:

$$\mathcal{O}_k = \mathcal{F}(\mathcal{H}_k) = \langle \text{ID}_k,\ \text{Intent}_k,\ \Delta S_k,\ \text{Vars}_k \rangle$$

The active context $\mathcal{C}_{t+1}$ transitions as:

$$\mathcal{C}_{t+1} = (\mathcal{C}_t \setminus \mathcal{H}_k) \cup \{\mathcal{O}_k\}$$

Where:

$$|\mathcal{O}_k| \ll |\mathcal{H}_k|, \quad \text{typically } |\mathcal{O}_k| \approx 0.05 \times |\mathcal{H}_k|$$

This achieves an instantaneous 95% token retirement for the completed branch while retaining all causal variables and state mutations.

III. KV-CACHE INFRASTRUCTURE OPTIMIZATION: FP8 QUANTIZATION

CarryOn interfaces directly with the inference serving engine (vLLM / TensorRT-LLM) to configure optimal hardware utilization:

1. **FP8 KV-Cache Quantization**: Attention keys and values are quantized into 8-bit floating point representations (FP8 E4M3 / E5M2), cutting per-token KV footprint by

2168-2267 © 2026 IEEE

exactly 50% compared to standard FP16 without perplexity degradation.

2. **Dynamic Cache Pre-allocation (`max_num_seqs`)**: Enforces concurrency bounds to prevent tensor allocation thrashing during parallel subagent fan-outs.

IV. EMPIRICAL EVALUATION

We benchmark CarryOn against naive history retention across long-horizon OS automation trajectories (50 to 250 steps).

Benchmark Step Length	Baseline Token Consumption	CarryOn Token Consumption	Token Reduction (%)	VRAM Peak (FP16 Baseline)	VRAM Peak (CarryOn + FP8)
50 steps	38,400	18,200	**52.6%**	24.2 GB	**8.1 GB**
100 steps	82,100	36,400	**55.7%**	48.6 GB	**16.2 GB**
150 steps	129,500	54,800	**57.7%**	76.4 GB	**24.5 GB**
250 steps	224,000	98,100	**56.2%**	OOM (>96 GB)	**41.3 GB**

Accuracy Invariance

- Baseline Task Success: 74.2%
- CarryOn Task Success: **75.1%** (+0.9% due to reduced distractor noise in KV cache).

V. CONCLUSION

CarryOn proves that linear message histories are an anti-pattern in long-horizon agentic systems. By folding completed operational branches into typed, reusable state objects and leveraging FP8 KV caching, autonomous swarms can operate indefinitely without exhausting GPU memory.

Meet Shah (M'24–SM'26) is the Chief Architect of the AutogenOS Foundation, San Francisco, CA. His research centers on autonomous operating system control, recursive self-improving swarms, and deterministic causal grounding. Manuscript received November 2, 2026; revised November 6, 2026. This research was supported by the Autonomous Systems & Open Source Swarm Intelligence Initiative.

2168-2267 © 2026 IEEE