

- 2.10 A DSB-SC modulated signal is demodulated by applying it to a coherent detector.
- Evaluate the effect of a frequency error Δf in the local carrier frequency of the detector, measured with respect to the carrier frequency of the incoming DSB-SC signal.
 - For the case of a sinusoidal modulating wave, show that because of this frequency error, the demodulated signal exhibits *beats* at the error frequency. Illustrate your answer with a sketch of this demodulated signal.

- 2.18 Figure P2.18 shows the block diagram of *Weaver's method* for generating SSB modulated waves. The message (modulating) signal $m(t)$ is limited to the band $f_a \leq |f| \leq f_b$. The auxiliary carrier applied to the first pair of product modulators has a frequency f_0 , which lies at the center of this band, as shown by

$$f_0 = \frac{f_a + f_b}{2}$$

The low-pass filters in the in-phase and quadrature channels are identical, each with a cutoff frequency equal to $(f_b - f_a)/2$. The carrier applied to the second pair of product modulators has a frequency f_c that is greater than $(f_b - f_a)/2$. Sketch the spectra at the various points in the modulator of Figure P2.18, and hence show that:

- For the lower sideband, the contributions of the in-phase and quadrature channels are of opposite polarity, and by adding them at the modulator output, the lower sideband is suppressed.
- For the upper sideband, the contributions of the in-phase and quadrature channels are of the same polarity, and by adding them, the upper sideband is transmitted.
- How would you modify the modulator of Figure P2.18 so that only the lower sideband is transmitted?




FIGURE P2.18