

SPECIFICATION FOR PRECISION SHAFT & FLANGE ASSEMBLY

Document No: MEC-ENG-2024-001 | Revision: C

Table of Contents

1 Scope 1

2 System Requirements 1

3 Manufacturing Tolerances 4

1 Scope

This engineering specification governs the precision machining, dimensional limits, and quality inspection for heavy industrial centrifugal pump drive shafts.

2 System Requirements

- The pump shaft operates in harsh environmental conditions.
- The maximum operating temperature = 80°C under continuous rated load.
- Verify that all maintenance schedules are strictly followed.
- The assembly must withstand maximum operating pressure = 10 bar without leakage.

3 Manufacturing Tolerances

3.1 Shaft Machining Limits

Critical bearing journal diameter tolerance = ± 0.5 mm on all bearing seating zones.
The specified surface roughness = 3.2 μ m for general unground surfaces.

3.3 Environmental Operating Limits

The drive shaft maximum operating temperature = 60°C during continuous operation.
Note that teh pump casing was recieved in good condition.

Table 1: Critical Component Dimensions

Component	Nominal Dimension	Machining Tolerance
Shaft Journal	50 mm	± 0.05 mm
Flange Collar	120 mm	-
Coupling Hub	12.5 cm	± 0.02 mm