

Name - Meet Kadam

Roll No. - 43

Batch - T12

EXPERIMENT 3

Aim: To Perform various GIT operations on local and Remote repositories.

Theory :

Directory and File Commands

- **mkdir git**
Creates a new directory (folder) named "git" in the current working directory. This command is used to create a new directory in Unix-like operating systems.
- **cd git**
Changes the current working directory to the directory named "git." After executing this command, all subsequent commands or file operations will occur within the "git" directory.
Note: "cd" stands for "change directory."
- **nano index.html**
Opens the Nano text editor for the file named "index.html." Nano is a simple command-line text editor that allows you to view and edit files directly in the terminal.
- **touch teststatus**
Creates an empty file named "teststatus" in the current directory. The **touch** command is commonly used to update the timestamps of a file or create an empty file if it doesn't exist.
- **git checkout -- teststatus**
Discards changes to the file "teststatus" in the working directory. This reverts the file to the state it has in the last commit.

Git Configuration

- **git config --global user.name "Your Name"**
Sets your global Git username, which will be associated with your commits.
- **git config --global user.email "youremail@example.com"**
Sets your global Git email address, which will be associated with your commits.
- **git config --list**
Displays the current configuration settings for Git, including user details and other preferences.

Staging and Committing Changes

- **git add <file>**
Stages changes in the working directory for the next commit in Git. It prepares modifications, additions, or deletions to be included in the upcoming commit.
- **git commit -am "commit message"**
Stages and commits all changes in tracked files with a commit message in a single command. This is a shorthand for **git add <file>** followed by **git commit**.
- **git log**
Displays the commit history of the Git repository, showing a chronological list of commits, including commit hashes, author information, timestamps, and commit messages.
- **git log --oneline**
Displays a simplified, one-line representation of the commit history, showing only the commit SHA-1 hash and the commit message.

Git Remote Operations

- **git clone <repository>**
Creates a copy of a Git repository. This command duplicates the entire repository (files, commit history, branches) and downloads it to your local machine. It is often the initial step when working with a project hosted on a remote Git repository.
- **git pull**
Fetches and integrates changes from a remote repository into the current branch of your local repository. It combines two actions: it fetches changes from the remote repository and merges them into your local branch.
- **git push**
Uploads or pushes local changes from your Git repository to a remote repository. It updates the remote repository with the latest changes made in your local branch.
- **git fetch**
Retrieves changes from a remote repository, including new branches or changes made since your last interaction. However, it does not automatically merge these changes into your local branches. After using **git fetch**, you can inspect the changes and decide whether to integrate them using **git merge** or **git rebase**.

```
Lab203@203-003 MINGW64 ~/git-dvcs43 (master)
```

```
$ git config --global
```

```
usage: git config [<options>]
```

Config file location

```
--[no-]global      use global config file
--[no-]system      use system config file
--[no-]local       use repository config file
--[no-]worktree    use per-worktree config file
-f, --[no-]file <file>
                  use given config file
--[no-]blob <blob-id> read config from given blob object
```

Action

```
--[no-]get         get value: name [value-pattern]
--[no-]get-all    get all values: key [value-pattern]
--[no-]get-regex   get values for regexp: name-regex [value-pattern]
--[no-]get-urlmatch get value specific for the URL: section[.var] URL
--[no-]replace-all replace all matching variables: name value [value-pattern]
```

ern]

```
--[no-]add         add a new variable: name value
--[no-]unset       remove a variable: name [value-pattern]
--[no-]unset-all  remove all matches: name [value-pattern]
--[no-]rename-section rename section: old-name new-name
--[no-]remove-section remove a section: name
-l, --[no-]list    list all
--[no-]fixed-value use string equality when comparing values to 'value-pattern'
```

ttern'

```
-e, --[no-]edit    open an editor
--[no-]get-color    find the color configured: slot [default]
--[no-]get-colorbool find the color setting: slot [stdout-is-tty]
```

Type

```
-t, --[no-]type <type>
                  value is given this type
--bool           value is "true" or "false"
--int            value is decimal number
--bool-or-int    value is --bool or --int
--bool-or-str    value is --bool or string
--path           value is a path (file or directory name)
--expiry-date    value is an expiry date
```

Other

```
-z, --[no-]null    terminate values with NUL byte
--[no-]name-only   show variable names only
--[no-]includes    respect include directives on lookup
--[no-]show-origin show origin of config (file, standard input, blob, command line)
```

```
--[no-]show-scope  show scope of config (worktree, local, global, system, command)
```

```
--[no-]default <value>
                  with --get, use default value when missing entry
```

```
Lab203@203-003 MINGW64 ~/git-dvcs43 (master)
```

```
$ git config --global user.name "meetk"
```

```
Lab203@203-003 MINGW64 ~/git-dvcs43 (master)
```

```
$ AC
```

```
Lab203@203-003 MINGW64 ~/git-dvcs43 (master)
```

```
$ git config --global user.email "meetkadam1812@gmail.com"
```

```
Lab203@203-003 MINGW64 ~/git-dvcs43 (master)
```

```
$ git config --global --list
```

```
user.name=meetk
```

```
user.email=meetkadam1812@gmail.com
```

```
15L@203-005 MINGW64 ~/git-dvcs (master)
$ mkdir git-demo-project

15L@203-005 MINGW64 ~/git-dvcs (master)
$ cd git-demo-project/

15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git init
Initialized empty Git repository in C:/Users/15L/git-dvcs/git-demo-project/.git/
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ ls -a
./ ../ .git/

15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ ls -al
total 4
drwxr-xr-x 1 15L 197121 0 Feb 12 11:10 ./
drwxr-xr-x 1 15L 197121 0 Feb 12 11:10 ../
drwxr-xr-x 1 15L 197121 0 Feb 12 11:10 .git/
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git add .

15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git status
On branch master
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git commit -m "First Commit"
[master (root-commit) 54ca444] First Commit
1 file changed, 1 insertion(+)
create mode 100644 index.html
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        index.htm

nothing added to commit but untracked files present (use "git add" to track)
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git add index.htm

15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        new file:   index.htm
```

```
15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git commit -am "Express commit"
[master 9404a12] Express commit
1 file changed, 1 insertion(+)
create mode 100644 index.htm

15L@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git status
On branch master
nothing to commit, working tree clean
```

```

LSL@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git log
commit 9404a121df804bffa5b7ed0f5304521509dfdc632 (HEAD -> master)
Author: ashvika <ashvikavk@gmail.com>
Date:   Wed Feb 12 11:35:09 2025 +0530

    Express commit

commit 54ca444578d21cdb937f12faa216b08c43bbf9de
Author: meetk <meetkadam1812@gmail.com>
Date:   Wed Feb 12 11:17:55 2025 +0530

    First Commit

LSL@203-005 MINGW64 ~/git-dvcs/git-demo-project (master)
$ git log --oneline
9404a12 (HEAD -> master) Express commit
54ca444 First Commit

```

Conclusion : Successfully performed various GIT operations on local and Remote repositories.