Lab 2 – Report

Meet Kansara – 220929270 Roll no. 54

Aim: To familiarize with ROS2 by creating and executing sample codes, publisher-subscriber models.

Code Execution and analysis:

- Nodes: sample, publisher, subscriber
- Topic: robot_news
- Messages displayed:
    a. Congratulation for starting your Robot Operating System Lab!!
    b. Hello ROBOT
    c. Greetings from COBOT

1. Writing and Executing a Sample Node

```python
#!/usr/bin/env python3
import rclpy
from rclpy.node import Node
class MyNode(Node): #MIDIFY NAME OF THE CLASS
    def __init__(self):
        super().__init__('sample')
        self.create_timer(0.2, self.timer_callback)

    def timer_callback(self):
        self.get_logger().info("Congratulation for starting your Robot Operating Syatem Lab!!")


def main(args=None):
    rclpy.init(args=args)
    node = MyNode()
    rclpy.spin(node)
    rclpy.shutdown()


if __name__ == '__main__':
    main()
```



2. Creating a Publisher Node

```python
#!/usr/bin/env python3
import rclpy
from rclpy.node import Node
from example_interfaces.msg import String
class RobotPublisher(Node):

    def __init__(self):
        super().__init__("publisher")
        self.robot_name_="ROBOT"
        self.publisher_ = self.create_publisher(String, "robot_news", 10)
        self.timer_ = self.create_timer(0.5, self.publish_news)
        self.get_logger().info("Node Started")


    def publish_news(self):
        msg = String()
        msg.data = "Hello " + str(self.robot_name_)
        self.publisher_.publish(msg)

def main(args=None):
    rclpy.init(args=args)
    node = RobotPublisher()
    rclpy.spin(node)
    rclpy.shutdown()
if __name__ == '__main__':
    main()
```



3. Creating a Subscriber Node

```python
#!/usr/bin/env python3
import rclpy
from rclpy.node import Node
from example_interfaces.msg import String

class RobotSubscriber(Node):
    def __init__(self):
        super().__init__("subscriber")
        self.subscriber_ = self.create_subscription(String, "robot_news",
        self.callback_robot_news, 10)
        self.get_logger().info("Subscriber Node Started")

    def callback_robot_news(self, msg):
        self.get_logger().info("Receiving info: "+msg.data)


def main(args=None):
    rclpy.init(args=args)
    node = RobotSubscriber()
    rclpy.spin(node)
    rclpy.shutdown()


if __name__ == "__main__":
    main()
```



Conclusion: The lab successfully introduced ROS2 basics, enabling effective creation and execution of nodes for robotic applications.