MINOR PROJECT SYNOPSIS

Early Sepsis Identification Using Multimodal Clinical Data: A Predictive and Explainable Framework

Submitted in partial fulfillment of the

Requirements for the award of

Degree of Bachelor of Technology in

AIDS/AIML/IOT

Under the Supervision of

Dr. Sapna Yadav

Assistant Prof.

VIVEKANANDA INSTITUTE OF PROFESSIONAL STUDIES - TECHNICAL CAMPUS

Grade A++ Accredited Institution by NAAC

NBA Accredited for MCA Programme; Recognized under Section 2(f) by UGC;
Affiliated to GGSIP University, Delhi; Recognized by Bar Council of India and AICTE
An ISO 9001:2015 Certified Institution

Submitted By :

Name: Chehak, Meet goyal , Anmol Dua

University Roll No.: 06317711923, 07017711923, 09717711923

Semester : 7th Sem

Academic Year: 2023-2027

Table of Contents

S.No.	Topic	Page No.
1.	Introduction	3
2.	Literature Review	4
3.	Problem Statement & Feasibility Study	6
4.	Hardware and Software Requirements	7
5.	References	8

Introduction

1.1 Clinical Background and Global Burden

Sepsis is defined under the international **Sepsis-3 consensus** as a life-threatening organ dysfunction caused by a dysregulated host response to infection. If left unmanaged, the cascading inflammatory response leads to widespread endothelial damage, microvascular thrombosis, hemodynamic collapse, and multi-organ failure. Globally, sepsis represents an overwhelming public health challenge, accounting for an estimated **48.9 million incident cases and 11 million sepsis-related deaths annually**—representing roughly 20% of all global all-cause mortality.

In intensive care units (ICUs) and emergency departments, clinical prognosis is governed by a strict temporal window. During septic shock and severe sepsis, every hour of delayed targeted antimicrobial and fluid resuscitation therapy is associated with an approximate **7.6% increase in mortality risk**. Consequently, identifying patients in the pre-symptomatic or subclinical transition phase—hours before overt physiological collapse—is essential to improving survival rates.

1.2 Limitations of Conventional Clinical Scoring Systems

Standard clinical workflows rely on rule-based scoring systems such as the **Sequential Organ Failure Assessment (SOFA)**, **quick SOFA (qSOFA)**, **Systemic Inflammatory Response Syndrome (SIRS)**, and the **Modified Early Warning Score (MEWS)**:

- **Reactive Nature:** These bedside scores are designed to quantify established organ damage rather than forecast prospective physiological deterioration. By the time a patient triggers a **SOFA > 2** threshold, irreversible tissue hypoperfusion or cellular injury may already be underway.
- **Low Sensitivity & Static Snapshots:** Tools like qSOFA often demonstrate high specificity but low sensitivity in early-stage detection. Furthermore, traditional scores evaluate static, point-in-time measurements, failing to capture non-linear, temporal trajectories hidden within continuous vital signs.

1.3 Evolution of Computational & AI-Driven Sepsis Detection

To move from reactive scoring to proactive risk stratification, machine learning (ML) and deep learning (DL) models have been increasingly investigated across major clinical databases (e.g., MIMIC-III, MIMIC-IV, eICU, and the PhysioNet/Computing in Cardiology Challenge 2019):

- **Unimodal Tabular & Time-Series Models:** Early automated alerting algorithms relied on gradient-boosted decision trees (XGBoost, LightGBM, CatBoost) and Random Forests trained on tabular laboratory values and vital signs. Deep sequential

architectures—such as Long Short-Term Memory (LSTM) networks, Gated Recurrent Units (GRUs), and Temporal Convolutional Networks (TCNs)—further advanced the field by modeling irregular sampling frequencies and temporal dependencies.

- **The Paradigm Shift to Multimodal Fusion:** While physiological time-series provide continuous numerical signals, they often miss qualitative diagnostic cues recorded by clinicians. Recent research has shifted toward multimodal architectures that combine:
    1. **High-frequency continuous vitals** (heart rate, mean arterial pressure, respiratory rate, SpO_2.
    2. **Intermittent laboratory profiles** (serum lactate, arterial blood gas metrics, white blood cell counts, platelets, creatinine).
    3. **Unstructured clinical text** (nursing shift narratives, triage notes, progress notes) processed via domain-specific Large Language Models and Clinical Transformers (e.g., ClinicalBERT).
- Multimodal joint fusion and cross-attention mechanisms allow linguistic indicators of infection suspicion (such as patient lethargy or subtle skin changes) to contextualize subtle, borderline shifts in numerical vitals.

1.4 The Class Imbalance Problem and the "Accuracy Paradox"

A fundamental hurdle in developing reliable clinical AI systems for sepsis is severe data distribution skew:

- **The Accuracy Paradox:** In typical ICU cohorts, sepsis-positive temporal windows account for a minute fraction of overall hospital stays (often representing **1.5% to 5%** of all hourly records). A naive classifier optimizing purely for standard accuracy can achieve 95% accuracy by universally predicting the majority "non-sepsis" class, rendering the system clinically ineffective.
- **Mitigation Strategies:** To prevent model bias toward majority negative instances, modern pipelines employ synthetic data generation techniques (such as the **Synthetic Minority Over-sampling Technique (SMOTE)** and its adaptive variants like Borderline-SMOTE), alongside cost-sensitive loss functions (e.g., Focal Loss) and precision-recall optimization (AUPRC evaluation rather than AUROC alone).

Literature Review & Research Gaps

2.1 Literature Review

The development of algorithmic sepsis prediction has evolved across four distinct paradigms: standard clinical rule-based systems, statistical and ensemble-based machine learning, deep sequential modeling, and multimodal deep learning architectures.

- **Clinical Foundations and Early Surveillance:**
  The clinical baseline for sepsis identification was formalized under the Sepsis-3 consensus (Singer et al., 2016), which defined sepsis as acute organ dysfunction driven by infection (SOFA2). Global epidemiological analyses (Rudd et al., 2020) demonstrated that sepsis accounts for nearly 20% of all global deaths, while early interventional studies (Kumar et al., 2006) established the foundational clinical imperative: every hour of delay in antimicrobial therapy increases mortality by approximately 7.6%. Early automated warning frameworks such as TREWScore (Henry et al., 2015) and InSight (Desautels et al., 2016) demonstrated that continuous data-driven scoring could identify septic shock and organ deterioration significantly earlier than traditional static scores (SOFA, qSOFA, MEWS).
- **Ensemble Learning and Temporal Feature Modeling:**
  Machine learning models leveraging longitudinal EHR streams have substantially improved prospective detection. Foundational tree-based ensemble architectures, including Random Forests (Breiman, 2001) and Gradient Boosted Decision Trees via XGBoost (Chen & Guestrin, 2016), proved highly adept at capturing non-linear interactions across high-dimensional physiological variables. Building on these methods, the Artificial Intelligence Sepsis Expert (AISE) (Nemati et al., 2018) demonstrated that ensemble models could forecast sepsis onset 4 to 12 hours prior to clinical suspicion. Concurrently, the PhysioNet/Computing in Cardiology Challenge 2019 (Reyna et al., 2020) standardized open ICU benchmarking, evaluating sliding-window temporal classifiers using a clinical utility scoring framework.
- **Deep Sequential Networks and Time-Series Dynamics:**
  Because physiological data in intensive care units is irregularly sampled and sparsely distributed, researchers turned to specialized temporal deep learning. Multi-Output Gaussian Process Recurrent Neural Networks (Futoma et al., 2017) and Gaussian Process Temporal Convolutional Networks (MGP-TCN) (Moor et al., 2021) addressed irregular sampling without introducing heavy interpolation artifacts. DeepSOFA (Shickel et al., 2019) leveraged Long Short-Term Memory (LSTM) networks to convert static organ failure scores into continuous acuity trajectories. To overcome irregular time steps directly, STraTS (Tipirneni & Reddy, 2022) introduced self-supervised continuous-time

Transformers, while Xu et al. (2023) demonstrated that multi-step physiological forecasting could anticipate Sepsis-3 onset criteria up to 6 hours in advance.

- **Multimodal Data Fusion and Clinical NLP:**
  Recognizing that vital signs capture late-stage physiological decompensation, recent architectures integrate unstructured EHR text. Clinical domain-adapted Transformers such as ClinicalBERT (Huang et al., 2019) demonstrated that clinical narratives and nursing shift notes contain latent signals of infection suspicion hours before vital thresholds shift. Subsequent multimodal frameworks (Bardak et al., 2021; Khurana et al., 2022; Akello et al., 2026) validated that fusing structured time-series vitals with unstructured clinical text via cross-modal attention mechanisms yields superior discrimination (AUPRC gains 10%) compared to unimodal baselines.
- **Prospective Deployment, Alert Fatigue, and Data Balancing:**
  Large-scale prospective implementations such as TREWS (Adams et al., 2022) and Sepsis Watch (Sendak et al., 2020) confirmed that real-time algorithmic alerts can reduce in-hospital mortality by over 18%. However, external validation of widely implemented commercial algorithms like the Epic Sepsis Model (Wong et al., 2021) revealed poor real-world discrimination (AUROC 0.63) and severe alert fatigue. A systematic review by Fleuren et al. (2020) highlighted that excessive false alarms stem largely from uncalibrated thresholds and extreme class imbalance. To counteract this data skew, oversampling techniques such as SMOTE (Chawla et al., 2002) and cost-sensitive loss formulations are widely deployed to balance training distributions and safeguard minority-class sensitivity.

2.2 Gaps in the Reviewed Literature

- **Temporal Asynchrony Across Disparate EHR Modalities:**
  ICU data streams exhibit severe multi-rate discrepancies: continuous vital signs update by the minute, laboratory panels arrive every 4–12 hours, and nursing progress notes are entered at shift intervals (every 8–12 hours). Existing studies predominantly rely on naive concatenation (early/late fusion) or rigid imputation, failing to dynamically align asynchronous text tokens with continuous physiological time series.
- **Severe Class Imbalance Leading to High False-Positive Rates:**
  Sepsis-positive windows typically constitute less than 5% of total ICU monitoring hours. Many predictive pipelines fail to adequately correct for this skew or evaluate performance solely using AUROC—a metric easily inflated by large true-negative volumes. This leads to poor positive predictive value (PPV) and severe clinical alarm fatigue when models are deployed at the bedside.
- **Lack of Lead-Time Optimization in Multimodal Pipelines:**
  While deep learning models achieve high retrospective classification accuracy, few frameworks are optimized specifically for the clinically actionable **3-to-6-hour pre-onset window**. Models often trigger alerts either too late (concurrent with overt organ failure) or too early without sufficient specificity, limiting their utility for timely fluid resuscitation and targeted antibiotic administration.
- **Lack of Actionable Interpretability (XAI) for Multimodal Interactions:**
  Although post-hoc explainability techniques (such as SHAP or Integrated Gradients) have been applied to tabular vital sign models, there is a lack of interpretable frameworks for multimodal pipelines. Clinicians are rarely provided with cross-modal explanations that link text mentions (e.g., a note indicating "new onset rigors") to concurrent physiological trajectories (e.g., fluctuating mean arterial pressure), creating a barrier to bedside adoption.

“This study addresses **Severe Class Imbalance Leading to High False-Positive Rates** using SMOTE/Borderline-SMOTE and **Lack of Lead-Time Optimization in Multimodal Pipelines** through temporal sliding windows for 4–6-hour early prediction.”

Problem Statement & Methodology

3.1 Problem Statement

Sepsis management in intensive care units (ICUs) is constrained by a critical mismatch between rapid physiological deterioration and delayed clinical recognition. Traditional bedside scoring systems (such as SOFA, qSOFA, and MEWS) are inherently reactive—they identify sepsis only after overt organ dysfunction or cellular injury has manifested, routinely missing the actionable 3–6 hour therapeutic window where fluid resuscitation and targeted antimicrobial administration can reduce mortality by approximately 7.6% per hour.

While computational approaches offer significant promise, current decision support systems face unimodal bottlenecks (omitting unstructured clinical text), extreme class distribution skew (<5% positive cases), and temporal asynchrony across heterogeneous EHR streams. Consequently, there is an urgent need for an end-to-end predictive and explainable multimodal framework capable of synchronizing numerical time series with clinical text narratives to deliver reliable, interpretable early sepsis warnings 4 to 6 hours prior to clinical onset.


3.2 Key Project Objectives

1. **Data Engineering and Imbalance Mitigation:** Preprocess 1.55M+ multi-parameter clinical records, applying sliding-window normalization, forward-fill/median imputation, and synthetic balancing (SMOTE / Borderline-SMOTE).
2. **Predictive Ensemble Modeling:** Build and benchmark high-performance tabular ensemble architectures (XGBoost, Random Forest, LightGBM) alongside deep temporal feature extractors for a 4–6 hour pre-onset prediction window.
3. **Multimodal Fusion:** Implement a joint representation pipeline combining structured physiological time series with clinical narrative embeddings derived from ClinicalBERT.
4. **Explainable AI (XAI) Integration:** Integrate SHAP (SHapley Additive exPlanations) and attention-weight visualizations to provide granular, feature-level and token-level clinical explanations for every generated alert.
5. **Clinical Utility Benchmarking:** Evaluate models using Area Under the Precision-Recall Curve (AUPRC), AUROC, F1-Score, and the PhysioNet Utility Metric to ensure false-alarm minimization.

Datasets Used in Reviewed Research

Research Paper	Dataset Used
Singer et al. (2016); Fleuren et al. (2020)	No single dataset — consensus clinical definitions / multi-study systematic review (28 studies aggregated)
Rudd et al. (2020)	Global Burden of Disease (GBD) 2017 study data — 195 countries, vital registration & modeled estimates
Kumar et al. (2006); Henry et al. (2015); Nemati et al. (2018); Futoma et al. (2017); Sendak et al. (2020); Adams et al. (2022); Wong et al. (2021)	Institution-specific EHR cohorts — Canada/USA ICUs, MIMIC-II, Emory University Hospitals, Duke Health System, five U.S. hospitals (prospective), Michigan Medicine
Desautels et al. (2016); Shickel et al. (2019); Huang et al. (2019); Khurana et al. (2022); Bardak et al. (2021); Akello et al. (2026)	MIMIC-III / MIMIC-IV database (clinical time-series and/or notes)
Reyna et al. (2020); Moor et al. (2021); Xu et al. (2023); Tipirneni & Reddy (2022)	PhysioNet/Computing in Cardiology Challenge 2019 dataset (used alone or combined with MIMIC-III)

3.3 Proposed System Architecture & Methodology



3.3.1 Dataset Description

- The primary multimodal evaluation uses **MIMIC-IV** matched with **MIMIC-IV-Note** to align continuous vital signs, intermittent lab panels, and clinical progress narratives. The **PhysioNet Challenge 2019** dataset (1.55M+ records records across 40 clinical variables) is utilized as a structured-only benchmarking baseline.

3.3.2 Data Preprocessing Pipeline

- **Temporal Imputation:** Multi-stage imputation using forward-fill (carrying forward recent observations up to 6 hours) followed by global median imputation for persistently missing entry points.
- **Feature Normalization:** Standardized feature scaling via Z-score normalization: $z = (x - \mu) / \sigma$.

- **Class Imbalance Handling:** Implementation of SMOTE (Synthetic Minority Over-sampling Technique) and Borderline-SMOTE on the training partition to balance minority sepsis-positive hourly windows without data leakage.

3.3.3 Modeling & Multimodal Fusion Strategy

- **Structured Feature Ensembles:** Optimized Random Forest (200+ estimators) and Gradient Boosted Decision Trees (XGBoost/LightGBM with 300 estimators and early stopping) trained on temporal sliding windows.
- **Text Embedding & Fusion:** Extraction of contextual clinical narrative embeddings via fine-tuned ClinicalBERT, fused with structured ensemble outputs using a calibrated Late Fusion / Cross-Attention layer.
- **Model Explainability:** TreeSHAP and KernelSHAP to compute global and patient-specific local feature importance values, visualizing the physiological drivers (e.g., lactate trajectory vs. MAP drop) behind each alert.

Hardware and Software Requirements

Hardware Requirements

- **Processor:** Intel Core i7 / AMD Ryzen 7 (8 cores or higher recommended).
- **RAM:** Minimum 16 GB (32 GB recommended for in-memory processing of 1.55M+ records and token tensors).
- **GPU:** NVIDIA GPU with 8GB VRAM (e.g., RTX 3060 / Google Colab / Kaggle T4/A100 instances for ClinicalBERT fine-tuning).
- **Storage:** Minimum 50 GB SSD available storage.

Software Requirements

- **Programming Environment:** Python 3.9+.
- **Core Data & ML Libraries:** Scikit-learn, Pandas, NumPy, XGBoost, LightGBM, Imbalanced-learn (imblearn).
- **Deep Learning & NLP:** PyTorch / Hugging Face transformers (ClinicalBERT).
- **Interpretability (XAI):** shap, lime.
- **Visualization & Development:** Matplotlib, Seaborn, Jupyter Notebook, Visual Studio Code.

References

1. Singer M, et al. "The Third International Consensus Definitions for Sepsis and Septic Shock (Sepsis-3)," *JAMA*, 2016.
2. Rudd KE, et al. "Global, regional, and national sepsis incidence and mortality, 1990–2017: analysis for the Global Burden of Disease Study," *The Lancet*, 2020.
3. Kumar A, et al. "Duration of hypotension before initiation of effective antimicrobial therapy is the critical determinant of survival in human septic shock," *Critical Care Medicine*, 2006.
4. Henry KE, et al. "A targeted real-time early warning score (TREWScore) for septic shock," *Science Translational Medicine*, 2015.
5. Desautels T, et al. "Prediction of Sepsis in the Intensive Care Unit With Minimal Electronic Health Record Data: A Machine Learning Approach (InSight)," *JMIR Medical Informatics*, 2016.
6. Futoma J, et al. "Learning to detect sepsis with a multitask Gaussian process RNN classifier," *International Conference on Machine Learning (ICML)*, 2017.
7. Nemati S, et al. "An Interpretable Machine Learning Model for Accurate Prediction of Sepsis in the ICU (AISE)," *Critical Care Medicine*, 2018.
8. Reyna MA, et al. "Early Detection of Sepsis from Clinical Data: The PhysioNet/Computing in Cardiology Challenge 2019," *Critical Care Medicine*, 2020.
9. Moor M, et al. "Early Prediction of Sepsis in the ICU Using Machine Learning: A Systematic Evaluation of Multi-Task Gaussian Processes and Temporal Convolutional Networks," *JAMIA*, 2021.
10. Shickel B, et al. "DeepSOFA: A continuous acuity score for intensive care unit patients using deep learning," *Scientific Reports*, 2019.
11. Fleuren LM, et al. "Machine learning for early sepsis prediction in the ICU: a systematic review," *The Lancet Digital Health*, 2020.
12. Adams R, et al. "Prospective, multi-site study of patient outcomes after implementation of the TREWS machine learning-based early warning system for sepsis," *Nature Medicine*, 2022.
13. Sendak MP, et al. "Real-World Integration of a Machine Learning Sepsis Early Warning System (Sepsis Watch)," *ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2020.
14. Huang K, et al. "ClinicalBERT: Modeling Clinical Notes and Predicting Hospital Readmission," *arXiv preprint arXiv:1904.05342*, 2019.
15. Khurana R, et al. "Multimodal Deep Learning for Critical Care Phenotyping Using Clinical Notes and Time Series," *ACM Conference on Health, Inference, and Learning (CHIL)*, 2022.
16. Xu J, et al. "Early Prediction of Sepsis Using Time Series Forecasting," *IEEE 19th International Conference on e-Science*, 2023.

17. Bardak B, et al. "Multimodal Deep Learning Approaches for Prediction of Clinical Outcomes in Intensive Care Units," *IEEE Journal of Biomedical and Health Informatics*, 2021.
18. Wong A, et al. "External Validation of a Widely Implemented Proprietary Sepsis Prediction Model in Hospitalized Patients," *JAMA Internal Medicine*, 2021.
19. Tipirneni C, Reddy CK. "STraTS: Self-Supervised Transformer for Irregularly Sampled Clinical Time Series," *ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2022.
20. Akello VB, et al. "Multimodal deep learning architectures for early sepsis prediction using longitudinal clinical time series and unstructured medical text," *International Journal of Innovative Science and Research Technology (IJISRT)*, 2026.