


Learning Loopy Graphical Models with Latent Variables: Efficient Methods and Guarantees

Anima Anandkumar


U.C. Irvine

Challenge: High-Dimensional Learning

Social Networks




Genetic Analysis



Financial Modeling



Neural Activity




Examples for Graphical Approaches

Modeling High-Dimensional Data


- Qualitative relationships: **graph structure**.
- Quantitative relationships: **interaction strengths**.

Topic Models



- Data: Word co-occurrences.
- Graph: Topic-word structure.

Financial Models



- Data: Stock returns.
- Graph: Company Classification.

Phylogenetics, Social Interactions, Computer Vision, ...


High-Dimensional Analysis

Steps Involved

- Estimate graph **structure** and **strength** of interactions.
- Employ the model to **predict** future behavior.

Focus on High-Dimensional Graph Estimation

- Graphical model on p (labeled) nodes
- n observations at the nodes



Challenges for High-Dimensional Estimation

- **Computational** Complexity: large p
- **Sample** Complexity: No. of samples n for consistency ($p \gg n$)
- Presence of **Hidden** or **Latent** Variables


Goals

Tractable **regimes**, Novel **methods**, Provable **guarantees**

Walk-up: Learning Tree Models


Data processing inequality for Markov chains

$$I(X_1; X_3) \leq I(X_1; X_2), I(X_2; X_3).$$



Tree Structure Estimation (Chow and Liu '68)


- **MLE:** Max-weight tree with estimated mutual information weights



Walk-up: Learning Tree Models


Data processing inequality for Markov chains

$$I(X_1; X_3) \leq I(X_1; X_2), I(X_2; X_3).$$



Tree Structure Estimation (Chow and Liu '68)


- **MLE**: Max-weight tree with estimated mutual information weights
- **Pairwise** statistics suffice



Walk-up: Learning Tree Models

Data processing inequality for Markov chains


$$I(X_1; X_3) \leq I(X_1; X_2), I(X_2; X_3).$$



Tree Structure Estimation (Chow and Liu '68)

- **MLE**: Max-weight tree with estimated mutual information weights
- **Pairwise** statistics suffice
- n samples and p nodes


Sample complexity: $\frac{\log p}{n} = O(1).$



Walk-up: Learning Tree Models

Data processing inequality for Markov chains


$$I(X_1; X_3) \leq I(X_1; X_2), I(X_2; X_3).$$



Tree Structure Estimation (Chow and Liu '68)

- **MLE**: Max-weight tree with estimated mutual information weights
- **Pairwise** statistics suffice
- n samples and p nodes

Sample complexity: $\frac{\log p}{n} = O(1).$




What other classes of graphical models are tractable for learning?

Beyond Tree Models: Motivation

Topic Models

- Common words in different topics.
- Presence of **latent** or hidden variables.



Efficient Methods for High-dimensional Graph Estimation.

State of Art Approaches

Approaches Employed

Combinatorial approaches, Convex relaxation.

Algorithms for Structure Estimation

- Chow and Liu (68): [Tree estimation](#)
- Meinshausen and Bühlmann (06): [Convex relaxation](#)
- Ravikumar, Wainwright, Lafferty (10): [Convex relaxation](#)
- Bresler, Mossel and Sly (09): [Bounded-degree graphs](#) ...


Learning with Hidden Variables

- Erdős, et. al. (99): [Latent trees](#)
- Daskalakis, Mossel and Roch (06): [Latent trees](#)
- Chandrasekaran, Parrilo and Willsky (11): [Latent Gaussian models](#),
...

Summary of Results

Structure Estimation in Latent Variable Models


- **Number** of hidden variables and **location** unknown
- Estimate graph over all variables



Summary of Results

Structure Estimation in Latent Variable Models


- **Number** of hidden variables and **location** unknown
- Estimate graph over all variables



Summary of Results

Structure Estimation in Latent Variable Models


- **Number** of hidden variables and **location** unknown
- Estimate graph over all variables



Summary of Results

Structure Estimation in Latent Variable Models

- **Number** of hidden variables and **location** unknown
- Estimate graph over all variables



Contributions

- **Trees** and **girth-constrained graphs**.
- Algorithms based on **pairwise** statistics.
 - ▶ **Local** tests to recover **global** structure.
- Low **sample** and **computational** requirements
- Applicable in **topic**, **financial** and **social** domains


Graph Estimation in Loopy Models with Latent Variables

Outline

- 1 Introduction
- 2 Structure Estimation in Latent Graphical Models
 - Latent Tree Models
 - Loopy Latent Models
- 3 Experiments
- 4 Conclusion and Extensions


Learning Latent Graphical Models

- **Number** and **location** of hidden variables unknown
 - Estimate graph over all variables
 - **Trees** and **girth-constrained graphs**
-



Learning Latent Graphical Models

- **Number** and **location** of hidden variables unknown
 - Estimate graph over all variables
 - **Trees** and **girth-constrained graphs**
-




Information Distances $[d_{i,j}]$ for Tree Models

Gaussian: $d_{ij} := -\log |\rho_{ij}|$. Discrete: $d_{ij} := -\log |\text{Det}(P_{i,j})|$.

Learning Latent Graphical Models

- **Number** and **location** of hidden variables unknown
- Estimate graph over all variables
- **Trees** and **girth-constrained graphs**



Information Distances $[d_{i,j}]$ for Tree Models


Gaussian: $d_{ij} := -\log |\rho_{ij}|$. Discrete: $d_{ij} := -\log |\text{Det}(P_{i,j})|$.

$[d_{i,j}]$ is an additive tree metric:

$$d_{k,l} = \sum_{(i,j) \in \text{Path}(k,l;E)} d_{i,j}.$$

Learning Latent Graphical Models

- **Number** and **location** of hidden variables unknown
- Estimate graph over all variables
- **Trees** and **girth-constrained graphs**



Information Distances $[d_{i,j}]$ for Tree Models

Gaussian: $d_{ij} := -\log |\rho_{ij}|$. Discrete: $d_{ij} := -\log |\text{Det}(P_{i,j})|$.


$[d_{i,j}]$ is an additive tree metric:

$$d_{k,l} = \sum_{(i,j) \in \text{Path}(k,l;E)} d_{i,j}.$$

- Extensions for multivariate linear models (**A.** et. al. '11)

Learning Latent Graphical Models

- **Number** and **location** of hidden variables unknown
- Estimate graph over all variables
- **Trees** and **girth-constrained graphs**



Information Distances $[d_{i,j}]$ for Tree Models

Gaussian: $d_{ij} := -\log |\rho_{ij}|$. Discrete: $d_{ij} := -\log |\text{Det}(P_{i,j})|$.

$[d_{i,j}]$ is an additive tree metric:

$$d_{k,l} = \sum_{(i,j) \in \text{Path}(k,l;E)} d_{i,j}.$$

- Extensions for multivariate linear models (A. et. al. '11)


Learning latent tree using $[\hat{d}_{i,j}]$

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.



Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$


Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.



Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$


Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.



Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$


Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.



Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$


Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.



Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$


Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Siblings Test Based on Information Distances

Exact Statistics: Distances $[d_{i,j}]$

Let $\Phi_{ijk} := d_{i,k} - d_{j,k}$.

- $-d_{i,j} < \Phi_{ijk} = \Phi_{ijk'} < d_{i,j} \quad \forall k, k' \neq i, j, \iff i, j$ leaves with common parent
- $\Phi_{ijk} = d_{i,j}, \quad \forall k \neq i, j, \iff i$ is a leaf and j is its parent.




Sample Statistics: ML Estimates $[\hat{d}_{i,j}]$

Use only short distances: $d_{i,k}, d_{j,k} < \tau$, Relax equality relationships

Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Recursive Grouping

Recursive Grouping Algorithm (Choi, Tan, A., Willsky)



- Sibling test and remove leaves
- Build tree from bottom up



Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)





Chow-Liu Based Grouping Algorithm

Efficient Initial Tree on Observed Nodes (MST)

Minimum spanning tree using edge weights $[\hat{d}_{i,j}]$.

Chow-Liu Based Grouping (Choi, Tan, A., Willsky '11)



Proof Ideas



Relating Chow-Liu Tree with Latent Tree

- Surrogate $\text{Sg}(i)$ for node i : observed node with strongest correlation

$$\text{Sg}(i) := \underset{j \in V}{\operatorname{argmin}} d_{i,j}$$

- Neighborhood preservation

$$(i, j) \in T \Rightarrow (\text{Sg}(i), \text{Sg}(j)) \in T_{\text{ML}}.$$




Chow-Liu grouping reverses edge contractions

Proof by induction

Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs


- Pairwise statistics not related to trees in general



Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs


- Pairwise statistics not related to trees in general



Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs


- Pairwise statistics not related to trees in general



Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs


- Pairwise statistics not related to trees in general
- Under weak interactions (absence of **long range correlations**), local statistics converge to a **tree limit**.



Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs


- Pairwise statistics not related to trees in general
- Under weak interactions (absence of **long range correlations**), local statistics converge to a **tree limit**.



Loopy Graphical Models with Latent Nodes


Motivation: Topic Models

- Common words among topics.
- Latent or hidden nodes.
- Typically long cycles: **Locally tree-like**.



Latent Models on Large Girth Graphs

- Pairwise statistics not related to trees in general
- Under weak interactions (absence of **long range correlations**), local statistics converge to a **tree limit**.




Local additivity


$$d_{k,l} \approx \sum_{(i,j) \in \text{Path}(k,l;E)} d_{i,j}.$$

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods




Original Graph




Local CL Grouping

Overview of Proposed Method

- Consider local neighborhoods for building **local MST**
- **Merge** the MSTs to obtain a loopy graph
- Run **latent tree routine** on different local neighborhoods



Original Graph



Local CL Grouping

Guarantees for Latent Structure Learning

- Depth δ : worst-case distance between hidden and observed nodes.
 - Parameter β : depends on min. and max. node and edge potentials
 - ▶ $\beta = 1$ for homogeneous models.
-

Theorem (A. , Valluvan '12)

Proposed method correctly recovers graph structure w.h.p. on p observed nodes and n samples when

$$\frac{J_{\min}^{-2\delta\beta(\beta+1)-2} \log p}{n} = O(1).$$

Guarantees for Latent Structure Learning

- Depth δ : worst-case distance between hidden and observed nodes.
 - Parameter β : depends on min. and max. node and edge potentials
 - ▶ $\beta = 1$ for homogeneous models.
-

Theorem (A. , Valluvan '12)

Proposed method correctly recovers graph structure w.h.p. on p observed nodes and n samples when

$$\frac{J_{\min}^{-2\delta\beta(\beta+1)-2} \log p}{n} = O(1).$$

-
- Fully observed case $\delta = 0$: $n = \Omega(J_{\min}^{-2} \log p)$.

Latent Models on Large Girth Graphs Akin to Latent Trees

Insights and Implications

Tradeoff between depth δ and girth g

Roughly require: $\delta < g/4$.

Tradeoff between max. edge strength J_{\max} and degree Δ

Require $J_{\max} < \operatorname{atanh}(\Delta^{-1})$.

Insights and Implications

Tradeoff between depth δ and girth g

Roughly require: $\delta < g/4$.

Tradeoff between max. edge strength J_{\max} and degree Δ

Require $J_{\max} < \operatorname{atanh}(\Delta^{-1})$.

Sample complexity for uniform node sampling

Given ρ fraction of nodes as observed nodes,

$$n = \Omega(\Delta^2 \rho^{-4} (\log p)^5).$$

Necessary conditions for structure recovery

For any deterministic algorithm, the number of samples n needs to be

$$n = \Omega\left(\frac{\Delta_{\min}}{\rho} \log p\right)$$

Insights and Implications

Tradeoff between depth δ and girth g

Roughly require: $\delta < g/4$.

Tradeoff between max. edge strength J_{\max} and degree Δ

Require $J_{\max} < \operatorname{atanh}(\Delta^{-1})$.

Sample complexity for uniform node sampling

Given ρ fraction of nodes as observed nodes,

$$n = \Omega(\Delta^2 \rho^{-4} (\log p)^5).$$

Necessary conditions for structure recovery


For any deterministic algorithm, the number of samples n needs to be

$$n = \Omega\left(\frac{\Delta_{\min}}{\rho} \log p\right)$$


Outline

- 1 Introduction
- 2 Structure Estimation in Latent Graphical Models
 - Latent Tree Models
 - Loopy Latent Models
- 3 Experiments
- 4 Conclusion and Extensions


Newsgroup Data




NewsGroup Data




Newsgroup Data




Newsgroup Data




Newsgroup Data




Stock Returns Data




Stock Returns Data




Stock Returns Data



Stock Returns Data



Stock Returns Data




Outline

- 1 Introduction
- 2 Structure Estimation in Latent Graphical Models
 - Latent Tree Models
 - Loopy Latent Models
- 3 Experiments
- 4 Conclusion and Extensions

Summary and Outlook

Summary


- High-dimensional estimation via **graphical** approaches
- Model **classes** where learning is tractable
- Efficient **methods** for learning
- **Guarantees** on sample and computational complexities



Summary and Outlook

Summary

- High-dimensional estimation via **graphical** approaches
- Model **classes** where learning is tractable
- Efficient **methods** for learning
- **Guarantees** on sample and computational complexities





Outlook

- Removing girth constraint on latent models
- Characterizing criterion for tractable learning
- Learning beyond regime of correlation decay

Extensions

Structure Estimation in Random Graph Models



- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Extensions

Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**





Graph Estimation Through Search for Vertex Separators


Extensions

Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**





Graph Estimation Through Search for Vertex Separators



Extensions


Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Graph Estimation Through Search for Vertex Separators



- Naïve search for separators is exponential in maximum **node degree**



Extensions


Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Graph Estimation Through Search for Vertex Separators



- Naïve search for separators is exponential in maximum **node degree**
- Novel criterion: **sparse local separation**



Extensions


Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Graph Estimation Through Search for Vertex Separators



- Naïve search for separators is exponential in maximum **node degree**
- Novel criterion: **sparse local separation**



Extensions


Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Graph Estimation Through Search for Vertex Separators



- Naïve search for separators is exponential in maximum **node degree**
- Novel criterion: **sparse local separation**
- A large family of graphs have sparse local separators: e.g **small world**, **Erdős-Rényi**.



Extensions


Structure Estimation in Random Graph Models

- Fully observed models (no latent nodes)
- Random graph models such as **Erdős-Rényi** and **small world**



Graph Estimation Through Search for Vertex Separators

- Naïve search for separators is exponential in maximum **node degree**
- Novel criterion: **sparse local separation**
- A large family of graphs have sparse local separators: e.g. **small world**, **Erdős-Rényi**.



Novel Criteria for High-Dimensional Estimation

Extensions and Connections

Topology Discovery With Few Participants (A. , Hassidim, Kelner '11)

- End-to-end delays between participants in Erdős-Rényi random graph
 - Edit distance guarantees with vanishing fraction of participants
-
-

Extensions and Connections

Topology Discovery With Few Participants (A. , Hassidim, Kelner '11)

- End-to-end delays between participants in Erdős-Rényi random graph
 - Edit distance guarantees with vanishing fraction of participants
-

Covariance Decomposition

- Multiple graphs: combination of statistical relationships
 - Markov and Independence Domains
-

$$\begin{bmatrix} & \end{bmatrix} = \begin{bmatrix} & \end{bmatrix}^{-1} + \begin{bmatrix} & \end{bmatrix}$$

Extensions and Connections

Topology Discovery With Few Participants (A. , Hassidim, Kelner '11)

- End-to-end delays between participants in Erdős-Rényi random graph
- Edit distance guarantees with vanishing fraction of participants


Covariance Decomposition

- Multiple graphs: **combination of statistical relationships**
- Markov and Independence Domains


$$\begin{bmatrix} & \end{bmatrix} = \begin{bmatrix} & \end{bmatrix}^{-1} + \begin{bmatrix} & \end{bmatrix}$$

Graphical Model Mixtures

- Multiple graphs: **context specific dependencies**
- **Hidden** context
- Learning guarantees



The Big Picture



<http://newport.eecs.uci.edu/anandkumar>