

Spherical aberrations — Solution

X22 (2022) — English translation

A1


0.45 pts



Construct the exact path of rays in a plano-convex and plano-concave lens. The radii of curvature of surfaces is $R = 5 \text{ cm}$, the refractive index of glass is $n = 1.5$. Indicate the point F' of convergence (divergence) of the parallel paraxial beam.

Note that the radius of the lens is 4 cm, the thickness of the lens is 2 cm, and the incident rays are drawn every centimeter from the optical axis of the lens. For a plano-convex (first) and plano-concave (third) lens, refraction occurs on only one surface. The focus position for the first and third lenses is noted using the thin lens formula:

$$F = \frac{R}{n - 1} = 10 \text{ cm}.$$

This distance is measured from bent surface. For convexly-flat (second) lens refraction occur immediately on two surface. So that find position focus, account for, that such lens be thick. After first refraction ray inside glass be gather on distance $\frac{n}{n-1}R = 15 \text{ cm}$ from bent surface, that is on distance 13 cm from flat surface. For refraction on flat surface image turn out in n times near, that is on distance 8.67 cm. And that, obtain focus on distance 10.67 cm from bent surface. So that construct refraction ray, use protractor, ruler and law Snell's: $n_1 \sin \alpha = n_2 \sin \beta$, where α – angle of incidence, β – refraction angle, n_1 and n_2 are the refractive indices of the media on opposite sides of the boundary.





A2

0.30 pts

Measure the magnitude of the maximum spherical aberration $\delta s'$ for all constructions. Record your results (in mm) on your answer sheet.

Based on the results of the constructions, we measure the maximum value of aberration. For convex-flat, the effect of aberrations is less. Below are the results, accurate to tenths of mm, obtained by calculations.

Answer: Plano-convex $\delta s'_{\max} = -51.8$ mm Convex-flat $\delta s'_{\max} = -11.5$ mm Plano-concave $\delta s'_{\max} = -51.8$ mm

B1

0.25 pts

What is the focal length f' for a thin plano-convex lens?

For a thin lens

$$\frac{1}{f'} = (n - 1) \left(\frac{1}{R_1} + \frac{1}{R_2} \right),$$

in our case $R_1 = \infty$, $R_2 = R$. From here we get the answer.

Answer: $f' = \frac{R}{n - 1}$

B2

1.50 pts

For a given lens, find the dependence of the longitudinal spherical aberration $\delta s'$ on the half-width of the beam h . Express your answer using R, n and h . Write an approximate expression for $\delta s'(h)$ by expanding the answer into a Taylor series of powers h to h^2 . Construct a schematic graph of the resulting relationship.

According to geometry (Fig. B2) and Snell's law:

$$n \sin \alpha = \sin(\alpha + \beta).$$

Express angle through segment and refractive index:

$$\alpha = \arcsin \frac{h}{R}, \quad \alpha + \beta = \arcsin \frac{nh}{R}.$$

Distance l along optical axis from point refraction to point intersection with optical axis:

$$l = h \operatorname{ctg} \beta = h \operatorname{ctg} \left(\arcsin \left(\frac{nh}{R} \right) - \arcsin \left(\frac{h}{R} \right) \right).$$

Refraction occur in point, shifted on

$$\delta x = R - \sqrt{R^2 - h^2}.$$

Express $\delta s'$:

$$\delta s' = l - \delta x - f'.$$

Substitute l and δx find earlier, substitute f' from B1, we get the answer.

Answer: Reply for $\delta s'$


$$\delta s' = \frac{\sqrt{R^2 - n^2 h^2} \sqrt{R^2 - h^2} + nh^2}{n \sqrt{R^2 - h^2} - \sqrt{R^2 - n^2 h^2}} - \frac{nR}{n - 1} + \sqrt{R^2 - h^2}$$


or

$$\delta s' = \frac{n \sqrt{R^2 - h^2 n^2} + \sqrt{R^2 - h^2}}{n^2 - 1} - \frac{nR}{n - 1} + \sqrt{R^2 - h^2}$$

or

$$h \operatorname{ctg} \left(\arcsin \left(\frac{nh}{R} \right) - \arcsin \left(\frac{h}{R} \right) \right) - \frac{nR}{n - 1} + \sqrt{R^2 - h^2}.$$





B3

0.50 pts

Find the value of transverse spherical aberration $\delta g'$. Express your answer in terms of $\delta s'$, f' and h .

From the similarity of triangles (Fig. B2) we obtain

$$\frac{h}{l} = \frac{\delta g'}{|\delta s'|}.$$

Note aberration small ($l = f'$), we express the answer.

Answer: From similarity of triangles:

$$\delta g' = |\delta s'| \frac{h}{f'}$$

B4

1.50 pts

Let us divide the scattering circle into rings of radii $0.2\delta g'$, $0.4\delta g'$, $0.6\delta g'$, $0.8\delta g'$. From what fraction (in %) of the transverse area of the incident beam are the rays collected into the central circle (radius $0.2\delta g'$)? From what fraction (in %) of the transverse area of the incident beam are the rays collected into subsequent rings (between $0.2\delta g'$ and $0.4\delta g'$ and so on, respectively)? What fraction of the area of the scattering circle is occupied by each ring? Tabulate all calculations on your answer sheet. Construct a schematic graph of light intensity versus radial coordinate in the scattering circle.

We count the area fractions of each ring:

$$0 \div 0.2\delta g' : 0.2^2 - 0^2 = 0.04 = 4\%;$$

$$0.2\delta g' \div 0.4\delta g' : 0.4^2 - 0.2^2 = 0.12 = 12\%;$$

$$0.4\delta g' \div 0.6\delta g' : 0.6^2 - 0.4^2 = 0.20 = 20\%;$$

$$0.6\delta g' \div 0.8\delta g' : 0.8^2 - 0.6^2 = 0.28 = 28\%;$$

$$0.8\delta g' \div 1.0\delta g' : 1.0^2 - 0.8^2 = 0.36 = 36\%;$$

From part B2 obtain $|\delta s'| \sim h^2$. Account for part B3 obtain, that $\delta g' \sim h^3$. Note fraction area ring in fall beam:

$$0 \div 0.2\delta g' : 0.2^{2/3} - 0^{2/3} = 0.34 = 34\%;$$

$$0.2\delta g' \div 0.4\delta g' : 0.4^{2/3} - 0.2^{2/3} = 0.20 = 20\%;$$

$$0.4\delta g' \div 0.6\delta g' : 0.6^{2/3} - 0.4^{2/3} = 0.17 = 17\%;$$

$$0.6\delta g' \div 0.8\delta g' : 0.8^{2/3} - 0.6^{2/3} = 0.15 = 15\%;$$

$$0.8\delta g' \div 1.0\delta g' : 1.0^{2/3} - 0.8^{2/3} = 0.14 = 14\%;$$

If divide fraction area in fall ring on fraction area ring in focal plane, that obtain quantity proportional intensity. We obtain qualitatively graph $I \sim r^{-4/3}$.

Answer: Ring Beam fraction of circle area
 0.0 – 0.2 34% 4% 0.2 – 0.4 20% 12% 0.4 – 0.6 17% 20% 0.6 – 0.8 15% 28% 0.8 – 1.0 14% 36%

C1

0.30 pts

Using the sine theorem for triangles MSC and $MS'C$, as well as Snell's law of refraction, obtain an invariant of the form $n \cdot f(r, s, p) = n' \cdot f(r, s', p') = \text{inv}$.

Theorem of sines for the triangle MSC (see Fig. 2 from the condition):

$$\frac{\sin \theta}{p} = \frac{\sin \angle SMC}{r - s}.$$

Theorem sine for triangle $MS'C$:

$$\frac{\sin \theta}{p'} = \frac{\sin \angle S'MC}{r - s'}.$$

Law refraction:

$$n \sin \angle SMC = n' \sin \angle S'MC.$$

Express from theorem sine $\sin \angle SMC$ and $\sin \angle S'MC$, substitute it into the law of refraction, we get invariant

Answer: $\frac{n(r - s)}{p} = \text{inv}$

C2

0.10 pts

Using the cosine theorem in triangle MSC , go invariantly from magnitude p to angle θ . Assuming the angle θ to be small, expand the factors in the form of roots in a Taylor series up to the first term with a non-zero degree θ . Divide the resulting approximate value by “ $-r$ ” to obtain the reduced value of the invariant.

Cosine theorem

$$p^2 = r^2 + (r - s)^2 - 2r(r - s) \cos \theta.$$

Use expansion cosine and total square

$$p^2 = (r - (r - s))^2 + 2r(r - s) \cdot \frac{\theta^2}{2}.$$

Substitute in invariant, obtain:

$$\frac{n(r - s)}{\sqrt{s^2 + r(r - s)\theta^2}} = \frac{n(r - s)}{s} \left(1 - \frac{r(r - s)}{2s^2} \right).$$

Divide on “ $-r$ ”, we get the answer.

Answer: $\frac{n(r - s)}{\sqrt{s^2 + r(r - s)\theta^2}} = \text{inv} \quad n \left(\frac{1}{r} - \frac{1}{s} \right) \left(1 - \frac{r(r - s)\theta^2}{2s^2} \right) = \text{inv}$

C3

0.10 pts

Having written the invariant from point C2 for paraxial rays before and after refraction, show the invariance of the quantity $Q(s_0)$.

Let us put $\theta = 0$ in the invariant of clause C2.

Answer: $n \left(\frac{1}{r} - \frac{1}{s_0} \right) = n' \left(\frac{1}{r} - \frac{1}{s'_0} \right) = Q(s) = \text{inv}$

C4

0.10 pts

The left-hand side of the invariant obtained in C2 is a function of f of s and θ . Find the value of $f(s, \theta) - f(s_0, \theta)$. Consider δs and θ to be small parameters.

The invariant is a function of s and θ :

$$f(s, \theta) = n \left(\frac{1}{r} - \frac{1}{s} \right) \left(1 - \frac{r(r-s)\theta^2}{2s^2} \right).$$

Find value difference, account for that θ identical:

$$f(s, \theta) - f(s_0, \theta) = \frac{\partial f}{\partial s} ds.$$

Since θ also small quantity, that

$$\frac{\partial f}{\partial s} = n \frac{1}{s^2}$$

Answer:

$$\frac{n\delta s}{s_0^2}$$

C5

0.20 pts

Using the results of the previous paragraphs, expressing the small angle θ in terms of the radius of curvature of the surface and the small height h , obtain the desired relationship:

$$\frac{n'\delta s'}{s_0'^2} - \frac{n\delta s}{s_0^2} = -\frac{h^2}{2} Q^2(s_0) \left(\frac{1}{n's_0'} - \frac{1}{ns_0} \right).$$

Let's express the angle θ through h :

$$\theta = \frac{h}{r}.$$

Representable expression through $Q(s)$:

$$\frac{r(r-s)\theta^2}{2s^2} = \frac{(r-s)h^2}{2s^2r} = n \left(\frac{1}{s} - \frac{1}{r} \right) \frac{h^2}{2ns} = Q(s) \frac{h^2}{2ns}.$$

Following quantity invariant

$$f(s, \theta) = f(s', \theta),$$

$$f(s_0, \theta) + \frac{n\delta s_0}{s_0^2} = f(s_0', \theta) + \frac{n'\delta s'}{s_0'^2},$$

$$Q(s_0) - \frac{h^2}{2ns_0} Q^2(s_0) + \frac{n\delta s}{s_0^2} = Q(s_0') - \frac{h^2}{2n's_0'} Q^2(s_0') + \frac{n'\delta s'}{s_0'^2}$$

We use the more, that $Q(s_0) = Q(s_0')$, obtain expression

$$\frac{n'\delta s'}{s_0'^2} - \frac{n\delta s}{s_0^2} = -\frac{h^2}{2} Q^2(s_0) \left(\frac{1}{n's_0'} - \frac{1}{ns_0} \right).$$

Answer: CTD

C6

0.20 pts

Show that the aberrations of the object and the image after the k th refractive surface are related by the relation:

$$n'_k \delta s'_k \alpha_k'^2 - n_1 \delta s_1 \alpha_1^2 = -\frac{1}{2} \sum_{i=1}^k h_i^4 Q_i^2(s) \left(\frac{1}{n'_i s'_i} - \frac{1}{n_i s_i} \right).$$

Other words, for calculation total aberration needed by all surface add right part prove relation, multiply

on h_i^2 .

Let's move from s_i to the angles on the left side of the formula from C5:

$$\alpha_i = \frac{h_i}{s_i}, \quad \alpha' = \frac{h_i}{s'_i}.$$

For passage ray between refract surface change distance from ray to optical axis, however, be conserved angle inclination:

$$\begin{aligned} \alpha'_i &= \alpha_{i+1}, \\ n'_i &= n_{i+1}, \\ \delta s'_i &= \delta s_{i+1}. \end{aligned}$$

Add such expression

$$n'_i \delta s'_i \alpha_i'^2 - n_i \delta s_i \alpha_i^2 = -\frac{h_i^4}{2} Q_i^2(s_i) \left(\frac{1}{n'_i s'_i} - \frac{1}{n_i s_i} \right).$$

on the left side there are only two terms left: one corresponds to the entry of rays into the optical system, the other - entry from it. This makes it possible to calculate aberrations for complex systems.

Answer: CTD

D1

2.00 pts

Find the spherical aberration $\delta s'_2$ of a thin converging lens for an incident parallel beam of light. Apply the result of step C6 for two refractive surfaces and the thin lens formula, leaving the dependence only on the radius of curvature of the first surface (where the original beam of light falls). Express your answer in terms of the refractive index n and the reciprocals $\rho = 1/r$ and $\varphi = 1/f$.

We will use the sign convention as in part C. Then

$$s_1 = \infty, \quad s'_2 = -f.$$

Position image after first refraction:

$$s'_1 = s_2 = r \frac{n}{n-1}.$$

Formula thin lens allows find radius curvature r_2 second surface for define focus f and radius first surface r :

$$\frac{1}{f} = (n-1) \left(-\frac{1}{r} + \frac{1}{r_2} \right).$$

Since lens thin, that $h_1 = h_2 = h$. Left part formula C6:

$$n'_2 \delta s'_2 \alpha_2'^2 - n_1 \delta s_1 \alpha_1^2 = \delta s'_2 \left(\frac{h}{f} \right)^2.$$

$$Q_1 = \frac{1}{r} = \rho.$$

$$Q_2 = \frac{1}{r_2} - \frac{1}{-f} = \frac{n}{n-1} \varphi + \rho.$$

Assemble still together:

$$\delta s'_2 = -\frac{h^2}{2\varphi^2} \left(Q_1^2 \frac{n-1}{n^2} \rho + Q_2^2 \left(-\varphi - \frac{n-1}{n^2} \rho \right) \right)$$

we get the answer.

Answer: $\delta s'_2 = \frac{h^2}{2} \left[\frac{\rho^2 n + 2}{\varphi n} + \rho \frac{2n+1}{n-1} + \varphi \frac{n^2}{(n-1)^2} \right]$

D2

0.50 pts

Find the value of ρ^* at which the spherical aberration $\delta s'_2$ is minimal. Express your answer using n and φ .

The expression in square brackets in D1 is a parabola with respect to ρ , the upward branch. The minimum aberration (modulo) will correspond to the vertex. From this we get the value for ρ^* . Note that these arguments are correct only when the parabola does not intersect the horizontal axis. After all, if it crosses, then generally speaking you can get zero aberration. Let's assume it does. Then the discriminant must be non-negative:

$$D = \frac{1 - 4n}{(n - 1)^2} \geq 0,$$

$$n \leq 1/4.$$

But for assemble lens $n > 1$, therefore, in reality the parabola does not intersect the horizontal axis in our conditions.


Answer: $\rho^* = -\frac{\varphi}{2} \frac{2n+1}{n-1} \frac{n}{n+2}$

D3

0.50 pts

Calculate the radii of curvature of the lens surfaces. Draw (qualitatively) your calculated lens on the answer sheet.


Answer: $R_1 = -5.83 \text{ cm}$, $R_2 = +35 \text{ cm}$, i.e. the lens is doubly convex, and the smaller radius of curvature faces the direction of the incident light beam.



D4

0.50 pts

Schematically depict a graph of the modulus of longitudinal spherical aberration $\delta s'_2$ for the lenses shown in Figure 4.



In what direction and at what distance should the observation plane be shifted from the focal plane so that the scattering circle is of minimum size?

The fact from part B is used that the aberration is quadratic in the distance of the beam from the optical axis h :

$$\delta s = \frac{h^2}{\varepsilon}, \quad \delta s' = \frac{H^2}{\varepsilon},$$

where ε – some coefficient (dimensions length). Here H – radius lens (maximally distant ray), h – arbitrary ray. Similarly, $\delta s'$ – maximum aberration, δs – point intersection optical axis ray h . If that here δs and $\delta s'$ positive, are measured from focus in side lens. Distance r from axis to point ray on distance x from focus, which to refraction goes on distance h from axis one can find from similarity (fig. E1):

$$\frac{r}{x - \delta s} = \frac{h}{f}.$$

We obtain that r is function plane observation x and ray h :

$$r(x, h) = \frac{1}{f} \left(xh - \frac{h^3}{\varepsilon} \right).$$

Find, for what h for some record x be maximum

$$h_1 = \sqrt{\frac{\varepsilon}{3}} x^{1/2}.$$

Maximum radius beam in dependence from plane observation

$$r_{\max}(x) = \frac{2\varepsilon^{1/2} x^{3/2}}{3^{3/2} f}.$$

This be obtained some envelope, which we obtain, looking on ray, which not intersect optical axis. The near to focus, the more less size mug, which give this ray. However, still is ray, which intersect optical axis and for approximation to focus increase size mug. Dependence distance from axis to point ray for extreme opposite ray from coordinate

$$y(x) = \frac{H}{f} (\delta s' - x).$$

Minimum circle be there, where this effect equal $r_{\max}(x) = y(x)$:


$$\frac{2\varepsilon^{1/2} x^{3/2}}{3^{3/2} f} = \frac{H}{f} (\delta s' - x),$$

$$\frac{2}{3^{3/2}} \left(\frac{x}{\delta s'} \right)^{3/2} = \left(1 - \frac{x}{\delta s'} \right).$$

Solve this equation, obtain answer

$$x = \frac{3}{4} \delta s'.$$

Answer: To the lens at a distance $\frac{3}{4} |\delta s'|$.



Draw a schematic graph of light intensity versus radial coordinate in the minimum scattering circle. To do this, follow steps similar to point B4.

Let us first answer the question: how does the radius of the circle (r) in the E1 plane relate to the radius of the circle (h) in the beam incident on the lens? From the previous paragraph it turns out that they are connected as follows:

$$r = h|3 - 4h^2|,$$

here r – is normalized on maximum radius spot $\left(\frac{1}{4} \frac{\delta s' H}{f}\right)$ in consider plane, h – on radius beam H . in general case one radius in plane observation corresponds integer three radius in fall beam. Fraction area mug turn out such same, as and in previous times. So that find fraction beam, needed add fraction area three ring, that is quantity form $h_2^2 - h_1^2$. For finding h_1 and h_2 of each ring you need to solve an equation of the third degree.

Answer: Ring Beam fraction Fraction of circle area Intensity 0.0 – 0.2 12% 4% 3.01 0.2 – 0.4 13% 12% 1.11 0.4 – 0.6 15% 20% 0.76 0.6 – 0.8 19% 28% 0.67 0.8 – 1.0 41% 36% 1.13

плоскость наблюдения			первое кольцо		второе кольцо		третье кольцо		доля пучка	интенсивность
r2	r1	r2^2-r1^2	h2	h1	h2	h1	h2	h1		
1	0,8	0,36	0,5	0,3042	0,6729	0,5	1	0,9771	0,40553236	1,12647878
0,8	0,6	0,28	0,3042	0,2129	0,7397	0,6729	0,9771	0,9526	0,18885056	0,67446629
0,6	0,4	0,2	0,2129	0,1367	0,7895	0,7397	0,9526	0,9262	0,152394	0,76197
0,4	0,2	0,12	0,1367	0,0671	0,8305	0,7895	0,9262	0,8976	0,13276516	1,10637633
0,2	0	0,04	0,0671	0	0,8660	0,8305	0,8976	0,8660	0,12045792	3,011448