

## Some strange spinner... — Solution

X23 (2023) — English translation

A1

0.30 pts

Determine the moment of inertia of the system of the rod and spheres relative to the axis of rotation. Express your answer in terms of  $m$  and  $l$ .

The moment of inertia of each sphere relative to the axis of rotation is  $ml^2$ , since their dimensions can be neglected. The original rod is equivalent to two others with mass  $2m$  and length  $l$ . The moment of inertia of a rod with mass  $M$  and length  $L$  relative to the axis passing perpendicular to the rod through its end is equal to:

$$I_{\text{CT}} = \frac{ML^2}{3}$$

Then moment of inertia  $I$  of the system relative to the axis of rotation is equal to:

**Answer: Answer:**

$$I = \frac{10ml^2}{3}$$

A3

0.20 pts

What is  $\omega_1$  equal to? Express your answer in terms of  $v$  and  $l$ .

Since  $\omega_0 = 0$ , we find:

**Answer: Answer:**

$$\omega_1 = \frac{6v}{13l}$$

A4

0.20 pts

Express  $\omega^*$  in terms of  $v$  and  $l$ .

Equating  $\omega_{i+1}$  and  $\omega_i$ , we find:

**Answer: Answer:**

$$\omega^* = \frac{v}{l}$$

A5

0.60 pts

By solving the recurrence equation obtained in step A1, you will obtain an explicit expression for  $\omega_i$ . Express your answer using  $i$ ,  $v$  and  $l$ . Hint: Use the variable  $\omega'_i = \omega_i - v/l$ .

Hint: Use the variable  $\omega'_i = \omega_i - v/l$ .

The equation obtained in step A1 is reduced to the following form:

$$13 \left( \omega_{i+1} - \frac{v}{l} \right) = 7 \left( \omega_i - \frac{v}{l} \right)$$

Introducing variable  $\omega'_i = \omega_i - v/l$ , obtain:

$$13\omega'_{i+1} = 7\omega'_i$$

From which:

$$\omega'_i = \omega'_1 \cdot \left(\frac{7}{13}\right)^{i-1}$$

Since  $\omega_0 = 0$ ,  $\omega_1 = 6v/(13l)$ . Then  $\omega'_1 = -7v/(13l)$ , from which :

$$\omega'_i = -\frac{v}{l} \left(\frac{7}{13}\right)^i$$

and finally

**Answer: Answer:**

$$\omega_i = \frac{v}{l} \left(1 - \left(\frac{7}{13}\right)^i\right)$$

**A6**

**0.20 pts**

*What would be the limiting value  $\omega^*$  for such a system?*

Let us note that if we put  $\omega_{i+1} = \omega_i$  in the recurrent equation obtained in point A1, then for any values of the moment of inertia  $I$  the value will be:

**Answer: Answer:**

$$\omega^* = \frac{v}{l}$$

$u_{\parallel}$ :


$$u_{\parallel}^2 = v^2 \cos^2 \alpha - \frac{I(\omega_{i+1}^2 - \omega_i^2)}{m} = \left(v \cos \alpha - \frac{I(\omega_{i+1} - \omega_i)}{ml \cos \alpha}\right)^2$$

Expanding скобки и сокращая множитель  $\omega_{i+1} - \omega_i$ , получим:

$$\frac{2v}{l} = \omega_{i+1} \left(1 + \frac{I}{ml^2 \cos^2 \alpha}\right) - \omega_i \left(\frac{I}{ml^2 \cos^2 \alpha} - 1\right)$$

**Answer: Answer:**

$$\omega_{i+1} = \frac{6v(1 - k^2)}{l(13 - 3k^2)} + \omega_i \cdot \frac{7 + 3k^2}{13 - 3k^2}$$



**B3****0.20 pts**

What is  $\omega_1$  equal to? Express your answer in terms of  $v_0$ ,  $l$  and  $k$ .

Since  $\omega_0 = 0$ , we find:

**Answer: Answer:**

$$\omega_1 = \frac{6v(1 - k^2)}{l(13 - 3k^2)}$$

**B4****0.80 pts**

By solving the recurrence equation obtained in step **B2**, you will obtain an explicit expression for  $\omega_i$ . Express your answer using  $i$ ,  $v$  and  $l$ .

Let's introduce the variable  $\omega'_i = \omega_i - v/l$  again and get:

$$\omega'_{i+1} \left( 1 + \frac{I}{ml^2 \cos^2 \alpha} \right) = \omega'_i \left( \frac{I}{ml^2 \cos^2 \alpha} - 1 \right)$$

from which after substitution  $I$ :

$$\omega'_{i+1} = \omega'_i \left( \frac{7 + 3k^2}{13 - 3k^2} \right) \Rightarrow \omega'_i = \omega'_1 \left( \frac{7 + 3k^2}{13 - 3k^2} \right)^{i-1}$$

For  $\omega'_1$  have:

$$\omega'_1 = \omega_1 - \frac{v}{l} = -\frac{v(7 + 3k^2)}{l(13 - 3k^2)}$$

Thus:

$$\omega'_i = \frac{v}{l} \left( \frac{7 + 3k^2}{13 - 3k^2} \right)^i$$

and finally:

**Answer: Answer:**

$$\omega_i = \frac{v}{l} \left( 1 - \left( \frac{7 + 3k^2}{13 - 3k^2} \right)^i \right)$$

**C1****0.50 pts**

Find at what values of the parameter  $\alpha$  the system in the dry friction mode will continue to move indefinitely long after the first collision with the ball.

For convenience of solution, let us first find the angular velocity of the system  $\omega^\uparrow$  after the first collision with the ball. Substituting  $\omega_i = 0$  and  $\omega_{i+1} = \omega^\uparrow$  into the recurrent equation, we obtain:

$$\omega^\uparrow = \frac{2\varepsilon\omega_0}{1 + \varepsilon}.$$

Time dependences  $\omega(t)$  for viscous friction modes can be found, as in the solution to paragraphs C5 and C7. The case of dry friction. The kinetic energy of the rotational motion of the system must be friction losses for half a revolution, i.e.:

$$\frac{I}{2} \omega^{\uparrow 2} > \pi \alpha I \Rightarrow \alpha < \frac{\omega^{\uparrow 2}}{2\pi} = \frac{2\varepsilon^2 \omega_0^2}{\pi(1 + \varepsilon)^2}.$$

The case of dry friction.

The kinetic energy of the rotational motion of the system must be friction losses for

half a revolution, i.e.:

$$\frac{I}{2}\omega^{\uparrow 2} > \pi\alpha I \implies \alpha < \frac{\omega^{\uparrow 2}}{2\pi} = \frac{2\varepsilon^2\omega_0^2}{\pi(1+\varepsilon)^2}.$$

**Answer: Answer:**

$$\alpha < \frac{2\varepsilon^2\omega_0^2}{\pi(1+\varepsilon)^2}$$

**C2**

**0.50 pts**

*Find at what values of the parameter  $\beta$  the system in the mode of linear viscous friction will continue to move indefinitely long after the first collision with the ball.*

The case of linear viscous friction. Since  $\omega(t) = \omega^{\uparrow}e^{-\beta t}$ , the maximum angle of rotation of the system after the first collision will be:

$$\varphi = \int_0^{+\infty} \omega^{\uparrow}e^{-\beta t} dt = \frac{\omega^{\uparrow}}{\beta}.$$

This angle must be greater than  $\pi$ , therefore:

$$\beta < \frac{\omega^{\uparrow}}{\pi} = \frac{2\varepsilon\omega_0}{\pi(1+\varepsilon)}$$

Since  $\omega(t) = \omega^{\uparrow}e^{-\beta t}$ , the maximum angle of rotation of the system after the first collision will be:

$$\varphi = \int_0^{+\infty} \omega^{\uparrow}e^{-\beta t} dt = \frac{\omega^{\uparrow}}{\beta}.$$

This angle must be greater than  $\pi$ , therefore:

$$\beta < \frac{\omega^{\uparrow}}{\pi} = \frac{2\varepsilon\omega_0}{\pi(1+\varepsilon)}$$

**Answer: Answer:**

$$\beta < \frac{2\varepsilon\omega_0}{\pi(1+\varepsilon)}$$

**C3**

**0.50 pts**

*Find at what values of the parameter  $\gamma$  the system in the mode of quadratic viscous friction will continue to move indefinitely long after the first collision with the ball.*

The case of quadratic viscous friction. Since the integral of the form  $\int \frac{1}{x} dx$  diverges at  $x \rightarrow +\infty$ , then for any value of  $\gamma$  the system can make one revolution in a finite, albeit exponentially large time. Thus,  $\gamma$  can be an arbitrary positive quantity.

Since the integral of the form  $\int \frac{1}{x} dx$  diverges at  $x \rightarrow +\infty$ , then for any value of  $\gamma$  the system can make one revolution in a finite, albeit exponentially large time. Thus,  $\gamma$  can be an arbitrary positive quantity.

Note: Since in reality, in the limit of low angular velocities, viscous friction transforms into a linear regime, then in reality the value  $\gamma$  has an upper limit, but we neglect this here.

**Answer: Answer:**

$$\gamma < +\infty$$

C4

0.70 pts

Find the steady-state average over the period angular velocity of the system  $\bar{\omega}_1$  in the dry friction mode. Express your answer in terms of  $\varepsilon$ ,  $\alpha$  and  $\omega_0$ .

Equating the change in the kinetic energy of the system per revolution to friction losses, we have:

$$\frac{I}{2}\omega^{\uparrow 2} - \frac{I}{2}\omega^{\downarrow 2} = \pi\alpha I \implies \omega^{\uparrow 2} - \omega^{\downarrow 2} = 2\pi\alpha.$$

Since in the dry friction mode the system moves with constant angular acceleration, the average angular velocity  $\bar{\omega}$  will be equal to the arithmetic average  $\omega^{\uparrow}$  and  $\omega^{\downarrow}$ . For convenience, we introduce one more quantity:

$$\Delta\omega = \frac{\omega^{\uparrow} - \omega^{\downarrow}}{2},$$

then, adding a recurrent equation, we obtain the following system:

$$\begin{cases} \bar{\omega}\Delta\omega = \frac{\pi\alpha}{2} \\ \bar{\omega} + \frac{\Delta\omega}{\varepsilon} = \omega_0 \end{cases} \implies \bar{\omega}^2 - \omega_0\bar{\omega} + \frac{\pi\alpha}{2\varepsilon} = 0.$$

This is a quadratic equation whose roots are:

$$\bar{\omega}_{\pm} = \frac{\omega_0 \pm \sqrt{\omega_0^2 - \frac{2\pi\alpha}{\varepsilon}}}{2}.$$

From physical considerations it is clear that it is necessary to take a larger root  $\bar{\omega}_+$ . So:

**Answer: Answer:**

$$\bar{\omega}_1 = \frac{1}{2} \left[ \omega_0 + \sqrt{\omega_0^2 - \frac{2\pi\alpha}{\varepsilon}} \right]$$

C5

0.50 pts

Find the stationary value of the angular velocity  $\omega_2^{\uparrow}$  of the system immediately after the next collision with the ball in the mode of linear viscous friction.

The case of linear viscous friction. The equation for the angular velocity between collisions with the ball will be written in the form:

$$\dot{\omega} = -\beta\omega.$$

Its solution with the initial condition  $\omega(t=0) = \omega^{\uparrow}$  has the form:

$$\frac{d\omega}{\omega} = -\beta dt \implies \omega = Ce^{-\beta t}, \quad \omega(t=0) = C = \omega^{\uparrow} \implies \omega(t) = \omega^{\uparrow}e^{-\beta t}.$$

Then the time  $T$  of the next collision with the ball will be determined from the condition:

$$\pi = \int_0^T \omega(t) dt = \int_0^T \omega^{\uparrow}e^{-\beta t} dt = \frac{1}{\beta} (1 - e^{-\beta T}) \omega^{\uparrow}.$$

Since the angular velocity of the system  $\omega^{\downarrow}$  immediately before the collision with the ball is equal to:

$$\omega^{\downarrow} = \omega^{\uparrow}e^{-\beta T},$$

then we have in result:

$$\omega^{\uparrow} - \omega^{\downarrow} = \pi\beta.$$

Substituting this into the recurrence equation, we get:

$$\omega^\uparrow (1 + \varepsilon^{-1}) + (\omega^\uparrow - \pi\beta) (1 - \varepsilon^{-1}) = 2\omega_0 \implies \omega^\uparrow = \omega_0 - \frac{\pi\beta}{2} (\varepsilon^{-1} - 1).$$

The equation for the angular velocity between collisions with the ball will be written in the form:

$$\dot{\omega} = -\beta\omega.$$

Its solution with the initial condition  $\omega(t=0) = \omega^\uparrow$  has the form:

$$\frac{d\omega}{\omega} = -\beta dt \implies \omega = Ce^{-\beta t}, \quad \omega(t=0) = C = \omega^\uparrow \implies \omega(t) = \omega^\uparrow e^{-\beta t}.$$

Then the time  $T$  of the next collision with the ball will be determined from the condition:

$$\pi = \int_0^T \omega(t) dt = \int_0^T \omega^\uparrow e^{-\beta t} dt = \frac{1}{\beta} (1 - e^{-\beta T}) \omega^\uparrow.$$

Since the angular velocity of the system  $\omega^\downarrow$  immediately before the collision with the ball is equal to:

$$\omega^\downarrow = \omega^\uparrow e^{-\beta T},$$

then we have in result:

$$\omega^\uparrow - \omega^\downarrow = \pi\beta.$$

Substituting this into the recurrence equation, we get:

$$\omega^\uparrow (1 + \varepsilon^{-1}) + (\omega^\uparrow - \pi\beta) (1 - \varepsilon^{-1}) = 2\omega_0 \implies \omega^\uparrow = \omega_0 - \frac{\pi\beta}{2} (\varepsilon^{-1} - 1).$$

**Answer: Answer:**

$$\omega^\uparrow = \omega_0 - \frac{\pi\beta}{2} (\varepsilon^{-1} - 1)$$

**C6**

**0.40 pts**

*Find the steady-state average over the period angular velocity of the system  $\bar{\omega}_2$  in the mode of linear viscous friction.*

From the results obtained in the previous paragraph, the exact value of the average angular velocity is:

$$\bar{\omega}_2 = \frac{\pi}{T} = \frac{\pi\beta}{-\ln\left(1 - \frac{\pi\beta}{\omega^\uparrow}\right)} = \frac{\pi\beta}{\ln(2\varepsilon\omega_0 - \pi\beta(1 - \varepsilon)) - \ln(2\varepsilon\omega_0 - \pi\beta(1 + \varepsilon))}.$$

**Answer: Answer:**

$$\bar{\omega}_2 = \frac{\pi\beta}{\ln(2\varepsilon\omega_0 - \pi\beta(1 - \varepsilon)) - \ln(2\varepsilon\omega_0 - \pi\beta(1 + \varepsilon))}$$

**C7**

**0.50 pts**

*Find the stationary value of the angular velocity  $\omega_3^\uparrow$  of the system immediately after the next collision with the ball in the quadratic viscous friction mode.*

The case of quadratic viscous friction. The equation for the angular velocity between collisions with the ball will be written in the form:

$$\dot{\omega} = -\gamma\omega^2.$$

Its solution with the initial condition  $\omega(t=0) = \omega^\uparrow$  has the form:

$$\frac{d\omega}{\omega^2} = -\gamma dt \Rightarrow \frac{1}{\omega} = \gamma t + C, \omega(t=0) = \frac{1}{C} = \omega^\uparrow \Rightarrow \omega(t) = \frac{1}{\gamma t + \frac{1}{\omega^\uparrow}} = \frac{\omega^\uparrow}{1 + \gamma\omega^\uparrow t}.$$

Then the time  $T$  of the next collision with the ball will be determined from the condition:

$$\pi = \int_0^T \omega(t) dt = \int_0^T \frac{\omega^\uparrow}{1 + \gamma\omega^\uparrow t} dt = \frac{1}{\gamma} \ln(1 + \gamma\omega^\uparrow T) \Rightarrow T = \frac{e^{\pi\gamma} - 1}{\gamma\omega^\uparrow}.$$

The angular velocity of the system  $\omega^\downarrow$  immediately before the collision with the ball will be:

$$\omega^\downarrow = \omega(T) = \omega^\uparrow e^{-\pi\gamma}.$$

Substituting this in recurrent equation, we have:

$$\omega^\uparrow (1 + \varepsilon^{-1}) + \omega^\uparrow e^{-\pi\gamma} (1 - \varepsilon^{-1}) = 2\omega_0 \Rightarrow \omega^\uparrow = \frac{2\omega_0 \varepsilon}{1 - e^{-\pi\gamma} + \varepsilon(1 + e^{-\pi\gamma})}.$$

The equation for the angular velocity between collisions with the ball will be written in the form:

$$\dot{\omega} = -\gamma\omega^2.$$

Its solution with the initial condition  $\omega(t=0) = \omega^\uparrow$  has the form:

$$\frac{d\omega}{\omega^2} = -\gamma dt \Rightarrow \frac{1}{\omega} = \gamma t + C, \omega(t=0) = \frac{1}{C} = \omega^\uparrow \Rightarrow \omega(t) = \frac{1}{\gamma t + \frac{1}{\omega^\uparrow}} = \frac{\omega^\uparrow}{1 + \gamma\omega^\uparrow t}.$$

Then the time  $T$  of the next collision with the ball will be determined from the condition:

$$\pi = \int_0^T \omega(t) dt = \int_0^T \frac{\omega^\uparrow}{1 + \gamma\omega^\uparrow t} dt = \frac{1}{\gamma} \ln(1 + \gamma\omega^\uparrow T) \Rightarrow T = \frac{e^{\pi\gamma} - 1}{\gamma\omega^\uparrow}.$$

The angular velocity of the system  $\omega^\downarrow$  immediately before the collision with the ball will be:

$$\omega^\downarrow = \omega(T) = \omega^\uparrow e^{-\pi\gamma}.$$

Substituting this in recurrent equation, we have:

$$\omega^\uparrow (1 + \varepsilon^{-1}) + \omega^\uparrow e^{-\pi\gamma} (1 - \varepsilon^{-1}) = 2\omega_0 \Rightarrow \omega^\uparrow = \frac{2\omega_0 \varepsilon}{1 - e^{-\pi\gamma} + \varepsilon(1 + e^{-\pi\gamma})}.$$

**Answer: Answer:**

$$\omega^\uparrow = \frac{2\omega_0 \varepsilon}{1 - e^{-\pi\gamma} + \varepsilon(1 + e^{-\pi\gamma})}$$

**C8**

**0.40 pts**

*Find the steady-state average over the period angular velocity of the system  $\bar{\omega}_3$  in the mode of quadratic viscous friction.*

From the results obtained in the previous paragraph, the exact value of the average angular velocity is:

$$\bar{\omega}_3 = \frac{\pi}{T} = \frac{\pi\gamma\omega^\uparrow}{e^{\pi\gamma} - 1} = \frac{\pi\varepsilon\gamma\omega_0}{2 \operatorname{sh} \frac{\pi\gamma}{2} (\operatorname{sh} \frac{\pi\gamma}{2} + \varepsilon \operatorname{ch} \frac{\pi\gamma}{2})}.$$

**Answer: Answer:**

$$\bar{\omega}_3 = \frac{\pi\varepsilon\gamma\omega_0}{2 \operatorname{sh}(\pi\gamma/2) [\operatorname{sh}(\pi\gamma/2) + \varepsilon \operatorname{ch}(\pi\gamma/2)]}$$

