

Hertz-Quincke effect — Solution

X26 (2026) — English translation

A1

0.40 pts

An infinite uniformly charged thin thread is in a vacuum. The thread is located along the z axis, the linear charge density is κ . Determine the dependence of the electrostatic potential of this thread $\varphi(r)$ in the entire space up to a constant. Express your answer using ε_0 , κ , r .

From symmetry, the electric field is directed radially. Then its value can be found from Gauss's theorem:

$$E(r) = \frac{\kappa}{2\pi\varepsilon_0 r}.$$

Integrate, obtain expression for potential:

$$\varphi(r) = - \int_a^r E(r) dr = - \frac{\kappa}{2\pi\varepsilon_0} \ln \frac{r}{a}.$$

Here a is the distance from which the potential is measured.

Answer: Answer:

$$\varphi(r) = - \frac{\kappa}{2\pi\varepsilon_0} \ln \frac{r}{a}$$

A2

0.40 pts

Now let's add a second thread with the opposite linear charge density $-\kappa$, parallel to the original one, at a very small distance from it. The dipole moment per unit length of this structure is constant and equal to $\vec{p}$. Determine the dependence of the electrostatic potential of this dipole line $\varphi(\vec{r})$ throughout space. The potential at a large distance from the dipole line tends to zero. Express your answer using ε_0 , $\vec{p}$, $\vec{r}$.

Let $\vec{a}$ be a vector perpendicular to the threads, drawn from a point of a negatively charged thread to a point of a positively charged one. For definiteness, we assume that the positively charged thread is located on the straight line $\vec{r} = 0$. If r_+ and r_- are the distances to positively and negatively charged threads, respectively, their total potential is:

$$\varphi(\vec{r}) = \frac{\kappa}{2\pi\varepsilon_0} \ln \frac{r_-}{r_+} + C = \frac{\kappa}{2\pi\varepsilon_0} \ln \frac{|\vec{r} + \vec{a}|}{r} + C.$$

in first order by $\vec{a}$ distance

$$r_- = |\vec{r} + \vec{a}| \simeq r + \frac{\vec{a}\vec{r}}{r},$$

then potential

$$\varphi(\vec{r}) = \frac{\kappa}{2\pi\varepsilon_0} \ln \left(1 + \frac{\vec{a}\vec{r}}{r^2} \right) \simeq \frac{\kappa(\vec{a}\vec{r})}{2\pi\varepsilon_0 r^2} = \frac{\vec{p}\vec{r}}{2\pi\varepsilon_0 r^2}$$

Here use $\vec{p} = \kappa\vec{a}$, and the constant is equal to 0, since at infinity this expression tends to 0.

Answer: Answer:

$$\varphi(\vec{r}) = \frac{\vec{r}\vec{p}}{2\pi\varepsilon_0 r^2}$$

A3

0.60 pts

Differentiating the expression obtained in the previous paragraph, find the electric field $\vec{E}(\vec{r})$ in the entire space. Express your answer using ε_0 , $\vec{p}$, $\vec{r}$.

Let us make the substitution $\vec{r} \rightarrow \vec{r} + \vec{\delta}$ in the expression for the potential and find the change in the potential to first order in $\vec{\delta}$. We use the relations for the distance

$$\Delta\varphi = (\vec{r} + \vec{\delta})^2 \simeq r^2 + 2(\vec{r}\vec{\delta}), \quad \frac{1}{(\vec{r} + \vec{\delta})^2} \simeq \frac{1}{r^2} - \frac{2\vec{r}\vec{\delta}}{r^4}.$$

Then for difference potential obtain

$$\begin{aligned} \varphi(\vec{r} + \vec{\delta}) - \varphi(\vec{r}) &\simeq \frac{\vec{p}(\vec{r} + \vec{\delta})}{2\pi\varepsilon_0(\vec{r} + \vec{\delta})^2} - \frac{\vec{r}\vec{p}}{2\pi\varepsilon_0 r^2} = \frac{\vec{p}}{2\pi\varepsilon_0} \cdot \left((\vec{r} + \vec{\delta}) \left(\frac{1}{r^2} - \frac{2\vec{r}\vec{\delta}}{r^4} \right) - \vec{r}r^2 \right) = \\ &= \frac{\vec{p}}{2\pi\varepsilon_0} \left(\frac{\vec{\delta}}{r^2} - \frac{2(\vec{r}\vec{\delta})\vec{r}}{r^4} \right) = -\frac{2(\vec{p}\vec{r})(\vec{r}\vec{\delta}) - (\vec{p}\vec{\delta})}{2\pi\varepsilon_0 r^4}. \end{aligned}$$

Taking into account определения gradient

$$\Delta\varphi = \vec{\nabla}\varphi \cdot \vec{\delta}, \quad \vec{\nabla}\varphi = -\frac{2(\vec{p}\vec{r})\vec{r} - \vec{p}}{2\pi\varepsilon_0 r^4}.$$

Then electric field

$$\vec{E}(\vec{r}) = -\vec{\nabla}\varphi(\vec{r}) = \frac{2(\vec{p}\vec{r})\vec{r} - \vec{p}}{2\pi\varepsilon_0 r^4}.$$

Derivative one can find and напрямую. Introduce unit vector: $\vec{e}_r$ – сонаправленный with radius-vector $\vec{r}$, $\vec{e}_\theta$ – perpendicular it and дипольным string, сонаправлен with positive direction отсчета θ . Write expression for electric field: Express $\vec{e}_\theta$:

$$\frac{\vec{p}}{p} = \vec{e}_r \frac{(\vec{p}, \vec{r})}{pr} - \vec{e}_\theta \sin \theta$$

Write down the answer:

This answer can also be obtained by considering the fields of two charged threads. To do this, let's find the field of 1 thread in vector form:

$$\vec{E} = \frac{\kappa}{2\pi\varepsilon_0} \frac{\vec{r}}{r^2}$$

And imagine the dipole field as a superposition of the fields of two threads:

$$\vec{E}(\vec{r}) = \frac{\kappa}{2\pi\varepsilon_0} \left(\frac{\vec{r}_+}{r_+^2} - \frac{\vec{r}_-}{r_-^2} \right) = \frac{\kappa}{2\pi\varepsilon_0} \left(\frac{\vec{r}}{r^2} - \frac{\vec{r} + \vec{a}}{(\vec{r} + \vec{a})^2} \right) = \frac{\kappa}{2\pi\varepsilon_0} \left(\frac{\vec{r}}{r^2} - \frac{\vec{r} + \vec{a}}{r^2 + a^2 + 2(\vec{r}, \vec{a})} \right) \approx \approx \frac{\kappa}{2\pi\varepsilon_0 r^2} \left(\vec{r} - (\vec{r} + \vec{a}) \left(1 - 2 \frac{(\vec{r}, \vec{a})}{r^2} \right) \right)$$

Answer: Answer:

$$\vec{E}(r) = \frac{1}{2\pi\varepsilon_0 r^2} \left(2 \frac{\vec{r}(\vec{r}\vec{p})}{r^2} - \vec{p} \right)$$

A4

0.60 pts

Show that the field distribution in space outside the cylinder is equal to the superposition of a uniform external field $\vec{E}_0$ and a dipole line field with a linear dipole moment density $\vec{p}$. Use the expression for the dipole line field in vacuum. Identify $\vec{p}$. Express your answer using ε_1 , ε_2 , $\vec{E}_0$, ε_0 , R . The value $\vec{p}$ you found includes both the dipole moment of the cylinder and the dipole moment of the polarization charges of the medium.

Let us write down the conditions for the components of the electric field at the medium-cylinder boundary:

$$\begin{cases} E_{\tau 2} = E_{\tau 2} \\ \varepsilon_1 E_{n1} = \varepsilon_2 E_{n2} \end{cases}$$

Assuming that the field outside is a superposition of the external homogeneous field and the dipole field, and inside it is homogeneous and codirectional with $\vec{E}_0$, we rewrite the previous system of equations:

$$\begin{cases} E_{in} \sin \theta = E_0 \sin \theta - \frac{p \sin \theta}{2\pi\varepsilon_0 R^2} \\ \varepsilon_1 E_{in} \cos \theta = \varepsilon_2 \left(E_0 \cos \theta + \frac{p \cos \theta}{2\pi\varepsilon_0 R^2} \right), \end{cases}$$

For $\vec{p} = 2\pi\varepsilon_0 \vec{E}_0 R^2 \frac{\varepsilon_1 - \varepsilon_2}{\varepsilon_1 + \varepsilon_2}$ the conditions written above are satisfied at each point of the cylinder, which means that according to the theorem uniqueness, this solution is correct.

Answer: Answer:

$$\vec{p} = 2\pi\varepsilon_0 \vec{E}_0 R^2 \frac{\varepsilon_1 - \varepsilon_2}{\varepsilon_1 + \varepsilon_2}$$

A5

0.30 pts

Determine the dependence of the electric field $\vec{E}(\vec{r})$ throughout space. Express your answer using ε_1 , ε_2 , $\vec{E}_0$, $\vec{r}$.

Let us substitute the found value $\vec{p}$ and obtain the field distribution throughout the entire space.

Answer: Answer: Inside the cylinder ($r \leq R$):

$$\vec{E}_1 = \frac{2\varepsilon_2}{\varepsilon_1 + \varepsilon_2} \vec{E}_0;$$

outside cylinder ($r > R$):

$$\vec{E} = \vec{E}_0 + \frac{\varepsilon_1 - \varepsilon_2}{\varepsilon_1 + \varepsilon_2} R^2 \left(\frac{2(\vec{r}\vec{E}_0)\vec{r}}{r^4} - \frac{\vec{E}_0}{r^2} \right).$$

A6

1.00 pts

Let the conductivity and permittivity of the cylinder be λ_1 , ε_1 , and that of the environment λ_2 , ε_2 . Electric field at a large distance from the cylinder $\vec{E}_0$. The current distribution is completely established. It is known that the field outside the cylinder is still equal to the superposition of the external field and the dipole field, and the field inside the cylinder is uniform. However, now a distribution of free (not associated with polarization) charges with a density of $\sigma_f(\theta)$ appears on the surface of the cylinder. Determine the volume current density $\vec{j}_1$ inside the cylinder and the surface charge density $\sigma_f(\theta)$ as a function of the angle θ . Direction $\vec{E}_0$ corresponds to $\theta = 0$. Note: in a conducting medium, the volumetric current density is related to the electric field by the relation $\vec{j} = \lambda \vec{E}$, where λ is the conductivity of the medium. Note: boundary conditions for the normal components of the electric field can be obtained by considering the normal components of the current density at the boundary of the cylinder and the medium. There are no surface currents flowing through the cylinder.

Note: in a conducting medium, the volumetric current density is related to the electric field by the relation $\vec{j} = \lambda \vec{E}$, where λ is the conductivity of the medium.

Note: boundary conditions for the normal components of the electric field can be ob-

tained by considering the normal components of the current density at the boundary of the cylinder and the medium. There are no surface currents flowing through the cylinder.

Let's write down new boundary conditions taking into account currents and charges
Condition for currents:

$$\lambda_1 E_{n1} = j_{n1} = j_{n2} = \lambda_2 E_{n2}$$

Condition for tangential field components:

$$E_{\tau 1} = E_{\tau 2}$$

Upon closer examination, the boundary section can be considered flat, and the charge on the boundary is constant, then writing the Gauss theorem for the electrostatic induction vector we obtain:

$$-\varepsilon_0 \varepsilon_1 E_{n1} + \varepsilon_0 \varepsilon_2 E_{n2} = \sigma_f$$

Substituting the field shape into the first two conditions, we obtain the system:

$$\begin{cases} E_{in} \sin \theta = E_0 \sin \theta - \frac{p \sin \theta}{2\pi \varepsilon_0 R^2} \\ \varepsilon_1 E_{in} \cos \theta = \varepsilon_2 \left(E_0 \cos \theta + \frac{p \cos \theta}{2\pi \varepsilon_0 R^2} \right), \end{cases}$$

which is similar to A4:

$$\vec{p} = 2\pi \varepsilon_0 \vec{E}_0 R^2 \frac{\lambda_1 - \lambda_2}{\lambda_1 + \lambda_2}$$

$$\vec{E}_{in} = \frac{2\lambda_2}{\lambda_1 + \lambda_2} \vec{E}_0$$

Substitute the expressions into the boundary condition at σ_f :

$$\sigma_f = -\varepsilon_0 \varepsilon_1 \frac{2\lambda_2}{\lambda_1 + \lambda_2} E_0 \cos \theta + \varepsilon_0 \varepsilon_2 \left(E_0 + E_0 \frac{\lambda_1 - \lambda_2}{\lambda_1 + \lambda_2} \right) \cos \theta$$

We get the answer:

Answer: Answer:

$$\sigma_f = 2\varepsilon_0 E_0 \frac{\varepsilon_2 \lambda_1 - \varepsilon_1 \lambda_2}{\lambda_1 + \lambda_2} \cos \theta$$

$$\vec{j}_1 = \frac{2\lambda_1 \lambda_2}{\lambda_1 + \lambda_2} \vec{E}_0$$

A7

0.70 pts

Now let the cylinder be ideally conducting, and the conductivity of the surrounding medium is λ_2 , its dielectric constant ε_2 . There is no external electric field. The initial charge of the cylinder is q_0 . Find the dependence of the charge of the cylinder $q(t)$ on time. Obtain an expression for the time τ_2 during which the charge of the cylinder is reduced by a factor of 2. Express your answers using λ_2 , ε_0 , ε_2 .

Because $\vec{j} = \lambda_2 \vec{E}$, the total current flowing from the cylinder is $I = \lambda_2 \Phi$. We get:

$$-\dot{q} = \lambda_2 \frac{q}{\varepsilon_0 \varepsilon_2} \Rightarrow q = q_0 e^{-\frac{\lambda_2 t}{\varepsilon_0 \varepsilon_2}}$$

We get the answer:

Answer: Answer:

$$\tau_2 = \frac{\varepsilon_0 \varepsilon_2}{\lambda_2} \ln(2)$$

B1**0.10 pts**

Write down the relationship between the tangential components of the electric fields at the interface between the medium and the cylinder.

From the condition of electric field potential:

Answer: Answer:

$$E_{\tau 1} = E_{\tau 2}$$

B2**0.50 pts**

When the cylinder moves, free charges on the surface of the cylinder rotate with it. Therefore, a surface current density $i(\theta)$ appears on the surface of the cylinder. Express it in terms of ω , R and the density of free charges. The value $i(\theta)$ is considered positive if the current is directed in the direction of increasing θ .

Answer: Answer:

$$i(\theta) = R\omega\sigma_f(\theta)$$

B3**0.70 pts**

Let us consider a small section of the cylinder surface corresponding to the interval of angles $(\theta_0, \theta_0 + d\theta)$ of area $dS = RLd\theta$. Charge flows into it through the boundaries $\theta = \theta_0$ due to $i(\theta_0)$, and current flows through the boundary at $\theta = \theta_0 + d\theta$ due to $i(\theta_0 + d\theta)$. Also, a normal current with density j_{1n} flows into it and a normal current with density j_{2n} flows out. In steady state, the total charge of the region under consideration does not change. Write down the following relationship between the currents $i(\theta_0)$, $i(\theta_0 + d\theta)$, j_{1n} , j_{2n} from the law of conservation of charge. The answer may also include R and $d\theta$.

From the law of conservation of charge we obtain the relation:

$$Li(\theta_0) - Li(\theta_0 + d\theta) + dSj_{1n} - dSj_{2n} = 0$$

By opening dS , we obtain:

Answer: Answer:

$$i(\theta_0) - i(\theta_0 + d\theta) + R(j_{1n} - j_{2n})d\theta = 0$$

B4**0.50 pts**

In the relation from the previous paragraph, substitute expressions for normal currents through the normal components of the electric field and surface currents through the charge density. Get the relationship between E_{1n} , E_{2n} , ω , λ_1 , λ_2 , $\partial\sigma_f/\partial\theta$.

Directing $d\theta$ to zero, we get:

$$-L\frac{\partial i}{\partial\theta}(\theta_0) + RL(j_{1n} - j_{2n}) = 0$$

We derive the answer by expanding i and taking into account that $\vec{j} = \lambda\vec{E}$, we get:

Answer: Answer:

$$-\omega\frac{\partial\sigma_f}{\partial\theta} + \lambda_1 E_{1n} - \lambda_2 E_{2n} = 0$$

B5**0.40 pts**

Express the density of free charges σ_f in terms of the electric field components near the boundary. Using the results of point B4, obtain from here the relationship only between the electric field components E_{1n} , E_{2n} and their derivatives with respect to θ . The answer may also include ε_1 , λ_1 , ε_2 , λ_2 , ω .

From the previous paragraph:

$$-\omega \frac{\partial \sigma_f}{\partial \theta} + \lambda_1 E_{1n} - \lambda_2 E_{2n} = 0$$

Let's write the boundary condition on the electrostatic induction vector:

$$-\varepsilon_0 \varepsilon_1 E_{n1} + \varepsilon_0 \varepsilon_2 E_{n2} = \sigma_f$$

differentiate it and substitute $\frac{\partial \sigma_f}{\partial \theta}$:

Answer: Answer:

$$\left(\lambda_1 + \omega \varepsilon_1 \varepsilon_0 \frac{\partial}{\partial \theta} \right) E_{1n} = \left(\lambda_2 + \omega \varepsilon_2 \varepsilon_0 \frac{\partial}{\partial \theta} \right) E_{2n}$$

B6

0.50 pts

Show that expressions for complex permeabilities can be written in the form

$$\varepsilon_1^* = \varepsilon_1 + \frac{i\lambda_1}{\varepsilon_0 \omega}, \quad \varepsilon_2^* = \varepsilon_2 + \frac{i\lambda_2}{\varepsilon_0 \omega}.$$

These formulas can then be used without proof. Note: Since the cylinder rotates with angular velocity ω , $d\theta/dt = +\omega$ and the angular derivative θ can be expressed in terms of the time derivative in the rotating frame.

$$\varepsilon_1^* = \varepsilon_1 + \frac{i\lambda_1}{\varepsilon_0 \omega}, \quad \varepsilon_2^* = \varepsilon_2 + \frac{i\lambda_2}{\varepsilon_0 \omega}.$$

Further, these formulas can be used without proof.

Note: Since the cylinder rotates with angular velocity ω , $d\theta/dt = +\omega$ and the angular derivative θ can be expressed in terms of the time derivative in the rotating frame.

The field in the reference frame of the cylinder rotates with angular velocity $-\omega$. Therefore $\frac{\partial}{\partial \theta} = \frac{1}{\omega} \frac{\partial}{\partial t} = \frac{-i\omega}{\omega} = -i$. Boundary condition:

$$(\lambda_1 - i\omega \varepsilon_1 \varepsilon_0) E_{1n} = (\lambda_2 - i\omega \varepsilon_2 \varepsilon_0) E_{2n}$$

From here:

Answer: Answer:

$$\varepsilon_1^* = \varepsilon_1 + \frac{i\lambda_1}{\omega \varepsilon_0}$$

$$\varepsilon_2^* = \varepsilon_2 + \frac{i\lambda_2}{\omega \varepsilon_0}$$

B7

0.50 pts

Determine the complex amplitude of the linear density of the dipole moment of the cylinder $\vec{p}^*$. Express your answer using ε_1 , λ_1 , ε_2 , λ_2 , ω , ε_0 , R , $\vec{E}_0^*$.

Similar to the electrostatic case from Part A, we can write the answer by substituting complex dielectric constants. Hence we have:

$$\vec{p}^* = 2\pi \varepsilon_0 \vec{E}_0^* R^2 \frac{\varepsilon_1^* - \varepsilon_2^*}{\varepsilon_1^* + \varepsilon_2^*} = 2\pi \varepsilon_0 \vec{E}_0^* R^2 \frac{\varepsilon_1 - \varepsilon_2 + \frac{i(\lambda_1 - \lambda_2)}{\omega \varepsilon_0}}{\varepsilon_1 + \varepsilon_2 + \frac{i(\lambda_1 + \lambda_2)}{\omega \varepsilon_0}}$$

$$\vec{p}^* = 2\pi\epsilon_0 \vec{E}_0^* R^2 \frac{\epsilon_1^* - \epsilon_2^*}{\epsilon_1^* + \epsilon_2^*} = 2\pi\epsilon_0 \vec{E}_0^* R^2 \frac{\epsilon_1 - \epsilon_2 + \frac{i(\lambda_1 - \lambda_2)}{\omega\epsilon_0}}{\epsilon_1 + \epsilon_2 + \frac{i(\lambda_1 + \lambda_2)}{\omega\epsilon_0}}$$

Answer: Answer:

$$\vec{p}^* = 2\pi\epsilon_0 \vec{E}_0^* R^2 \frac{\epsilon_1 - \epsilon_2 + \frac{i(\lambda_1 - \lambda_2)}{\omega\epsilon_0}}{\epsilon_1 + \epsilon_2 + \frac{i(\lambda_1 + \lambda_2)}{\omega\epsilon_0}}$$

B8

0.80 pts

Determine the projections on the x and y axes of the $\vec{p}$ vector in the laboratory frame.

Let's express p_x :

$$p_x = \text{Re}(\vec{p}^*, \vec{e}_x)$$

The expression for p_y is similar:

$$p_y = \text{Re}(\vec{p}^*, \vec{e}_y)$$

We use that $\vec{E}_0^* = E_0(\vec{e}_x - i\vec{e}_y)$. Let's transform the expression from the previous paragraph:

$$\vec{p}^* = 2\pi\epsilon_0 \vec{E}_0^* R^2 \frac{\left(\epsilon_1 - \epsilon_2 + \frac{i(\lambda_1 - \lambda_2)}{\omega\epsilon_0}\right) \left(\epsilon_1 + \epsilon_2 - \frac{i(\lambda_1 + \lambda_2)}{\omega\epsilon_0}\right)}{(\epsilon_1 + \epsilon_2)^2 + \frac{(\lambda_1 + \lambda_2)^2}{\omega^2\epsilon_0^2}} = 2\pi\epsilon_0 \vec{E}_0^* R^2 \frac{\epsilon_1^2 - \epsilon_2^2 + \frac{(\lambda_1^2 - \lambda_2^2)}{\omega^2\epsilon_0^2} + 2i\frac{\lambda_1\epsilon_2 - \lambda_2\epsilon_1}{\omega\epsilon_0}}{(\epsilon_1 + \epsilon_2)^2 + \frac{(\lambda_1 + \lambda_2)^2}{\omega^2\epsilon_0^2}}$$

and get the answers:

Answer: Answer:

$$p_x = 2\pi R^2 \epsilon_0 E_0 \frac{\omega^2 \epsilon_0^2 (\epsilon_1^2 - \epsilon_2^2) + \lambda_1^2 - \lambda_2^2}{(\epsilon_1 + \epsilon_2)^2 + (\omega\epsilon_0)^2 (\epsilon_1 + \epsilon_2)^2},$$

$$p_y = -4\pi\omega R^2 \epsilon_0^2 E_0 \frac{(\epsilon_1 \lambda_2 - \epsilon_2 \lambda_1)}{(\lambda_1 + \lambda_2)^2 + (\omega\epsilon_0)^2 (\epsilon_1 + \epsilon_2)^2}$$

B9

0.60 pts

Determine the projection of the moment of force M_E acting on the cylinder (with the polarization charges of the medium surrounding it) from the external electric field onto the axis z . Express your answer using E_0 , ϵ_0 , ω , ϵ_1 , λ_1 , ϵ_2 , λ_2 , R , L .

The total effective dipole moment of the cylinder is $\vec{p}L$, then:

$$\vec{M} = [\vec{p}, \vec{E}_0]L$$

Let us express M_z :

$$M_z = -p_y E_0 L = 4\pi\omega L R^2 \epsilon_0^2 E_0^2 \frac{(\epsilon_1 \lambda_2 - \epsilon_2 \lambda_1)}{(\lambda_1 + \lambda_2)^2 + (\omega\epsilon_0)^2 (\epsilon_1 + \epsilon_2)^2}$$

Answer: Answer:

$$M_z = 4\pi\omega L R^2 \epsilon_0^2 E_0^2 \frac{(\epsilon_1 \lambda_2 - \epsilon_2 \lambda_1)}{(\lambda_1 + \lambda_2)^2 + (\omega\epsilon_0)^2 (\epsilon_1 + \epsilon_2)^2}$$

B10

0.40 pts

At a certain relationship between the system parameters, the torque obtained above causes a further increase in the angular velocity of the cylinder. Indicate the relationship between

the parameters at which this is possible.

Rotation is possible at $M_z > 0$, this corresponds to the relation:

$$\varepsilon_2/\lambda_2 < \varepsilon_1/\lambda_1$$

We note that this expression is not accidental: its physical meaning: the characteristic discharge time of the medium is less than the characteristic discharge time of the cylinder, therefore the phenomenon of delayed repolarization may occur, which is the cause of rotation.

Answer: Answer:

$$\varepsilon_2/\lambda_2 < \varepsilon_1/\lambda_1$$

C1

0.70 pts

The moment of forces can be written in the form $M_\eta = -\alpha\eta^a\omega^b R^c L^d$, where α is a dimensionless constant. Using the dimensional method and physical considerations, determine the exponents a, b, c, d .

There is no movement of the liquid along the z axis, which means the movement of the fluid elements does not depend in any way on z from symmetry. The area of the lateral surface of the cylinder is proportional to L , the distance from the point of application of force to the axis does not depend on L , therefore:

To find the remaining powers, we use the method of dimensions:

$$\cdot \text{m} = (\cdot \text{m}^{-2} \cdot \text{s})^a \cdot \text{c}^{-b} \cdot \text{m}^c \cdot \text{m}$$

Equating the coefficients before Newtons, we obtain:

Equating the coefficients before seconds, we get:

Equating the coefficients in front of meters, we get:

Answer: Answer:

$$d = 1$$

C2

0.30 pts

Find the moment of viscous friction forces M acting on the outer side of a cylindrical layer of liquid of radius r , where $r > R$. Express your answer using $\eta, r, L, \frac{\partial \omega}{\partial r}$.

Moment of force acting on a small cylindrical layer of liquid:

$$M = \tau_{\theta z} \cdot S \cdot r = 2\pi\eta r^3 L \frac{\partial \omega}{\partial r}$$

Answer: Answer:

$$M = \tau_{\theta z} \cdot S \cdot r = 2\pi\eta r^3 L \frac{\partial \omega}{\partial r}$$

C3

1.20 pts

Determine the coefficient α in the formula for the moment of force M_η .

Since each fluid element rotates uniformly, the moment acting on the outer side of the fluid layer will be equal to the moment with which this fluid layer acts on the layer below it. That is, $M = M_\eta = \text{const}$. Let's separate the variables and integrate this equation:

$$\frac{M_\eta}{2\pi\eta L} \frac{dr}{r^3} = d\omega$$

Since $\omega(r \rightarrow \infty) = 0$, and $\omega(R) = \omega_0$, then:

$$\frac{M_\eta}{2\pi\eta L} \int_\infty^R \frac{dr}{r^3} = \omega_0$$

Write the final expression:

Answer: Answer:

$$M_\eta = -4\pi\omega_0\eta LR^2$$

C4

0.30 pts

Let us give the cylinder a small angular velocity $\delta\omega$. If the external electric field is greater than a certain critical value $E_0 > E_{cr}$, the angular velocity will increase. Express the critical field E_{cr} in terms of $\varepsilon_1, \varepsilon_2, \varepsilon_0, \eta, \lambda_1, \lambda_2, \alpha$.

The minimum condition is $\omega_0 = 0$. Neglecting the term with ω^2 in the denominator, we get:

Answer: Answer:

$$E_{cr} = \sqrt{\frac{\alpha\eta}{4\pi\varepsilon_0^2} \frac{(\lambda_1 + \lambda_2)^2}{(\varepsilon_1\lambda_2 - \varepsilon_2\lambda_1)}}$$

C5

0.50 pts

Let $E_0 > E_{cr}$. Determine the steady-state angular velocity of the cylinder ω_0 . Express your answer using $E_0, E_{cr}, \varepsilon_0, \varepsilon_1, \lambda_1, \varepsilon_2, \lambda_2$.

Condition for setting the speed:

$$M_z + M_\eta = 0$$

From here we get:

Answer: Answer:

$$\omega_0 = \frac{\sqrt{\frac{(\varepsilon_1\lambda_2 - \varepsilon_2\lambda_1)\varepsilon_0^2 E_0^2}{\eta} - (\lambda_1 + \lambda_2)^2}}{\varepsilon_0(\varepsilon_1 + \varepsilon_2)}$$