

Coulomb's law — Solution

X26 (2026) — English translation

00

-20.00 pts

Attention! The solenoids supplied include low-melting plexiglass (melting point 140 °C). The resistance of the thermistor during the experiment SHOULD NOT exceed 145 Ω . Equipment breakdown if you act contrary to the instructions of the conditions will lead to your disqualification from the tour!

Equipment breakdown if you act contrary to the instructions of the conditions will lead to your disqualification from the tour!

A0

1.00 pts

Write down the distance x_0 between the axes of the solenoids in the absence of current through them. After assembling the setup, invite the audience member to take a photo of your setup. The photograph should show: Solenoids attached to threads of as long a length as possible. The solenoids must be parallel and horizontal! Wires brought out through the top near the solenoid suspension points (otherwise the wires will create an additional deflecting moment of force). The entire installation must be secured and cannot be supported by hands! Attention! In case of violation of the order of assembly of the installation and recognition of the installation as unsuitable for measurements or absence of photographs, all points related to measurements and data processing WILL BE ASSESSED WITH 0 POINTS!

After assembling the setup, invite the audience member to take a photo of your setup. The photo should show:

The entire installation must be secured and cannot be supported by hands!

Attention! In case of violation of the order of assembly of the installation and recognition of the installation as unsuitable for measurements or absence of photographs, all points related to measurements and data processing WILL BE ASSESSED WITH 0 POINTS!

Let us fix the equilibrium distance between the axes of the solenoids in the absence of current:

Answer: \textbf{Answer:}

$$x_0 = 5.1 \text{ cm}$$

A1

0.30 pts

Obtain a formula relating the repulsive force F of solenoids from each other with the distance x between them. Express this force in terms of the magnetic charges q_m on the ends of the solenoids, the lengths of the solenoids l , x and μ_0 .

Let us consider a solenoid that has deviated by a small angle α from the equilibrium position (see Figure 2). Let's write Newton's II law for this solenoid in projection onto the y axis:

$$2F_k \cos \alpha = mg \sin \alpha.$$

Coefficient 2 появляется from-за того, что solenoid имеет два полюса (магнитных chargea), каждый from которых взаимодействует с соседним полюсом другого solenoida. Taking into account that for малого угла α справедливы формулы $\sin \alpha \approx \alpha \approx \frac{x - x_0}{2L}$ and

$\cos \alpha \approx 1$, transforming II Newton's law:


$$F_k = \frac{mg}{2} \frac{x - x_0}{2L} = \frac{\mu_0 q_m^2}{4\pi} \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

Во всех партиях задачи использовались высота подвеса $h = 1.37 \text{ m}$ and density намотки

$$n = \frac{N}{l} = \frac{300}{20.9 \text{ cm}} = 1435 \text{ m}^{-1}.$$

Answer: \textbf{Answer:}

$$F = 2F_k = 2 \frac{mg}{2} \frac{x - x_0}{2L} = \frac{\mu_0 q_m^2}{2\pi} \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$



A2

0.20 pts

Express the magnetic field induction B in the center of the solenoids cores through the distance x between them, the mass of the solenoids m , the length of the suspension L , as well as other necessary quantities.

In A4 of the introduction it was said that the magnetic charge of the solenoid is equal to the flux of the magnetic field induction vector B through the end of the solenoid. This flow is equal to:

$$\Phi_B = B \cdot S$$

where B - value индукции магнитного поля на торце solenoida, S - area сечения solenoida.

A therefore:

$$\mu_0 q_m = B \cdot S$$

Substituting формулу for магнитного chargea q_m в формулу for силы Кулона, we get:

$$F_k = \frac{mg}{2} \frac{x - x_0}{2L} = \frac{B^2 S^2}{4\pi\mu_0} \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

Let us express hence индукцию магнитного поля внутри solenoida B via/through distance x between solenoids:

This means:

$$\mu_0 q_m = B \cdot S$$

Substituting формулу for магнитного chargea q_m в формулу for силы Кулона, we get:

$$F_k = \frac{mg}{2} \frac{x - x_0}{2L} = \frac{B^2 S^2}{4\pi\mu_0} \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

Let us express hence индукцию магнитного поля внутри solenoida B via/through distance x between the solenoids:

Answer: \textbf{Answer:}

$$B = \frac{1}{S} \sqrt{\frac{\pi\mu_0 mg(x - x_0)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right) L}}$$

A3

5.00 pts

Measure the dependence of the distance x between the axes of the solenoids on the strength of the current I flowing through each of the solenoids, changing the current in the range from -5 A to $+5$ A with a step of 0.2 A, and for currents less than 0.6 A in absolute value - with a step of 0.15 A. Since the magnetic permeability of the solenoid core depends on temperature, try to keep the solenoids' temperature within 10 °C of room temperature in your measurements.

Since the magnetic permeability of the solenoid core depends on temperature, try to keep the solenoids' temperature within 10 °C of room temperature in your measurements.

Let us remove the dependence of the distance between the solenoids x on the strength of the current I flowing through them, in the current range from -5 A to $+5$ A.

Answer: \textbf{Answer:} $I, \text{ A } x, \text{ cm } I, \text{ A } x, \text{ cm } I, \text{ A } x, \text{ cm } I, \text{ A } x, \text{ cm } -5 \ 9 \ -2.2 \ 8.1 \ 0.3 \ 5.3 \ 3 \ 8.5 \ -4.8 \ 9 \ -2 \ 7.9 \ 0.45 \ 5.6 \ 3.2 \ 8.6 \ -4.6 \ 9 \ -1.8 \ 7.6 \ 0.6 \ 5.9 \ 3.4 \ 8.7 \ -4.4 \ 8.9 \ -1.6 \ 7.5 \ 0.8 \ 6.2 \ 3.6 \ 8.7 \ -4.2 \ 8.9 \ -1.4 \ 7.2 \ 1 \ 6.6 \ 3.8 \ 8.7 \ -4 \ 8.8 \ -1.2 \ 7 \ 1.2 \ 6.8 \ 4 \ 8.8 \ -3.8 \ 8.7 \ -1 \ 6.6 \ 1.4 \ 7.2 \ 4.2 \ 8.9 \ -3.6 \ 8.7 \ -0.8 \ 6.4 \ 1.6 \ 7.5 \ 4.4 \ 8.9 \ -3.4 \ 8.6 \ -0.6 \ 6 \ 1.8 \ 7.6 \ 4.6 \ 8.9 \ -3.2 \ 8.6 \ -0.45 \ 5.8 \ 2 \ 7.8 \ 4.8 \ 8.9 \ -3 \ 8.5 \ -0.3 \ 5.6 \ 2.2 \ 8 \ 5 \ 8.9 \ -2.8 \ 8.4 \ -0.15 \ 5.3 \ 2.4 \ 8.2 \ -2.6 \ 8.3 \ 0 \ 5.1 \ 2.6 \ 8.2 \ -2.4 \ 8.2 \ 0.15 \ 5.1 \ 2.8 \ 8.4$

A4


1.20 pts

From the dependence obtained in A3, calculate the values of the magnetic field induction B inside the solenoid and the magnetic field strength $H = nI$ inside the solenoid, where n is the number of turns per unit length of the solenoid, I is the current through the solenoid. Plot $B(H)$ for currents I from -5 A to $+5$ A, neglecting hysteresis.

Let's calculate the values of H and B . Let's construct a hysteresis loop for the given values of H and B (red loop in Figure 3).

$H, \text{ A/m } B, \text{ Tl } H, \text{ A/m } B, \text{ Tl } H, \text{ A/m } B, \text{ Tl } H, \text{ A/m } B, \text{ Tl } -7175 \ -0.37563 \ -3157 \ -0.29406 \ 430.5 \ 0.050919 \ 4305 \ 0.329651 \ -6888 \ -0.37563 \ -2870 \ -0.27663 \ 645.75 \ 0.082839 \ 4592 \ 0.338711 \ -6601 \ -0.37563 \ -2583 \ -0.25091 \ 861 \ 0.109779 \ 4879 \ 0.347838 \ -6314 \ -0.3663 \ -2296 \ -0.24244 \ 1148 \ 0.135063 \ 5166 \ 0.347838 \ -6027 \ -0.3663 \ -2009 \ -0.21731 \ 1435 \ 0.167933 \ 5453 \ 0.347838$

-5740 -0.35703 -1722 -0.20076 1722 0.184312 5740 0.357033 -5453 -0.34784 -1435 -0.16793 2009 0.217314 6027 0.366298 -5166 -0.34784 -1148 -0.15155 2296 0.242443 6314 0.366298 -4879 -0.33871 -861 -0.11832 2583 0.250912 6601 0.366298 -4592 -0.33871 -645.75 -0.10107 2870 0.268003 6888 0.366298 -4305 -0.32965 -430.5 -0.08284 3157 0.285315 7175 0.366298 -4018 -0.32066 -215.25 -0.05092 3444 0.302862 -3731 -0.31173 0 -0.01476 3731 0.302862 -3444 -0.30286 215.25 0.01476 4018 0.320657



A5


0.30 pts

From the experimental data, estimate the residual magnetization B_r for the hysteresis loop from A4.

from the graph from point 4 we find:

Answer: \textbf{Answer:}

$$B_r = (15 \pm 5) \text{ mT}$$



A6

0.30 pts

From the experimental data, estimate the coercive force H_c for the hysteresis loop from A4.

The solenoids return to their original equilibrium position when current flows through them $I \approx 150$ mA. Let us express the coercive force:

Answer: \textbf{Answer:}

$$H_c = (85 \pm 20) \text{ A/m}$$

A7

0.20 pts

At what maximum absolute value of the current flowing through the solenoids, the dependence $B(H)$, neglecting hysteresis, is still described by direct proportionality?

The dependence $B(H)$ becomes nonlinear at $H > 1000$ A/, which corresponds to:

Answer: \textbf{Answer:} $I_{cr} = 0.8$ A

A8

1.50 pts

Calculate the magnetic permeability $\mu = \frac{1}{\mu_0} \frac{dB}{dH}$ of the solenoid core in the linear section. To improve measurement accuracy, use linearization, which does not require knowledge of the value x_0 .

To improve measurement accuracy, use linearization, which does not require knowledge of the value x_0 .

The value of the magnetic susceptibility of the iron core can be calculated using the formula:

$$\mu = \frac{1}{\mu_0} \frac{dB}{dH}$$

Максимальную магнитную восfor/atandmчивость $\mu_{\max}$ железный сердечник будет иметь then, когда ratio $\frac{dB}{dH}$ максимально, that is вблfromand нуля. Максимальный current не должен превышать значения I_{cr} , найденного в parte A7 . Condition equalsвесия:

$$B = \frac{1}{S} \sqrt{\frac{\pi \mu_0 m g (x - x_0)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} = \mu \mu_0 n I$$

Hence the dependence

$$\xi(x) = I^2 \cdot \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

is linear. Let's recalculate the points and plot the resulting relationship:

Equilibrium condition:

$$B = \frac{1}{S} \sqrt{\frac{\pi \mu_0 m g (x - x_0)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} = \mu \mu_0 n I$$

Hence the dependence

$$\xi(x) = I^2 \cdot \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

linear. Let's recalculate the points and plot the resulting relationship:

$I, \text{ A } x, \text{ cm } \xi, \text{ A}^2/\text{m}^2$ 0 5.1 0 0.15 5.1 8.51 0.3 5.3 31.47 0.45 5.6 63.23 0.6 5.9 100.94 0.8 6.2 161.93

Let's calculate the slope of the resulting graph:


$$k = \frac{\partial \xi}{\partial x} = \frac{\pi mg}{\mu_0 L S^2 n^2 \mu^2} = (14300 \pm 600) \frac{\text{A}^2}{3},$$

from:

$$\mu = \sqrt{\frac{\pi mg}{\mu_0 L S^2 n^2 k}} = 94 \pm 4$$

Answer: \textbf{Answer:}

$$\mu = 94 \pm 4$$



B1

0.30 pts

Derive a theoretical expression relating the distance x between solenoids and the current I through one solenoid. The answer may include the function $B(H)$ and any necessary quantities.

Same as part A:

$$B(nI) = \frac{1}{S} \sqrt{\frac{\pi \mu_0 mg(x_0 - x)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} \approx \frac{x}{S} \sqrt{\frac{\pi \mu_0 mg(x_0 - x)}{L}}$$

$$B(nI) = \frac{1}{S} \sqrt{\frac{\pi \mu_0 mg(x_0 - x)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} \approx \frac{x}{S} \sqrt{\frac{\pi \mu_0 mg(x_0 - x)}{L}}$$

Answer: \textbf{Answer:}

$$B(nI) = \frac{x}{S} \sqrt{\frac{\pi \mu_0 mg(x_0 - x)}{L}}$$

B2

1.00 pts

At what minimum current I_{high} does a sharp “sticking together” of solenoids occur with a smooth increase in current? The answer may include the function $H(B)$ and any necessary quantities.

Abrupt sticking of solenoids occurs at the moment when their equilibrium becomes unstable. Equilibrium condition:

$$\frac{B^2(nI)S^2L}{x^2} = \pi\mu_0mg(x_0 - x)$$

Differentiate with respect to x :

$$-2\frac{B^2(nI)S^2L}{x^3} = -\pi\mu_0mg$$

Solving jointly, we obtain:

$$x = 2x_0/3$$

$$B^2(nI)S^2L = \frac{4\pi}{27}\mu_0mgx_0^3$$

$$F_k = \frac{mg}{2} \frac{x - x_0}{2L} = \frac{\mu_0q_m^2}{4\pi} \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

Answer: \textbf{Answer:}

$$B(nI_{\text{high}}) = \sqrt{\frac{4\pi}{27S^2L}\mu_0mgx_0^3}$$

B3

0.30 pts

At what current I_{low} do the solenoids come apart again? The answer may include the function $H(B)$ and any necessary quantities.

After adhesion, the solenoids are in equilibrium due to the reaction force generated when they press against each other. Unsticking occurs at moment $N = 0$:

$$B(nI_{\text{low}}) = \frac{x_1}{S} \sqrt{\frac{\pi\mu_0mg(x_0 - x_1)}{L}},$$

where $x_1 = 2.5 \text{ cm}$ - the distance between the axes of the solenoids when they are pressed closely to each other.

Answer: \textbf{Answer:}

$$B(nI_{\text{low}}) = \frac{x_1}{S} \sqrt{\frac{\pi\mu_0mg(x_0 - x_1)}{L}}$$

B4



1.90 pts

Measure the relationship $I_{\text{low,high}}(x_0)$ for three different values of x_0 . Plot these dependencies on the same graph with the theoretical dependencies calculated from the curve obtained in the previous part. Do any of these dependencies diverge from the theoretical ones? If yes, please explain why.

Let's measure the dependences $I_{\text{low,high}}(x_0)$, calculate the corresponding theoretical values and construct the corresponding graphs:

$x_0, \text{ cm}$	$I_{\text{high,exp}}$	$I_{\text{low,exp}}$	B_{high}	B_{low}	$I_{\text{high,th}}$	$I_{\text{low,th}}$
4.40	254	239	0.0720	0.0699	421	411
5.1	378	311	0.0898	0.0818	511	470
5.5	396	321	0.1006	0.0878	565	501

Answer: \textbf{Answer:} Both dependences diverge from the theoretical ones because the wires create additional torque.



C1

4.50 pts

Get at least four different values of $\mu(T)$. To measure, use repulsion as in Part A. If you are reassembling the unit, you cannot use the value obtained in Part A at room temperature. This is due to the fact that differences in the values of μ arising due to non-ideal assembly of the installation can be comparable to the measured effect. When processing experimental data, use the linearization from A8. Attention! The issued cores have low thermal conductivity. You can consider the core temperature to be equal to the thermocouple temperature by maintaining the corresponding constant thermocouple temperature for at least 10 minutes.

Attention! The issued cores have low thermal conductivity. You can consider the core temperature to be equal to the thermocouple temperature by maintaining the corresponding constant thermocouple temperature for at least 10 minutes.

The issued cores heat up quite slowly. Let's set a constant current value through the coils. After 10 minutes, turn the current to zero and remove the dependence of the distance between the axes of the solenoids on the current through them. Hysteresis can be ignored because it is small and in linearization will affect the constant shift. The maximum current must not exceed the value I_{cr} found in point A8. There should not be a large number of points in the dependencies because the cores will cool down. The equilibrium

condition is the same as in Part A:

$$B = \frac{1}{S} \sqrt{\frac{\pi\mu_0 mg(x - x_0)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} = \mu\mu_0 nI$$

Hence зависимость $\xi(x)$ линейна. Снимем зависимости $I(x)$ at four different temperatures. The core cools down quite slowly, so as the temperature for the experiment, we will record the temperature corresponding to the ohmmeter readings at the moment the measurements begin.

The equilibrium condition is the same as in part A:

$$B = \frac{1}{S} \sqrt{\frac{\pi\mu_0 mg(x - x_0)}{\left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}}\right) L}} = \mu\mu_0 nI$$

Hence the dependence

$$\xi(x) = I^2 \cdot \left(\frac{1}{x^2} - \frac{x}{(x^2 + l^2)^{\frac{3}{2}}} \right)$$

linear.

Let us remove the dependences $I(x)$ at four different temperatures. The core cools down quite slowly, so as the temperature for the experiment, we will record the temperature corresponding to the ohmmeter readings at the moment the measurements begin.

$R = 111 \, \Omega, T = 299 \, \text{K}$ $I, \text{ A}$ $x, \text{ cm}$ $\xi, \text{ A}^2/\mu^2$ 0 6.1 0 0.15 6.2 5.69 0.3 6.4 21.3 0.45 6.5 46.4 0.6 6.7 77.5 0.75 6.9 113.8 0.9 7.3 145.5

$R = 111 \, \Omega, T = 299 \, \text{K}$

$R = 122 \, \Omega, T = 328 \, \text{K}$ $I, \text{ A}$ $x, \text{ cm}$ $\xi, \text{ A}^2/\mu^2$ 0 6.2 0.0 0.15 6.3 5.5 0.3 6.4 21.3 0.45 6.5 46.4 0.6 6.7 77.5 0.75 7 110.4 0.9 7.2 149.8

$R = 122 \, \Omega, T = 328 \, \text{K}$

$R = 131 \, \Omega, T = 352 \, \text{K}$ $I, \text{ A}$ $x, \text{ cm}$ $\xi, \text{ A}^2/\mu^2$ 0 6.2 0.0 0.15 6.4 5.3 0.3 6.5 20.6 0.45 6.6 45.0 0.6 6.7 77.5 0.75 7 110.4 0.9 7.2 149.8

$R = 131 \, \Omega, T = 352 \, \text{K}$

$R = 143 \, \Omega, T = 383 \, \text{K}$ $I, \text{ A}$ $x, \text{ cm}$ $\xi, \text{ A}^2/\mu^2$ 0 6.2 0.0 0.15 6.3 5.5 0.3 6.4 21.3 0.45 6.5 46.4 0.6 6.7 77.5 0.75 6.9 113.8 0.9 7.1 154.3

$R = 143 \, \Omega, T = 383 \, \text{K}$

We obtain the angular coefficients using least squares. The obtained values are related to the parameters of the cores as follows:


$$k = \frac{\partial \xi}{\partial x} = \frac{\pi mg}{\mu_0 L S^2 n^2 \mu^2},$$

from:

$$\mu = \sqrt{\frac{\pi mg}{\mu_0 L S^2 n^2 k}}$$

Calculate the values $\mu(T)$ and construct a linearized graph:

$T, \text{ K}$ $k, \text{ A}^2/\mu^3$ $\mu, \text{ T}^{\frac{3}{2}}, \text{ K}^{\frac{3}{2}}$ 299 13200 97.92 5177 328 15130 91.46 5944 352 16080 88.72 6598 383 17650 84.68 7504



C2

2.00 pts

Define $\mu(0)$ and T_c for issued cores.

Angular coefficient of the plotted graph:

$$k = -\mu(0)T_c^{-\frac{3}{2}} = -5.54 \cdot 10^{-3} \text{ K}^{-\frac{3}{2}},$$

Free term:

$$\mu(0) = 126$$

From here:

$$T_c = 800 \text{ K}$$

Answer: \textbf{Answer:

$$\mu(0) = 126$$

$$T_c = 800 \text{ K}$$