



Advanced Parallel School 2022

Quantum Computing – Day 2

Quantum Error Correction

Mengoni Riccardo, PhD

15 Feb 2022

Intro to QEC

Common sources of errors in QC

- **Coherent quantum errors:** Gates which are incorrectly applied
- **Environmental decoherence:** errors due to the interaction with the external environment
- **Initialization errors:** failing to prepare the correct initial state
- **Qubit loss**

Classical Error Correction

Classical error correction employs **redundancy**.

The simplest way is **to store the information multiple times**, and just take a **majority vote** if these copies are later found to disagree

0 → 0 0 0

1 → 1 1 1


Quantum Error Correction

It is possible to reuse **redundancy** in **quantum error correction**. However, there are some complications:

- **No-cloning Theorem**
- Qubits are susceptible to both bit-flips (**X-errors**) and phase-flips (**Z-errors**). (Classically, only bit-flip errors)
- **Measuring affects the quantum state.** Detecting errors must not compromise encoded information


Cryptography

Shor's Algorithm
Exponential Speedup



Optimization

Grover's Algorithm
Quadratic Speedup



Cryptography

Shor's Algorithm
Exponential Speedup

Optimization

Grover's Algorithm
Quadratic Speedup


These algorithms assume to
have **ideal qubits** that are **not**
subjected to noise and errors

Cryptography

Shor's Algorithm
Exponential Speedup

Optimization

Grover's Algorithm
Quadratic Speedup



- Require **error corrected (fault-tolerant)** quantum computers with about **1 million or 100 thousands of qubits**
- Will be available in **10-20 years**

Quantum Error Correction

It is possible to reuse **redundancy** in **quantum error correction**. However, there are some complications:

- **No-cloning Theorem**
- Qubits are susceptible to both bit-flips (**X-errors**) and phase-flips (**Z-errors**). (Classically, only bit-flip errors)
- **Measuring affects the quantum state.** Detecting errors must not compromise encoded information

No Cloning Theorem

No Cloning theorem

It does NOT exist an universal cloning machine which is a unitary transformation such that

$$U|\psi\rangle|\alpha\rangle = |\psi\rangle|\psi\rangle$$

$$\forall |\psi\rangle \in \mathcal{H} \quad \text{and} \quad |\alpha\rangle \in \mathcal{H} \text{ fixed}$$

No Cloning theorem: proof

Suppose such universal cloning machine exists and apply it to two states like below

$$U|\psi_1\rangle|\alpha\rangle = |\psi_1\rangle|\psi_1\rangle$$

$$U|\psi_2\rangle|\alpha\rangle = |\psi_2\rangle|\psi_2\rangle$$

No Cloning theorem: proof

Suppose such universal cloning machine exists and apply it to two states like below

$$U|\psi_1\rangle|\alpha\rangle = |\psi_1\rangle|\psi_1\rangle$$

$$U|\psi_2\rangle|\alpha\rangle = |\psi_2\rangle|\psi_2\rangle$$

Consider a scalar product between the terms of the eqn.s above

$$\langle\alpha|\langle\psi_2|U^\dagger U|\psi_1\rangle|\alpha\rangle = \langle\psi_2|\langle\psi_2|\psi_1\rangle|\psi_1\rangle$$

No Cloning theorem: proof

Suppose such universal cloning machine exists and apply it to two states like below

$$U|\psi_1\rangle|\alpha\rangle = |\psi_1\rangle|\psi_1\rangle$$

$$U|\psi_2\rangle|\alpha\rangle = |\psi_2\rangle|\psi_2\rangle$$

Consider a scalar product between the terms of the eqn.s above

$$\langle\alpha|\langle\psi_2|U^\dagger U|\psi_1\rangle|\alpha\rangle = \langle\psi_2|\langle\psi_2|\psi_1\rangle|\psi_1\rangle$$

$$\langle\alpha|\alpha\rangle\langle\psi_2|\psi_1\rangle = |\langle\psi_2|\psi_1\rangle|^2$$

$$\langle\psi_2|\psi_1\rangle = |\langle\psi_2|\psi_1\rangle|^2$$

No Cloning theorem: proof

Suppose such universal cloning machine exists and apply it to two states like below

$$U|\psi_1\rangle|\alpha\rangle = |\psi_1\rangle|\psi_1\rangle$$

$$U|\psi_2\rangle|\alpha\rangle = |\psi_2\rangle|\psi_2\rangle$$

Consider a scalar product between the terms of the eqn.s above

$$\langle\alpha|\langle\psi_2|U^\dagger U|\psi_1\rangle|\alpha\rangle = \langle\psi_2|\langle\psi_2|\psi_1\rangle|\psi_1\rangle$$

$$\langle\alpha|\alpha\rangle\langle\psi_2|\psi_1\rangle = |\langle\psi_2|\psi_1\rangle|^2$$

$$\langle\psi_2|\psi_1\rangle = |\langle\psi_2|\psi_1\rangle|^2$$

Contradiction

(true only for
orthogonal states)

$$\begin{cases} \langle\psi_1|\psi_2\rangle = 0 \\ \langle\psi_1|\psi_2\rangle = 1 \end{cases}$$

QEC: Three qubits repetition codes

Repetition codes

This techniques use **redundancy**, **entanglement** and **syndrome measurements** to **correct** single qubits bit-flip and phase-flip errors which may occur with some probability p

$$U_{ERR}^X = (1-p)I + pX$$

$$U_{ERR}^Z = (1-p)I + pZ$$

Bit-flip error code

Encoding


$$|0\rangle \rightarrow |000\rangle$$

$$|1\rangle \rightarrow |111\rangle$$

Syndrome Measurement

$$(Z_1 Z_2), (Z_2 Z_3)$$

Bit-flip errors code




Step by step analysis (two qubit case)

Initial state

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

$$|\psi\rangle|0\rangle$$



Step by step analysis (two qubit case)


Encoding

$$|0\rangle \longrightarrow |0_L\rangle = |00\rangle$$

$$|1\rangle \longrightarrow |1_L\rangle = |11\rangle$$

Obtained with a Control-X

$$\begin{aligned} U_{CX} |\psi\rangle |0\rangle &= \alpha |00\rangle + \beta |11\rangle \\ &= \alpha |0_L\rangle + \beta |1_L\rangle \end{aligned}$$




Step by step analysis (two qubit case)

Assume a bit-flip error on the first qubit

$$U_{ERR} = X_1$$

$$\alpha|00\rangle + \beta|11\rangle \xrightarrow{U_{ERR}} \alpha|10\rangle + \beta|01\rangle$$




Step by step analysis (two qubit case)

Assume a bit-flip error on the first qubit

$$U_{ERR} = X_1$$

$$\alpha|00\rangle + \beta|11\rangle \xrightarrow{U_{ERR}} \alpha|10\rangle + \beta|01\rangle$$

$$|0\rangle_A \xrightarrow{H} \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$




Step by step analysis (two qubit case)

Assume a bit-flip error on the first qubit

$$U_{ERR} = X_1$$

$$\alpha|00\rangle + \beta|11\rangle \xrightarrow{U_{ERR}} \alpha|10\rangle + \beta|01\rangle$$

$$|0\rangle_A \xrightarrow{H} \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$




$$\left(\alpha|10\rangle + \beta|01\rangle \right) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$

Step by step analysis (two qubit case)

Control gate for
syndrome measurement

$$\left(\alpha |10\rangle + \beta |01\rangle \right) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{C-Z_1 Z_2} \left(\begin{array}{l} Z|0\rangle = |0\rangle \\ Z|1\rangle = -|1\rangle \end{array} \right)$$

$$|0\rangle_A \left(\frac{\alpha |10\rangle + \beta |01\rangle}{\sqrt{2}} \right) - |1\rangle_A \left(\frac{\alpha |10\rangle + \beta |01\rangle}{\sqrt{2}} \right)$$




Step by step analysis (two qubit case)

Control gate for syndrome measurement


$$\underbrace{(\alpha|10\rangle + \beta|01\rangle)}_{C-Z_1Z_2} \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right) \quad \left(\begin{array}{l} Z|0\rangle = |0\rangle \\ Z|1\rangle = -|1\rangle \end{array} \right)$$

$$|0\rangle_A \left(\frac{\alpha|10\rangle + \beta|01\rangle}{\sqrt{2}} \right) - |1\rangle_A \left(\frac{\alpha|10\rangle + \beta|01\rangle}{\sqrt{2}} \right) = \alpha|10\rangle + \beta|01\rangle \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right)$$



Step by step analysis (two qubit case)


$$\alpha|10\rangle + \beta|01\rangle \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{H_A} \boxed{(\alpha|10\rangle + \beta|01\rangle)|1\rangle_A}$$



Step by step analysis (two qubit case)

$$\alpha|10\rangle + \beta|01\rangle \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{H_A} (\alpha|10\rangle + \beta|01\rangle) |1\rangle_A$$


Measuring the state of the ancillary qubit in $|1\rangle_A$ will reveal that a bit-flip error has occurred



Step by step analysis (two qubit case)

$$\alpha|10\rangle + \beta|01\rangle \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{H_A} (\alpha|10\rangle + \beta|01\rangle) |1\rangle_A$$


Measuring the state of the ancillary qubit in $|1\rangle_A$ will reveal that a bit-flip error has occurred



We need 3 qubits in the encoding to perfectly locate where bit-flip error has occurred

Step by step analysis (two qubit case)

	$(Z_1 Z_2)$	$(Z_2 Z_3)$	
outcome	+ 1	+ 1	error on none qubits
outcome	- 1	+ 1	error on first qubit
outcome	+ 1	- 1	error on third qubit
outcome	- 1	- 1	error on second qubit



We need 3 qubits in the encoding to perfectly locate where bit-flip error has occurred




Step by step analysis (two qubit case)

Assume a no error on the first qubit

$$U_{ERR} = I$$

$$\alpha|00\rangle + \beta|11\rangle \xrightarrow{U_{ERR}} \alpha|00\rangle + \beta|11\rangle$$



$$\left(\alpha|00\rangle + \beta|11\rangle \right) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{C-Z_1 Z_2} \left(\alpha|00\rangle + \beta|11\rangle \right) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right) \xrightarrow{H_A}$$

$$\xrightarrow{H_A} \left(\alpha|00\rangle + \beta|11\rangle \right) |0\rangle_A$$

Measuring the state of the ancillary qubit in 0 reveals that no error has occurred

Phase-flip errors code

Encoding

$$|0\rangle \rightarrow |+++ \rangle$$


$$|1\rangle \rightarrow |-- - \rangle$$

$$\left(\begin{array}{l} |+\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}} \\ |-\rangle = \frac{|0\rangle - |1\rangle}{\sqrt{2}} \end{array} \right)$$

Syndrome Measurement

$$(X_1 X_2), (X_2 X_3)$$

Phase-flip errors code




Step by step analysis (two qubit case)

Initial state

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

$$|\psi\rangle|0\rangle$$



Step by step analysis (two qubit case)


Encoding

$$|0\rangle \rightarrow |++\rangle$$

$$|1\rangle \rightarrow |--\rangle$$

Obtained with a Control-X and Hadamards

$$\begin{aligned} (\alpha|0\rangle + \beta|1\rangle)|0\rangle &\xrightarrow{U_{CX}} \alpha|00\rangle + \beta|11\rangle \xrightarrow{H^{\otimes 2}} \alpha \left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes \frac{|0\rangle + |1\rangle}{\sqrt{2}} \right) + \beta \left(\frac{|0\rangle - |1\rangle}{\sqrt{2}} \otimes \frac{|0\rangle - |1\rangle}{\sqrt{2}} \right) = \\ &= \alpha |++\rangle + \beta |--\rangle \end{aligned}$$




Step by step analysis (two qubit case)

Assume a phase-flip error on the first qubit

$$[U_{ERR} = Z_1]$$

$$\alpha|++\rangle + \beta|--\rangle \xrightarrow{U_{ERR}} \alpha| - + \rangle + \beta| + - \rangle$$




Step by step analysis (two qubit case)

Assume a phase-flip error on the first qubit

$$[U_{ERR} = Z_1]$$

$$\alpha|++\rangle + \beta|--\rangle \xrightarrow{U_{ERR}} \alpha| - + \rangle + \beta| + - \rangle$$

$$|0\rangle_A \xrightarrow{H} \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$




Step by step analysis (two qubit case)

Assume a phase-flip error on the first qubit

$$[U_{ERR} = Z_1]$$

$$\alpha|++\rangle + \beta|--\rangle \xrightarrow{U_{ERR}} \alpha| - + \rangle + \beta| + - \rangle$$

$$|0\rangle_A \xrightarrow{H} \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$



$$(\alpha| - + \rangle + \beta| + - \rangle) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$


Step by step analysis (two qubit case)

Control gate for
syndrome measurement

$$(\alpha| - + \rangle + \beta| + - \rangle) \left(\frac{|0\rangle_A + |1\rangle_A}{\sqrt{2}} \right)$$

\swarrow
 $X_{1/2}$

$$\left(\begin{array}{l} X|+\rangle = |+\rangle \\ X|-\rangle = -|-\rangle \end{array} \right)$$




$$|0\rangle_A \left(\frac{\alpha| - + \rangle + \beta| + - \rangle}{\sqrt{2}} \right) - |1\rangle_A \left(\frac{\alpha| - + \rangle + \beta| + - \rangle}{\sqrt{2}} \right) = \left(\alpha| - + \rangle + \beta| + - \rangle \right) \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right)$$

Step by step analysis (two qubit case)

$$(\alpha| - + \rangle + \beta| + - \rangle) \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right)$$

$\downarrow H_A$

$$(\alpha| - + \rangle + \beta| + - \rangle) |1\rangle_A$$




Step by step analysis (two qubit case)

$$(\alpha| - + \rangle + \beta| + - \rangle) \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right)$$

\downarrow
 σ_z

$$(\alpha| - + \rangle + \beta| + - \rangle) |1\rangle_A$$

Measuring the state of the ancillary qubit in $|1\rangle_A$ will reveal that a phase-flip error has occurred



Step by step analysis (two qubit case)

$$(\alpha| - + \rangle + \beta| + - \rangle) \left(\frac{|0\rangle_A - |1\rangle_A}{\sqrt{2}} \right)$$


\downarrow
 \mathbb{H}

$$(\alpha| - + \rangle + \beta| + - \rangle) |1\rangle_A$$

Measuring the state of the ancillary qubit in $|1\rangle_A$ will reveal that a phase-flip error has occurred




We need 3 qubits in the encoding to perfectly locate where phase-flip error has occurred



Step by step analysis (two qubit case)

	$(X_1 X_2)$	$(X_2 X_3)$	
outcome	+ 1	+ 1	error on none qubits
outcome	- 1	+ 1	error on first qubit
outcome	+ 1	- 1	error on third qubit
outcome	- 1	- 1	error on second qubit



We need 3 qubits in the encoding to perfectly locate where phase-flip error has occurred

Shor Code

Nine qubit repetition code

Uses nine qubits to correct both bit-flip and phase-flip errors

Encoding

Encoding 1

$$|0\rangle \rightarrow |+++ \rangle$$

$$|1\rangle \rightarrow |-- - \rangle$$

then \rightarrow

Encoding 2

$$|0\rangle \rightarrow |000 \rangle$$

$$|1\rangle \rightarrow |111 \rangle$$

Nine qubit repetition code

Uses nine qubits to correct both bit-flip and phase-flip errors

Encoding

Encoding 1

$$|0\rangle \rightarrow |+++ \rangle$$


$$|1\rangle \rightarrow |-- - \rangle$$

then

Encoding 2

$$|0\rangle \rightarrow |000\rangle$$

$$|1\rangle \rightarrow |111\rangle$$



Nine qubit repetition code

Uses nine qubits to correct both bit-flip and phase-flip errors

Encoding

Encoding 1		Encoding 2
$ 0\rangle \rightarrow +++ \rangle$	$\xrightarrow{\text{then}}$	$ 0\rangle \rightarrow 000\rangle$
$ 1\rangle \rightarrow -- - \rangle$		$ 1\rangle \rightarrow 111\rangle$

Syndrome Measurement

$$(X_1 X_2 X_3)(X_4 X_5 X_6), (X_4 X_5 X_6)(X_7 X_8 X_9)$$
$$(Z_1 Z_2), (Z_2 Z_3), (Z_4 Z_5), (Z_5 Z_6), (Z_7 Z_8), (Z_8 Z_9)$$

Quantum Computing @ CINECA

CINECA: Italian HPC center

CINECA Quantum Computing Lab:

- Research with Universities, Industries and QC startups
- Internship programs, Courses and Conference (HPCQC)

<https://www.quantumcomputinglab.cineca.it>



r.mengoni@cineca.it

